

## Ocularc 2.0

# 11W 0° - 35° Adjustable Round

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2BRA-11	F 45°	927 2700K - 90	955	1349	BK Black
		930 3000K - 90	1005	1420	<b>BN</b> Brushed Nickel
	N 25°	<b>927</b> 2700K - 90	930	2549	WT White
		930 3000K - 90	980	2683	
	S 15°	<b>927</b> 2700K - 90	860	4293	
		930 3000K - 90	935	4666	

Example: R2BRA-11-F927-BK

#### **DESCRIPTION**

Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

#### **FEATURES**

- Cutout 3 1/16"
- Single spot light source
- Ceiling thickness: 1/2" 1"
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty

### **SPECIFICATIONS**

**Construction** Die-cast aluminum trim with aluminum heat sink

Power: 11W

**Input:** 120 VAC,50/60Hz

Dimming: ELV: 100-5%, 0-10V: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED, 3 Step Mac Adam Ellipse

**Rated Life:** 50,000 Hours **Cut Out:** 3 1/16"

Finish: Electrostatically Powder Coated: Black, Brushed Nickel, White

Ceiling Thickness: 1/2" - 1"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Damp Location Listed, Energy Star 2.0, Airtight, IC



#### **FINISHES:**







Brushed Nickel

White

#### **LINE DRAWING:**

