
EXTERMINATOR II

Monopoint Luminaire - 1023







_	
Fixture Type:	
Catalog Number	r:
Project:	
Location:	

PRODUCT DESCRIPTION

Exterminator offers superior light output in a small, unobtrusive design. Developed for upscale residential and commercial environments.

FEATURES

• Accommodates one lens accessory and one glare control accessory

Color Tomp

- 365° horizontal rotation and 180° vertical aiming
- · Ceiling and wall mountable
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Die-cast aluminum with removable front cap **Construction:**

for easy change of lenses or accessories

Power Consumption: 1023S: 22W; 1023N/F: 24W

120V-277V AC 50/60HZ Input:

100%-1% Electronic low voltage (ELV, 120V only), TRIAC (120V only) Dimming:

Finish: Powder coated Black and White, Electroplated Brushed Nickel. ETL&cETL Damp Location listed, Title 24 JA8 compliant Standards:

Einich

Lumons CPCD

System	Bean	n	Color I	emp	CKI	Lumens	CRCh	Finis	sn				
			827	2700K	85	1545	11625						
			927	2700K	90	1275	9600						
	S	12°	830	3000K	85	1640	12350						
	3	12	930	3000K	90	1335	10030						
			835	3500K	85	1680	12650						
			840	4000K	85	1690	12725						
			827	2700K	85	2115	9810						
MO 4022		21°	927	2700K	90	1750	8100	BK BN	Black Brushed Nickel				
	N		830	3000K	85	2250	10425						
MO-1023	IN		21	21	21	21	930	3000K	90	1825	8465	WT	White
			835	3500K	85	2305	10675	VV I	vviille				
			840	4000K	85	2315	10730						
				827	2700K	85	2045	4575					
			927	2700K	90	1690	3780						
	F	39°	830	3000K	85	2175	4860						
	-		930	3000K	90	1765	3950						
			835	3500K	85	2225	4980						

			02/	270011	05	1575	11025	
		12°	927	2700K	90	1275	9600	
	s		830	3000K	85	1640	12350	
	3		930	3000K	90	1335	10030	
			835	3500K	85	1680	12650	
			840	4000K	85	1690	12725	
			827	2700K	85	2115	9810	
			927	2700K	90	1750	8100	DV 01 1
		240	830	3000K	85	2250	10425	BK Black
MO-1023	N	21°	930	3000K	90	1825	8465	BN Brushed Nickel
			835	3500K	85	2305	10675	WT White
			840	4000K	85	2315	10730	
			827	2700K	85	2045	4575	
		39°	927	2700K	90	1690	3780	
	_		830	3000K	85	2175	4860	
	F		930	3000K	90	1765	3950	
			835	3500K	85	2225	4980	
			840	4000K	85	2235	5000	

LENS ACCESSORIES

LENS-16-AMB	Amber
LENS-16-BLU	Blue
LENS-16-GRN	Green
LENS-16-RED	Red
LENS-16-UVF	UV Filter
LENS-16-FR	Frosted
LENS-16-SPR	Spread
LENS-16-BEL	Beam Elongating

GLARE CONTROL - CROSS LOUVER

LENS-16P-CRL-BK	Black
LENS-16P-CRL-BN	Brushed Nickel
LENS-16P-CRL-WT	White

GLARE CONTROL - SNOOT

LENS-16-SNOOT-BK	Black
LENS-16-SNOOT-BN	Brushed Nickel
LENS-16-SNOOT-WT	White

Example: MO-1023F-830-BK

EXTEN	SIONS	Custom	order	as	a com	plete	unit.	Ceiling	mount	only.
X6	6"			8	327				⊐‡5%"	

Х6	6"			827		5/8"			
X12	12"			830					
X18	18"		N	835	BN	Extension			
X24	24"	MO1023	E	840	BK	<u>HI</u>			
X36	36"		•		WT				
				927		45%"			
X48	48"			930					
Evample: Y12-M01022N020WT									

Example: X12-MO1023N930WT

waclighting.com Phone (800) 526.2588 (800) 526.2585

Headquarters, East Manufacturing Facility 44 Harbor Park Drive Port Washington, NY 11050

South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122

Central Manufacturing Facility 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104

West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761

1