

## Patriot 3"

## Downlight and Adjustable Recessed

Catalog Number:			
Project:	-		
Location:			

Model	Description	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R3HRAR		F 25°. 45°	9CS	1000	3095	WT White
R3HRDR			2700K/3000K/3500K/4000K/5	1035	3045	
R3HSAR			000K - 90			
R3HSDR			9CS			
			2700K/3000K/3500K/4000K/5			
			000K - 90			

Fixture Type

Example: R3HRAR-F9CS-WT

### **DESCRIPTION**

Minimum profile downlight with driver and electrical connection box attached to fixture for easy remodel or new construction installation.

#### **FEATURES**

• 5-CCT Switchable between 2700K and 5000K

• Twist-on trim with removable film to adjust beam angle

• Silicon gasket on adjustable to prevent vision past ceiling level

Driver included

5 year warranty

#### **SPECIFICATIONS**

Construction Die-cast Aluminum

Power: 12W

Input: 120-277 VAC,50/60Hz
Dimming: ELV: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED Rated Life: 50,000 Hours

**Mounting:** Heavy gauge rentention clips secures fixture to ceiling

Cut Out: 4 1/4"

Finish: Electrostatically Powder Coated: White

Ceiling Thickness: 1/2" - 1 1/2"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Wet Location Listed, Energy Star 2.0, Airtight, IC




#### **FINISHES:**



White

#### **LINE DRAWING:**





# Patriot 3"

Downlight and Adjustable Recessed

Fixture Type:
Catalog Number:
Project:
Location:

ACCESSORIES			
	Model	Description	Finish
	R3H-FRAME	Patriot 3"	