# WAC LIGHTING

## **Tube Pendant Downlight**

### Ceiling Mount 3000K

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
PD-W2605 5"	2 3000K 90	16W 16W	1188 800	AL Brushed Aluminum BK Black BZ Bronze GH Graphite WT White

#### Example: PD-W2605-AL

#### **DESCRIPTION**

Precision engineered using advanced proprietary LED technology with a built-in reflector. An appealing cylindrical profile with powerful LED lighting is perfect for accent down lighting applications. Five architectural metallic finishes offered.

#### **FEATURES**

- Hang-straight swivel
- Three 12" and one 6" down rods included
- Title 24 may not be available for all finishes, check for availability
- Driver concealed within the canopy
- 5 year warranty

#### **SPECIFICATIONS**

Construction Die-cast Aluminum

Power: 16W

**Input:** 120-277V,50/60Hz

**Dimming:** ELV: 100-10%, 0-10V: 100-5%

Light Source: Integrated LED Rated Life: 70,000 Hours

Mounting: Mounts directly to junction box

Finish: Electrostatically Powder Coated: Powder Coat Graphite

Graphite, Black, Powder Coat Bronze Bronze, Brushed Aluminum with Clear Powder Coat Brushed Aluminum,

Powder Coat White White

Operating Temp: -40°F to 122°F (-40°C to 50°C)

**Standards:** ETL, cETL, Wet Location Listed, IP65



#### **FINISHES:**

Fixture Type:

Project:

Location:

Catalog Number:



#### **LINE DRAWING:**

