BEN 228

LINEAR EASY-SPEC™

Fixture Type: _____

Project: _____

Location: _____

White Lens (WH)

Mounting Clips (PC)

Suspension Cable (SP)



KELVIN COLOR TEMPERATURE SCALE

FEATURES

- Optional Seamless Lensing Up to 100ft
- 100 to 1000 Lumens per Foot
- Field Replaceable Light Source
- 50,000 Hour Lamp Life
- Dimmable to 1%
- Anodized Finish
- Adjustable-Length Power Feed Included

SPECIFICATIONS

Input Voltage	24V DC / Constant Voltage
CRI	90+
Dimming Options	PWM, Triac, 0-10V
Temp Range	-40°F to 149°F
Channel Height	25.4mm (1")
Channel Width	35mm (1-3/8")

PART NUMBER BUILDER

Example:

228-I-48-DV-35K-WH-CP-SV-ULV

Model	Setting	Length (Unlimited)[1]	Output	CCT	Lens	Mounting Method	Finish	Power Supply
228	I						SV	ULV
228	**I** - Indoor	**Inches**	**DL** - 200+lm/ft **DK** - 400+lm/ft **DV** - 700+lm/ft **VT** - 1000+lm/ft **RGBW-1** **RGBW-2** **RGBW-3**	**24K** - 2400 Kelvin **27K** - 2700 Kelvin **30K** - 3000 Kelvin **35K** - 3500 Kelvin **40K** - 4000 Kelvin **50K** - 5000 Kelvin	**NA** - None **WH** - White **SWH** - Seamless White *(SWH for direct view applications only)*	**CP** - Mounting Clips **SP** - Suspension	**SV** - Silver *(Custom Finishes Available)*	**ULV** - Universal Power Supply[2]

[1] Light Source is installed in field allowing for seamless lensing and unlimited run lengths

[2] 120V = Forward Phase Dimming | 120/277 = 0-10V Dimming

For use with c UL us Light Source

Certified to CAN/CSA Standard C22.2 No. 250.0

RoHS COMPLIANT | 24V DC | DRY LOCATION RATED