



Introduction to Algorithms

Dynamic Programming

Dynamic programming

- It is used, when the solution can be recursively described in terms of solutions to subproblems (*optimal substructure*)
- Algorithm finds solutions to subproblems and stores them in memory for later use
- More efficient than “*brute-force methods*”, which solve the same subproblems over and over again

Optimal Substructure Property

- Definition:

- If S is an optimal solution to a problem, then the components of S are optimal solutions to subproblems

- Examples:

- True for knapsack
- True for coin-changing
- True for single-source shortest path
- Not true for longest-simple-path

Dynamic Programming

- Works “bottom-up”
 - Finds solutions to small sub-problems first
 - Stores them
 - Combines them somehow to find a solution to a slightly larger subproblem
- Compare to greedy approach
 - Also requires optimal substructure
 - But greedy makes choice first, then solves

Problems Solved with Dyn. Prog.

- Coin changing
- Multiplying a sequence of matrices
 - Can do in various orders: $(AB)C$ vs. $A(BC)$
 - Pick order that does fewest number of scalar multiplications
- Longest common subsequence
- All-pairs shortest paths (Floyd's algorithm)
- Constructing optimal binary search trees
- Knapsack problems (we'll do 0/1)

Remember Fibonacci numbers?

- Recursive code:

```
long fib(int n) {  
    assert(n >= 0);  
    if ( n == 0 ) return 0;  
    if ( n == 1 ) return 1;  
    return fib(n-1) + fib(n-2);  
}
```

- What's the problem?

- Repeatedly solves the same subproblems
- Exponential time complexity

Memorization

- Before talking about dynamic programming, another general technique:
Memoization
 - AKA using a *memory function*
- Simple idea:
 - Calculate and store solutions to subproblems
 - Before solving it (again), look to see if you've remembered it

Memorization

- Use a Table abstract data type
 - Lookup key: whatever identifies a subproblem
 - Value stored: the solution
- Could be an array/vector
 - E.g. for Fibonacci, store **fib(n)** using index **n**
 - Need to initialize the array
- Could use a map / hash-table

Memorization and Fibonacci

- Before recursive code below called, must initialize results[] so all values are -1

```
long fib_mem(int n, long results[]) {  
    if ( results[n] != -1 )  
        return results[n]; // return stored value  
    long val;  
    if ( n == 0 || n == 1 )  
        val = n; // odd but right  
    else  
        val = fib_mem(n-1, results)  
            + fib_mem(n-2, results);  
    results[n] = val; // store calculated value  
    return val;  
}
```

Observations on fib_mem()

- Same elegant top-down, recursive approach based on definition
 - Without repeated subproblems
- Memory function: a function that remembers
 - Save time by using extra space
- Can show this runs in $\Theta(n)$

General Strategy of Dyn. Prog.

1. Structure: What's the structure of an optimal solution in terms of solutions to its subproblems?
2. Give a recursive definition of an optimal solution in terms of optimal solutions to smaller problems
 - Usually using min or max
3. Use a data structure (often a table) to store smaller solutions in a bottom-up fashion
 - Optimal value found in the table
4. (If needed) Reconstruct the optimal solution
 - I.e. what produced the optimal value

Dyn. Prog. vs. Divide and Conquer

- Remember D & C?
 - Divide into subproblems. Solve each. Combine.
- Good when subproblems do not overlap, when they're independent
 - No need to repeat them
- Divide and conquer: top-down
- Dynamic programming: bottom-up

Longest Common Subsequence (LCS)

Application: comparison of two DNA strings

Ex: $X = \{A B C B D A B\}$, $Y = \{B D C A B A\}$

Longest Common Subsequence:

$X = A \text{ **B** } \text{ **C** } \text{ **B** } D \text{ **A** } B$

$Y = \text{ **B** } D \text{ **C** } A \text{ **B** } \text{ **A** }$

Brute force algorithm would compare each subsequence of X with the symbols in Y

LCS Algorithm

- if $|X| = m$, $|Y| = n$, then there are 2^m subsequences of X ; we must compare each with Y (n comparisons)
- So the running time of the brute-force algorithm is $O(n 2^m)$
- Notice that the LCS problem has *optimal substructure*: solutions of subproblems are parts of the final solution.
- Subproblems: “find LCS of pairs of *prefixes* of X and Y ”

LCS Algorithm

- First we'll find the length of LCS. Later we'll modify the algorithm to find LCS itself.
- Define X_i, Y_j to be the prefixes of X and Y of length i and j respectively
- Define $c[i,j]$ to be the length of LCS of X_i and Y_j
- Then the length of LCS of X and Y will be $c[m,n]$

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

LCS recursive solution

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

- We start with $i = j = 0$ (empty substrings of x and y)
- Since X_0 and Y_0 are empty strings, their LCS is always empty (i.e. $c[0, 0] = 0$)
- LCS of empty string and any other string is empty, so for every i and j : $c[0, j] = c[i, 0] = 0$

LCS recursive solution

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

- When we calculate $c[i, j]$, we consider two cases:
- **First case:** $x[i] = y[j]$: one more symbol in strings X and Y matches, so the length of LCS X_i and Y_j equals to the length of LCS of smaller strings X_{i-1} and Y_{j-1} , plus 1

LCS recursive solution

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

- **Second case:** $x[i] \neq y[j]$
- As symbols don't match, our solution is not improved, and the length of $\text{LCS}(X_i, Y_j)$ is the same as before (i.e. maximum of $\text{LCS}(X_i, Y_{j-1})$ and $\text{LCS}(X_{i-1}, Y_j)$)

Why not just take the length of $\text{LCS}(X_{i-1}, Y_{j-1})$?

LCS Length Algorithm

LCS-Length(X, Y)

1. $m = \text{length}(X)$ // get the # of symbols in X
2. $n = \text{length}(Y)$ // get the # of symbols in Y
3. for $i = 1$ to m $c[i,0] = 0$ // special case: Y_0
4. for $j = 1$ to n $c[0,j] = 0$ // special case: X_0
5. for $i = 1$ to m // for all X_i
6. for $j = 1$ to n // for all Y_j
7. if ($X_i == Y_j$)
8. $c[i,j] = c[i-1,j-1] + 1$
9. else $c[i,j] = \max(c[i-1,j], c[i,j-1])$
10. return $c[m,n]$ // return LCS length for X and Y

LCS Example

We'll see how LCS algorithm works on the following example:

- $X = \text{ABCB}$
- $Y = \text{BDCAB}$

What is the Longest Common Subsequence of X and Y ?

$LCS(X, Y) = \text{BCB}$

$X = A \quad B \quad C \quad B$

$Y = \quad B \quad D \quad C \quad A \quad B$

LCS Example (0)

		<i>ABCB</i>						<i>ABCB</i>
		<i>0</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>	<i>BDCAB</i>
<i>i</i>	<i>j</i>	<i>Y_j</i>	<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>	
<i>0</i>	<i>X_i</i>							
<i>1</i>	<i>A</i>							
<i>2</i>	<i>B</i>							
<i>3</i>	<i>C</i>							
<i>4</i>	<i>B</i>							

$X = ABCB; \quad m = |X| = 4$

$Y = BDCAB; \quad n = |Y| = 5$

Allocate array $c[5,6]$

LCS Example (1)

ABCB
BDCAB

		<i>j</i>	0	1	2	3	4	5	
			<i>Y_j</i>	<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>	
<i>i</i>	<i>X_i</i>								
0			0	0	0	0	0	0	
1	<i>A</i>		0						
2	<i>B</i>		0						
3	<i>C</i>		0						
4	<i>B</i>		0						

for i = 1 to m *c[i,0] = 0*
for j = 1 to n *c[0,j] = 0*

LCS Example (2)

ABCB

BDCAB

<i>i</i>	<i>j</i>	0	1	2	3	4	5
		<i>Y_j</i>	B	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	A	0	0				
2	<i>B</i>	0					
3	<i>C</i>	0					
4	<i>B</i>	0					

if ($X_i == Y_j$)

$c[i,j] = c[i-1,j-1] + 1$

else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (3)

***ABC*B**

B**D**C*A*B

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>	<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>	
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0		
2	<i>B</i>	0					
3	<i>C</i>	0					
4	<i>B</i>	0					

$if (X_i == Y_j)$
 $\quad c[i,j] = c[i-1,j-1] + 1$
 $else \ c[i,j] = max(c[i-1,j], c[i,j-1])$

LCS Example (4)

ABCB

BDC**A**B

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>		<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	
2	<i>B</i>	0					
3	<i>C</i>	0					
4	<i>B</i>	0					

$$\text{if } (X_i == Y_j)$$

$$c[i,j] = c[i-1,j-1] + 1$$

$$\text{else } c[i,j] = \max(c[i-1,j], c[i,j-1])$$

LCS Example (5)

ABCB

BD**C**AB

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>		<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0					
3	<i>C</i>	0					
4	<i>B</i>	0					

$if (X_i == Y_j)$
 $c[i,j] = c[i-1,j-1] + 1$
 $else\ c[i,j] = max(c[i-1,j], c[i,j-1])$

LCS Example (6)

A**B****C****B**

B**D****C****A****B**

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>		B	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	B	0	1				
3	<i>C</i>	0					
4	<i>B</i>	0					

if ($X_i == Y_j$)

$c[i,j] = c[i-1,j-1] + 1$

else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (7)

ABCB

BDCAB

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>		<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0	1	1	1	1	
3	<i>C</i>	0					
4	<i>B</i>	0					

$$\text{if } (X_i == Y_j)$$

$$c[i,j] = c[i-1,j-1] + 1$$

$$\text{else } c[i,j] = \max(c[i-1,j], c[i,j-1])$$

LCS Example (8)

ABCB

BD CAB

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>		<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0	1	1	1	1	2
3	<i>C</i>	0					
4	<i>B</i>	0					

if ($X_i == Y_j$)

$c[i,j] = c[i-1,j-1] + 1$

else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (10)

ABCB

BD CAB

<i>i</i>	<i>j</i>	0	1	2	3	4	5
		<i>Y_j</i>	<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0	1	1	1	1	2
3	<i>C</i>	0	↓	↓			
4	<i>B</i>	0	1	1			

$if (X_i == Y_j)$
 $c[i,j] = c[i-1,j-1] + 1$
 $else c[i,j] = max(c[i-1,j], c[i,j-1])$

LCS Example (11)

*ABC**B*

*BD**C**AB*

<i>i</i>	<i>j</i>	0	1	2	³ C	4	5
	<i>Y_j</i>	<i>B</i>	<i>D</i>			<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0	1	1	1	1	2
³ C	<i>C</i>	0	1	1	2		
4	<i>B</i>	0					

if ($X_i == Y_j$)

$c[i,j] = c[i-1,j-1] + 1$

else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (12)

ABCB

BDCAB

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>		<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0	1	1	1	1	2
3	<i>C</i>	0	1	1	2	2	2
4	<i>B</i>	0					

$$\text{if } (X_i == Y_j)$$

$$c[i,j] = c[i-1,j-1] + 1$$

$$\text{else } c[i,j] = \max(c[i-1,j], c[i,j-1])$$

LCS Example (13)

ABCB

BDCAB

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>		<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0	1	1	1	1	2
3	<i>C</i>	0	1	1	2	2	2
4	<i>B</i>	0	1				

if ($X_i == Y_j$)

$c[i,j] = c[i-1,j-1] + 1$

else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (14)

ABCB

BDCAB

<i>i</i>	<i>j</i>	0	1	2	3	4	5
	<i>Y_j</i>		<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0	1	1	1	1	2
3	<i>C</i>	0	1	1	2	2	2
4	<i>B</i>	0	1	1	2	2	

if ($X_i == Y_j$)

$c[i,j] = c[i-1,j-1] + 1$

else $c[i,j] = \max(c[i-1,j], c[i,j-1])$

LCS Example (15)

		<i>j</i>	0	1	2	3	4	5
<i>i</i>	<i>X_i</i>	<i>Y_j</i>		<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X₀</i>		0	0	0	0	0	0
1	<i>A</i>		0	0	0	0	1	1
2	<i>B</i>		0	1	1	1	1	2
3	<i>C</i>		0	1	1	2	2	2
4	<i>B</i>		0	1	1	2	2	3

ABCB
BD CAB

$$\text{if } (X_i == Y_j)$$

$$c[i,j] = c[i-1,j-1] + 1$$

$$\text{else } c[i,j] = \max(c[i-1,j], c[i,j-1])$$

LCS Algorithm Running Time

- LCS algorithm calculates the values of each entry of the array $c[m,n]$
- So what is the running time?

*$O(m*n)$*

*since each $c[i,j]$ is calculated in constant time, and there are $m*n$ elements in the array*


How to find actual LCS

- So far, we have just found the *length* of LCS, but not LCS itself.
- We want to modify this algorithm to make it output Longest Common Subsequence of X and Y

Each $c[i,j]$ depends on $c[i-1,j]$ and $c[i,j-1]$
or $c[i-1,j-1]$

For each $c[i,j]$ we can say how it was acquired:

2	2
2	3



For example, here
 $c[i,j] = c[i-1,j-1] + 1 = 2 + 1 = 3$

How to find actual LCS - continued

- Remember that

$$c[i, j] = \begin{cases} c[i-1, j-1] + 1 & \text{if } x[i] = y[j], \\ \max(c[i, j-1], c[i-1, j]) & \text{otherwise} \end{cases}$$

- So we can start from $c[m, n]$ and go backwards
- Look first to see if 2nd case above was true
- If not, then $c[i, j] = c[i-1, j-1] + 1$, so remember $x[i]$ (because $x[i]$ is a part of LCS)
- When $i=0$ or $j=0$ (i.e. we reached the beginning), output remembered letters in reverse order

Algorithm to find actual LCS

- Here's a recursive algorithm to do this:

```
LCS_print(x, m, n, c) {  
    if (c[m][n] == c[m-1][n]) // go up?  
        LCS_print(x, m-1, n, c);  
    else if (c[m][n] == c[m][n-1] // go left?  
        LCS_print(x, m, n-1, c);  
    else { // it was a match!  
        LCS_print(x, m-1, n-1, c);  
        print(x[m]); // print after recursive call  
    }  
}
```

Finding LCS

		<i>j</i>	0	1	2	3	4	5
<i>i</i>			<i>Yj</i>	<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
		<i>Xi</i>						
0		<i>Xi</i>	0	0	0	0	0	0
1	<i>A</i>		0	0	0	0	1	1
2	<i>B</i>		0	1	1	1	1	2
3	<i>C</i>		0	1	1	2	2	2
4	<i>B</i>		0	1	1	2	2	3

Finding LCS (2)

		<i>j</i>					
		0	1	2	3	4	5
<i>i</i>		<i>Y_j</i>	<i>B</i>	<i>D</i>	<i>C</i>	<i>A</i>	<i>B</i>
0	<i>X_i</i>	0	0	0	0	0	0
1	<i>A</i>	0	0	0	0	1	1
2	<i>B</i>	0	1	1	1	1	2
3	<i>C</i>	0	1	1	2	2	2
4	<i>B</i>	0	1	1	2	2	3

LCS (reversed order): B C B

LCS (straight order): B C B
(this string turned out to be a palindrome)

Review: Dynamic programming

- DP is a method for solving certain kind of problems
- DP can be applied when the solution of a problem includes solutions to subproblems
- We need to find a recursive formula for the solution
- We can recursively solve subproblems, starting from the trivial case, and save their solutions in memory
- In the end we'll get the solution of the whole problem

Properties of a problem that can be solved with dynamic programming

- Simple Subproblems
 - We should be able to break the original problem to smaller subproblems that have the same structure
- Optimal Substructure of the problems
 - The solution to the problem must be a composition of subproblem solutions
- Subproblem Overlap
 - Optimal subproblems to unrelated problems can contain subproblems in common

Review: Longest Common Subsequence (LCS)

- Problem: how to find the longest pattern of characters that is common to two text strings X and Y
- Dynamic programming algorithm: solve subproblems until we get the final solution
- Subproblem: first find the LCS of *prefixes* of X and Y .
- this problem has *optimal substructure*: LCS of two prefixes is always a part of LCS of bigger strings

Conclusion

- Dynamic programming is a useful technique of solving certain kind of problems
- When the solution can be recursively described in terms of partial solutions, we can store these partial solutions and re-use them as necessary
- Running time (Dynamic Programming algorithm vs. naïve algorithm):
 - LCS: $O(m * n)$ vs. $O(n * 2^m)$
 - 0-1 Knapsack problem: $O(W * n)$ vs. $O(2^n)$