



Print reference

Colour build, gamut and production notes

COLOUR BUILD

Converted from sRGB through FOGRA39L Coated at relative colorimetric intent. Not by arithmetic.

TOKEN	SCREEN	HEX	C / M / Y / K	TAC	DE	PROCESS	NOTE
ink-900		#04141D	95 / 56 / 29 / 96	277%	6.4		out of gamut
ink-800		#0A2231	98 / 49 / 15 / 92	253%	2.5		
ink-700		#123449	92 / 42 / 10 / 77	222%	0.8		
ink-600		#1E4A63	90 / 48 / 24 / 52	214%	1.0		
ink-400		#4E7E96	68 / 30 / 21 / 26	145%	0.3		
ink-200		#AFC6D2	37 / 15 / 15 / 0	67%	0.3		
ink-100		#DCE7ED	15 / 7 / 8 / 0	31%	2.0		
paper		#F4F8FA	5 / 3 / 3 / 0	10%	1.3		
pitch-900		#06301F	89 / 17 / 84 / 89	280%	3.6		
pitch-700		#0A5537	95 / 28 / 90 / 53	265%	0.5		
pitch-600		#0C6B45	91 / 26 / 87 / 33	236%	0.6		
pitch-500		#12A26C	80 / 1 / 72 / 7	160%	0.4		
pitch-400		#2ACE8C	64 / 0 / 58 / 0	122%	20.3		out of gamut
pitch-300		#54E8AC	49 / 0 / 41 / 0	89%	30.1		out of gamut
pitch-200		#8DF3C9	35 / 0 / 27 / 0	62%	24.5		out of gamut
pitch-100		#CDFAE6	17 / 0 / 14 / 0	31%	10.9		out of gamut

The mint does not reproduce in process colour

pitch-300 lands 30.1 dE from its screen value in four-colour process. Anything past about 3 dE is a visible difference; 30 is a different colour. The bright end of the green ramp is all out of gamut.

For CMYK print use the deep green, pitch-700, which converts at 0.5 dE. Where the mint is genuinely required (reversed on navy, for instance) specify a fifth plate as a spot colour and have the printer match it against a physical guide. No spot reference is given here because none has been verified.

SIMULATED SIDE BY SIDE



Screen mint



Mint in process colour



Deep green, screen



Deep green in process

Print reference

Sizes, clear space and file index

MINIMUM SIZE IN PRINT

Primary horizontal	22 mm wide
Horizontal with tagline	34 mm wide
Stacked	22 mm wide
Stacked with tagline	34 mm wide
Primary symbol	6 mm wide
Small-size symbol variant	5 mm wide

Embroidery, etching, debossing and vinyl need their own physical trials. These figures do not transfer to them.

CLEAR SPACE



One unit is the dot at the centre of the symbol. Hold two of them clear on every side. The clear space is already built into every page in this folder, so placing the PDF edge to edge still respects it.

WHAT IS IN THIS FOLDER

cmyk-for-print/	CMYK vector, FOGRA39L output intent embedded. Use these on press.
rgb-for-office/	sRGB vector, for documents, slides and email.
soccolo-print-reference.pdf	This document.

Naming	soccolo-[lockup]-[colourway]-[space].pdf
--------	--

STOCK AND PROCESS

Coated	As specified. The build above is measured against this condition.
Uncoated	Ink spreads and the navy gains. Ask for a proof on the actual stock and expect to lighten the navy build rather than accept a heavier mark.
Newsprint, low grade	Use the one-colour black file. A four-colour navy will fill in.
One colour	Use the black or white files, never a tint or a screen of the navy.
Foil, emboss, screen	Supply the one-colour black as artwork. These are line processes: re-test the minimum sizes physically before committing.

PRODUCTION NOTES

No fonts are embedded. Every mark is a filled path, so nothing can substitute or reflow.
 No transparency, no overprint set, no spot channels. Nothing needs flattening.
 Fills are non-zero winding. Counters are real holes, not white shapes laid on top.
 Highest total area coverage in the palette is 280% (pitch-900), inside the 330% FOGRA39 limit.
 Pages are trimmed to the artwork plus its clear space. There is no bleed because there is no background: place the file on your own ground.
 This is a clean CMYK vector PDF with an embedded output intent. It is not certified PDF/X.
 Do not recolour, rasterise, add a keyline, or scale below the minimums above.