

Enter password: *****

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 30

Server version: 8.0.43 MySQL Community Server - GPL

Copyright (c) 2000, 2025, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

```
mysql> select 10+2;
```

```
+-----+
```

```
| 10+2 |
```

```
+-----+
```

```
| 12 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select 10*2;
```

```
+-----+
```

```
| 10*2 |
```

```
+-----+
```

```
| 20 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select 10/2;
```

```
+-----+
```

```
| 10/2 |
```

```
+-----+
```

```
| 5.0000 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select 10//2;
```

```
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '/2' at line 1
```

```
mysql> select 10%2;
```

```
+-----+
```

```
| 10%2 |
```

```
+-----+
```

```
| 0 |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> show databases;
```

```
+-----+
```

```
| Database |
```

```
+-----+
```

```
| information_schema |
```

```

| mysql
| nit
| performance_schema
| sys
+-----+
5 rows in set (0.01 sec)

```

```

mysql> create sqlpractice;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near
'sqlpractice' at line 1
mysql> create database sqlpractice;
Query OK, 1 row affected (0.01 sec)

```

```

mysql> show databases;
+-----+
| Database
+-----+
| information_schema
| mysql
| nit
| performance_schema
| sqlpractice
| sys
+-----+
6 rows in set (0.00 sec)

```

```

mysql> use sqlpractice;
Database changed
mysql> create table customer(ID int not null primary key,NAME varchar(50),AGE
int,ADDRESS varchar(50),SALARY int);
Query OK, 0 rows affected (0.04 sec)

```

```

mysql> insert into customer
values(1,'sumayya',21,'hyd',8000),(2,'ram',24,'mbn',5000),(3,'Neha',38,'up',6500
),(4,'sidra',45,'andh',7000),(5,'Reshmi',39,'Ap',8500),(6,'raj',40,'zhh',3000),(
7,'chitra',28,'mumbai',45000);
Query OK, 7 rows affected (0.01 sec)
Records: 7 Duplicates: 0 Warnings: 0

```

```

mysql> desc customer;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| ID     | int           | NO   | PRI | NULL    |       |
| NAME   | varchar(50)   | YES  |     | NULL    |       |
| AGE    | int           | YES  |     | NULL    |       |
| ADDRESS | varchar(50)   | YES  |     | NULL    |       |
| SALARY | int           | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

```

```

mysql> select * from customer;
+-----+-----+-----+-----+-----+

```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
2	ram	24	mbn	5000
3	Neha	38	up	6500
4	sidra	45	andh	7000
5	Reshmi	39	Ap	8500
6	raj	40	zhb	3000
7	chitra	28	mumbai	45000

7 rows in set (0.00 sec)

```
mysql> select * from customer where salary>5000;
```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
3	Neha	38	up	6500
4	sidra	45	andh	7000
5	Reshmi	39	Ap	8500
7	chitra	28	mumbai	45000

5 rows in set (0.01 sec)

```
mysql> select * from customer where salary>7000;
```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
5	Reshmi	39	Ap	8500
7	chitra	28	mumbai	45000

3 rows in set (0.00 sec)

```
mysql> select * from customer where salary!=8000;
```

ID	NAME	AGE	ADDRESS	SALARY
2	ram	24	mbn	5000
3	Neha	38	up	6500
4	sidra	45	andh	7000
5	Reshmi	39	Ap	8500
6	raj	40	zhb	3000
7	chitra	28	mumbai	45000

6 rows in set (0.00 sec)

```
mysql> select * from customer where salary<6000;
```

ID	NAME	AGE	ADDRESS	SALARY
2	ram	24	mbn	5000
6	raj	40	zhb	3000

2 rows in set (0.00 sec)

```
mysql> select * from customer where salary<>6000;
```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
2	ram	24	mbn	5000
3	Neha	38	up	6500
4	sidra	45	andh	7000
5	Reshmi	39	Ap	8500
6	raj	40	zhb	3000
7	chitra	28	mumbai	45000

7 rows in set (0.00 sec)

```
mysql> select * from customer where salary<>5000;
```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
3	Neha	38	up	6500
4	sidra	45	andh	7000
5	Reshmi	39	Ap	8500
6	raj	40	zhb	3000
7	chitra	28	mumbai	45000

6 rows in set (0.00 sec)

```
mysql> select * from customer where salary >=8000;
```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
5	Reshmi	39	Ap	8500
7	chitra	28	mumbai	45000

3 rows in set (0.00 sec)

```
mysql> select * from customer;
```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
2	ram	24	mbn	5000
3	Neha	38	up	6500
4	sidra	45	andh	7000
5	Reshmi	39	Ap	8500
6	raj	40	zhb	3000
7	chitra	28	mumbai	45000

7 rows in set (0.00 sec)

```
mysql> select * from customer where age=38 and salary=65000;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'selct * from customer where age=38 and salary=65000' at line 1

```
mysql> select * from customer where age=38 and salary=65000;
Empty set (0.00 sec)
```

```
mysql> select * from customer where age=38 and salary=6500;
```

ID	NAME	AGE	ADDRESS	SALARY
3	Neha	38	up	6500

1 row in set (0.00 sec)

```
mysql> select * from customer where age>24 and salary>=6500;
```

ID	NAME	AGE	ADDRESS	SALARY
3	Neha	38	up	6500
4	sidra	45	andh	7000
5	Reshmi	39	Ap	8500
7	chitra	28	mumbai	45000

4 rows in set (0.00 sec)

```
mysql> select * from customer where age>24 or salary>=6500;
```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
3	Neha	38	up	6500
4	sidra	45	andh	7000
5	Reshmi	39	Ap	8500
6	raj	40	zhb	3000
7	chitra	28	mumbai	45000

6 rows in set (0.00 sec)

```
mysql> select * from customer where age in
-> (25,30);
```

Empty set (0.00 sec)

```
mysql> select * from customer where age in(21,24);
```

ID	NAME	AGE	ADDRESS	SALARY
1	sumayya	21	hyd	8000
2	ram	24	mbn	5000

2 rows in set (0.00 sec)

```
mysql> select * from customer where age in(25,28);
```

ID	NAME	AGE	ADDRESS	SALARY
----	------	-----	---------	--------

```

+-----+-----+-----+-----+-----+
| 7 | chitra | 28 | mumbai | 45000 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

```

mysql> select * from customer where age between 21 and 28;

```

+-----+-----+-----+-----+-----+
| ID | NAME   | AGE | ADDRESS | SALARY |
+-----+-----+-----+-----+-----+
| 1 | sumayya | 21 | hyd     | 8000   |
| 2 | ram     | 24 | mbn     | 5000   |
| 7 | chitra  | 28 | mumbai  | 45000  |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

```

mysql> select age from customer where excits(select age from customer where salary>6500);

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'select age from customer where salary>6500)' at line 1

mysql> select age from customer where exists(select age from customer where salary>6500);

```

+-----+
| age |
+-----+
| 21 |
| 24 |
| 38 |
| 45 |
| 39 |
| 40 |
| 28 |
+-----+

```

7 rows in set (0.00 sec)

mysql> select * from customer where age>all(select age from customer where salary >6500);
Empty set (0.00 sec)

mysql> SELECT * FROM CUSTOMERS WHERE AGE > ALL (SELECT AGE FROM CUSTOMERS WHERE SALARY > 6500);

ERROR 1146 (42S02): Table 'sqlpractice.customers' doesn't exist

mysql> SELECT * FROM CUSTOMER WHERE AGE > ALL (SELECT AGE FROM CUSTOMER WHERE SALARY > 6500);

Empty set (0.00 sec)

mysql> SELECT * FROM CUSTOMER WHERE AGE > ALL (SELECT AGE FROM CUSTOMER WHERE SALARY > 3000);

Empty set (0.00 sec)

mysql> SELECT * FROM CUSTOMER WHERE AGE > ALL (SELECT AGE FROM CUSTOMER WHERE SALARY > 5000);

Empty set (0.00 sec)

```
mysql> SELECT *
-> FROM CUSTOMER
-> WHERE AGE < ALL (SELECT AGE FROM CUSTOMER WHERE SALARY > 6500);
Empty set (0.00 sec)
```

```
mysql> SELECT *
-> FROM CUSTOMER
-> WHERE AGE >= ALL (SELECT AGE FROM CUSTOMER WHERE SALARY > 6500);
+----+-----+-----+-----+-----+
| ID | NAME  | AGE  | ADDRESS | SALARY |
+----+-----+-----+-----+-----+
| 4  | sidra | 45   | andh    | 7000   |
+----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT *
-> FROM CUSTOMER
-> WHERE AGE > ALL (SELECT AGE FROM CUSTOMER WHERE SALARY > 40000);
+----+-----+-----+-----+-----+
| ID | NAME  | AGE  | ADDRESS | SALARY |
+----+-----+-----+-----+-----+
| 3  | Neha  | 38   | up      | 6500   |
| 4  | sidra | 45   | andh    | 7000   |
| 5  | Reshmi | 39  | Ap      | 8500   |
| 6  | raj   | 40   | zhb     | 3000   |
+----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> select * from customer where age> any(select * from customer where
salary>6500);
ERROR 1241 (21000): Operand should contain 1 column(s)
```

```
mysql> SELECT *
-> FROM CUSTOMER
-> WHERE AGE > ANY (SELECT AGE FROM CUSTOMER WHERE SALARY > 6500);
+----+-----+-----+-----+-----+
| ID | NAME  | AGE  | ADDRESS | SALARY |
+----+-----+-----+-----+-----+
| 2  | ram   | 24   | mbn     | 5000   |
| 3  | Neha  | 38   | up      | 6500   |
| 4  | sidra | 45   | andh    | 7000   |
| 5  | Reshmi | 39  | Ap      | 8500   |
| 6  | raj   | 40   | zhb     | 3000   |
| 7  | chitra | 28  | mumbai  | 45000  |
+----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

```
mysql> select * from customer;
+----+-----+-----+-----+-----+
| ID | NAME  | AGE  | ADDRESS | SALARY |
+----+-----+-----+-----+-----+
| 1  | sumayya | 21  | hyd     | 8000   |
| 2  | ram   | 24   | mbn     | 5000   |
| 3  | Neha  | 38   | up      | 6500   |
| 4  | sidra | 45   | andh    | 7000   |
+----+-----+-----+-----+-----+
```

5	Reshmi	39	Ap	8500
6	raj	40	zhh	3000
7	chitra	28	mumbai	45000

7 rows in set (0.00 sec)

```
mysql> select (15+6) as addition;
```

addition
21

1 row in set (0.00 sec)

```
mysql> select count(*) as 'records' from customer;
```

records
7

1 row in set (0.01 sec)

```
mysql> select current timestamp;
```

ERROR 1054 (42S22): Unknown column 'current' in 'field list'

```
mysql> SELECT CURRENT_TIMESTAMP;
```

CURRENT_TIMESTAMP
2025-09-10 14:49:17

1 row in set (0.00 sec)

```
mysql> SELECT GETDATE();
```

ERROR 1305 (42000): FUNCTION sqlpractice.GETDATE does not exist

```
mysql> SELECT GETDATE();;
```

ERROR 1305 (42000): FUNCTION sqlpractice.GETDATE does not exist

ERROR:

No query specified

```
mysql> SELECT GETDATE();;
```

ERROR 1305 (42000): FUNCTION sqlpractice.GETDATE does not exist

ERROR:

No query specified

```
mysql> mysql> SELECT NOW();
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'mysql> SELECT NOW()' at line 1

```
mysql> +-----+
-> | NOW() |
-> +-----+
-> | 2025-09-10 15:30:45 |
-> +-----+
->
```

```
-> mysql> SELECT CURDATE();  
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that  
corresponds to your MySQL server version for the right syntax to use near
```

```
' +-----+  
| NOW()      |  
+-----+  
| 2025-0' at line 1
```

```
mysql> +-----+  
-> | CURDATE() |  
-> +-----+  
-> | 2025-09-10 |  
-> +-----+  
-> select now();
```

```
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that  
corresponds to your MySQL server version for the right syntax to use near
```

```
' +-----+  
| CURDATE() |  
+-----+  
| 2025-09-10 |  
+-----+  
selec' at line 1
```

```
mysql> select curdate;
```

```
ERROR 1054 (42S22): Unknown column 'curdate' in 'field list'
```

```
mysql> SELECT NOW(); -- Current date and time
```

```
+-----+  
| NOW()      |  
+-----+  
| 2025-09-10 14:54:14 |  
+-----+  
1 row in set (0.00 sec)
```

```
mysql> SELECT CURDATE(); -- Current date only
```

```
+-----+  
| CURDATE() |  
+-----+  
| 2025-09-10 |  
+-----+  
1 row in set (0.00 sec)
```

```
mysql> SELECT CURTIME(); -- Current time only
```

```
+-----+  
| CURTIME() |  
+-----+  
| 14:54:14 |  
+-----+  
1 row in set (0.00 sec)
```

```
mysql> create database testdb;
```

```
Query OK, 1 row affected (0.01 sec)
```

```
mysql> use testdb;
```

```
Database changed
```

```
mysql> show databases;
```

```
+-----+
```

Database
information_schema
mysql
nit
performance_schema
sqlpractice
sys
testdb

7 rows in set (0.00 sec)

```
mysql> drop testdb;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near
'testdb' at line 1
mysql> drop database testdb;
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| nit |
| performance_schema |
| sqlpractice |
| sys |
+-----+
6 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE SALARY AS SELECT ID, SALARY FROM CUSTOMER;
ERROR 1046 (3D000): No database selected
mysql> use sqlpractice;
Database changed
mysql> CREATE TABLE SALARY AS SELECT ID, SALARY FROM CUSTOMER;
Query OK, 7 rows affected (0.03 sec)
Records: 7 Duplicates: 0 Warnings: 0
```

```
mysql> select * from salary;
+----+-----+
| ID | SALARY |
+----+-----+
| 1 | 8000 |
| 2 | 5000 |
| 3 | 6500 |
| 4 | 7000 |
| 5 | 8500 |
| 6 | 3000 |
| 7 | 45000 |
+----+-----+
7 rows in set (0.00 sec)
```

```
mysql> SELECT id,name from customer;
```

id	name
1	sumayya
2	ram
3	Neha
4	sidra
5	Reshmi
6	raj
7	chitra

```
7 rows in set (0.00 sec)
```

```
mysql> SELECT ID, NAME, SALARY FROM CUSTOMER WHERE SALARY > 4000;
```

ID	NAME	SALARY
1	sumayya	8000
2	ram	5000
3	Neha	6500
4	sidra	7000
5	Reshmi	8500
7	chitra	45000

```
6 rows in set (0.00 sec)
```

```
mysql> ^C
```

```
mysql> SELECT ID, NAME, SALARY FROM CUSTOMERS WHERE NAME = 'sumayya';  
ERROR 1146 (42S02): Table 'sqlpractice.customers' doesn't exist
```

```
mysql> SELECT ID, NAME, SALARY FROM CUSTOMER WHERE NAME = 'sumayya';
```

ID	NAME	SALARY
1	sumayya	8000

```
1 row in set (0.00 sec)
```

```
mysql>
```