Preprint PDF Available

Brain Tumor Detection Using KNN

December 2019
DOI:10.13140/RG.2.2.35232.12800

Authors:

Miss Priyanka Aiwale

Saniya mukram Ansari
Dr. D. Y. Patil Vidyapeeth

Abstract

Detection of Brain Tumor is actually a difficult task and the correct analysis of the Tumor structure is also difficult as a result an automatic method for the detection of Tumor is in usage nowadays. Undoubtedly, this saves the time as well as it gives more accurate results as in comparison to manual detection. The proposed method is a novel approach for detection Tumor along with the ability to calculate the area (%age) occupied by the Tumor in the overall brain cells. Firstly, Tumor regions from an MR image are segmented using an OSTU Algorithm. KNN& LLOYED are used for detecting as well as distinguishing Tumor affected tissues from the not affected tissues. 12 features are extracted like correlation, contrast, energy, homogeneity etc. by performing "wavelet transform on the converted gray scale image". For feature extraction DB5 wavelet transform is used.

International Journal of Scientific & Engineering Research Volume 10, Issue 12, December-2019
ISSN 2229-5518

Brain Tumor Detection Using KNN

Miss. Priyanka Aiwale,
E&TC Department, D.Y.P.S.O.E Pune, Maharashtra, India
E-mail - aiwalepriyanka9@gmail.com

Dr. Saniya Ansari
E&TC Department, D.Y.P.S.O.E Pune, Mahara India
E-mail- ansari.saniya6@gmail.com

Abstract- Detection of Brain Tumor is actually a difficult task and the correct analysis of the Tumor structur difficult as a result an automatic method for the detection of Tumor is in usage nowadays. Undoubtedly, this s time as well as it gives more accurate results as in comparison to manual detection. The proposed method is approach for detection Tumor along with the ability to calculate the area (%age) occupied by the Tumor in th brain cells. Firstly, Tumor regions from an MR image are segmented using an OSTU Algorithm. KNN& LLO used for detecting as well as distinguishing Tumor affected tissues from the not affected tissues. 12 features are e like correlation, contrast, energy, homogeneity etc. by performing wavelet transform on the converted gray scal For feature extraction DB5 wavelet transform is used.

Keywords- KNN& Lloyd, wavelet transform, tumour, MRI image

1. INTRODUCTION

The development of additional phones frequently shapes a mass of tissue called a development or tumour. Cerebrum Tumor is one of the real reasons for death among individuals. The manifestations of a mind Tumor rely upon Tumor size, sort and area. Indications might be caused when a Tumor pushes on a nerve or damages a piece of a cerebrum. Additionally, they might be caused when a Tumor obstructs the liquid that moves through and around the or when the mind swells since develop of liquid. Cerebral pains, queasiness and heaving, Changes in discourse, vision or hearing, issue adjusting or strolling, changes in temperament, identity or capacity to focus, issues with memory, muscle snapping or tingling, deadness or shivering in the arms or legs. Accurate identification of the type of mind variation among the majority is extremely basic for treatment arranging which could restrict the deadly outcomes. [2]

Detection of mind Tumor manually is a activity which consumes a lot of time and results are not accurate, shifts starting v specialist then onto the next. PC supported frameworks provides the appropriate outcor only being exactly same, these procedures mu at a brick pace with a mind set that the final their implemation on continuous applicatio helps in analyzation of brain Tumor along images as well as ultrasonic or X-Rays. MRI (Resonance Imaging) is an essential instrume in a great many fields of recommendation outfitted for producing a explicit image of an the body of human. X-ray remains for Magnetic Resonance Imaging scanner mak magnets for the objective of enrapturing as w energizing hydrogen cores (single proton) in humans, that produces a flag that can be disti and it's encoded spatially, bringing about imag body. The MRI machine produces radio re

International Journal of Scientific & Engineering Research Volume 10, Issue 12, December-2019
ISSN 2229-5518

(RF) beat that particularly ties just to hydrogen. The framework sends the beat to that particular territory of the body that should be inspected. Because of the RF beat, protons here retain the vitality expected to influence them to turn in an alternate heading. This is implied by the reverberation of MRI. The RF beat influences the protons to turn at the larmour

Jin Liu, Min Li, Jianxin Wang et al, st MRI based brain Tumor segmentation which and more attractive because of good soft tissue and non-invasive imaging of Magnetic R Imaging images. They purposed to make an introduction for MRI-based brain Tumor segr strategies. Then, the pre processing activities a

and the quality of the principle attractive field. [5]

Grouping of the mind Tumor is likewise a vital undertaking for treatment arranging. There are two sorts of Tumor which are-benevolent (non-destructive) and threatening (carcinogenic) tumours. Ordinary strategies include intrusive systems, for example, biopsy, lumbar cut and flag tap technique, to identify and group cerebrum Tumor into benevolent and harmful which are exceptionally agonizing and tedious. Wavelet investigation is a [illegible] to unveil various sections [illegible] flag as procedures for [illegible] images at a great many [illegible] eliminate much better reason of interest from itself as well as thusly inflates the behaviour of the image. What is more, for the process of compacting or de-noising a flag, equipment of it is done with no extensive debasement. It is actually of from almost all importance when there ought to develop an event of flimsy details, for instance, when there to be an event of therapeutic imaging [7]

2. RELATED WORK

In below section, various techniques are utilized in literature by various authors who summarized grounded on primary categories such as segmentation, feature extraction as well as classification method used.

Different methods Used in previous research work.

Pavel Dvorak and Bjoern Menze et al

even under treatment, patients don't make things considered over fourteen weeks after c [3]. Present day medicines incorporate radiotherapy, chemotherapy or all of them. very beneficial to make use of gliomas in clinical practices, as it is conceivable to proc arrangements giving corresponding informa actual division of glioma's as well as its intra- [illegible] for the regular [illegible] manual divisio[illegible] along with int[illegible] this manner, doctors more often than not util measures for assessment. Hence, accurate se or perhaps programmed techniques are needed

V. Karthikeyan, B. Menze and K. Sreed

the Tumor mass impact alter the couse of acti encompassing typical tissues. Along these emphasis is on planning structures as op creating handmade elements, which may particular learning. CNNs have been utilized few question acknowledgment [6], [12] as challenges of natural picture division [5]. Sinc operates over patches utilizing pieces, it has th of considering as well as being used wi information. In the arena of mind Tumor divi proposition additionally examine the utiliz CNNs [11].

J. Selvakumar, A. Lakshami & T. Ariv

analyzes the methodologies carried out by t

International Journal of Scientific & Engineering Research Volume 10, Issue 12, December-2019
ISSN 2229-5518

Intensification used in Mathematical Morphological [MM] theory on the dark images. Some Morphological Transformation have been processed through Block Analysis, Morphological Operation and Opening by Reconstruction on the Images with poor lighting.

illustrated. In Mathematical Morphology transformation that enables filtering of the Im new contour leads to closing by reconstruc opening by reconstruction. [13]

Bjoern Menze and Pavel Dvorak worke

various filtering techniques along with various background images of less intensity of light. [7]

Raunaq Rewari, with the utilization of pan morphological methods for the purpose of detection of various background features of the images with poor lighting has implemented the improvement in the digital images. The intial operator works with the information reterived from the block analysis while the next tranformation make use of the reconstruction opening employed to state various backgrounds. Lastly, through the images with different backgrounds, most of them light backgrounds, the performances of the proposed operators are processed. [8]

Stefan Bauer, Roland Wiest et al, the creators decided on 2D filters despite the fact that 3D filters can exploit the 3D way of the pictures, however, it builds computational load. The vast spatial and basic fluctuation in mind tumours is additionally an essential worry that we think about utilizing information growth. [9]

K. Sreedhar and B. Panlal, taken automation of brain Tumor segmentation continues to be a challenging task because of significant variations in its structure. In this paper, an automated brain Tumor segmentation algorithm using deep convolutional neural network (DCNN) is presented. [12]

Nikesh T. Gadare, Dr. S. A. Ladhake, et al, implemented few of the transformations which were morphological in nature and these were processed through block analysis, morphological operations followed by reconstruction opening of images with less intensity of light. Through Weber's Law Operator, Background detection and Image enhancement are

of various image modalities. All the images correlation used by local image patches. As there is a high correlation between close labe image; this feature is utilized in "local prediction" of the local label patches. segmentation tasks and for systematically e different parameters that are appropriate for t annotation of anatomical" structures, local fr prediction approach is used by them. [14]

Vaishnavi S. Mehekare, Dr.S.R., G from all among cerebrum tumours, Glioma most widely recognized, forceful, prompting long term in their most likely evaluation. T different proposals of automatic division str light of Convolutional Neural Networks), inve little kernel. The use of kernel permits outlin more deep design, apart from not having a de outcome against over fitting, provided the les of weights in the system.. [15]

3. PROPOSED METHODOLOGY

Image processing techniques are being used the bain tumour. For the purpose of detecting the MRI images we are using MATLAB softw The figure shown below is the block diagra proposed system.

International Journal of Scientific & Engineering Research Volume 10, Issue 12, December-2019
ISSN 2229-5518

- **Feature extraction:** For the purpose of e features from input image different opera needed to perform like entropy, correlation, energy, root mean square,

Figure 1: Block Diagram of proposed system

The detail description of system proposed is as follows:

- **Pre-processing:** It generally entails removal of background noise having frequency low, normalizing the intensity of the individual particles' images, masking of some portions of the images and removing reflections. Image pre-processing is the meth d to impro dat images prior to computational ocessing.
- **Image conversion:** I greyscale age or RGB image is that image the alue f ea pixel ly a single sample which carries information related to the intensity of light or in other words which reprensents only the amount of light. This sort of images is composed of various shades of gray colour. The range of the contrats from black colour at the weakest intensity to the white colour at the strongest. Keeping this in mind, the conversion of the image in black and white is done. As we understand Tumor is actually big enough to not deemed as tiny bound, therefore we are going to detach little pixel bound.
- **Wavelets transform:** The Daubechies wavelets, based on each wavelet type of this class, there is a scaling function (called the father wavelet) which generates an orthogonal multi resolution analysis. the scaling filter associated with the Daubechies wavelet specified by wname. Where f is a real-valued vector.

of classifying the tissue into normal or c
If the tissue is normal or not-infectious, n
detected displays on MATLAB output wi
in case the tissue is infectious or in simp
we can say that if Tumor is detected
following steps are taken.

Step 1: For smoothing the Tumor MRI In
pass and high pass filter are applied.

Step 2: For encircling the areas which are
OSTU Thresholding is used. Draw a
maximum possible size covering n
affecte area an next then other
small e are dra

Step 3: One cle ing exact center as
maxim m radius rcle from above
60% large radius is chosen so that it
complete affected areas called r
interest.

Step 4: For calculating the area of Tun
thresholding is performed. Threshol
be approximated as follow:

$$\%\, Area = \frac{no.of\ tumour\ pixels}{no.of\ total\ brain\ pixels}$$

Step 5: Segment the tumour

Step 6: Classify the tumour

Step 7: Display the resulting Image

4. FLOW CHART

Below figure shows the flow diagram.

6. RESULT

shows that all outperforming the existing me
classification on available dataset images.

Original Image & Resize Image

Low Pass Filtered Image

Figure3. Flow chart

High Pass Filtered Image

5. ALGORITHM

1. Start
2. Take input original MRI brain image
3. Convert it into gray scale
4. Filter the image using LPF & HPF
5. Morphological operations on image
6. Take OSTU Segmentation
7. LLOYD clustering to segment Tumor
8. Use KNN to find Equlidian distance
9. Hybrid feature extraction using 2 stage Discrete Wavelet Transform
10. Calculate contrast, colleration, Energy, Mean, RMS, Standard Deviation, Smoothness
11. Tran image using PNN & RBF
12. Classify the tumour
13. Find the percentage of Tumor
14. Stop

Morphological Processing

OSTU Thresholding

LLOYD Clustering

International Journal of Scientific & Engineering Research Volume 10, Issue 12, December-2019
ISSN 2229-5518

pass and High Pass filter along with morp

Segmented Tumour

Resulting Image

Fig 2. Image Processing Technique and the resulting Images of Tumour

Image Feature Parameter	Value
Contrast	4.6787
Correlation	0.5147
Energy	4659
Homogeneity	8131
Mean	3217
Standard Deviation	4570
Entropy	3.0240
RMS	0.3217
Variance	1.4588
Smoothness	0.9992
Kurtosis	21.9046
Skewness	4.1910

Table 1. Image Parameters of Feature Extraction

Brain Classifier	Percentage
Malignant	80%
Bennie	45%

Table 2. Percentage of the Brain Tumour

7. CONCLUSION

Features of Tumor cells are extracted efficiently from the MRI image which is further processed by classifier system. In this research work KNN & Lloyd are used to calculate the area occupied by brain tumour. Low classify using CNN & Deep Learning algo obtain good result of MRI image, it can be po using Neural Network.

8. REFERENCES

[1] Saniya Ansari, Dr U. S Sutar "an efficien of segmentation for handwriting Devna recognization" international journal of & engineering research (IJSER) volume May 2015 ISSN 2229-5518 pp230-235

[2] Saniya Ansari, Dr U. S Sutar "an efficien of segmentation for handwriting devna recognization" international journal of applications ISSN (0975-8887) volu September 2015 edition

[3] S. Baue et al., review of x-ra therapeuti picture e mination for min thinks ab t, P ics in solution and vol. 58, n 13, pp. 9 129, 2013.

[4] Sérgio Pereira, Adriano Pinto, Victor A Carlos A. Silva, "Brain Tumor Segr utilizing Convolutional Neural Network Images",2016.

[5] Pavel Dvorak and Bjoern Menze,"S Prediction with Convolutional Neural for Multimodal Brain Tumor Segm MICCAI-BRATS 2015.

[6] Sheela. V. K and Dr. S. Suresh Babu,"P Technique for Brain Tumor Detect Segmentation," International Research J Engineering and Technology Volume: (2014

[7] Jaypatel and Kaushal Doshi, "An investi Segmentation Method for recognition c in Brain", Advance in Electronic and Engineering, 2014.

picture division benchmark (wheips)," IEEE Transactions on Medical Imaging, vol. 34, no. 10, pp. 1993–2024, 2015.

[9] J. Selvakumar, A. Lakshami & T. Arivoli,"Brain Tumor Segmentation and Its Area Calculation utilizing K-mean Clustering and Fuzzy C-Mean Algorithm", IEEE-International Conference On Advances In Engineering, March30,2012.

[10] Raunaq Rewari, "Programmed Tumor Segmentation Using Convolutional Neural Network."

[11] Stefan Bauer, Roland Wiest and Lutz-P Nolte, "A Survey Of MRI-based restorative picture examination for Brain Tumor Studies".

[12] Vaishnavi Dr. P. Eswaran "Enhanced Color Image Enhancement Scheme utilizing Mathematical Morphology ", Volume 3, Issue 4, April 2013 IJARCSSE.

[13] V. Karthikeyan1, V. J. Vijayalakshmi, P. Jeyakumar, "A Novel Approach For The Enrichment Of Digital Images Morphological Operators", 2013.

[14] K.Sreedhar and B.Panl, Enhancement of image using morphological transformation, 2012.

[15] Nikesh T. Gadare, Dr. S. A. Ladhake, Prof. P. D. Gawande, "Mathematical Morphology based Image Enhancement and Background Detection" 2014.

[16] Pavel Dvoˇr´ak1,2 and Bjoern Menze3 Structured Prediction with Convolutional Neural Networks for Multimodal Brain Tumor Segmentation, 2015.

[17] Vaishnavi S. Mehekare, Dr.S.R.Ganorkar, "A Survey on Brain Tumor Detection Using Neural Network 2017.Samjith Raj C.P. and Shreeja R, weighted MRI 2017.

[18] Manisha, Radhakrishnan.B and Dr. Suresh, "Tumor Region Extraction usi Detection Method in Brain MRI Images"

[19] V. Zeljkovic1, C. Druzgalski2, Y. Zh Zhu1, Z. Xu1, D. Zhang1, P. M "Automatic Brain Tumor Detecti Segmentation in MR Images" 2014.

[20] Anatoly Sorokin, Evgeny Zhvansky, K Bocharov, and Vsevolod Shurkhay, A Potapov, "Multi-label classification Tumor mass spectrometry data" 2017.

[21] Alexis Arnaud, Florence Forbes, Coquery, Nora Collomb, Benjamin L and Emmanuel L. Barbier, "Fully A Lesion Localization and Charact Application to Brain Tumours usin parametric Quantitative MRI Data"2018.

[22] Swathi P S, "Brain Tumor Detect Classification Using Histogram Thresho

[23] Ms. Priya atil, Ms. ema Pawar, Ms. Pro Archal, "A Review Brain Tumor Segmentation and Detectio

[24] Moitra D and Mandal R" Review of Bra Detection using Pattern Re Techniques"2017

[25] Neha Rani" Brain Tumor Detect Classification with Feed Forward B Neural Network"2016.

[26] M. Avula, and Lakkhkula, et al., ``Bon from MRI Scan Imagery using Me intensity", The International Confe Electronic Computer Technology, pp, 2014.

Citations (0) References (21)

Review of Brain Tumor Detection using Pattern Recognition Techniques

Article Full-text available

Feb 2017 · IJCSE

Dipanjan Moitra

View Show abstract

Fully Automatic Lesion Localization and Characterization: Application to Brain Tumors Using Multiparametric Quantitative MRI Data

Article Full-text available

Jan 2018 · IEEE T MED IMAGING

Alexis Arnaud · Florence Forbes · Nicolas Coquery · Emmanuel L Barbier

View Show abstract

Structured prediction with convolutional neural networks for multimodal brain tumor segmentation

Article Full-text available

Oct 2015

Pavel Dvorak · Bjoern Menze

View Show abstract

Brain Tumor Detection and Classification with Feed Forward Back-Prop Neural Network

Article Full-text available

Jul 2016

Neha Rani · Sharda Vashisth

View Show abstract

Enhancement of Images Using Morphological Transformations

Article Full-text available

Mar 2012

Sreedhar Reddy Kollem · B. Panlal

View Show abstract

Multi-label classification of brain tumor mass spectrometry data In pursuit of tumor boundary detection method

Conference Paper

Nov 2017

Anatoly A Sorokin · Evgeny Zhvansky · Konstantin Bocharov · Alexander A. Potapov

View

Tumor region extraction using edge detection method in brain MRI images

Conference Paper

Apr 2017

Manisha · B. Radhakrishnan · L. Padma Suresh

View

Brain Tumor Segmentation Using Convolutional Neural Networks in MRI Images

Article

Mar 2016 · IEEE T MED IMAGING

Sérgio Pereira · Adriano Pinto · Victor Alves · Carlos A Silva

View Show abstract

Automatic brain tumor detection and segmentation in MR images

Vesna Zeljkovic · C. Druzgalski · Y. Zhang · P. Mayorga

View Show abstract

The multimodal mind Tumor picture division benchmark (whelps)

Jan 2015 · 1993-2024

B Menze

B. Menze et al., "The multimodal mind Tumor picture division benchmark (whelps)," IEEE Transactions on Medical Imaging, vol. 34, no. 10, pp. 1993-2024, 2015.

Show more

thus a programmed technique for the location of Tumor is in use these days. Without a doubt, this spares the time just as it gives increasingly exact outcomes as in contrast with manual location. The proposed technique is a hybrid methodology for discovery Tumor ... [Show full abstract]

Read more

Conference Paper

Segmentation of brain tumor from MRI images

October 2017

Sharda Vashisth · Pallavi Asthana

Read more

Article

Detection of Brain Tumor using KNN and LLOYED Clustering

February 2020 · International Journal of Engineering and Advanced Technology

Priyanka Aiwale · Saniya Ansari

Today world the brain tumor is life threatening and the main reason for the death. The growth of abnormal cells in brain leads to brain tumor. Brain tumor is categorized into malignant tumor and benign tumor. Malignant is cancerous whereas Benign tumor is non-cancerous. Diagnosing at earlier stage can save the person. It is actually a great challenge to find the brain tumor and classifying its ... [Show full abstract]

Read more

Conference Paper

Brain Tumor Segmentation Using Machine Learning Classifier

March 2019

I. Kalaivani · Sheryl Oliver · Dr. Pugalenthi Ramamurthy · [...] · G. Saranya

Read more

Article

3D Segmentation of Brain Tumor Imaging

January 2020

M. Sumithra · P. Madhumitha · S. Madhumitha · [...] · B. Poorni Vinayaa

Read more