

Big O Explained

can you explain me what does it really mean when we say $O(1)$, $O(n)$ $O(\log n)$, $n \log n$.. i undersand that $O(1)$ means it wil tlake same time no matter how how records are there... $O(n)$ means it will impact n records.. like shifting.. what abut others.2



can you explain me what does it really mean when we say $O(1)$, $O(n)$ $O(\log n)$, $n \log n$.. i undersand that $O(1)$ means it wil tlake same time no matter how how records are there... $O(n)$ means it will impact n records.. like shifting.. what about others

Yes — your understanding of **$O(1)$** and **$O(n)$** is basically right. The key is to stop thinking of Big-O as “how much time” and instead think:

How does the amount of work grow when the number of records n grows?

Let's build intuition.

1. $O(1)$ — Constant

The amount of work **doesn't depend on n** .

```
Java
arr[500];
```

Whether the array has 1,000 records or 10 crore records, accessing index 500 is essentially one operation.

1,000 → 1 operation

10,00,000 → 1 operation

10 crore → 1 operation

Think: **"Just do the job once."**

2. $O(n)$ — Linear

You potentially touch **every record**.

```
Java
for (int i = 0; i < n; i++) {
    System.out.println(arr[i]);
}
```

If you double the data, you roughly double the work.

Records	Work
10	10
100	100
1,000	1,000
1,00,000	1,00,000

Your **shifting** example can also be $O(n)$, because inserting/removing from certain positions in an array may require shifting many elements.

Think: "**Check/touch records one by one.**"

3. $O(\log n)$ — This is the interesting one

Here you're **not processing all records**.

You're repeatedly **cutting the problem down**, usually by half.

Classic example: **binary search**.

Suppose you have 1,000,000 sorted records.

Instead of checking:

```
1
2
3
4
5
...
1,000,000
```

you check the middle:

```
500,000
```

Then decide whether the answer is on the left or right.

Now you have:

```
1,000,000
  ↓
 500,000
  ↓
 250,000
  ↓
 125,000
  ↓
 62,500
  ↓
  ...
  ↓
   1
```

How many times can you divide 1,000,000 by 2?

About **20 times**.

Because:

```
2^20 ≈ 1,000,000
```

So:

1,000,000 records → ~20 steps

That's why $O(\log n)$ is extremely efficient.

Think:

"I don't go through the records. I keep eliminating half of them."

4. $O(n \log n)$ — Combination of the two


This commonly appears in efficient sorting algorithms such as **Merge Sort**.

The easiest intuition is:

You have n records, and you perform something that takes $\log n$ levels of work.

For example, imagine 1,000 records.

You repeatedly split:



The number of levels is approximately:

$$\log_2(n)$$

But at **each level**, you process approximately n elements.

So:

$$n \times \log n$$

For 1,000 records:

$$1000 \times \sim 10 \\ \approx 10,000 \text{ operations}$$

That's much better than:

$$O(n^2) \\ = 1,000 \times 1,000 \\ = 1,000,000$$

The really useful mental picture

Imagine $n = 1,000,000$.

Big-O	Rough amount of work	Mental model
$O(1)$	1	Directly access it
$O(\log n)$	~ 20	Keep cutting problem in half
$O(n)$	1,000,000	Go through records
$O(n \log n)$	$\sim 20,000,000$	Go through records across ~ 20 levels
$O(n^2)$	1,000,000,000,000	Compare/process records against each other

The last one is where things can get ugly.

$O(n^2)$

A simple example:

```
Java
for (int i = 0; i < n; i++) {
    for (int j = 0; j < n; j++) {
        // work
    }
}
```

For 1,000 records:

```
1,000 × 1,000
= 1,000,000
```

For 1,000,000 records:

```
1,000,000 × 1,000,000
= 1,000,000,000,000
```

So the important thing is **how fast the work grows**, not the exact number of operations.

One correction to your wording

You said:

$O(n)$ means it will impact n records

That's a good beginner intuition, but I'd refine it to:

$O(n)$ means the amount of work grows proportionally with n .

Because sometimes an $O(n)$ algorithm doesn't literally modify all n records—it might scan them, compare them, calculate something, etc.

And similarly:

$O(\log n)$ → work grows very slowly because the problem keeps getting smaller, typically by a factor such as 2.

$O(n \log n)$ → you have roughly n work at each of $\log n$ levels.

If you're learning this for **Java interviews**, the next really useful step is to connect these directly to **ArrayList, LinkedList, HashMap, TreeMap, binary search, sorting, and Java Collections**. That's where Big-O starts becoming practical rather than theoretical.

Files, images, and data analysis are unavailable until usage resets at 7:29 PM. Continue chatting with text only, or upgrade for more access.

ChatGPT can make mistakes. Check important info.