

**DESIGN AND ANALYSIS OF ALGORITHMS**  
**LAB WORKBOOK WEEK – 8**

**NAME: BH.SUMITRANAND**

**ROLL NUMBER: CH.SC.U4CSE24162**

**CLASS: CSE-B**

## **Huffman Coding:**

DATA ANALYTICS AND INTELLIGENCE LABORATORY

**Code:**

```

//CH.SC.U4CSE24120
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#define MAX 100
struct Node {
    char data;
    int freq;
    struct Node *left, *right;
};

struct Node* createNode(char data, int freq) {
    struct Node* node = (struct Node*)malloc(sizeof(struct Node));
    node->data = data;
    node->freq = freq;
    node->left = node->right = NULL;
    return node;
}

void sort(struct Node* arr[], int n) {
    for(int i = 0; i < n-1; i++) {
        for(int j = i+1; j < n; j++) {
            if(arr[i]->freq > arr[j]->freq) {
                struct Node* temp = arr[i];
                arr[i] = arr[j];
                arr[j] = temp;
            }
        }
    }
}

void printCodes(struct Node* root, int code[], int top,
               int *totalBits, int *totalFreq) {

    if(root->left) {
        code[top] = 0;
        printCodes(root->left, code, top+1, totalBits, totalFreq);
    }
    if(root->right) {
        code[top] = 1;
        printCodes(root->right, code, top+1, totalBits, totalFreq);
    }
}

```

```

        if(!root->left && !root->right) {
            printf("%c : ", root->data);
            for(int i = 0; i < top; i++)
                printf("%d", code[i]);
            printf(" (freq=%d, length=%d)\n", root->freq, top);
            *totalBits += root->freq * top;
            *totalFreq += root->freq;
        }
    }
}

int main() {
    char text[] = "DATA ANALYTICS AND INTELLIGENCE LABORATORY";
    int freq[256] = {0};
    for(int i = 0; text[i]; i++) {
        if(text[i] != ' ')
            freq[(int)text[i]]++;
    }
    struct Node* nodes[MAX];
    int n = 0;
    for(int i = 0; i < 256; i++) {
        if(freq[i] > 0) {
            nodes[n++] = createNode((char)i, freq[i]);
        }
    }
    while(n > 1) {
        sort(nodes, n);
        struct Node* left = nodes[0];
        struct Node* right = nodes[1];
        struct Node* newNode = createNode('$',
                                            left->freq + right->freq);

        newNode->left = left;
        newNode->right = right;
        nodes[0] = newNode;
        nodes[1] = nodes[n-1];
        n--;
    }
    struct Node* root = nodes[0];
    int code[100], totalBits = 0, totalFreq = 0;
    printf("Huffman Codes:\n\n");
    printCodes(root, code, 0, &totalBits, &totalFreq);
    printf("\nTotal Compressed Bits = %d\n", totalBits);
}

```

```

printf("\nTotal Compressed Bits = %d\n", totalBits);
float avg = (float)totalBits / totalFreq;
printf("Average Code Length = %.2f bits\n", avg);
return 0;
}

```

## Output:

```

 Huffman Codes:
R : 0000 (freq=2, length=4)
D : 0001 (freq=2, length=4)
C : 0010 (freq=2, length=4)
O : 0011 (freq=2, length=4)
L : 010 (freq=4, length=3)
T : 011 (freq=4, length=3)
N : 100 (freq=4, length=3)
Y : 1010 (freq=2, length=4)
S : 10110 (freq=1, length=5)
B : 101110 (freq=1, length=6)
G : 101111 (freq=1, length=6)
E : 1100 (freq=3, length=4)
I : 1101 (freq=3, length=4)
A : 111 (freq=7, length=3)

Total Compressed Bits = 138
Average Code Length = 3.63 bits

```

## Working:

Job Sequencing:

Let there be 14 jobs with profit of 22, 19, 28, 30, 21, 27, 25, 24, 14, 27, 19, 11

deadlines :- 3, 3, 8, 6, 7, 5, 10, 4, 6, 12, 13, 2, 14, 1

Construct the Huffman Coding for the word.

[ "DATA ANALYTICS AND INTELLIGENCE LABORATORY" ]

- Construct the Huffman tree
- Assigning binary codes for each character
- Calculate average code length

D-2 Y-2 G-1  
A-7 I-3 B-1  
T-4 C-2 O-2  
N-4 S-1 R-2  
L-4 E-3

Step 1 creating nodes for frequency and arrange in ascending order


① ① ⑧ ③ ② ② ② ② ③ ③ ④ ④ ④ ⑦  
S G B D Y C O R J E T N L A

arrange it in alphabetical order if same frequency


① ① ① ② ② ② ② ② ③ ③ ④ ④ ④ ⑦  
B G S C D O R Y E I L N T A

Step 2 Combine lowest frequency nodes into a first node


new frequency = Sum of both nodes and make the two nodes as left and right children




The newly appeared node shows




Step 3




rearrange




Step 4




rearrange




Step 5



rearrange




Step 6







Rearrange




Step-7




Rearrange




Step-8




Rearrange




Step-9




Rearrange









Step 10




rearrange




Step 11




rearrange



Step 12



rearrange





4

Ste-

75

8

$$F = -1011 \quad -4$$

$g = 1100 - 4$

L-000-3

N - 001-3

T - 010 - 3

A - 111 - 3

A - 111 - 3

Average code length  $\rightarrow \sum (d_i x_i)$

$$\frac{(1 \times 5) + (2 \times 5) + (1 \times 5) + (2 \times 5) + 2(4) + 2(4) + 2(4) + 3(4) + 3(7) + 4(9)}{1+1+1+2+2+2+2+2+2+3+3+4+4+4+4+2}$$

$$= \frac{138}{38} = 3.631 \quad = 3.631$$

Length of Huffman encoded msg = total len  $\times$  avg code length

$$= 38 \times 3.631$$

$$= 137.97$$

$$\approx 138 \text{ bits}$$

=

**Time Complexity:**

The algorithm repeatedly sorts the nodes in ascending order and merges the two smallest nodes.

Since Bubble Sort is used inside a loop, sorting is done multiple times.

- Best / Average Case =  $O(n^3)$
- Worst Case =  $O(n^3)$

**Space Complexity:**

Space is required for storing the Huffman tree and node list.

Recursion is used to generate codes.

- Average Case =  $O(n)$
- Worst Case =  $O(n)$