

EPISODE 01

THE ORIGINS OF JAVASCRIPT


THE 10-DAY LANGUAGE THAT CHANGED THE WEB FOREVER.

“FIRST, SOLVE THE PROBLEM. THEN, WRITE THE CODE.”

— BRENDAN EICH

WHY WAS JAVASCRIPT CREATED?

- In the mid-1990s, the web was growing fast.
- Web pages were static and boring.
- Netscape wanted to make the web more interactive.
- They needed a lightweight scripting language that could run in the browser.



EST. MAY 1995

THE CREATOR



← BRENDAN EICH

A programmer at Netscape.
Brilliant. Focused. Independent.

He was given a nearly impossible task with an impossible deadline.

THE 10-DAY CHALLENGE

In May 1995, Brendan Eich was given just 10 days to create a scripting language.

He started on May 6.
and finished around May 16.



10 DAYS

That's all it took.

The goal was simple:

Make the web alive.

- ✓ Easy to learn
- ✓ Lightweight
- ✓ Integrated with the browser
- ✓ Accessible to non-programmers


FROM MOCHA TO JAVASCRIPT

Mocha
(The original name)

LiveScript
(Netscape changed it)

JavaScript
(The name that stayed forever)

THE FIRST VERSION



JavaScript was first shipped in Netscape Navigator 2.0 in September 1995.

It could manipulate HTML, validate forms, and respond to user actions.

“I wanted a language that non-programmers could use to extend their environment. Something boring, safe, and predictable.”


— BRENDAN EICH

IMPACT

- It gave the web interactivity.
- It empowered a generation of developers.
- It became the language of the web.

From a 10-day experiment to the most popular language in the world.

A TIMELINE OF THE BEGINNING



“Every great story on the web begins with JavaScript.”

EPISODE 02

THE BROWSER WARS



THE BATTLE THAT MADE JAVASCRIPT FAMOUS.

1995 - 1999

1 THE INTERNET WAS EXPLODING



- Millions of new users were coming online.
- Every company wanted to own the web.

2 NETSCAPE



- The king of browsers.
- Market Share: ~90%
- Browser: Netscape Navigator

3 MICROSOFT ENTERS



Microsoft launches:

Internet Explorer

The war begins.

4 THE COMPETITION

NETSCAPE:

"We have JavaScript."



MICROSOFT:

"We'll make our own."

Microsoft created:

JScript

A JavaScript clone.

5 THE PROBLEM



Code working in Netscape often failed in Internet Explorer.

Developers had to write:

```
if (browser === "IE")
```

everywhere. 😞

6 BROWSER HELL

- ✓ Different APIs
- ✓ Different Features
- ✓ Different Bugs
- ✓ Different Behaviors



One website.
Two browsers.
Two headaches.

7 THE RESULT




- JavaScript adoption exploded.
- Every major browser needed scripting support.
- The web became interactive. ★

LESSON

Competition accelerated JavaScript's growth.

Without the Browser Wars, JavaScript might never have become the language of the web.



“Great wars don't just destroy. They build the future.” ★



STANDARDIZATION

THE BIRTH OF ECMASCRIPT



JavaScript was growing fast, but there was a problem...

THE PROBLEM

- ⊗ Every browser had its own version of JavaScript.
- ⊗ No standard.
- ⊗ Developers had to write different code for different browsers.
- ⊗ Browser compatibility was a nightmare.



The web needed one common language standard.

THE SOLUTION

Netscape submitted JavaScript to a standards organization:

ECMA

European Computer Manufacturers Association

ECMA decided to standardize the language.

ECMAScript



The official standard of JavaScript.

WHAT IS ECMASCRIPT?

- A standard that defines how JavaScript should work.
- It doesn't define how the browser looks.
- It defines the language features and behavior.



WHY IT MATTERED

- Brings consistency across browsers.
- Reduces the chaos.
- Makes JavaScript reliable.
- Opens the door for future growth.



“Standards turn chaos into compatibility.”

THE FIRST STANDARD



ECMAScript 1 was published.

- Basic syntax
- Data types
- Operators
- Functions
- Objects



ECMAScript 2

- Small improvements.
- Clarifications.
- More stability.



TIMELINE



“A standard today, a powerful future tomorrow.” ❤️



JAVASCRIPT'S DARK AGES



1999-2008

THE BROWSER COMPATIBILITY HELL

After the Browser Wars, JavaScript became powerful... but also messy.

1. THE CHAOS

- Every browser implemented JavaScript differently.
- Same code, different output.
- Features supported in one browser were missing in another.

```

Netscape
var a = [1, 2, 3];
a.join("-");
Result: 1-2-3
  
```



```

Internet Explorer
var a = [1, 2, 3];
a.join("-");
Result: 1,2,3
  
```




“Developers spent more time fixing bugs than building features.”



2. WHY DEVELOPERS SUFFERED

- ✗ Different JS Engines
- ✗ Different DOM Models
- ✗ Different Event Handling
- ✗ Different Bugs (and strange ones!)



```

if (navigator.appName == "Netscape") {
  // do this
} else if (navigator.appName == "Microsoft Internet Explorer") {
  // do that
} else {
  // pray
}
  
```

Real code from that era. 😞

3. WORKAROUNDS EVERYWHERE

- Libraries like jQuery didn't exist yet.
- Developers wrote custom fixes.
- Huge scripts, messy code, poor performance.



Fix one bug, break another.

5. THE IMPACT



- Despite the pain, JavaScript kept growing.
- Web apps became more complex.
- Developers demanded a solution.
- The need for a standard became impossible to ignore.


4. DEVELOPERS' MOOD

“JavaScript is amazing... but also pain.”




Memes weren't enough. We needed standards.

6. THE TURNING POINT (NEXT EPISODE)



A new hope was coming. A standard that would bring consistency, stability and trust back to JavaScript. Next Episode: The birth of ECMAScript.

WHERE WE ARE



“Every dark age prepares the world for a brighter future.”



ES5 & THE MODERN JAVASCRIPT FOUNDATION



2009

Making JavaScript more powerful, stable & developer-friendly.

1. WHAT IS ES5?

- ES5 (ECMAScript 5) was released in 2009.
- It brought much-needed improvements to the language.
- Focus: Reliability, Security & Performance.



2009

2. STRICT MODE

- Introduced "use strict".
- Helps catch common mistakes.
- Prevents silent errors.
- Makes JS a safer language.



Example

```
"use strict";
x = 10; // Error! x is not defined
```

3. KEY IMPROVEMENTS

- ✓ Better Error Handling
Catch errors early.
- { } JSON Support
Built-in JSON.parse() and JSON.stringify().
- More Array Methods
forEach, map, filter, reduce, every, some.
- String Improvements
trim(), split(), charAt(), etc.
- Object Enhancements
Object.create(), Object.defineProperty().



Smarter
Cleaner
Stronger

4. BETTER PERFORMANCE

- Engine optimizations made JS faster.
- Better memory management.



"ES5 didn't add flashy features. It made JavaScript solid."

5. REAL-WORLD IMPACT

- More reliable applications.
- Better tools & libraries.
- Paved the way for modern JavaScript.



BEFORE vs AFTER

Before ES5

- ❌ Inconsistent behavior
- ❌ Hard to debug
- ❌ Limited native features
- ❌ Browser compatibility issues



After ES5

- ✓ Consistent & predictable
- ✓ Easier debugging
- ✓ Powerful native features
- ✓ Better performance

ES5 was the bridge between the chaos of old JS and the power of modern JS.

JOURNEY SO FAR

EP 01

Origins



EP 02

Browser Wars



EP 03

Standardization (ECMAScript)



EP 04

Dark Ages (Browser Hell)



EP 05

ES5 & Modern Foundation



NEXT UP

ES6

Changes Everything!



"

Great foundations don't make noise, but they make everything possible.




JS

ES6+ THE GAME CHANGER

A NEW ERA FOR JAVASCRIPT


1. THE EVOLUTION

ES5 was good.

ES6 made it **GREAT**.

2. WHY ES6?

- Developers needed better ways to write code.
- Large applications were becoming complex.
- ES6 brings modern syntax, powerful features & better structure.



3. TOP ES6+ FEATURES

let & const

```
let x = 10;
const PI = 3.14;
```

Block scope
& no more
hoisting issues.

Arrow Functions

```
() => {}
```

Shorter syntax.
Lexical *this*.

Template Literals

```
`Hello,
${name}!`
```

String interpolation
made easy.

Destructuring

```
[a, b] = arr;
{x, y} = obj;
```

Extract values
easily.

Spread & Rest

```
...arr
...args
```

Work with arrays
& functions like
a pro.

Classes

```
class User {
  constructor() {}
}
```

Cleaner syntax
for OOP.

4. MODULES (IMPORT/EXPORT)

```
// math.js
export const add =
(a, b) => a + b;
```

```
// app.js
import { add }
from './math.js';
```

Finally, **native modules** in JavaScript!

5. DEFAULT PARAMETERS

```
function greet(name = 'Dev') {
  return `Hello, ${name}`;
}
```

No more
undefined
surprises!

6. PROMISES

```
fetch('/data')
  .then(res => res.json())
  .then(data => console.log(data));
```

Better async handling.
Goodbye callback hell!

7. THE IMPACT

- ☑ Cleaner Code
- ☑ Better Performance
- ☑ Easier Maintenance
- ☑ Modern Development

**ES6 MADE
JAVASCRIPT
THE LANGUAGE
OF THE WEB.**

JOURNEY SO FAR

EP 01

Origins



EP 02

Browser Wars



EP 03

Standardization
(ECMAScript)

EP 04

Dark Ages
(Browser Hell)

EP 05

ES5 & Modern
Foundation

EP 06

ES6+
Game Changer

“

GOOD CODE ISN'T JUST WORKING CODE.
IT'S CODE THAT'S EASY TO READ, MAINTAIN & SCALE.

”



ASYNC / AWAIT MAKES ASYNC SIMPLE.

++
++
++
++
++

.....

CLEANER CODE. BETTER READABILITY.
GOODBYE CALLBACK HELL.

01 THE PROBLEM: CALLBACK HELL

```
fetchData(data) => {  
  processData(data, (result) => {  
    saveData(result, (res) => {  
      sendEmail(res, () => {  
        console.log("Done!");  
      });  
    });  
  });  
};
```


HARD TO READ.
HARD TO MAINTAIN.
ERROR-PRONE. ❌

02 THE SOLUTION: ASYNC / AWAIT

```
async function process() {  
  const data = await fetchData();  
  const result = await processData(data);  
  const res = await saveData(result);  
  await sendEmail(res);  
  console.log("Done!");  
}
```

CLEAN. READABLE. MAINTAINABLE. ✅

03 HOW IT WORKS



Behind the scenes: Promises handle the heavy lifting.

04 EXAMPLE

```
async function getUser() {  
  try {  
    const res = await fetch('https://api.dev/users/1');  
    const user = await res.json();  
    return user;  
  } catch (error) {  
    console.error('Something went wrong!');  
  }  
}
```

USAGE

```
getUser().then(user => {  
  console.log(user.name);  
});
```

05 TRY... CATCH

```
async function loadData() {  
  try {  
    const data = await fetchData();  
    return data;  
  } catch (err) {  
    console.error(err.message);  
  } finally {  
    console.log('Done!');  
  }  
}
```

💡 Always handle errors gracefully.

06 TOP BENEFITS

- ✓ Makes async code look synchronous
- ✓ Easier to read & write
- ✓ Better error handling
- ✓ Improved debugging
- ✓ Goodbye callback hell!

07 AWAIT CAN BE USED WITH

- fetch()
- Promises
- Async functions
- Any promise-based API



08 IMPORTANT NOTES

- ❗ await only works inside async functions.
- ❗ Top-level await works in modules.
- ❗ It doesn't block the whole app, just the async function.

JOURNEY SO FAR


“ ASYNC / AWAIT ISN'T JUST SYNTAX.
IT'S A SUPERPOWER FOR MODERN JAVASCRIPT. ”



PROMISES

HANDLE ASYNC OPERATIONS
LIKE A PRO.

PROMISES ARE THE FOUNDATION
OF MODERN ASYNC JAVASCRIPT.



01 WHAT IS A PROMISE?

A Promise is an object that represents the eventual completion (or failure) of an asynchronous operation.



02 CREATING A PROMISE

```
const myPromise = new Promise((resolve, reject) => {
  const success = true;

  if (success) {
    resolve("Success!");
  } else {
    reject("Failed!");
  }
});
```

`resolve()` → when operation succeeds
`reject()` → when operation fails

03 CONSUMING A PROMISE

```
.then()

myPromise
  .then((result) => {
    console.log(result);
  })
  .catch((error) => {
    console.error(error);
  });
```

`.then()` → handles success
`.catch()` → handles failure

04 PROMISE STATES

PENDING
Initial state.
Neither fulfilled nor rejected.

FULFILLED
Operation completed successfully.

REJECTED
Operation failed.
Reason is provided.

05 CHAINING PROMISES

```
fetchUser()
  .then(user => fetchPosts(user.id))
  .then(posts => fetchComments(posts))
  .then(comments => {
    console.log(comments);
  })
  .catch(err => console.error(err));
```

Each `.then()` returns a new promise.
This allows chaining.

06 PROMISE METHODS

Promise.resolve(value) Returns a resolved promise.

Promise.reject(reason) Returns a rejected promise.

Promise.all([]) Resolves when all promises resolve. Fails fast.

Promise.race([]) Resolves/rejects as soon as one promise settles.

Promise.allSettled([]) Waits for all. Returns all results with status.

Promise.any([]) Resolves as soon as one promise resolves. Fails if all reject.

07 REAL LIFE EXAMPLE

Simulate API call with Promise.

```
function getData() {
  return new Promise((resolve, reject) => {
    setTimeout(() => {
      const ok = Math.random() > 0.3;
      ok ? resolve({ data: "Here is your data" }) :
        reject("Server Error");
    }, 1000);
  });
}
```

```
getData()
  .then(res => console.log(res.data))
  .catch(err => console.error(err));
```



08 ASYNC / AWAIT (WITH PROMISES)

```
async function loadData() {
  try {
    const res = await getData();
    console.log(res.data);
  } catch (err) {
    console.error(err);
  }
}
```

`loadData();`

Async/await is built on Promises.
It is just syntactic sugar.

09 BEST PRACTICES

- ✓ Always handle rejections.
- ✓ Use `async/await` for better readability.
- ✓ Don't forget `try/catch` with `await`.
- ✓ Keep promise chains flat and clean.
- ✓ Use `Promise.all` for parallel requests.

JOURNEY
SO FAR



“ PROMISES MAKE ASYNC CODE PREDICTABLE. BETTER CODE. BETTER YOU. ”



SCOPE

WHERE VARIABLES LIVE.
WHERE THEY DIE.



UNDERSTAND SCOPE.
WRITE BETTER, BUG-FREE CODE.

01 WHAT IS SCOPE?

Scope determines the accessibility of variables in different parts of your code.

If a variable is out of scope, you can't use it.



Scope is all about visibility.

02 TYPES OF SCOPE

- **Global Scope**
Accessible everywhere in the code.
- **Function Scope**
Accessible only inside the function.
- **Block Scope (let, const)**
Accessible only inside the block {}.

03 GLOBAL SCOPE

```
let name = 'JavaScript'; // global

function show() {
  console.log(name); // accessible
}

show(); // JavaScript
console.log(name); // JavaScript
```



Declared outside any function or block.
Accessible everywhere.

04 FUNCTION SCOPE (var)

```
function demo() {
  var x = 10;
  console.log(x); // 10
}

demo();
console.log(x); // ReferenceError
```



var is function-scoped.
Accessible only inside the function.

05 BLOCK SCOPE (let, const)

```
{
  let y = 20;
  const z = 30;
  console.log(y, z); // 20 30
}

console.log(y); // ReferenceError
console.log(z); // ReferenceError
```



let and const are block-scoped.
Accessible only inside the block {}.

06 NESTED SCOPE

```
let a = 'global';

function outer() {
  let b = 'outer';
  function inner() {
    let c = 'inner';
    console.log(a, b, c); // global outer inner
  }
  inner();
}
outer();
```



Inner scope can access outer scope variables.
Outer scope can't access inner.

07 SCOPE CHAIN

When looking for a variable, JavaScript searches:

- 1 Current scope
- 2 Outer scope
- 3 Global scope

```
let a = 'global';

function first() {
  let b = 'first';

  function second() {
    let c = 'second';
    console.log(a); // global
    console.log(b); // first
    console.log(c); // second
  }
  second();
}
first();
```

08 VAR vs LET/CONST IN LOOPS

var (function scoped)

```
for (var i = 0; i < 3; i++) {}
console.log(i); // 3
```

var i is accessible outside the loop. ❌

let (block scoped)

```
for (let i = 0; i < 3; i++) {}
console.log(i); // ReferenceError
```

let i is not accessible outside the loop. ✅



Always use let/const.
Avoid unexpected behavior.

BEST PRACTICES



Use let and const over var.



Keep variables in the smallest scope possible.



Avoid polluting the global scope.



Understand scope, avoid bugs.

JOURNEY SO FAR



EP 01



EP 02



EP 03



EP 04



EP 05



EP 06



EP 07



EP 08



EP 09

CLOSURES.

WHEN FUNCTIONS REMEMBER.
EVEN AFTER THEY'RE GONE.

JS

CLOSURES LET FUNCTIONS ACCESS VARIABLES
FROM THEIR OUTER SCOPE, EVEN AFTER
THE OUTER FUNCTION HAS FINISHED.

01 WHAT IS A CLOSURE?

A closure is a function that "closes over" variables from its outer (enclosing) function. It allows the inner function to access those variables even after the outer function has returned.



Closure = Function +
Preserved Lexical Scope

02 HOW CLOSURE WORKS

- 1 Outer function is executed.
- 2 It creates variables.
- 3 Inner function is returned.
- 4 Even after outer function finishes, inner function remembers those variables.

03 BASIC EXAMPLE

```
function outer() {  
  let message = "Hello, Closure!";  
  
  function inner() {  
    console.log(message); // Accessing  
  }  
  return inner;  
}  
  
const greet = outer(); // outer finished  
greet(); // "Hello, Closure!"
```



inner() remembers message
even after outer() is done.

04 COUNTER EXAMPLE

```
function counter() {  
  let count = 0;  
  return function () {  
    count++;  
    return count;  
  };  
}  
  
const c = counter();  
console.log(c()); // 1  
console.log(c()); // 2  
console.log(c()); // 3
```



count is preserved between
multiple calls.

05 MULTIPLE CLOSURES

```
function makeFunctions() {  
  let arr = [];  
  for (let i = 0; i < 3; i++) {  
    arr.push(function () {  
      console.log(i);  
    });  
  }  
  return arr;  
}  
  
const funcs = makeFunctions();  
funcs[0](); // 3  
funcs[1](); // 3  
funcs[2](); // 3
```



All functions share the same i.
Use let to fix it.

06 FIX WITH LET (BLOCK SCOPE)

```
function makeFunctions() {  
  let arr = [];  
  for (let i = 0; i < 3; i++) {  
    arr.push(function () {  
      console.log(i);  
    });  
  }  
  return arr;  
}  
  
const funcs = makeFunctions();  
funcs[0](); // 0  
funcs[1](); // 1  
funcs[2](); // 2
```




Each function gets its own
i using let.

07 PRACTICAL USES

- 🔒 Data Privacy: Keep variables private.
- ⚙️ Function Factories: Generate functions with preset data.
- 🕒 Maintaining State: Remember values between calls.
- 🔗 Callbacks & Event Handlers: Preserve context and data.

08 CLOSURE DIAGRAM



inner() has a reference to the
outer() scope.

09 COMMON MISTAKES

- ✗ Using var in loops.
- ✗ Forgetting closures keep references, which can cause memory leaks.
- ✗ Modifying outer variables unintentionally.
- ✗ Not understanding lexical scope.

KEY TAKEAWAYS



Closures capture the
lexical environment.



Inner functions can
access outer variables.



Powerful for encapsulation
and state management.



Understand scope,
write better code.

JOURNEY SO FAR



“ CLOSURES TURN FUNCTIONAL CODE INTO POWERFUL, RELIABLE AND ELEGANT SOLUTIONS. ”



ARRAYS.

STORE MANY VALUES.
WORK WITH EASE.

ARRAYS HELP YOU STORE, ACCESS,
AND MANIPULATE LISTS OF DATA EFFICIENTLY.

X X X
X X X
X X X
X X X
X X X



01 WHAT IS AN ARRAY?

An array is a special object used to store multiple values in a single variable.

```
let fruits = ["Apple", "Banana",  
             "Mango", "Orange"];
```

Ordered collection of values.
Zero-based indexing.

02 ACCESSING ELEMENTS

Use the index to access elements.

```
let fruits = ["Apple", "Banana",  
             "Mango", "Orange"];  
  
console.log(fruits[0]); // Apple  
console.log(fruits[2]); // Mango  
console.log(fruits[3]); // Orange
```

Index starts at 0.
fruits[0] is the first item.

03 MODIFYING ELEMENTS

You can change elements using their index.

```
let fruits = ["Apple", "Banana",  
             "Mango"];  
  
fruits[1] = "Blueberry";  
console.log(fruits);  
// ["Apple", "Blueberry", "Mango"]
```

Just assign a new value to the index.

04 ARRAY LENGTH

Use .length to get the number of elements.

```
let fruits = ["Apple", "Banana",  
             "Mango"];  
  
console.log(fruits.length);  
// 3
```

Length is always one more than the last index.

05 COMMON ARRAY METHODS

push() Adds an element to the end.

```
fruits.push("Grapes");  
// ["Apple", "Banana", "Mango", "Grapes"]
```

indexOf() Returns the index of an element.

```
fruits.indexOf("Mango");  
// 2
```

pop() Removes and returns the last element.

```
fruits.pop();  
// removes "Grapes"
```

includes() Checks if an element exists.

```
fruits.includes("Banana");  
// true
```

unshift() Adds an element to the beginning.

```
fruits.unshift("Papaya");  
// ["Papaya", "Apple", "Banana", "Mango"]
```

slice() Returns a portion of the array.

```
fruits.slice(1, 3);  
// ["Banana", "Mango"]
```

shift() Removes and returns the first element.

```
fruits.shift();  
// removes "Papaya"
```

join() Joins all elements into a string.

```
fruits.join(" - ");  
// "Apple - Banana - Mango"
```

06 LOOPING THROUGH ARRAYS

Use loops to iterate over arrays.

```
let fruits = ["Apple", "Banana", "Mango"];  
  
// For Loop  
for (let i = 0; i < fruits.length; i++) {  
  console.log(fruits[i]);  
}  
  
// For...of Loop (ES6)  
for (let fruit of fruits) {  
  console.log(fruit);  
}
```

For...of is cleaner and easier for simple iteration.

07 MULTI-DIMENSIONAL ARRAYS

Arrays can store other arrays.

```
let matrix = [  
  [1, 2, 3],  
  [4, 5, 6],  
  [7, 8, 9]  
];  
  
console.log(matrix[1][2]); // 6
```

Access row first, then column.
matrix[row][col]

08 SPREAD OPERATOR (...)

Copy or merge arrays easily.

```
let a = [1, 2, 3];  
let b = [4, 5, 6];  
let c = [...a, ...b];  
console.log(c); // [1, 2, 3, 4, 5, 6]
```

[1, 2, 3] ... [4, 5, 6] → [1, 2, 3, 4, 5, 6]

Great for copying, merging and passing arrays.

BEST PRACTICES

Use meaningful names for arrays.

Avoid using arrays as fixed-size lists.


Prefer built-in methods over manual loops.

Keep your arrays clean and simple.

JOURNEY SO FAR



“ ARRAYS MAKE YOUR CODE STRONGER. STRUCTURE TODAY, SCALE TOMORROW. ”



04 DELETING PROPERTIES

```
delete person.isDeveloper;
console.log(person);
// { name: 'Alice', age: 26
//   city: 'New York',
//   country: 'USA',
//   role: 'Engineer' }
```

	Deletes the property from the object.
---	---------------------------------------



Objects are mutable.
You can change them

08 OBJECT KEYS, VALUES, ENTRIES

```
console.log(Object.entries(user));
// [[{"id": 1}, {"name": "Bob"}, ...]]
```

Useful for looping
and data manipulation



this refers to the object that owns the method.

12 CHECKING PROPERTIES

```

// then property check
console.log(user.hasOwnProperty("name"));
// true

```

```

// then property check
console.log(user.hasOwnProperty("name"));
// true

```

Useful for safe access and validation.



```
property name = variable name
shortHand;
```

 Remove unused properties.12
note
1

1


“ OBJECTS TURN DATA INTO STRUCTURE. STRUCTURE POWERS SOLUTIONS. ”



DOM MANIPULATION.


BRING YOUR WEB PAGES TO LIFE.

THE DOM (DOCUMENT OBJECT MODEL) ALLOWS YOU TO ACCESS AND CHANGE HTML WITH JS.



01 WHAT IS DOM?

The DOM represents the structure of an HTML document as a tree. JS can access and modify it.



HTML becomes a tree that JS can work with.

02 SELECTING ELEMENTS

Select HTML elements using different methods.

```

document.getElementById("title");
document.getElementsByClassName("box");
document.getElementsByTagName("p");
document.querySelector(".box");
document.querySelectorAll("p");
  
```

Choose the right method for the right job.

03 CHANGING CONTENT

Change text, HTML or values of elements.

```

const heading = document.getElementById("title");
heading.textContent = "Hello!";
heading.innerHTML = "<b>Hello</b>";
const input = document.getElementById("name");
input.value = "Faisal";
  
```

Update what users see on the page.

04 CHANGING STYLES

Modify CSS styles using JavaScript.

```

const box = document.querySelector(".box");
box.style.color = "red";
box.style.backgroundColor = "#ffeb3b";
box.style.padding = "20px";
  
```

Style elements dynamically.

05 ADD ELEMENTS

Create new elements and add them to the page.

```

const newP = document.createElement("p");
newP.textContent = "I am new!";
document.body.appendChild(newP);
  
```

Create it. Add it. Show it.

06 REMOVE ELEMENTS

Remove elements from the DOM.

```

const p = document.querySelector("p");
p.remove();
// or
p.parentNode.removeChild(p);
  
```

Remove what you don't need.

07 TOGGLE CLASSES

Add, remove or toggle classes to change styles.

```

const box = document.querySelector(".box");
box.classList.add("active");
box.classList.remove("active");
box.classList.toggle("active");
  
```

Classes help you switch styles easily.

08 EVENT LISTENERS

Listen to user actions like clicks, typing, etc.

```

const btn = document.querySelector("button");
btn.addEventListener("click", () => {
  alert("Button clicked!");
});
  
```

React to user interactions.

09 PRACTICAL EXAMPLE

A simple todo app idea.

```

const input = document.getElementById("task");
const list = document.getElementById("list");
const btn = document.getElementById("add");
btn.addEventListener("click", () => {
  const li = document.createElement("li");
  li.textContent = input.value;
  list.appendChild(li);
  input.value = "";
});
  
```

DOM + JS = Powerful web experiences.

10 PARENT, CHILD, SIBLINGS

Navigate between elements.

```

const child = document.querySelector("li");
const parent = child.parentNode;
const firstChild = parent.firstChild;
const nextSibling = child.nextSibling;
  
```

Move around the DOM like a pro.

11 DATA ATTRIBUTES

Store extra information in HTML elements.

```

<div id="user" data-id="123" data-name="Faisal"></div>
  
```

```

const user = document.getElementById("user");
console.log(user.dataset.id); // 123
console.log(user.dataset.name); // Faisal
  
```

data-* attributes keep info close to elements.

12 BEST PRACTICES

- ✓ Select elements once and reuse.
- ✓ Avoid inline styles.
- ✓ Use classes for styling.
- ✓ Keep JS and HTML clean.
- ✓ Test in your browser.

Clean code. Better performance. Happy users.

KEY TAKEAWAYS


DOM connects HTML and JS.

You can change, create and remove elements.

Make your pages interactive and dynamic.

Small changes in DOM, big impact on the user experience.

JOURNEY SO FAR



“ YOU DON'T JUST BUILD WEBSITES. YOU BRING THEM TO LIFE. ”

EP 14

THE EVENT LOOP


Why JavaScript can do multiple things at once while being single-threaded

① WHAT IS THE EVENT LOOP?

The Event Loop is what allows JavaScript to perform non-blocking operations even though it is single-threaded.

Key Idea:

Do one thing at a time, but never get blocked.



② HOW IT WORKS

- ① JS code runs in the Call Stack.
- ② When it encounters an async operation, it sends it to Web APIs.
- ③ Once the operation is done, the callback is pushed to Task Queue.
- ④ Event Loop checks the Call Stack.
- ⑤ If Call Stack is empty, it takes the first task from the queue and pushes it to the stack.
- ⑥ Steps repeat.

③ EXAMPLE

```

console.log('Start');
setTimeout(() => {
  console.log('Timeout');
}, 0);
console.log('End');
  
```


Output:

```

Start
End
Timeout
  
```

- `setTimeout` goes to Web APIs.
- `'End'` runs immediately.
- After 0ms, callback goes to Task Queue.
- Event Loop moves it to Call Stack.
- `'Timeout'` is printed.

④ VISUAL FLOW



⑤ REMEMBER

- ✓ JS is single-threaded.
- ✓ Event Loop enables concurrency.
- ✓ Never blocks the Call Stack.
- ✓ Microtasks (Promise callbacks) have higher priority than Task Queue.
- ✓ Understand the flow, write better code!

Practice.
Observe.
Master JS.

EP 15

EXECUTION CONTEXT

The environment in which JavaScript code is executed.


① WHAT IS IT?

Every time JavaScript runs some code, it creates an Execution Context. It contains everything needed to run the code.

② TYPES OF EXECUTION CONTEXT

- Global Execution Context - Created when JS starts running.
- Function Execution Context - Created when a function is called.
- Eval Execution Context - Created when code runs inside `eval()`.


③ ANATOMY OF AN EXECUTION CONTEXT



④ HOW IT WORKS (EXAMPLE)


```

let x = 10;
function greet(name) {
  let msg = "Hi " + name;
  console.log(msg);
}
greet("Faisal");
    
```



- ① JS starts → Global Execution Context is created.
- ② greet() is called → Function Execution Context for greet is created.
- ③ greet() finishes → Its Execution Context is removed (destroyed).
- ④ Global Execution Context remains until the program ends.

⑤ VISUAL FLOW




⑥ KEY POINTS

- ✓ Only one Execution Context runs at a time (single-threaded).
- ✓ Contexts are pushed to the Call Stack.
- ✓ When a function finishes, its context is popped from the stack.
- ✓ Scope Chain helps in variable lookup.



Execution Context is the foundation of how JavaScript works. Understand it well, and the magic of JS becomes clear! ✨

CALL STACK (Behind the scenes)



EP 16

FUNCTIONS

The building blocks of reusable code.



① WHAT IS A FUNCTION?

A function is a block of code designed to perform a particular task. You can reuse it whenever you need.



Why Functions?

- ✓ Reusability
- ✓ Readability
- ✓ Maintainability

② FUNCTION DECLARATION

```
function greet(name) {
  console.log("Hello, " + name + "!");
}
greet("Faisal"); // Hello, Faisal!
```

→ Function Declaration (Hoisted)

③ FUNCTION EXPRESSION

```
const greet = function(name) {
  console.log("Hello, " + name + "!");
}
greet("Faisal"); // Hello, Faisal!
```

→ Function Expression (Not Hoisted)

④ ARROW FUNCTIONS

```
const add = (a, b) => {
  return a + b;
}
console.log(add(3, 4)); // 7
```

- Shorter syntax
- Doesn't have its own 'this'

⑤ PARAMETERS & ARGUMENTS

```
function multiply(x, y) {
  return x * y;
}
multiply(4, 5); // 20
```

- Parameters → Variables in function definition.
- Arguments → Values passed when calling the function.

⑥ DEFAULT PARAMETERS

```
function greet(name = "Guest") {
  console.log("Hi, " + name);
}
greet(); // Hi, Guest
greet("Ali"); // Hi, Ali
```

If no argument is passed, default value is used.

⑦ RETURN STATEMENT

```
function square(n) {
  return n * n;
}
let result = square(5);
console.log(result); // 25
```

return sends a value back to where the function was called.

⑧ KEY TAKEAWAYS

- ✓ Functions help in writing DRY (Don't Repeat Yourself) code.
- ✓ You can declare, express or use arrow functions.
- ✓ Parameters are placeholders, arguments are actual values.
- ✓ Use return to send a value back.
- ✓ Functions make code modular and easy to manage.



66 Functions are not just code. They are solutions you can reuse.



EP 17

THE THIS KEYWORD

'this' refers to the context in which a function is called.

'this' doesn't have a fixed value. It depends on how a function is invoked.

① WHAT IS 'this'?

'this' is a special keyword that refers to the object that is currently calling the function.

Think of 'this' as a placeholder that gets its value at runtime.

② HOW 'this' WORKS

The value of 'this' depends on how a function is called.

4 WAYS 'this' CAN BE BOUND

- Default Binding
- Implicit Binding
- Explicit Binding (call, apply, bind)
- New Binding (with new keyword)

⑤ EXPLICIT BINDING

We can explicitly set 'this' using call(), apply() or bind().

```
function greet() {
  console.log("Hi, " + this.name);
}
const user = { name: "Faisal" };
const admin = { name: "Admin" };
greet.call(user); // Hi, Faisal
greet.apply(admin); // Hi, Admin
```

bind() returns a new function with 'this' bound.

```
const greetUser = greet.bind(user);
greetUser(); // Hi, Faisal
```

③ DEFAULT BINDING

In non-strict mode, 'this' refers to the global object ('window' in browsers).

```
function show() {
  console.log(this);
}
show(); // Window (in browser)
```

In strict mode, 'this' is undefined.

```
'use strict';
function show() {
  console.log(this);
}
show(); // undefined
```

④ IMPLICIT BINDING

When a function is called as a method of an object, 'this' refers to that object.

```
const user = {
  name: "Faisal",
  greet() {
    console.log("Hi, " + this.name);
  }
};
user.greet(); // Hi, Faisal
```

The object before the dot becomes the context.

⑥ NEW BINDING

When a function is used with 'new', 'this' refers to the new object being created.

```
function Person(name) {
  this.name = name;
}
const p1 = new Person("Faisal");
console.log(p1.name); // Faisal
console.log(p1 instanceof Person); // true
```

'this' in constructor functions refers to the new empty object that is created.

⑦ ARROW FUNCTIONS & 'this'

- Arrow functions do not have their own 'this'.
- They inherit 'this' from their surrounding (lexical) scope.

```
const user = {
  name: "Faisal",
  regular() {
    console.log(this.name); // Faisal
  },
  arrow: () => {
    console.log(this.name); // undefined
  }
};
user.regular(); // Faisal
user.arrow(); // undefined
```

Arrow functions are great for callbacks where you don't want 'this' to change.

⑧ KEY TAKEAWAYS

- ✓ 'this' is determined by how a function is called, not where it is written.
- ✓ Default binding → global object (or undefined in strict mode).
- ✓ Implicit binding → object before the dot.
- ✓ Explicit binding → call(), apply(), bind().
- ✓ New binding → new object created.
- ✓ Arrow functions inherit 'this' from their parent scope.

EP 18

MEMORY MANAGEMENT

How JavaScript manages memory automatically so you can focus on building, not cleaning.




1 WHAT IS MEMORY MANAGEMENT?

Memory management is the process of allocating, using and releasing memory during program execution.


In JavaScript, this is done automatically by a mechanism called Garbage Collection.

2 HOW MEMORY WORKS IN JS



3 GARBAGE COLLECTION (GC)


GC is the process of finding and removing memory that is no longer used.



Unreachable objects are cleaned up and memory is freed!

4 EXAMPLE

```
let user = { name: 'Ali' };
let data = user;
user = null; // original reference gone
// but object is still reachable via 'data'
data = null; // now object is unreachable
// GC will remove it from memory
```



5 COMMON MEMORY LEAKS

- Global variables (accidentally creating globals).
- Unremoved event listeners.
- Closures holding onto unused data.
- Timers / intervals not cleared.
- Detached DOM elements.



Leaks keep memory alive that you no longer need!

6 BEST PRACTICES

- ✓ Declare variables with `let` and `const`.
- ✓ Remove event listeners when not needed.
- ✓ Clear timers / intervals.
- ✓ Avoid unnecessary globals.
- ✓ Nullify references when done (if needed).
- ✓ Keep closures small and intentional.



KEY TAKEAWAY

JavaScript automatically manages memory using Garbage Collection. Write clean code, avoid leaks, and let the engine handle the rest!



EP 19

PROTOTYPE & PROTOTYPE CHAIN

The mechanism behind inheritance in JavaScript.




① WHAT IS A PROTOTYPE?

Every JavaScript object has a hidden property called `[[Prototype]]` (or `__proto__`). It is a reference to another object. That object is called its **prototype**.



Prototypes allow objects to inherit properties and methods from other objects.

② HOW IT WORKS



If a property or method is not found in the object, JavaScript looks for it in its **prototype**.


③ EXAMPLE

```
const person = {
  name: "Ali"
};

person.greet = function() {
  console.log("Hi, I'm Ali");
};


const user = Object.create(person);
user.age = 20;

console.log(user.name); // Ali
user.greet();           // Hi, I'm Ali
```



④ THE PROTOTYPE CHAIN

JavaScript looks up properties in a chain of prototypes until it finds them.



⑤ KEY TAKEAWAYS

- ✓ Every object has a prototype (except null).
- ✓ Prototypes enable inheritance.
- ✓ JS uses the prototype chain to look up properties and methods.
- ✓ `Object.create()` links an object to a prototype.
- ✓ The chain ends at `Object.prototype`, whose prototype is null.



Prototypes are the backbone of JavaScript's inheritance model. Instead of copying properties, objects can access them from their prototypes through the prototype chain. This makes JS powerful, efficient and memory-friendly.



EP 20

HOISTING

Moving declarations to the top before code execution.

Hoisting is JavaScript's default behavior of moving declarations to the top of their scope before code execution.

① WHAT IS HOISTING?

During the creation phase of Execution Context, JavaScript moves all declarations to the top of their scope.



Only declarations are hoisted, not initializations or assignments.

② TYPES OF HOISTING

VARIABLE HOISTING

var variables are hoisted and initialized as undefined.

Ex:
`console.log(a); // undefined`
`var a = 10;`

FUNCTION HOISTING

Function declarations are hoisted with their entire function body.

Ex:
`sayHi(); // Hi!`
`function sayHi() {`
 `console.log("Hi!");`
`}`

③ VAR HOISTING

```
console.log(a); // undefined
var a = 10;
console.log(a); // 10
```

} Declaration is hoisted to the top and initialized as undefined.

How JS sees it:

```
var a;           // hoisted
console.log(a); // undefined
a = 10;
console.log(a); // 10
```

④ LET & CONST HOISTING (TDZ)

let and const are hoisted but not initialized. They stay in the Temporal Dead Zone (TDZ) until the actual declaration.

```
console.log(b);
let b = 20;
```

✗ ReferenceError



TDZ (Temporal Dead Zone)

The time between hoisting and initialization where the variable exists but cannot be used.

⑤ FUNCTION EXPRESSIONS

```
sayHi(); // TypeError: sayHi is not a function
var sayHi = function() {
  console.log("Hi!");
};
```

How JS sees it:

```
var sayHi;           // hoisted (undefined)
sayHi();             // TypeError
sayHi = function() {
  console.log("Hi!");
};
```

Only the variable declaration is hoisted, not the function expression.

⑥ HOISTING IN ACTION

```
console.log(x); // undefined
console.log(y); // ReferenceError
console.log(add); // [Function: add]
```

```
var x = 5;
let y = 10;
```

```
function add(a, b) {
  return a + b;
}
```

var x is hoisted and initialized as undefined.

let y is hoisted but not initialized. (TDZ)

Function declaration is hoisted with its entire body.

⑦ KEY TAKEAWAYS

- ✓ Hoisting happens in the creation phase of Execution Context.
- ✓ var declarations are hoisted and initialized as undefined.
- ✓ let and const are hoisted but stay in the TDZ.
- ✓ Function declarations are fully hoisted.
- ✓ Function expressions are not hoisted, only the variable is.



Hoisting is not magic. It's just JavaScript preparing the stage before the show begins.



EP 21

CALL STACK

The structure that keeps track of function calls in JavaScript.



① WHAT IS THE CALL STACK?

The Call Stack is a data structure that follows LIFO (Last In, First Out). It keeps track of where we are in the program.


💡 Whenever a function is called, it is pushed onto the stack. When it finishes, it is popped off.

② HOW IT WORKS


① Global Execution
Global context is pushed onto the stack.



② Function Call
When a function is called, it is pushed on top.



③ Another Call
Another function call is pushed on top.



④ Function Returns
When a function finishes, it is popped off.



Push → ← Pop

③ EXAMPLE


```
function first() {
  second();
}

function second() {
  third();
}

function third() {
  console.log("Hello!");
}

first(); // Execution starts here
```

Step by Step Execution



The Call Stack is empty when the Global context is popped.

6. first() finishes (popped)



Now only the Global context remains. ★

④ KEY POINTS

- JavaScript is single-threaded, which means it has one Call Stack.
- Only one function runs at a time.
- If an error occurs, the stack trace shows the order of function calls.
- Infinite recursion can overflow the stack and cause an error. ⚠️

⑤ STACK OVERFLOW (EXAMPLE)

```
function loop() {
  loop(); // calling itself
}

loop();
```

This will keep pushing loop() onto the stack until the stack size limit is reached.
Result: RangeError: Maximum call stack size exceeded.



Stack Overflow!

⑥ KEY TAKEAWAYS

- ✓ The Call Stack tracks function calls.
- ✓ It follows LIFO (Last In, First Out).
- ✓ Functions are pushed when called and popped when they return.
- ✓ Only one function executes at a time.
- ✓ Stack trace helps in debugging.
- ✓ Too many calls without returning can cause a stack overflow.



The Call Stack keeps JavaScript organized, one call at a time.



EP 22

LEXICAL ENVIRONMENT & SCOPE CHAIN

How JavaScript finds variables.

JavaScript uses Lexical Scoping — which means scope is determined by where something is written, not where it is executed.


1 WHAT IS A LEXICAL ENVIRONMENT?

A Lexical Environment is a data structure that holds identifier-variable mappings and a reference to its outer (parent) lexical environment.



It is created whenever a function is called and is destroyed when the function finishes execution.

2 COMPONENTS OF A LEXICAL ENVIRONMENT




3 HOW THE SCOPE CHAIN WORKS

When JavaScript looks for a variable, it searches in the current lexical environment first.

If not found, it moves to the outer environment.

This continues until the variable is found or the global scope is reached.



This chain of environments is called the SCOPE CHAIN.

4 EXAMPLE

```
const a = "Global";

function outer() {
  const b = "Outer";


  function inner() {
    const c = "Inner";
    console.log(a); // Global
    console.log(b); // Outer
    console.log(c); // Inner
  }
  inner();
}

outer();
```

`inner()` tries to find variables in this order:

1. its own env (c)
2. outer env (b)
3. global env (a)
4. null

SCOPE CHAIN VISUALIZATION (when `inner()` runs)



If not found in any environment, JavaScript returns `ReferenceError`.

5 LEXICAL SCOPE VS DYNAMIC SCOPE

LEXICAL SCOPE (JavaScript)	DYNAMIC SCOPE (Other languages)
• Determined at the time of writing code. • Based on where a function is defined. • More predictable and easier to optimize.	• Determined at the time of function call. • Based on the call stack. • Harder to predict and reason about.



JavaScript uses Lexical Scope. That's why `inner()` can access outer variables even if it is called from somewhere else!

6 KEY TAKEAWAYS

- ✓ A Lexical Environment stores variables and a reference to its outer environment.
- ✓ The Scope Chain is the path JS follows to find variables.
- ✓ JS uses Lexical Scope (where defined).
- ✓ Environment is created at function call and destroyed when function finishes.
- ✓ Closures work because functions "remember" their lexical environment.



Understanding Lexical Environment is the key to understanding closures, scope, and hoisting deeply.

EP 23

TEMPORAL DEAD ZONE (TDZ)

The hidden time between entering scope and initializing a variable.



1 WHAT IS TDZ?


The Temporal Dead Zone (TDZ) is the period from the start of a scope until a variable is initialized (declared with `let` or `const`). During this time, the variable exists but cannot be accessed.



It only applies to `let` and `const`, not to `var`.

2 WHEN DOES TDZ HAPPEN?

TDZ happens in every block scope `{}` and function scope for `let` and `const`.



Accessing a variable in the TDZ throws a `ReferenceError`.

`ReferenceError: Cannot access 'x' before initialization`

3 EXAMPLE


```
console.log(a); // ReferenceError
let a = 10;     // Initialization
console.log(a); // 10

{
  console.log(b); // ReferenceError
  const b = 20;   // Initialization
  console.log(b); // 20
}
```

What's happening?

- At the start of the scope, 'a' and 'b' exist in memory but are uninitialized.
- Any access before initialization is in the TDZ.
- After initialization, they can be used safely.

Memory Timeline (for 'a')



4 TDZ VS VAR HOISTING

let / const

- Hoisted but not initialized.
- In TDZ until declaration line.
- Access before init → `ReferenceError`

var

- Hoisted and initialized as `undefined`.
- Can be accessed before declaration.
- No TDZ.

Example

```
let x = 5;
console.log(x); // ReferenceError
let x = 5;

var y = 5;
console.log(y); // undefined
var y = 5;
```

Feature	let / const	var
Hoisted?	✓	✓
Initialized?	No	Yes (undefined)
TDZ?	Yes	No
Access before declaration?	<code>ReferenceError</code>	<code>undefined</code>

5 REAL WORLD EXAMPLE

```
function demo() {
  console.log(msg); // ReferenceError
  if (true) {
    let msg = "Hello!"; // TDZ until here
  }
  demo();
}
```



Even though the block runs, trying to access `msg` before it is initialized causes an error because it's in the TDZ.

6 KEY TAKEAWAYS

- ✓ TDZ exists for `let` and `const` (not for `var`).
- ✓ A variable cannot be accessed before initialization.
- ✓ TDZ starts at the beginning of the scope and ends at the declaration.
- ✓ Accessing during TDZ throws `ReferenceError`.
- ✓ TDZ helps catch bugs early and makes JS more predictable.



TDZ is JavaScript's way of saying: "You can't use it... until it's ready!"



EP 24

EVENT DELEGATION

Handle events efficiently using bubbling to our advantage.


Instead of attaching an event listener to every child node, attach it to their common parent! ☆

① WHAT IS EVENT DELEGATION?

Event Delegation is a technique where we attach a single event listener to a parent element, and handle events triggered on its child elements using event bubbling.

Events bubble up from the target element to its ancestors. Delegation uses this behavior to manage events efficiently.

② HOW EVENT BUBBLING WORKS



The event triggered on bubbles up to , then <div>, and finally to document.

Delegation relies on this bubbling behavior. ♥

③ EXAMPLE

HTML

```

<ul id="menu">
  <li> Home </li>
  <li> About </li>
  <li> Services </li>
  <li> Contact </li>
</ul>
  
```

Without Event Delegation ✗

```

const items = document.querySelectorAll("#menu li");
items.forEach(item => {
  item.addEventListener("click", function () {
    console.log("Clicked!", this.textContent);
  });
});
  
```

↳ Listener added to every (Not efficient!)

With Event Delegation ✓

```

document.getElementById("menu")
  .addEventListener("click", function (e) {
    if (e.target.tagName === "LI") {
      console.log("Clicked!", e.target.textContent);
    }
  });
  
```

↳ Only one listener on parent !

④ HOW IT WORKS (WITH DELEGATION)

```

document.getElementById("menu")
  .addEventListener("click", function (e) {
    if (e.target.tagName === "LI") {
      console.log("Clicked!", e.target.textContent);
    }
  });
  
```


e → event object
e.target → the element that was actually clicked
We check if the clicked element is , then handle it.

⑤ REAL WORLD BENEFITS

- ✓ Works for existing and future elements (even dynamically added).
- ✓ Better performance (fewer listeners).
- ✓ Cleaner code.
- ✓ Less memory usage.

More efficient & scalable! 📈

⑥ DELEGATION IN ACTION (DYNAMIC ELEMENTS)



Even though "Blog" was added after the listener was attached, clicking it still works!
That's the power of Event Delegation ☆

```

document.getElementById("menu")
  .addEventListener("click", function (e) {
    if (e.target.tagName === "LI") {
      console.log("Clicked!", e.target.textContent);
    }
  });
  
```

No need to re-attach listener for new items! ♥

⑦ KEY TAKEAWAYS



- ✓ Event Delegation uses event bubbling.
- ✓ Attach the listener to a parent, not to every child.
- ✓ Use e.target to find the actual element that triggered the event.
- ✓ It's efficient, scalable and works great for dynamic content.

Delegate once, handle many! 😊

Event Delegation is not just a technique, it's a smart way to write better JavaScript. ☆

EP 25

FETCH API

The modern way to make network requests in JavaScript.

Fetch API provides an interface for fetching resources (data) over the network. It returns Promises and is built on top of the Request and Response objects.

1 WHAT IS FETCH API?

Fetch API is a modern, promise-based interface provided by browsers to make HTTP requests to servers. It is an alternative to older methods like XMLHttpRequest.

Fetch is built into modern browsers, so no extra library is needed!

3 FETCH REQUEST METHODS

Method	Description	Example Use
GET	Retrieve data from server	Get user profile
POST	Send data to server to create something	Create a new user
PUT	Update existing data completely	Update user info
PATCH	Update existing data partially	Update user email
DELETE	Delete data from server	Delete user account

2 BASIC SYNTAX

```
fetch(url, options)
  .then(response => response.json())
  .then(data => console.log(data))
  .catch(error => console.error(error));
```

- fetch() returns a Promise.
- The response is resolved even if the HTTP status is 404 or 500 (only network errors are rejected).
- You must check response.ok or response.status.

4 EXAMPLES

GET Request

```
fetch('https://jsonplaceholder.typicode.com/posts/1')
  .then(res => res.json())
  .then(data => console.log(data))
  .catch(error => console.error('Error:', error));
```

POST Request

```
fetch('https://jsonplaceholder.typicode.com/posts', {
  method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify({
    title: 'Hello World',
    body: 'This is a post',
    userId: 1
  })
})
  .then(res => res.json())
  .then(data => console.log(data));
```

PUT Request

```
fetch('https://jsonplaceholder.typicode.com/posts/1', {
  method: 'PUT',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify({ id: 1, title: 'Updated Title' })
})
  .then(res => res.json())
  .then(data => console.log(data));
```

DELETE Request

```
fetch('https://jsonplaceholder.typicode.com/posts/1', {
  method: 'DELETE'
})
  .then(res => {
    if (res.ok) console.log('Deleted successfully');
  })
  .catch(error => console.error('Error:', error));
```

5 REQUEST & RESPONSE OBJECTS

Request Options (2nd parameter)

```
{
  method: 'GET', // or POST, PUT, etc.
  headers: { // set headers
    'Content-Type': 'application/json',
    'Authorization': 'Bearer token'
  },
  body: JSON.stringify(data) // for POST, PUT
}
```

Response Object

The Response object has useful properties and methods:

- ok → true if status is 200-299
- status → HTTP status code
- statusText → e.g. 'Not Found'
- json() → parses JSON body
- text() → parses text body
- headers → response headers

6 CHECKING RESPONSE STATUS

```
fetch('https://api.example.com/data')
  .then(response => {
    if (!response.ok) {
      throw new Error('HTTP error! Status: ${response.status}');
    }
    return response.json();
  })
  .then(data => console.log(data))
  .catch(error => console.error('Fetch error:', error));
```

Always handle errors properly with .catch() or try...catch (with async/await).

7 FETCH WITH ASYNC / AWAIT

```
async function getData() {
  try {
    const res = await fetch('https://jsonplaceholder.typicode.com/users');
    if (!res.ok) throw new Error('Status: ${res.status}');
    const data = await res.json();
    console.log(data);
  } catch (err) {
    console.error('Error:', err);
  }
  getDetail();
}
```

Why Async/Await?

- ✓ Cleaner code
- ✓ Easier error handling
- ✓ Looks synchronous but is still async under the hood

8 KEY TAKEAWAYS

- ✓ Fetch API is promise-based and modern.
- ✓ Use fetch() to make network requests.
- ✓ It supports all major HTTP methods.
- ✓ Always handle errors and check response status.
- ✓ Async/Await makes code cleaner and easier to read.



Fetch API is the foundation for modern web apps to communicate with servers. Master it, and you can build anything that talks to the internet!



EP 26

LOCALSTORAGE

Store data in the browser
with no expiration time.


LocalStorage stores data with no expiration date. Data is not sent to the server.

1 WHAT IS LOCALSTORAGE?

LocalStorage is a Web Storage API that allows us to store key-value pairs in the browser with no expiration time.

- ✓ Data persists even after the browser is closed.
- ✓ Stores only strings (objects need to be converted to JSON).
- ✓ Domain specific (data is not shared across different domains).
- ✓ Storage limit is around 5-10 MB.

2 HOW LOCALSTORAGE WORKS



★ Data is stored in the browser, not on the server. It is specific to the domain (e.g., example.com).

3 LOCALSTORAGE METHODS

Method	Description	Example
setItem(key, value)	Stores a key-value pair	localStorage.setItem('key', 'value');
getItem(key)	Gets the value by key	localStorage.getItem('key');
removeItem(key)	Removes a key-value pair	localStorage.removeItem('key');
clear()	Removes all data	localStorage.clear();
key(index)	Gets the key at the specified index	localStorage.key(0);
length	Returns the number of stored items.	localStorage.length;

4 EXAMPLES

```
// Store data
localStorage.setItem('name', 'John');
localStorage.setItem('age', '25');
localStorage.setItem('isLoggedIn', 'true');


// Get data
let name = localStorage.getItem('name');
let age = localStorage.getItem('age');
console.log(name); // John

// Remove data
localStorage.removeItem('age');

// Clear all data
localStorage.clear();
```

Note:
Only strings can be stored.
To store objects or arrays, use JSON.stringify() and JSON.parse().

5 STORE & RETRIEVE OBJECTS



6 CHECKING IF DATA EXISTS

```
if (localStorage.getItem('token')) {
  console.log('Token exists');
} else {
  console.log('Token not found');
}
```

💡 Useful for maintaining login sessions, user preferences, theme, etc.

7 PRACTICAL EXAMPLE - THEME PREFERENCES

Save Theme

```
function saveTheme(theme) {
  localStorage.setItem('theme', theme);
}

// Save 'dark' theme
saveTheme('dark');
```

Load Theme

```
function loadTheme() {
  const theme = localStorage.getItem('theme');
  || 'light'; // default theme
  document.body.setAttribute('data-theme', theme);
}

loadTheme();
```

HTML + CSS

```
body[data-theme='dark'] {
  background: #121212;
  color: #ffffff;
}
body[data-theme='light'] {
  background: #ffffff;
  color: #000000;
}
```

Result

User's theme preference is saved and applied even after closing the browser.

KEY TAKEAWAYS

- ✓ LocalStorage stores data with no expiration.
- ✓ Data is stored in key-value pairs as strings.
- ✓ Use JSON methods to store objects or arrays.
- ✓ Great for saving user preferences and persistent data.

EP 27

SESSIONSTORAGE

Store data for a single session
(tab/window)


SessionStorage is similar to LocalStorage but the data is cleared when the page session ends.

1 WHAT IS SESSIONSTORAGE?

SessionStorage is a Web Storage API that stores data for a single page session. The data is cleared when the tab or window is closed.

- ✓ Data exists only for the duration of the page session.
- ✓ Data is not shared between tabs or windows.
- ✓ Survives page refresh (FS).
- ✓ Storage limit is around 5-10 MB.

2 HOW SESSIONSTORAGE WORKS



Every tab/window has its own sessionStorage. Closing the tab ends the session and clears the data.

3 SESSIONSTORAGE METHODS

Method	Description	Example
setItem(key, value)	Stores a key-value pair.	sessionStorage.setItem('key', 'value');
getItem(key)	Gets the value by key.	sessionStorage.getItem('key');
removeItem(key)	Removes a key-value pair.	sessionStorage.removeItem('key');
clear()	Removes all data.	sessionStorage.clear();
key(index)	Gets the key at the specified index.	sessionStorage.key(0);
length	Returns the number of stored items.	sessionStorage.length;

4 EXAMPLES

```
// Store data
sessionStorage.setItem('name', 'Alice');
sessionStorage.setItem('role', 'Admin');

// Get data
let name = sessionStorage.getItem('name');
console.log(name); // Alice

// Remove data
sessionStorage.removeItem('role');

// Clear all data
sessionStorage.clear();
```

Only strings can be stored. To store objects or arrays, use `JSON.stringify()` and `JSON.parse()`.

5 SESSIONSTORAGE VS LOCALSTORAGE

Feature	SessionStorage	LocalStorage
Lifetime	Until tab/window is closed	No expiration (until cleared)
Scope	Per tab/window	Per origin (domain)
Data Sharing	Not shared between tabs	Shared across all tabs of same origin
Survives Refresh	Yes	Yes
Storage Limit	~5-10 MB	~5-10 MB

- Use SessionStorage for temporary data (e.g., form data, session info).
- Use LocalStorage for persistent data (e.g., theme, preferences).

6 PRACTICAL EXAMPLE - LOGIN SESSION

```
// Save login info
const user = { id: 1, name: 'John' };
sessionStorage.setItem('user', JSON.stringify(user));

// Get login info
const userStr = sessionStorage.getItem('user');
const user = JSON.parse(userStr);
console.log(user.name); // John

// Logout (clear session)
sessionStorage.clear();
```

When the user closes the tab, the session ends and all data is removed automatically.

7 KEY TAKEAWAYS

- ✓ SessionStorage stores data for a single session (tab/window).
- ✓ Data is cleared when the tab or window is closed.
- ✓ It is not shared between different tabs.
- ✓ Survives page refresh.
- ✓ Stores only strings (use JSON for objects/arrays).
- ✓ Useful for temporary session-based data.



REMEMBER:

If you need data to live beyond the session, use LocalStorage. If it's temporary, use SessionStorage!



EP 28

COOKIES



Small pieces of data stored on the client and sent to the server with every request.

Cookies are sent to the server automatically with every HTTP request to the same domain.

1 WHAT IS A COOKIE?

A cookie is a small piece of data stored in the user's browser by a website. It has a name, value, and optional attributes like expiration, domain, path, secure, and HttpOnly.




Cookies are mainly used for:

- ✓ Session management
- ✓ User preferences
- ✓ Tracking & analytics



2 HOW COOKIES WORK



Cookies are stored by the browser and attached to every request to the same domain.



3 COOKIE STRUCTURE

Attribute	Description
Name	The name of the cookie
Value	The value of the cookie
Expires / Max-Age	When the cookie expires
Domain	The domain the cookie belongs to
Path	The path on the server where the cookie is valid
Secure	Cookie is sent only over HTTPS
HttpOnly	Cookie is not accessible via JavaScript
SameSite	Controls when cookies are sent with cross-site requests

4 SETTING & GETTING COOKIES IN JAVASCRIPT

Setting a Cookie

```
// Set a cookie
document.cookie = "username=John; Max-Age=3600; Path=/; Secure; SameSite=Strict";
```

Max-Age=3600 → Expires in 1 hour
 Path=/ → Available across the site
 Secure → Sent over HTTPS only
 SameSite=Strict → Sent only on same-site requests

Getting Cookies

```
// Get all cookies
console.log(document.cookie);
```

// Example output
 // username=John; theme=dark; token=abc123

document.cookie can only read non-HttpOnly cookies. HttpOnly cookies are accessible only by the server.

5 EXAMPLE: SET, GET & DELETE

```
// 1. Set a cookie
document.cookie = "user=Alice; Max-Age=3600; Path=/; SameSite=Lax";

// 2. Get cookies
console.log(document.cookie); // user=Alice

// 3. Delete a cookie
document.cookie = "user=; Max-Age=0; Path=/; SameSite=Lax";
// Setting Max-Age=0 removes the cookie
```

6 COOKIES VS LOCALSTORAGE VS SESSIONSTORAGE

Feature	Cookies	LocalStorage	SessionStorage
Sent to Server	Yes (automatically)	No	No
Storage Limit	~4 KB	~5-10 MB	~5-10 MB
Lifetime	Configurable	Until manually cleared	Until tab/window is closed
Access	Automatic	Via JavaScript	Via JavaScript
Use Case	Sessions, Auth, Tracking	User preferences, Persistent data	Temporary data, Form state



Use Cookies for data that must be sent to the server.
 Use Web Storage (Local/Session) for client-side data.



7 REAL WORLD EXAMPLE - REMEMBER ME

Login Form

Username

Password

☒ Remember Me

```
// After successful login
if (rememberMeChecked) {
  document.cookie = "token=abc123; Max-Age=604800; Path=/; Secure; SameSite=Lax"; // 7 days
} else {
  document.cookie = "token=abc123; Max-Age=3600; Path=/; Secure; SameSite=Lax"; // 1 hour
}
```



The server reads the "token" cookie on every request to authenticate the user.



KEY TAKEAWAYS

- ✓ Cookies store small pieces of data on the client.
- ✓ Cookies are sent automatically with every request.
- ✓ Use attributes like Secure, HttpOnly, SameSite for safety.
- ✓ Use Cookies for sessions, auth, and tracking.
- ✓ For larger client-side data, use LocalStorage or SessionStorage.



Cookies may be small, but they power a big part of the web!



EP 29

ERROR HANDLING

Handle errors gracefully and make your code more robust.

Errors happen.
Good developers handle them.
Great developers expect them!

1 WHAT IS ERROR HANDLING?

Error handling is the process of responding to runtime errors in a controlled way to prevent the application from crashing.



Errors can occur due to:

- ✓ Invalid input
- ✓ Network failures
- ✓ Unexpected conditions
- ✓ Programmer mistakes

2 TYPES OF ERRORS IN JAVASCRIPT

Error Type	Description	Example
<code>SyntaxError</code>	Occurs when code violates JavaScript syntax rules.	<code>let a = ;</code>
<code>ReferenceError</code>	Occurs when accessing a variable that is not defined.	<code>console.log(x);</code> // x is not defined
<code>TypeError</code>	Occurs when a value is not of the expected type.	<code>null.length</code>
<code>RangeError</code>	Occurs when a value is not within the range.	<code>new Array(-1)</code>
<code>URIError</code>	Occurs when URI-related functions are used incorrectly.	<code>decodeURIComponent('%')</code>
<code>CustomError</code>	Errors created by developers.	<code>new Error('Something went wrong')</code>

3 THE TRY...CATCH...FINALLY STATEMENT

```
try {
  // Code that might throw an error
} catch (error) {
  // Handle the error
} finally {
  // Code that always runs
}
```

Place risky code here.

Handle the error if it occurs.

Always executed, whether error occurs or not.



If an error occurs in try, the control jumps to catch. Finally block always executes.

4 EXAMPLE

```
try {
  let result = 10 / 0;
  if (!isFinite(result)) {
    throw new Error("Cannot divide by zero");
  }
  console.log("Result:", result);
} catch (error) {
  console.log("Error:", error.message);
} finally {
  console.log("Execution completed.");
}
```



Output

Error:
Cannot divide by zero
Execution completed.

5 ACCESSING ERROR INFORMATION

The error object contains useful properties.

Property	Description
<code>name</code>	The type of error (e.g., <code>TypeError</code>)
<code>message</code>	Human-readable description of the error
<code>stack</code>	Stack trace showing where the error occurred
<code>lineNumber</code>	Line number where the error occurred (non-standard)
<code>fileName</code>	File name where the error occurred (non-standard)



Use `error.message` to show user-friendly messages.
Use `error.stack` for debugging.

6 THROWING CUSTOM ERRORS

```
class ValidationError extends Error {
  constructor(message) {
    super(message);
    this.name = "ValidationError";
  }
}

// Usage
function validateAge(age) {
  if (age < 18) {
    throw new ValidationError("Age must be 18 or above");
  }
}
```



Custom errors help you create meaningful error types for your application.

Built-in Constructor for Custom Errors

Error is the base constructor.

7 BEST PRACTICES

- ✓ Always wrap risky code in try...catch.
- ✓ Provide meaningful error messages.
- ✓ Log errors for debugging.
- ✓ Don't expose sensitive information in errors.
- ✓ Use specific error types (custom errors) when needed.



8 COMMON MISTAKES

- ✗ Swallowing errors silently (empty catch block).
- ✗ Not handling promise rejections (Use `catch()`).
- ✗ Throwing non-Error values.
- ✗ Not validating inputs.



KEY TAKEAWAYS

✓ Errors are inevitable.



✓ Handle them gracefully.



✓ Use try...catch...finally to control errors.



✓ Good error handling builds reliable apps.



A good application doesn't just work when everything goes right, it handles things right when something goes wrong!



EP 30

DESTRUCTURING

A clean and concise way to extract values from arrays and objects.

Destructuring makes your code shorter, cleaner, and easier to read.

1 WHAT IS DESTRUCTURING?

Destructuring is a JavaScript expression that makes it possible to unpack values from arrays, or properties from objects, into distinct variables.



Why use it?

- ✓ Less code
- ✓ More readable
- ✓ Easy to extract what you need

2 ARRAY DESTRUCTURING

Basic Example

```
const numbers = [10, 20, 30];
const [a, b, c] = numbers;
// a = 10, b = 20, c = 30
console.log(a, b, c); // 10 20 30
```

Skip / Ignore Values

```
const [x, , z] = numbers;
// x = 10, z = 30
console.log(x, z); // 10 30
```

Default Values

```
const [p, q, r = 0] = [1, 2];
// r = 0 (default value used)
console.log(p, q, r); // 1 2 0
```



The order matters! Values are assigned based on position.

3 OBJECT DESTRUCTURING

Basic Example

```
const user = {
  name: 'Alice',
  age: 25,
  city: 'New York'
};
const { name, age, city } = user;
console.log(name); // Alice
console.log(age); // 25
console.log(city); // New York
```

Rename Variables

```
const { name: fullName, city: location } = user;
console.log(fullName); // Alice
console.log(location); // New York
```

Default Values

```
const { country = 'USA' } = user;
console.log(country); // USA
```

Extract Only What You Need

```
const { name } = user;
console.log(name); // Alice
// age and city are ignored
```



Order does not matter in objects. You can pick any property by name.

4 NESTED DESTRUCTURING

Nested Objects

```
const person = {
  id: 1,
  info: {
    name: 'John',
    address: {
      city: 'London'
    }
  }
};
const { info: { name, address: { city } } } = person;
console.log(name); // John
console.log(city); // London
```

Nested Arrays

```
const arr = [1, [2, 3], 4];
const [a, [b, c], d] = arr;
console.log(a, b, c, d); // 1 2 3 4
```



You can destructure multiple levels deep!

5 FUNCTION PARAMETERS DESTRUCTURING

Object in Function

```
function printUser({ name, age }) {
  console.log(`Name: ${name}, Age: ${age}`);
}
printUser({ name: 'Bob', age: 30 });
// Name: Bob, Age: 30
```

Array in Function

```
function sum([a, b]) {
  return a + b;
}
console.log(sum([5, 7])); // 12
```



Great for working with API responses and functions!

6 SWAP VARIABLES (EASY WAY)

```
let a = 5, b = 10;
[a, b] = [b, a];
console.log(a, b); // 10 5
```



7 REST OPERATOR WITH DESTRUCTURING

```
const [first, ...rest] = [1, 2, 3, 4, 5];
console.log(first); // 1
console.log(rest); // [2, 3, 4, 5]
```

Rest (...) collects the remaining values!

8 PRACTICAL EXAMPLE

```
const product = {
  id: 101,
  name: 'Laptop',
  price: 999,
  specs: {
    ram: '16GB',
    storage: '512GB SSD'
  }
};
const { name, price, specs: { ram } } = product;
console.log(name, price, ram);
// Laptop 999 16GB
```



KEY TAKEAWAYS

- ✓ Destructuring extracts values from arrays or objects.
- ✓ It makes code cleaner and easier to read.
- ✓ Use default values to handle missing data.
- ✓ Order matters in arrays, not in objects.
- ✓ Works great in functions and real-world apps.
- ✓ Combine with rest operator for more power.



Destructuring is a small feature that makes a BIG difference in your code!



EP 31

SPREAD & REST OPERATORS

Powerful syntax for expanding and collecting values in arrays, objects, and functions.

Spread expands.
Rest collects.
Small syntax,
BIG impact! 🌟

1 WHAT ARE THEY?

Operator	Used For	Does
<code>...</code> (Spread)	Arrays, Objects, Strings, Iterables	Expands elements into individual items
<code>...</code> (Rest)	Function Parameters, Arrays, Objects	Collects multiple items into a single entity

💡 Spread = Expand 📦
Rest = Collect 📦

2 SPREAD OPERATOR (...)

Expands an iterable (array, string, object) into individual elements.

In Arrays	In Objects	In Strings
<pre>const arr1 = [1, 2, 3]; const arr2 = [4, 5, 6]; const merged = [...arr1, ...arr2]; console.log(merged); // [1, 2, 3, 4, 5, 6]</pre>	<pre>const obj1 = { a: 1, b: 2 }; const obj2 = { c: 3, d: 4 }; const merged = { ...obj1, ...obj2 }; console.log(merged); // { a: 1, b: 2, c: 3, d: 4 }</pre>	<pre>const str = 'Hello'; const chars = [...str]; console.log(chars); // ['H', 'e', 'l', 'l', 'o']</pre>

🌟 Spread is mostly used to copy, merge, or expand values.

3 REST OPERATOR (...)

Collects multiple elements into a single array or object.

In Function Parameters	In Arrays
<pre>function sum(...numbers) { return numbers.reduce((a, b) => a + b, 0); } console.log(sum(1, 2, 3, 4)); // 10 console.log(sum(5, 10)); // 15</pre>	<pre>const [first, ...rest] = [1, 2, 3, 4, 5]; console.log(first); // 1 console.log(rest); // [2, 3, 4, 5]</pre>

🔒 Rest must be the last parameter in functions and the last element in array destructuring.

4 REST IN OBJECTS (ES2018+)

```
const { name, ...details } = {
  name: 'Alice',
  age: 25,
  city: 'New York',
  role: 'Developer'
};
console.log(name); // Alice
console.log(details); // { age: 25, city: 'New York', role: 'Developer' }
```

🌟 Rest in objects collects the remaining properties into a new object.

5 COPYING & CLONING

Array Copy	Object Copy
<pre>const original = [1, 2, 3]; const copy = [...original]; copy.push(4); console.log(original); // [1, 2, 3] console.log(copy); // [1, 2, 3, 4]</pre>	<pre>const user = { name: 'John', age: 30 }; const copyUser = { ...user }; copyUser.age = 35; console.log(user.age); // 30 console.log(copyUser.age); // 35</pre>

💡 Spread creates shallow copies (nested objects/arrays are still shared).

6 PRACTICAL USE CASES

Add Items to Array	Merge Objects
<pre>const items = [1, 2, 3]; const newItem = { ...items, 4, 5 }; // [1, 2, 3, 4, 5]</pre>	<pre>const settings = { theme: 'dark' }; const userSettings = { ...settings, fontSize: 14 }; // { theme: 'dark', fontSize: 14 }</pre>
Pass Multiple Args	Function with Variable Args
<pre>const nums = [10, 20, 30]; console.log(Math.max(...nums)); // 30</pre>	<pre>function greet(greeting, ...names) { names.forEach(n => console.log(`\${greeting}, \${n}!`)); } greet('Hi', 'John', 'Jane');</pre>

🎯 Makes your code clean, flexible, and easier to work with!

7 SPREAD VS REST

	Spread (...)	Rest (...)
Purpose	Expands elements	Collects elements
Used In	Arrays, Objects, Strings, Function Calls	Function Parameters, Arrays, Objects
Syntax Position	Anywhere	Last in parameters / destructuring
Example	<pre>const arr = [...items]; const obj = { ...user };</pre>	<pre>function f(...args) {} const [a, ...rest] = arr;</pre>

8 QUICK EXAMPLE - COMBINE ALL

```
const user = { name: 'Sam', age: 28, city: 'Delhi' };
const { name, ...otherDetails } = user; // Rest in object
const arr = [1, 2, 3];
const newArr = [0, ...arr, 4, 5]; // Spread in array
function printInfo(greet, ...details) { // Rest in function
  console.log(greet, details);
}
printInfo('User Info', name, ...Object.values(otherDetails), ...newArr);
```

Rest helps you collect.
Spread helps you expand.



KEY TAKEAWAYS

- ✓ Spread expands elements.
- ✓ Rest collects elements.
- ✓ Used in arrays, objects, and function parameters.
- ✓ Makes code shorter, cleaner & more powerful.



Master Spread & Rest - Write less code, do more! 🚀



EP 32

MODULES (IMPORT / EXPORT)



Modules are the building blocks of modern JavaScript apps!

Modules let you split your code into reusable files. They help keep your code organized and maintainable.

1 WHAT ARE MODULES?

Modules are external JavaScript files that export values and import them in other files.

They help in:

- ✓ Code reusability
- ✓ Better organization
- ✓ Avoiding global scope pollution
- ✓ Easier maintenance



★ ES6 Modules are supported in all modern browsers. ♥

2 TYPES OF EXPORTS

Type	Syntax	Description	Example
Named Export	<code>export const name = value;</code>	Export multiple values by name.	<code>export const PI = 3.14; export function add() {}</code>
Default Export	<code>export default value;</code>	Export a single main value.	<code>export default function() {}</code>
Export List	<code>export { name1, name2 };</code>	Export multiple things together.	<code>const x = 1; export { x };</code>

3 NAMED EXPORTS

```
math.js
export const PI = 3.14;
export const add = (a, b) => a + b;
export function multiply(a, b) {
  return a * b;
}
```

```
app.js
import { PI, add, multiply } from './math.js';
console.log(PI); // 3.14
console.log(add(2, 3)); // 5
console.log(multiply(2, 4)); // 8
```

💡 You can import only what you need using named imports. ♥

4 DEFAULT EXPORT

```
greet.js
export default function greet(name) {
  return `Hello, ${name}!`;
}
```

```
app.js
import greet from './greet.js';
console.log(greet('John'));
// Hello, John!
```

★ Each module can have only one default export. ♥

5 EXPORT LIST (MULTIPLE EXPORTS TOGETHER)

```
utils.js
const PI = 3.14;
const square = (n) => n * n;
const cube = (n) => n * n * n;
export { PI, square, cube };
```

```
app.js
import { PI, square, cube } from './utils.js';
console.log(square(4)); // 16
console.log(cube(3)); // 27
console.log(PI); // 3.14
```

★ Great when you want to export multiple things at once. ♥

6 RENAME IMPORTS

```
math.js
export const add = (a, b) => a + b;
export const PI = 3.14;
```

```
app.js
import { add as sum, PI as PValue }
  from './math.js';
console.log(sum(2, 3)); // 5
console.log(PValue); // 3.14
```

💡 Use renaming to avoid name conflicts. ♥

7 IMPORT EVERYTHING (*)

```
constants.js
export const API_URL = 'https://api.com';
export const TIMEOUT = 5000;
export const VERSION = '1.0.0';
```

```
app.js
import * as constants from './constants.js';
console.log(constants.API_URL);
console.log(constants.TIMEOUT);
console.log(constants.VERSION);
```

🔒 Use * only when you really need everything. ♥

8 DEFAULT + NAMED EXPORT TOGETHER

```
user.js
export default function User(name) {
  this.name = name;
}
export const ROLE = 'Admin';
export const isActive = true;
```

```
app.js
import User, { ROLE, isActive } from './user.js';
const u = new User('Alice');
console.log(u.name); // Alice
console.log(ROLE); // Admin
console.log(isActive); // true
```

★ Default import first, then named imports inside {}. ♥

9 IMPORTANT NOTES

- ✓ Use `script type="module"` in HTML.
- ✓ Modules run in strict mode automatically.
- ✓ Each module has its own scope.
- ✓ Variables, functions, and classes declared in a module are not added to the global object (window).
- ✓ Modules are fetched asynchronously.

10 HOW TO USE MODULES IN HTML

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <title>Modules Example</title>
  </head>
  <body>
    <script type="module" src="/app.js"></script>
  </body>
</html>
```

`type="module"` tells the browser this script uses ES6 Modules. ♥



KEY TAKEAWAYS

- ✓ Modules keep your code clean and well-organized.
- ✓ Export to share.
- ✓ Import to use.
- ✓ Reuse code.
- ✓ Save time.
- ✓ Build better apps.



Write modular code today, build scalable apps tomorrow! 🚀



EP 33

HIGHER ORDER FUNCTIONS

Functions that work with other functions.
They can take functions as arguments or return functions.

HOFs are the superpower of JavaScript!

1 WHAT ARE HIGHER ORDER FUNCTIONS?

A function is called Higher Order if it does at least one of the following:

- ✓ Takes one or more functions as arguments.
- ✓ Returns a function as its result.



Examples: `map()`, `filter()`, `reduce()`, `forEach()`, `sort()`, `setTimeout()`, etc.

2 EXAMPLES

Takes a Function as Argument

```
function greet(name) {
  return `Hello, ${name}`;
}

function processUserInput(callback) {
  const name = 'Alice';
  console.log(callback(name));
}

processUserInput(greet); // Hello, Alice
```

Returns a Function

```
function multiplier(factor) {
  return function (num) {
    return num * factor;
  };
}

const double = multiplier(2);
console.log(double(5)); // 10
```

3 WHY USE HIGHER ORDER FUNCTIONS?

- ✓ Write less code
- ✓ Reusability
- ✓ Abstraction
- ✓ Better readability
- ✓ Functional programming



4 COMMON HIGHER ORDER FUNCTIONS IN JAVASCRIPT

Method	Purpose	Mutates Original Array?
<code>forEach()</code>	Performs an action for each element	No
<code>map()</code>	Creates a new array with results	No
<code>filter()</code>	Creates a new array with elements that pass a test	No
<code>reduce()</code>	Reduces array to a single value	No
<code>sort()</code>	Sorts the array elements	Yes
<code>every()</code>	Checks if all elements pass a test	No
<code>some()</code>	Checks if at least one element passes a test	No

5 PRACTICAL EXAMPLES

forEach() - Do something for each element

```
const nums = [1, 2, 3];
nums.forEach(num => {
  console.log(num * 2);
});
// Output: 2 4 6
```

map() - Transform each element

```
const nums = [1, 2, 3];
const doubled = nums.map(num => num * 2);
console.log(doubled); // [2, 4, 6]
```

filter() - Filter elements

```
const nums = [1, 2, 3, 4, 5];
const even = nums.filter(num => num % 2 === 0);
console.log(even); // [2, 4]
```

reduce() - Reduce to a single value

```
const nums = [1, 2, 3, 4];
const sum = nums.reduce((acc, curr) => acc + curr, 0);
console.log(sum); // 10
```

every() - Check if all pass the test

```
const nums = [2, 4, 6];
const allEven = nums.every(num => num % 2 === 0);
console.log(allEven); // true
```

some() - Check if any pass the test

```
const nums = [1, 3, 4, 5];
const hasEven = nums.some(num => num % 2 === 0);
console.log(hasEven); // true
```

sort() - Sort elements (mutates original array)

```
const names = ['Charlie', 'Alice', 'Bob'];
names.sort();
console.log(names); // ['Alice', 'Bob', 'Charlie']
```

⚠ `sort()` changes the original array!



These methods take Functions (callbacks) as arguments. That's what makes them Higher Order Functions!

6 CUSTOM HIGHER ORDER FUNCTION

```
function operate(arr, operation) {
  const result = [];
  for (let i = 0; i < arr.length; i++) {
    result.push(operation(arr[i]));
  }
  return result;
}

const nums = [1, 2, 3];
const squared = operate(nums, n => n * n);
console.log(squared); // [1, 4, 9]
```



HOFs help you create powerful, flexible, and reusable code!

7 NESTED HIGHER ORDER FUNCTIONS

```
const nums = [1, 2, 3, 4];
const result = nums
  .filter(n => n % 2 === 0) // [2, 4]
  .map(n => n * 10) // [20, 40]
  .reduce((acc, n) => acc + n, 0); // 60
console.log(result); // 60
```

```
Filter even
[2, 4]
↓
Map * 10
[20, 40]
↓
Reduce sum
60
```



KEY TAKEAWAYS

- ✓ HOFs take functions as arguments or return functions.
- ✓ They make code reusable and easier to maintain.
- ✓ Enable functional and declarative programming.
- ✓ Master HOFs = Write better JavaScript!



Higher Order Functions = Higher Level of JavaScript Mastery!



EP 34

ARRAY METHODS

map() • filter() • reduce()

Powerful methods to transform, filter, and reduce arrays.

Master these 3 and you can solve 90% of array problems! 🌟

1 WHY ARRAY METHODS?

- ✓ Make code shorter and cleaner
- ✓ Avoid complex loops
- ✓ More readable and expressive
- ✓ Built for functional programming



They don't change the original array (except reduce which returns a single value). ❤️


2 OVERVIEW

Method	Purpose	Returns	Changes Original Array?
map()	Transforms each element and returns a new array	New array	No
filter()	Filters elements based on a condition and returns a new array	New array	No
reduce()	Reduces the array to a single value	Single value	No

3 map() - TRANSFORM EACH ELEMENT

Creates a new array by applying a function to each element.

```
const nums = [1, 2, 3, 4];
const doubled = nums.map(num => num * 2);
console.log(doubled); // [2, 4, 6, 8]
```



More Examples

```
// Square each number
const squares = nums.map(n => n * n); // [1, 4, 9, 16]


// Convert to strings
const strings = nums.map(String); // ["1", "2", "3", "4"]

// Get lengths of words
const words = ["hi", "hello", "hey"];
const lengths = words.map(w => w.length); // [2, 5, 3]
```

4 filter() - FILTER ELEMENTS

Creates a new array with elements that pass a test (return true).

```
const nums = [1, 2, 3, 4, 5, 6];
const even = nums.filter(n => n % 2 === 0);
console.log(even); // [2, 4, 6]
```



```
// Get numbers greater than 3
const greaterThan3 = nums.filter(n => n > 3); // [4, 5, 6]


// Filter by length
const words = ["apple", "bat", "cat", "elephant"];
const longWords = words.filter(w => w.length > 3); // ["apple", "elephant"]

// Filter objects
const users = [
  {name: "Alice", age: 22},
  {name: "Bob", age: 17},
  {name: "Charlie", age: 25}
];
const adults = users.filter(u => u.age >= 18);
// [{name: "Alice", age: 22}, {name: "Charlie", age: 25}]
```

5 reduce() - REDUCE TO A SINGLE VALUE

Executes a reducer function on each element, resulting in a single output.

```
const nums = [1, 2, 3, 4];
const sum = nums.reduce((acc, curr) => acc + curr, 0);
console.log(sum); // 10 (0 + 1 + 2 + 3 + 4)
```



More Examples

```
// Multiply all numbers
const product = nums.reduce((acc, curr) => acc * curr, 1); // 24

// Find maximum number
const max = nums.reduce((acc, curr) => Math.max(acc, curr), nums[0]); // 4

// Concatenate strings
const words = ["Hello", " ", "World", "!"];
const sentence = words.reduce((acc, curr) => acc + curr, ""); // "Hello World!"

// Count occurrences
const votes = ["A", "B", "A", "C", "A", "B"];
const count = votes.reduce((acc, vote) => {
  acc[vote] = (acc[vote] || 0) + 1;
  return acc;
}, {});
// {A: 3, B: 2, C: 1}
```

6 QUICK COMPARISON

Method	Use When...	Returns	Example
map()	You want to transform each element	New array	nums.map(n => n * 2)
filter()	You want to select elements that match a condition	New array	nums.filter(n => n > 3)
reduce()	You want to combine all elements into one value	Single value	nums.reduce((a, b) => a + b, 0)

7 CHAINING (COMBINE METHODS)

```
const nums = [1, 2, 3, 4, 5, 6];
const result = nums
  .filter(n => n % 2 === 0) // [2, 4, 6]
  .map(n => n * 3) // [6, 12, 18]
  .reduce((acc, curr) => acc + curr, 0); // 36
console.log(result); // 36
```

Methods return new arrays, so you can chain them together beautifully! 🌟



KEY TAKEAWAYS

✓ map() transforms each element

✓ filter() selects elements

✓ reduce() combines to a single value

✓ These methods make your code clean and powerful

✓ Practice them on real problems to get better! 🌟



Learn these deeply, and you'll write JavaScript like a PRO! 🌟



EP 35

JAVASCRIPT STRINGS

Strings are used to store and manipulate text.
Powerful methods to work with words!

Strings are
immutable in
JavaScript!

1 WHAT IS A STRING?

A string is a sequence of characters enclosed in single, double, or backtick quotes.

'Hello'
"Hello"
`Hello`



Backticks (``) allow template literals and multiline strings.

2 CREATING STRINGS

Single Quotes (')	Double Quotes (")	Backticks (`)
<pre>const single = 'Hello'; console.log(single); // Hello</pre>	<pre>const double = "Hello"; console.log(double); // Hello</pre>	<pre>const backtick = `Hello`; console.log(backtick); // Hello</pre>



Backticks allow embedded expressions using \${ }.

```
const name = 'Alice';
console.log(`Hello, ${name}!`); // Hello, Alice!
```

3 COMMON STRING PROPERTIES

Property	Description	Example
length	Returns length	<code>'hello'.length</code> // 5
charAt(index)	Character at index	<code>'hello'.charAt(1)</code> // 'e'
at(index)	Character at index (supports -ve)	<code>'hello'.at(-1)</code> // 'o'
[index]	Access using index	<code>'hello'[0]</code> // 'h'



Strings are zero-indexed!

4 COMMON STRING METHODS (PART 1)

Method	Description	Example
toUpperCase()	Convert to UPPERCASE	<code>'hello'.toUpperCase()</code> // 'HELLO'
toLowerCase()	Convert to lowercase	<code>'HELLO'.toLowerCase()</code> // 'hello'
trim()	Remove whitespace from both ends	<code>' hello '.trim()</code> // 'hello'
includes(search)	Check if string contains value	<code>'hello world'.includes('world')</code> // true
startsWith(search)	Check if starts with	<code>'hello'.startsWith('he')</code> // true
endsWith(search)	Check if ends with	<code>'hello'.endsWith('lo')</code> // true

5 COMMON STRING METHODS (PART 2)

Method	Description	Example
indexOf(search)	Index of first occurrence	<code>'hello'.indexOf('l')</code> // 2
lastIndexOf(search)	Index of last occurrence	<code>'hello'.lastIndexOf('l')</code> // 3
slice(start, end)	Extract part of string (end not included)	<code>'hello'.slice(1, 4)</code> // 'ello'
substring(start, end)	Similar to slice	<code>'hello'.substring(1, 4)</code> // 'ello'
replace(search, new)	Replace first match	<code>'hello'.replace('l', 'o')</code> // 'heo'
replaceAll(search, new)	Replace all matches	<code>'hello'.replaceAll('l', 'o')</code> // 'heoo'
split(separator)	Split into an array	<code>'a,b,c'.split(',')</code> // ['a', 'b', 'c']



Strings are immutable - methods return new strings.

6 TEMPLATE LITERALS

Use backticks (``) to create template literals.

- ✓ Multiline strings
- ✓ Embedded expressions
- ✓ More readable

```
const user = 'Bob';
const age = 25;
const message = `
Hello, ${user}!
You are ${age} years old.
Welcome to JavaScript!
`;
console.log(message);
```



7 ESCAPING CHARACTERS

Escape Sequence	Meaning
\'	Single quote
\"	Double quote
\\	Backslash
\n	New line
\t	Tab

```
const text = 'It\'s a
\great\ day!\nLet\'s code.';
console.log(text);
// It's a "great" day!
// Let's code.
```



Use \ to escape special characters inside strings.

8 EXAMPLES

```
// Check palindrome
const str = 'madam';
const reversed = str.split('').reverse().join('');
console.log(str === reversed); // true

// Count vowels
const s = 'JavaScript is awesome';
const vowels = 'aeiouAEIOU';
const count = [...s].filter(ch => vowels.includes(ch)).length;
console.log(count); // 10
```

Strings are
✓ powerful
✓ flexible
✓ and FUN!



KEY TAKEAWAYS

- ✓ Strings store text in JS
- ✓ Use methods to manipulate strings
- ✓ Template literals are modern & useful
- ✓ Strings are immutable
- ✓ Practice makes perfect!



Strings help you express, communicate, and create amazing things in code! 🚀



EP 36

MODERN JAVASCRIPT ESSENTIALS

Three small features that make your code cleaner, safer, and smarter. ✨

Small syntax.
BIG impact!
Master these
and level up! 🍀

1 OPTIONAL CHAINING (?.)

Access nested object properties without worrying about "undefined" or "null".

// Without Optional Chaining
`console.log(user.profile.address.city);`

❌ **TypeError: Cannot read properties of undefined (reading 'address')**

Problem

If any link in the chain is null or undefined, it throws an error.

// With Optional Chaining
`console.log(user?.profile?.address?.city);`

// Output: undefined

Good! 😊

Returns undefined instead of throwing an error.



Real Example

```
const user = {
  name: 'Nemon',
  profile: {
    address: { city: 'Tokyo' }
  }
};
console.log(user?.profile?.address?.city);
// Tokyo
console.log(user?.profile?.contact?.email);
// undefined (no error)
```



2 NULLISH COALESCING (??)

Provides a default value only when the left side is null or undefined (not for 0, '', or false).

// Using || (OR) - can be misleading
`const count = 0;
const result = count || 10;
console.log(result); // 10 (X wrong!)`

`const name = '';
const displayName = name || 'Guest';
console.log(displayName); // 'Guest' (X wrong!)`

Problem

|| treats 0, '', false, NaN, as falsy and replaces them.

// Using ?? (Nullish Coalescing)
`const count = 0;
const result = count ?? 10;
console.log(result); // 0 (✅ correct!)`

`const name = '';
const displayName = name ?? 'Guest';
console.log(displayName); // '' (✅ correct!)`

Good! 😊

?? only replaces null or undefined. Everything else is returned as-is.

Real Example

```
const user = { name: '', age: null, isAdmin: false };
console.log(user.name ?? 'Anonymous'); // ''
console.log(user.age ?? 18); // 18
console.log(user.isAdmin ?? true); // false
```



3 TEMPLATE LITERALS

Create strings with embedded expressions, multi-line support, and cleaner syntax.

// Old Way (Concatenation)
`const name = 'Nemon';
const age = 21;
const msg = 'Hello, ' + name + '!' + ' You are ' + age + ' years old.';
console.log(msg);`

Not great

Hard to read, ugly with variables, and messy for multi-line.

// Template Literals (Backticks ``)
`const name = 'Nemon';
const age = 21;
const msg = `Hello, ${name}!
You are ${age} years old.`;
console.log(msg);`

Awsome! 😍

Readable, powerful, and supports expressions!



More Power with Template Literals

Multi-Line Strings	Expressions
<code>const about = `I'm Nemon. I love JavaScript. Building awesome things!`;</code>	<code>const a = 5, b = 10; console.log(`Sum: \${a + b}`); // Sum: 15</code>



KEY TAKEAWAYS

Optional Chaining (?.)

- ✓ Prevents "Cannot read property of undefined"
- ✓ Returns undefined instead of crashing

Nullish Coalescing (??)

- ✓ Only checks for null or undefined
- ✓ Better defaults without breaking valid values

Template Literals (``)

- ✓ Cleaner strings with \$(expressions)
- ✓ Supports multi-line strings easily
- ✓ More readable and maintainable

Use these together and write clean, modern, robust JavaScript! 🍀

QUICK REFERENCE

Feature	Syntax	When to Use	Example
Optional Chaining	<code>obj?.prop?.subProp</code>	When any property in the chain might be null or undefined.	<code>user?.profile?.name</code>
Nullish Coalescing	<code>value ?? defaultValue</code>	When you want a default only for null or undefined.	<code>user.name ?? 'Guest'</code>
Template Literals	<code>`Hello, \${name}`</code>	When you need dynamic strings or multi-line text.	<code>`Sum: \${a + b}`</code>

THINGS TO REMEMBER

- ❑ ?. is short-circuiting - stops at the first nullish value.
- ❑ ?? is not the same as ||. It's smarter!
- ❑ Template literals are wrapped in backticks (``).
- ❑ These features work together beautifully to write modern, clean code.



Better Syntax. Better Code. Better Developer. 🍀



EP 37


CONSTRUCTOR FUNCTIONS

The foundation of OOP in JavaScript

Before ES6 classes, JavaScript used Constructor Functions to create objects and manage data.

1 WHY CONSTRUCTOR FUNCTIONS?

- Provide a blueprint to create multiple objects with the same properties & methods.
- Each object has its own copy of properties.
- They are called using the 'new' keyword.



2 HOW IT WORKS (with 'new')

When you use 'new', JavaScript does 4 things:

1. Creates a new empty object {}
2. Sets 'this' to point to that object
3. Executes the function (adds properties/methods)
4. Returns the object implicitly

Example

```

function Person(name, age) {
  this.name = name;
  this.age = age;
  this.greet = function() {
    console.log('Hi, I am ' + this.name);
  }
}

const p1 = new Person('Neen', 21);
const p2 = new Person('Time', 22);
  
```

Output:

```

p1.greet(); // Hi, I am Neen
p2.greet(); // Hi, I am Time
  
```

Every object gets its own copy of properties!

3 THE 'new' KEYWORD

The magic behind creating instances from a constructor.

```

const person = new Person('Fabulous', 19);

// 1. {} is created
// 2. this -> {}
// 3. Person function runs
// 4. {} returned automatically
  
```

Note:

If you forget 'new', 'this' won't refer to the new object (it may point to window or be undefined in strict mode).

4 CONSTRUCTOR vs NORMAL FUNCTION

Constructor Function

- Called with 'new'
- Creates new object
- this refers to new object
- Naming convention: PascalCase
- Returns object implicitly

VS

Normal Function

- Called without 'new'
- Does not create new object
- this depends on how it's called
- Naming convention: camelCase
- Returns undefined by default

REMEMBER

Constructor functions were the backbone of JavaScript OOP before classes arrived in ES6.

5 ONE MORE EXAMPLE

```

function Car(brand, speed) {
  this.brand = brand;
  this.speed = speed;
  this.drive = function() {
    console.log('this.brand + ' is driving at ' +
      this.speed + ' km/h');
  }
}
  
```

```

const car1 = new Car('Tesla', 120);
const car2 = new Car('BMW', 100);

car1.drive(); // Tesla is driving at 120 km/h
car2.drive(); // BMW is driving at 100 km/h
  
```



KEY TAKEAWAYS

- ✓ Constructor functions create blueprint for objects.
- ✓ Use 'new' to create instances.
- ✓ Each instance has its own properties.
- ✓ Forms the base for OOP in JavaScript.

Every object starts from a constructor. Build smart. Think OOP.

EP 38

CLASSES & INHERITANCE

ES6 Classes are syntactic sugar over constructor functions. They make OOP in JavaScript cleaner and easier to use.

Classes in JS make creating objects and sharing behavior much better! ❤️

1. THE CLASS SYNTAX

A class is a blueprint to create objects. It uses the 'class' keyword.

```
class Person {
  constructor(name, age) {
    this.name = name;
    this.age = age;
  }

  greet() {
    console.log('Hi, I am ${this.name}');
  }
}

const p = new Person('Neon', 21);
p.greet(); // Hi, I am Neon
```

constructor() is called automatically when we use new.

2. KEY FEATURES

- ✓ Classes are not hoisted.
- ✓ Methods are added to the prototype automatically.
- ✓ No need to write 'function' keyword.
- ✓ Always use 'new' to create instances.
- ✓ Inside methods, 'this' refers to the current object.

Without 'new'?

```
const x = Person('Neo', 20);
// TypeError: Class constructor
// cannot be invoked without 'new'
```



3. CLASS METHODS TYPES

- Instance Methods - work on instances

```
class User {
  sayHi() {
    console.log('Hello!');
  }
}
```

Called on object instances.

- Static Methods - called on the class itself;

```
class MathUtil {
  static add(a, b) {
    return a + b;
  }
}
```

Called on class, not on instances.

- Getter / Setter - control access to properties

```
class Product {
  constructor(price) {
    this._price = price;
  }

  get price() {
    return this._price;
  }

  set price(val) {
    if (val > 0) this._price = val;
  }
}
```

Looks like property, works like methods.

Note

- ♥ Classes are just cleaner syntax.
- ♥ Behind the scenes, they still use prototypes.
- ♥ Use classes when building real-world applications.



4. INHERITANCE WITH 'extends'

One class can inherit properties and methods from another class.

```
class Animal {
  constructor(name) {
    this.name = name;
  }

  speak() {
    console.log('Some sound...');
  }
}

class Dog extends Animal {
  speak() {
    console.log('Woof!');
  }
}

const d = new Dog('Buddy');
d.speak(); // Woof!
```

Dog inherits name from Animal and overrides speak().



5. USING 'super()'

Use 'super()' to call the constructor or methods of the parent class.

```
class Dog extends Animal {
  constructor(name, breed) {
    super(name); // calls Animal constructor
    this.breed = breed;
  }

  speak() {
    super.speak(); // call parent method
    console.log('I am a ${this.breed}');
  }
}
```

super() helps us reuse parent logic. ❤️

★ Classes give structure. Inheritance gives power. Build better, not harder. ❤️ ★

EP 39

OOP PRINCIPLES IN JAVASCRIPT

Three core principles of OOP that make code scalable, maintainable and powerful.

Good code isn't just about running, it's about structure that lasts.

1 ENCAPSULATION

Wrapping data (properties) and methods that use that data into a single unit (class) and restricting direct access to some of an object's components.

```
class BankAccount {
  #balance = 0; // private field
  constructor(owner) {
    this.owner = owner; // public
  }
  deposit(amount) {
    if (amount > 0) this.#balance += amount;
  }
  getBalance() {
    return this.#balance; // controlled access
  }
}
```

Why?

- Protects data from unwanted changes.
- Exposes only what's necessary.

2 POLYMORPHISM

The ability of different objects to respond to the same method or function call in different ways.

```
class Animal {
  speak() {
    console.log('Some sound...');
  }
}
class Dog extends Animal {
  speak() {
    console.log('Woof!');
  }
}
class Cat extends Animal {
  speak() {
    console.log('Meow!');
  }
}
const animals = [new Dog(), new Cat()];
animals.forEach(a => a.speak());
```

Why?

- Same interface, different behavior.
- Makes code flexible and extensible.

3 ABSTRACTION


Hiding complex implementation details and showing only the essential features of an object.

```
class Car {
  start() {
    this.#initEngine();
    this.#checkSystems();
    console.log('Car started 🚗');
  }
  // Internal details (hidden)
  #initEngine() {
    console.log('Igniting engine...');
  }
  #checkSystems() {
    console.log('Checking systems...');
  }
}
const car = new Car();
car.start(); // User sees only 'Car started'
```

Why?

- Reduces complexity.
- Users interact with high-level features without worrying about how it works.

HOW THEY WORK TOGETHER



Together, these principles help us build software that is

- Easy to maintain
- Easy to extend
- Less error-prone
- Scalable

REAL WORLD EXAMPLES



Encapsulation → Your bank app hides how transactions are stored, you just use it.



Polymorphism → Different payment methods (UPI, Card, Wallet) work with the same interface "pay()".



Abstraction → You drive a car without knowing how the engine or brakes work.

KEY TAKEAWAYS

- Encapsulation protects data and controls access.
- Polymorphism allows one interface, many forms.
- Abstraction hides complexity, shows what matters.

Use these principles to write clean, strong and future-proof JavaScript code.

MINI EXAMPLE

```
class Shape {
  area() {
    throw new Error('Must implement area()');
  }
}
class Circle extends Shape {
  constructor(r) { super(); this.r = r; }
  area() { return Math.PI * this.r * this.r; }
}
class Rectangle extends Shape {
  constructor(w, h) { super(); this.w = w; this.h = h; }
  area() { return this.w * this.h; }
}
```

Different shapes, same method area(), different behavior.

Follow the principles. Write better code. Build better products.

EP 40

ADVANCED FUNCTIONAL JAVASCRIPT

Functional programming in JS helps us write **cleaner**, more **reusable**, and **efficient** code. ❤️

Functions are first-class citizens in JavaScript. Use them. Compose them. Love them. ❤️

1. CURRYING

Currying is the process of taking a function with multiple arguments and turning it into a series of functions, each taking **one argument at a time**.

EXAMPLE

```
function add(a) {
  return function(b) {
    return function(c) {
      return a + b + c;
    }
  }
}

add(2)(3)(4); // 9
```

Instead of add(2,3,4) we call it step by step!

REAL WORLD USE

- Partial application
- Event handlers
- Configurable functions

CURRYING with arrow functions →

```
const add = a => b => c => a + b + c;

add(1)(2)(3); // 6
```

2. MEMOIZATION

Memoization is an optimization technique where we store the result of expensive function calls and return the **cached** result when the same inputs occur again.

EXAMPLE

```
function memoize(fn) {
  const cache = {};
  return function(...args) {
    const key = JSON.stringify(args);
    if (key in cache) {
      console.log('Fetching from cache');
      return cache[key];
    }
    console.log('Calculating result...');
    const result = fn(...args);
    cache[key] = result;
    return result;
  }
}
```

Saves time & resources by avoiding repeated computations! 😊

EXAMPLE USAGE

```
const expensiveFn = n => {
  for (let i = 0; i < 1e8; i++) {}
  return n * n;
}

const fastFn = memoize(expensiveFn);
fastFn(10); // Calculating result...
fastFn(10); // Fetching from cache
```

Big win for performance! ⚡

CURRYING vs PARTIAL APPLICATION

→ CURRYING

- Transforms a function with N args into N functions.
- Takes one argument at a time.
- More strict.

VS

PARTIAL APPLICATION

- Fixes one or more arguments at a time.
- More flexible.
- Doesn't have to be one-by-one.

SNIPPET

```
const multiply = (a, b, c) => a * b * c;
const double = multiply.bind(null, 2);
double(3, 4); // 24

// Here, 2 is fixed. Remaining args are provided later.
```

BEST PRACTICES

- ✓ Use pure functions.
- ✓ Avoid side effects.
- ✓ Compose small functions.
- ✓ Memoize expensive operations.

WHEN TO USE?

- ★ Currying → When you want flexible & reusable functions.
- ★ Memoization → When your function is expensive & called repeatedly.
- ★ Functional style → Cleaner, testable & scalable code!

Think in functions. Compose with care. Optimize with memoization. This is how you level up in JavaScript. ❤️

EP 41


ASYNCHRONOUS JAVASCRIPT

JavaScript is single-threaded, but it can do multiple things at once using asynchronous programming. ♥

Async JS helps us perform time-consuming tasks without blocking the code. 😊

1. WHY ASYNCHRONOUS?

- Some operations take time (eg. API calls, reading files, timers).
- If JS waits, the whole program freezes.
- Async JS allows other code to run while waiting.



2. CALLBACKS

The oldest way to handle async operations. We pass a function (callback) to be executed later.

```
function fetchData(callback) {
  setTimeout(() => {
    const data = { user: 'Fabulous' };
    callback(data);
  }, 2000);
}

fetchData(data) => {
  console.log('Data received!', data);
};
```

Problem?

- Callback Hell
- Hard to maintain
- Not scalable

3. PROMISES

A Promise represents the eventual completion (or failure) of an async operation.



```
const fetchData = () => {
  return new Promise((resolve, reject) => {
    setTimeout(() => {
      const success = true; // or false
      if (success) resolve('Data received ✅');
      else reject('Failed to fetch data ❌');
    }, 2000);
  });
};

fetchData()
  .then(result => console.log(result))
  .catch(error => console.log(error));
```

Benefits

- ♥ Better error handling
- ♥ Chainable
- ♥ Cleaner than callbacks

4. PROMISE CHAINING

We can chain multiple .then() to handle sequential async operations.

```
fetchData()
  .then(data => {
    console.log(data);
    return 'Process step 2';
  })
  .then(msg => {
    console.log(msg);
    return 'Process step 3';
  })
  .then(final => console.log(final))
  .catch(err => console.log('Error!', err));
```



5. ASYNC / AWAIT (Modern Way)

Built on top of Promises. Makes async code look and behave like synchronous code.

```
const fetchData = () => {
  return new Promise(resolve => {
    setTimeout(() => resolve('Data ✅'), 2000);
  });
};

async function getData() {
  try {
    const data = await fetchData();
    console.log(data);
  } catch (error) {
    console.log('Error!', error);
  }
}

getData();
```

async makes a function return a Promise. await pauses execution until the Promise resolves. ♥


6. COMMON ASYNC APIS

- ☆ setTimeout() / setInterval() // timers
- ☆ fetch() // API calls
- ☆ addEventListener() // events
- ☆ FS (Node.js) // file operations
- ☆ Promises // custom async tasks



EVENT LOOP (In Short)

1. JS code runs in Call Stack.
2. Async tasks go to Web APIs.
3. When ready, they go to Callback Queue.
4. Event Loop pushes them to Call Stack.



KEY TAKEAWAYS

- ☑ Async JS prevents blocking.
- ☑ Callbacks -> first approach but messy.
- ☑ Promises -> better way to handle async code.
- ☑ Async/Await -> clean & readable.
- ☑ Event Loop -> makes async possible.



Write async code like a pro. Keep it clean, handle errors, and never block the flow! ♥

EP 42


GENERATORS & ITERATORS

Power tools to work with sequences in a smarter way.

Iterators let us go one step at a time. Generators let us pause & resume execution. 😊

1. ITERATORS

An iterator is an object that defines a sequence and has a `next()` method that returns `{ value, done }`.



EXAMPLE: Manual Iterator

```

const rangeIterator = {
  current: 1,
  last: 3,
  next() {
    if (this.current <= this.last) {
      return { value: this.current++, done: false };
    }
    return { done: true };
  }
};

console.log(rangeIterator.next()); // { value: 1, done: false }
console.log(rangeIterator.next()); // { value: 2, done: false }
console.log(rangeIterator.next()); // { value: 3, done: false }
console.log(rangeIterator.next()); // { done: true }
  
```

2. GENERATORS

Generators are functions that can pause (`yield`) and resume later. They are created using `function*`.

```

function* countUpTo(n) {
  for (let i = 1; i <= n; i++) {
    yield i; // pause & yield the value
  }
}
  
```

USAGE

```

const counter = countUpTo(3);
console.log(counter.next()); // { value: 1, done: false }
console.log(counter.next()); // { value: 2, done: false }
console.log(counter.next()); // { value: 3, done: false }
console.log(counter.next()); // { value: undefined, done: true }
  
```

Generators remember their state between yields. That's the magic! ❤️

3. YIELD VS RETURN

yield	return
Pauses the function and returns a value.	Ends the function completely.
Can be used multiple times.	Can be used only once.
Used in Generators.	Used in regular functions.

4. ITERATING OVER A GENERATOR

```

function* letters() {
  yield 'A';
  yield 'B';
  yield 'C';
}

for (let ch of letters()) {
  console.log(ch); // A B C
}
  
```

Generators are iterable, so we can use `for...of` loop! 😊

REAL WORLD USES

- ✓ Pagination (load one page at a time)
- ✓ Reading large files line by line
- ✓ Infinite sequences
- ✓ Game loops
- ✓ Lazy data streams

5. GENERATOR METHODS

Generator objects have extra methods:

- `.next(value)` → resume & get next value
- `.return(value)` → stop the generator and return a value
- `.throw(error)` → throw an error inside the generator



Remember

- ♥ Iterators follow the protocol.
- ♥ Generators make it easier.
- ♥ Use the right tool for the job! ❤️

EXAMPLE: `return()` & `throw()`

```

function* demo() {
  try {
    yield 1;
    yield 2;
    yield 3;
  } catch (err) {
    console.log('Caught:', err.message);
  } finally {
    console.log('Generator closed.');

```

OUTPUT

Caught: Oops!
Generator closed.


Iterate smart. Generate power. Write elegant JavaScript. ❤️

EP 43

PROXY & REFLECT

Powerful built-in features that let us **intercept** and customize operations on objects. ❤️

Proxy adds superpowers. Reflect gives you the tools. 😊



Proxy sits in between you and the object and can control what happens. ⭐

1. WHAT IS PROXY?

A Proxy is an object that wraps another object and **intercepts** operations (like reading, writing, deleting, checking) on that object.

```

const user = { name: 'John' };
const proxy = new Proxy(user, {
  get(target, prop) {
    console.log('Accessing ${prop}');
    return target[prop];
  }
});
console.log(proxy.name); // Accessing name
                          // John
  
```

Any operation on proxy can be intercepted and customized!

2. COMMON PROXY TRAPS

Traps are special methods that define how a Proxy handles specific operations.

- **get** → Read a property
- **set** → Write/Update a property
- **has** → Check if property exists (in)
- **deleteProperty** → Delete a property (delete)
- **apply** → Call a function (for function proxies)
- **construct** → Create instance with new
- **ownKeys** → Get all keys (Object keys, etc.)
- **getOwnPropertyDescriptor** → Get property details

3. WHAT IS REFLECT?

Reflect is a built-in object that provides methods for common operations. It makes code cleaner, safer and easier to maintain.

```

const obj = { name: 'Alice' };
Reflect.get(obj, 'name'); // 'Alice'
Reflect.set(obj, 'age', 25); // true
Reflect.has(obj, 'name'); // true
Reflect.deleteProperty(obj, 'age'); // true
  
```

Reflect does the operation. No magic. Just tools.

4. PROXY vs REFLECT

	Proxy	Reflect
Role	Intercepts operations	Performs operations
Purpose	Customize behavior	Default behavior
Syntax	<code>new Proxy(target, handler)</code>	<code>Reflect.method(target, ...)</code>
Control	You decide what happens	Follows default rules
Used For	Powerful abstractions, validation, logging, etc.	Utility & forwarding in handlers

5. PROXY IN ACTION

Let's build a simple logger using Proxy.

```

const user = { name: 'John', age: 20 };
const logger = new Proxy(user, {
  get(target, prop) {
    console.log('Getting ${prop}: ${target[prop]}');
    return Reflect.get(target, prop);
  },
  set(target, prop, value) {
    console.log('Setting ${prop} to ${value}');
    return Reflect.set(target, prop, value);
  },
  deleteProperty(target, prop) {
    console.log('Deleting ${prop}');
    return Reflect.deleteProperty(target, prop);
  }
});
logger.name; // Getting name: John
logger.age = 21; // Setting age to 21
delete logger.name; // Deleting name
  
```

Using Reflect inside Proxy keeps behavior correct! ⭐

6. REAL WORLD USES

📝 Form Validation	Validate and sanitize data on the fly.
📊 State Management	Used in libraries like Vue 3 (reactivity system).
👁️ Logging & Debugging	Track access, changes and errors easily.
🔒 Access Control	Restrict or allow access to properties.
🔄 Reactive Systems	Auto-update UI when data changes.

HOW THEY WORK TOGETHER



7. KEY TAKEAWAYS

- ✓ Proxy lets you intercept and control operations.
- ✓ Reflect provides clean, default operations.
- ✓ Use Proxy for custom logic. Reflect for safety.
- ✓ Together, they make code powerful and elegant. ❤️

NOTE
Don't overuse Proxy. It can make code harder to read and debug if misused! ⚠️

Proxy gives you control. Reflect gives you power to act. Use both wisely and build next-level JavaScript! ❤️

EP 44

WEAKMAP & WEAKSET

Weak collections that hold **weak references** to objects. Perfect for memory efficiency! 💖

Weak collections don't prevent Garbage Collection. Less memory leaks, more performance! 😊

1. WHY WEAK COLLECTIONS?

- In Map/Set, keys are strongly referenced.
- The object stays in memory even if nothing else uses it.
- WeakMap & WeakSet hold **weak references**.
- If the object is no longer used, it can be **garbage collected**.

GARBAGE COLLECTION (GC)



2. WEAKMAP

A collection of key/value pairs where keys **must be objects** (not primitive).

```

const wm = new WeakMap();
const obj = { id: 1 };

wm.set(obj, 'data'); // set
wm.get(obj);          // 'data'
wm.has(obj);          // true
wm.delete(obj);       // true
wm.has(obj);          // false (deleted)
  
```

Keys must be objects. Values can be anything. 💖

4. WEAKSET

A collection of unique objects. Only **objects**, no primitive values.

```

const ws = new WeakSet();
const obj1 = { name: 'A' };
const obj2 = { name: 'B' };

ws.add(obj1); // add
ws.has(obj1); // true
ws.delete(obj1); // true
ws.has(obj1); // false
  
```

WeakSet is like Set, but for objects only! 😊

6. REAL WORLD USES

	DOM Metadata	Store extra info about DOM elements without memory leaks.
	Private Data	Attach private data to objects without modifying them.
	Cache	Cache results based on object keys. Auto-cleanup when unused.
	Avoid Memory Leaks	Perfect for long-lived apps with dynamic objects.

7. EXAMPLES

WeakMap Example

```

const wm = new WeakMap();
const user = { name: 'Faisal' };
wm.set(user, { age: 21 });
wm.get(user); // { age: 21 }
// if 'user' is no longer referenced, it can be GC'ed
  
```

WeakSet Example

```

const ws = new WeakSet();
let obj = { id: 1 };
ws.add(obj);
ws.has(obj); // true
obj = null; // no other references
// GC can collect the object
// and remove it from WeakSet
  
```

8. KEY TAKEAWAYS

- ☑ WeakMap & WeakSet hold weak references to objects.
- ☑ They allow garbage collection of unused objects.
- ☑ Perfect for memory-sensitive and long-running applications.
- ☑ Not iterable, no size property - use when you don't need them.
- ☑ Use Proxy, Reflect, WeakMap, WeakSet together for powerful patterns! ★

NOTE
Weak collections are not enumerable by design. That's the trade-off! 😊

"Strong when you need it. Weak when you don't." Smart JavaScript always chooses the right tool! 💖

Write efficient code. Manage memory smartly. Build better applications! 💚

EP 45

SYMBOLS IN JAVASCRIPT

Symbols are primitive values used to create unique identifiers for object properties. ♥

Symbols help us avoid naming conflicts and add hidden properties to objects. 😊

1. WHAT IS A SYMBOL?

- Introduced in ES6.
- Each Symbol is unique.
- Often used as object property keys.
- Not enumerable by default.
- Useful for creating "private" or hidden properties.

Think of Symbols as secret keys that don't clash with any other keys. 🗝️

```
const id = Symbol();
const id2 = Symbol('id');

console.log(id === id2); // false (always unique)
console.log(id.description); // id
```

3. USING SYMBOLS AS OBJECT KEYS

```
const user = {
  name: 'Faisal',
  [Symbol('id')]: 101,
};

const id = Symbol('id');
console.log(user[id]); // undefined (different symbol!)
```

To access the symbol property, you must use the same symbol reference.

Correct Way:

```
const ID = Symbol('id');
const user = { name: 'Faisal', [ID]: 101 };
console.log(user[ID]); // 101
```

Always store your symbols in variables so you can reuse them! ♥

5. GLOBAL SYMBOL REGISTRY

Symbols can be shared across files/realm using the global registry.

```
const s1 = Symbol.for('token');
const s2 = Symbol.for('token');
console.log(s1 === s2); // true (shared)

const s3 = Symbol('token');
const s4 = Symbol('token');
console.log(s3 === s4); // false (unique)
```

Symbol for(key) Looks for a symbol with the given key in the global registry. If not found, it creates one. 🌐

7. REAL WORLD USE CASES

Private Properties	Add hidden data to objects without name clashes.
Library Development	Avoid overwriting user-defined properties.
Meta Programming	Attach metadata safely to objects.
Unique Identifiers	Generate guaranteed unique keys.

8. SYMBOL vs STRING

Feature	Symbol	String
Type	Primitive	Primitive
Unique	Always unique	May not be unique
Visible in loops	No (by default)	Yes
JSON.stringify	Ignored	Included
Use case	Hidden keys, meta	Normal keys

Use Symbols when you need uniqueness and privacy. 😊

2. CREATING SYMBOLS

```
const sym1 = Symbol(); // no description
const sym2 = Symbol('name'); // with description
console.log(sym2.description); // "name"
```

TIP

Description is just a label. It doesn't affect uniqueness.

```
Symbol('a') !== Symbol('a') // true
```

4. SYMBOLS ARE NOT ENUMERATED

```
const id = Symbol('id');
const user = { name: 'Faisal', [id]: 101, age: 21 };

console.log(Object.keys(user)); // ['name', 'age']
console.log(Object.getOwnPropertySymbols(user)); // [id]
console.log(JSON.stringify(user)); // '{"name":"Faisal","age":21}'
```

Object.keys(user)

name age

(Symbol property is hidden)

Object.getOwnPropertySymbols(user)

id

6. WELL-KNOWN SYMBOLS

JavaScript has built-in (well-known) symbols.

- Symbol.iterator → for iteration
- Symbol.toStringTag → for Object.prototype.toString()
- Symbol.toPrimitive → for type conversion
- Symbol.hasInstance → for instanceof

// Example: iterable using Symbol.iterator

```
const range = {
  from: 1, to: 3,
  [Symbol.iterator]() {
    let current = this.from;
    let last = this.to;
    return {
      next() {
        if (current <= last) return { value: current++, done: false };
        return { done: true };
      }
    };
  }
};

for (let n of range) console.log(n); // 1 2 3
```

9. KEY TAKEAWAYS

- ✓ Symbols are unique primitive values.
- ✓ Used as object property keys.
- ✓ Not enumerated in loops.
- ✓ Can be shared using Symbol.for().
- ✓ Great for hidden properties and advanced patterns.

Symbols = Unique. Hidden. Powerful. Use them wisely! ♥

EP 46

SET, MAP & THEIR METHODS IN JAVASCRIPT

Set and Map are built-in data structures that store unique values and key-value pairs. ❤️

Set stores unique values of any type. Map stores key-value pairs with any type of keys. 😊

1. WHAT ARE SET AND MAP?

- Introduced in ES6 (2015).
- Provide better performance than arrays/objects for specific use cases.
- Maintain insertion order.



2. SET

```
const set = new Set();
set.add(1);
set.add('hello');
set.add({ a: 1 });
set.add(1); // duplicate - ignored
console.log(set); // Set(3) {1, 'hello', {a: 1}}
```

SET METHODS

- `add(value)` → Adds value
- `has(value)` → Checks existence
- `delete(value)` → Removes value
- `size` → Number of values
- `clear()` → Removes all
- `values()` → Returns iterator
- `forEach()` → Iterates values

3. MAP

```
const map = new Map();
map.set('name', 'Faizal');
map.set(1, 'one');
map.set({ id: 1 }, 'object key');

console.log(map.get('name')); // Faizal
console.log(map.has(1)); // true
console.log(map.size); // 3
```

MAP METHODS

- `set(key, value)` → Adds/updates
- `get(key)` → Gets value
- `has(key)` → Checks existence
- `delete(key)` → Removes key
- `size` → Number of entries
- `clear()` → Removes all
- `keys()` → Returns key iterator
- `values()` → Returns value iterator
- `entries()` → Returns [key, value] iterator
- `forEach()` → Iterates entries

4. SET vs ARRAY

Feature	Set	Array
Stores	Unique values	Allows duplicates
Has method	<code>.has(value)</code>	<code>.includes(value)</code>
Add method	<code>.add(value)</code>	<code>.push(value)</code>
Remove	<code>.delete(value)</code>	<code>.splice(index)</code>
Performance (lookup)	Faster	Slower (O(n))
Use case	When uniqueness is required	When order + duplicates matter

5. MAP vs OBJECT

Feature	Map	Object
Keys	Any type	String or Symbol
Order	Preserves insertion order	Mostly, but integer keys are sorted
Size	<code>.size</code> property	<code>Object.keys(obj).length</code>
Iterable	Yes	No (need <code>Object methods</code>)
Performance	Better for frequent add/remove	Good for simple key-value storage
Use case	Dynamic keys, frequent operations	Fixed structure, config/data

Map is like an Object on steroids! 😊

6. EXAMPLES

SET EXAMPLE

```
const unique = new Set();
unique.add(10);
unique.add(20);
unique.add(10); // ignored
unique.add('30');

console.log(unique.size); // 3
for (let val of unique) {
  console.log(val);
}
```

MAP EXAMPLE

```
const userMap = new Map();
userMap.set('id', 1);
userMap.set('name', 'Faizal');
userMap.set('role', 'dev');

for (let {key, value} of userMap) {
  console.log(`${key}: ${value}`);
}
```

7. REAL WORLD USE CASES

Tracking Unique Items	Use Set to store unique user IDs, tags, selected items, etc.
Caching	Use Map to cache responses, DOM nodes, API results.
Counting / Grouping	Use Map to count occurrences or group by keys.
Configuration	Use Map for dynamic configs with non-string keys.

Remember:
Set = Unique Values
Map = Key → Value
Both = Ordered,
Fast & Powerful! ❤️

8. KEY TAKEAWAYS

- Set stores unique values of any type.
- Map stores key-value pairs with any type of keys.
- Both maintain insertion order.
- Use Set when you need uniqueness.
- Use Map when you need key-value storage.
- Powerful methods make your code clean and fast!

NOTE

They are iterable! 😊

LOOPING REMINDER

For...of with Set

```
for (let value of mySet) {
  console.log(value);
}
```

For...of with Map (keys)

```
for (let key of myMap.keys()) {
  console.log(key);
}
```

For...of with Map (values)

```
for (let value of myMap.values()) {
  console.log(value);
}
```

Master these and your JS skills level up! 🚀

EP 47

JAVASCRIPT ENGINE & SERIES FINALE


From the first line of code to the last episode, what a journey! Let's wrap it up with how JavaScript runs under the hood.

You started with basics and reached the engine. That's massive! Proud of you! 🌟

1. WHAT IS JS ENGINE?

- JS Engine is a program that executes JavaScript code.
- It reads your code, compiles it, and runs it line by line.
- Examples: V8 (Chrome, Node.js), SpiderMonkey (Firefox), JavaScriptCore (Safari)


2. THE BIG PICTURE



Not all engines follow the exact same steps, but this is the general flow!

Think of it like this: You write JS → Engine reads it → Understands it → Optimizes it → Runs it super fast! 🌟

3. MEMORY IN JS ENGINE



4. JS ENGINE FEATURES

- High Performance**: Optimizes code for speed.
- Garbage Collection**: Cleans up unused memory automatically.
- Security**: Runs code in a safe environment.
- Cross Platform**: Same JS code runs everywhere.
- JIT Compilation**: Compiles on the fly for better performance.

5. EXAMPLE ENGINES

V8		Used in Chrome, Edge, Node.js, Deno.
SpiderMonkey		Used in Firefox.
JavaScriptCore		Used in Safari.

6. JS ENGINE IN ACTION

```
function add(a, b) {
  return a + b;
}
console.log(add(2, 3));
// Output: 5
```

→

- ☒ Scanned
- ☒ Parsed
- ☒ Converted to bytecode
- ☒ Optimized
- ☒ Executed
- ☒ Result shown

7. WHAT WE LEARNED IN THIS SERIES

- ☒ Variables & Data Types
- ☒ Operators
- ☒ Control Flow
- ☒ Functions
- ☒ Arrays & Objects
- ☒ Strings & Template Literals
- ☒ DOM & Events
- ☒ Scope & Closures
- ☒ This Keyword
- ☒ Prototypes & Inheritance
- ☒ ES6+ Features
- ☒ Error Handling
- ☒ Asynchronous JS
- ☒ Promises
- ☒ Async/Await
- ☒ Modules
- ☒ Map, Set, WeakMap, WeakSet
- ☒ Symbols
- ☒ Iterators & Generators
- ☒ Advanced Patterns
- ☒ And the JS Engine!

8. SERIES FINALE

- 🌟 You made it to the end of an incredible journey!
- 🌟 From "Hello, World!" to understanding how JavaScript runs under the hood.
- 🌟 Keep building, keep experimenting.
- 🌟 The best way to master JS is to build real things.
- 🌟 This is not the end, it's just the beginning of your coding story!



Thank you for being part of this series! Keep coding. Keep growing. The world is yours! 🌟

Stay curious, Keep creating! +

One more console.log("Legend"); because you are one! 🌟