Retrieving Data Using HTTP




Deborah Kurata Consultant | Speaker | Author | MVP | GDE

@deborahkurata



Web Server



Module Overview




Observables and Reactive Extensions

Sending an HTTP request

Exception handling

Subscribing to an Observable

Application Architecture



To understand the HTTP code, it's important to understand Reactive Extensions and Observables

Reactive Extensions (RxJS)



A library for composing data using observable sequences

And transforming that data using operators

- Similar to .NET LINQ operators

Angular uses Reactive Extensions for working with data

Especially asynchronous data

Synchronous vs. Asynchronous





Asynchronous: No immediate response



HTTP requests are asynchronous: request and response

Getting Data

Application

- Get me a list of products
- Notify me when the response arrives
- I'll continue along

Get me products

Web Server

At some later point in time...

Application

- "Hey, your data arrived"
- OK, I'll process it. Thanks!

Here are the products

Web Server


Observable

A collection of items over time

- Unlike an array, it doesn't retain items
- Emitted items can be observed over time

Array: [A, P, P, L, E]


Observable:



What Does an Observable Do?



Nothing until we subscribe



next: Next item is emitted



error: An error occurred and no more items are emitted



complete: No more items are emitted

Getting Data

Application

- Call http get
- http get returns an Observable, which will emit notifications
- Subscribe to start the Observable and the get request is sent
- Code continues along

At some later point in time...

Application

- The response is returned
- The Observable emits a next notification
- We process the emitted response

Get me products


Web Server

Here are the products

[{cart},{hammer},{saw}]

Web Server


Observable Pipe



Common Observable Usage




Start the Observable (subscribe)



Pipe emitted items through a set of operators



Process notifications: next, error, complete



Stop the Observable (unsubscribe)


Example

Example


```
import { Observable, range, map, filter } from 'rxjs';
const source$: Observable<number> = range(0, 10);
source$.pipe(
   map(x => x * 3),
   filter(x => x % 2 === 0)
).subscribe(x => console.log(x));
```

Result 0 6 12 18 24

Application Architecture



Sending an HTTP Request




```
import { HttpClient } from '@angular/common/http';
@Injectable({
   providedIn: 'root'
})
export class ProductService {
  private productUrl = 'www.myWebService.com/api/products';
  constructor(private http: HttpClient) { }
  getProducts() {
   return this.http.get(this.productUrl);
```

Registering the HTTP Service Provider

app.module.ts

```
import { HttpClientModule } from '@angular/common/http';
@NgModule({
  imports: [
      BrowserModule,
      FormsModule,
      HttpClientModule ],
  declarations: [
      AppComponent,
      ProductListComponent,
      ConvertToSpacesPipe,
      StarComponent ],
  bootstrap: [ AppComponent ]
export class AppModule { }
```




```
import { HttpClient } from '@angular/common/http';
@Injectable({
   providedIn: 'root'
export class ProductService {
  private productUrl = 'www.myWebService.com/api/products';
  constructor(private http: HttpClient) { }
  getProducts() {
   return this.http.get(this.productUrl);
```

```
import { HttpClient } from '@angular/common/http';
@Injectable({
   providedIn: 'root'
export class ProductService {
  private productUrl = 'www.myWebService.com/api/products';
  constructor(private http: HttpClient) { }
  getProducts() {
   return this.http.get<IProduct[]>(this.productUrl);
```

```
import { HttpClient } from '@angular/common/http';
import { Observable } from 'rxjs';
@Injectable({
   providedIn: 'root'
export class ProductService {
  private productUrl = 'www.myWebService.com/api/products';
  constructor(private http: HttpClient) { }
  getProducts(): Observable<IProduct[]> {
   return this.http.get<IProduct[]>(this.productUrl);
```

Demo



Setting up an HTTP request

Exception Handling

```
import { HttpClient, HttpErrorResponse } from '@angular/common/http';
import { Observable, catchError, tap } from 'rxjs';
• • •
 getProducts(): Observable<IProduct[]> {
   return this.http.get<IProduct[]>(this.productUrl).pipe(
     tap(data => console.log('All: ', JSON.stringify(data))),
     catchError(this.handleError)
  private handleError(err: HttpErrorResponse) {
```

Subscribing to an Observable



```
x.subscribe()
x.subscribe(Observer)
x.subscribe({
    nextFn,
    errorFn,
    completeFn
})
const sub = x.subscribe({
     nextFn,
     errorFn,
     completeFn
```

Subscribing to an Observable

product.service.ts

```
getProducts(): Observable<IProduct[]> {
  return this.http.get<IProduct[]>(this.productUrl).pipe(
    tap(data => console.log('All: ', JSON.stringify(data))),
    catchError(this.handleError)
  );
}
```

product-list.component.ts

```
ngOnInit(): void {
   this.productService.getProducts().subscribe({
     next: products => this.products = products,
     error: err => this.errorMessage = err
   });
}
```

Unsubscribing from an Observable



Store the subscription in a variable



Implement the OnDestroy lifecycle hook



Use the subscription variable to unsubscribe


Unsubscribing from an Observable

product-list.component.ts

```
ngOnInit(): void {
   this.sub = this.productService.getProducts().subscribe({
      next: products => this.products = products,
      error: err => this.errorMessage = err
   });
}
```

```
ngOnDestroy(): void {
   this.sub.unsubscribe();
}
```

Demo



Subscribing to an Observable
Unsubscribing from an Observable

HTTP Checklist: Setup



Add HttpClientModule to the imports array of one of the application's Angular Modules

```
@NgModule({
   imports: [
      BrowserModule,
      FormsModule,
      HttpClientModule ],
   declarations: [...],
   bootstrap: [ AppComponent ]
})
export class AppModule { }
```

HTTP Checklist: Calling HTTP Get



Define a dependency for the Http Client Service in the constructor

Create a method for each HTTP request

Call the desired HTTP method, such as get

Use generics to specify the returned type

```
export class ProductService {
  private productUrl = 'www.myService.com/api/products';

  constructor(private http: HttpClient) { }

  getProducts(): Observable<IProduct[]> {
    return this.http.get<IProduct[]>(this.productUrl);
  }
}
```

HTTP Checklist: Exception Handling



Add error handling

```
getProducts(): Observable<IProduct[]> {
   return this.http.get<IProduct[]>(this.productUrl).pipe(
     tap(data => console.log(JSON.stringify(data))),
     catchError(this.handleError)
   );
}

private handleError(err: HttpErrorResponse) {
}
```

HTTP Checklist: Subscribing



Call the subscribe method of the returned observable

Provide a function to handle an emitted item

Provide a function to handle any returned errors

```
ngOnInit(): void {
   this.productService.getProducts().subscribe({
     next: products => this.products = products,
     error: err => this.errorMessage = err
   });
}
```

HTTP Checklist: Unsubscribing



Store the subscription in a variable

```
this.sub = this.ps.getProducts().subscribe(...)
```

Implement the OnDestroy lifecycle hook

export class PLComponent implements OnInit, OnDestroy

Use the subscription variable to unsubscribe

```
ngOnDestroy(): void {
   this.sub.unsubscribe();
}
```

Learning More



Pluralsight Courses

"Angular: Reactive Forms"

HTTP and CRUD


"RxJS in Angular: Reactive Development"


RxJS and Observables

"Angular HTTP Communication"

Intermediate HTTP Techniques

Application Architecture





Coming up next ...

Navigation and Routing Basics