



Automata Formal Languages & Logic

Preet Kanwal

Department of Computer Science & Engineering

Automata Formal Languages & Logic


Unit 3

Preet Kanwal

Department of Computer Science & Engineering

1. Construct a PDA for language $L = \{a^n b^n \mid n \geq 0\}$


Solution :



2. Construct a PDA for language $L = \{a^n b^{2n} \mid n \geq 1\}$

Solution : Two ways of solving the above language

- For every 2 b's pop one a




Automata Formal Languages and Logic

Unit 3 - Deterministic Pushdown Automata


Solution:

- Push 2 a's by encountering one a




3. Construct a PDA for language $L = \{a^n b^{2n+1} \mid n \geq 1\}$

Solution :




4. Construct a PDA for language $L = \{a^n b b^n \mid n \geq 1\}$

Solution :




5. Construct a PDA for language $L = \{a^n b^m c^{m+n} \mid m, n \geq 1\}$

Solution :




6. Construct a PDA for language $L = \{w \mid n_a(w) = n_b(w)\}$
where $w \in \{a, b\}^*$

Solution :




7. Construct a PDA for language $L = \{n_a(w) > n_b(w)\}$
where $w \in \{a,b\}^*$

Solution :



8. Construct PDA for language $L = \{wcw^R \mid w \in \{a,b\}^*\}$

Solution :





THANK YOU

Preet Kanwal

Department of Computer Science & Engineering

preetkanwal@pes.edu

+91 80 6666 3333 Extn 724