



BIG DATA

Big Data Algorithms

Page Rank Computations

K V Subramaniam

Computer Science and Engineering

Matrix Multiplication



BIG DATA

Overview



- Page Rank
- Source
 - Leskovec, Jure, Anand Rajaraman, and Jeffrey David Ullman. *Mining of massive datasets*. Cambridge University Press, 2014.
 - <http://infolab.stanford.edu/~ullman/mmds/book.pdf>

Page Rank : Overview




BIG DATA


Search Engine working



PES
UNIVERSITY
ONLINE



Pages in the WWW



Importance computation based on
usage of terms within the page.

BIG DATA

Issues with early search engines



- Term Spam
 - Unethical use add terms multiple times
- Example
 - I could setup a page with PES University occurring a 1000 times in the page.
 - Search Engine would think that my page is an authority for PES Univesity mark it as *important*
 - How to fix this?

BIG DATA


One possible solution



- Instead of taking terms in my page
- Consider how many pages are pointing into my page?
- Will this not solve the problem.
- NO!!
- Can add many spam pages that point to my page.

- Two techniques
 - Consider random surfers starting at a random pages
 - What fraction of surfers end up at my page?
 - This gives an indication of the importance of my page.
 - Page Rank
 - Take into account the terms near the links present in pages that point to my page
 - Gives an indication of how relevant my page is.


Page Rank : Transition Matrix



0	1	1	1
1	0	0	1
1	1	0	0
0	1	1	0

Let us start from our graph model of the internet

- Adjacency matrix represents which pages are reachable from a given page



If we are at node 4 (page 4) and we follow a link out


Then

- the pages we can visit are 1 and 2
- 3 is not reachable directly from 4

To summarize for node 4

#in links = 2

#out links = 2




Consider, a random surfer starting from page 4

Assume, that we have equal probability of taking either out link

So,

$$P(\text{transition at node 4}) = 1/\text{\#outlinks}$$


$$= \frac{1}{2}$$



For node for we can represent the probabilities of directly transitioning

- To every other page as a column vector

Source	
Dest	$\begin{bmatrix} 1/2 \\ 1/2 \\ 0 \\ 0 \end{bmatrix}$




For the entire graph with n nodes, this would be a $n \times n$ matrix

- Transition matrix (**M**)
- Each entry represents the probability of transition from a source to a destination
- Source column #
- Destination row #

Dest	Source →			
	0	1/3	1/2	1/2
↓	1/2	0	0	1/2
	1/2	1/3	0	0
	0	1/3	1/2	0

Page Rank : Following the random surfer




The random surfer can start off on any of the nodes

So each node has equal chance of being a starting node.

Lets call the relative importance of each node - **importance** represented as vector \mathbf{v}

Our first guess at this is called \mathbf{v}_0

$$\mathbf{v}_0 = \begin{bmatrix} 1/4 \\ 1/4 \\ 1/4 \\ 1/4 \end{bmatrix} \text{ Node importance}$$




As random surfer moves once

Compute chance they will land up in each of the nodes

For each node we compute the probability of ending up at that node based on previous node

Multiply transition matrix and \mathbf{v}

$$\begin{bmatrix} 0 & 1/3 & 1/2 & 1/2 \\ 1/2 & 0 & 0 & 1/2 \\ 1/2 & 1/3 & 0 & 0 \\ 0 & 1/3 & 1/2 & 0 \end{bmatrix} \begin{matrix} \mathbf{v}_0 \\ 1/4 \\ 1/4 \\ 1/4 \\ 1/4 \end{matrix} = \begin{bmatrix} 1/3 * 1/4 + 1/2 * 1/4 + 1/2 * 1/4 \\ 1/2 * 1/4 + 1/2 * 1/4 \\ 1/2 * 1/4 + 1/3 * 1/4 \\ 1/3 * 1/4 + 1/2 * 1/4 \end{bmatrix} = \begin{matrix} \mathbf{v}_1 \\ 1/3 \\ 1/4 \\ 5/24 \\ 5/24 \end{matrix}$$



With each move of the random surfer, we will repeat the computation

Multiply transition matrix and \mathbf{v}

	\mathbf{v}_1
0	1/3
1/2	1/4
1/2	5/24
0	5/24

$$= \mathbf{v}_2$$

Page Rank : As an Eigen vector problem

- x satisfies the equation to the right.
 - Generally: some set of equations for x .
- How do we solve for x ?
- Iterative algorithm: widely used in Big Data
 - i = number of times we have looped,
 - x_i = value of x on i^{th} iteration,
 - Calculate some "error term" based upon
 - Shows how far x_i is from the correct value.
 - E.g., $Ax_i - x_i$
 - Derive x_{i+1} based upon x_i and error term.
 - Loop over steps 3 and 4 until error term is small.
- Iterative algorithm calculates $x_0 x_1 x_2 x_3 \dots$ which eventually converges to a good (or the good) solution.

$$A \cdot \begin{bmatrix} x_1 \\ x_2 \\ x_3 \\ x_4 \end{bmatrix} = \begin{bmatrix} x_1 \\ x_2 \\ x_3 \\ x_4 \end{bmatrix}$$

BIG DATA

Iterative Algorithms: Fixed Point Iteration



- Suppose the equation that x satisfies has the form $x=f(x)$
- x may be a matrix or vector, then the following simplified iterative algorithm frequently works
- **Fixed point iteration**
 - Initialize x_0 to some value
 - Calculate $x_{i+1} = f(x_i)$
 - Loop over step 2 until either
 - error term = $|x_{i+1}-x_i|$ is small i.e., not much change between x_{i+1} and x_i
 - or for some maximum number of iterations.

https://en.wikipedia.org/wiki/Fixed-point_iteration#:~:text=In%20numerical%20analysis%2C%20fixed%2Dpoint,the%20fixed%20point%20iteration%20is

- Multiplying a $m \times n$ matrix by an n element vector gives an m element vector.
- If matrix is $n \times n$, the product will also be an n element vector.
$$A\mathbf{v} = \lambda\mathbf{v}$$
- Suppose
 - Multiplying A by \mathbf{v} gives back the same vector apart from a scale change .
 - λ is called the eigenvalue and \mathbf{v} the eigenvector.
 - Many problems (e.g., page rank) can be converted into finding eigenvalues of a matrix.

BIG DATA

Page Rank as Eigenvector Problem – Eigenvector Computation



- Initialize \mathbf{v} to be a vector of equal values.
- Loop
 - $\mathbf{v}_{i+1} = \mathbf{A}\mathbf{v}_i$
- Until there is little difference between \mathbf{v}_i and \mathbf{v}_{i+1}
- At this point
 - $\mathbf{v} = \mathbf{A}\mathbf{v}$
- \mathbf{v} is the eigenvector and page rank of the transition matrix of the web graph.

- We want to compute the *importance* (page rank) of each Web page.
- Assume that
 - If a page has importance I .
 - n links to other pages
 - It distributes its importance I among the n links equally (I/n)
- Use this assumption to calculate page rank

Page Rank : Map Reduce Implementation

BIG DATA

Implementation in Map Reduce



- We need support for
 - Handling multiple files as input to the mapper
 - The initial page rank
 - Part of the Transition Matrix
- Iteration over multiple matrix-vector multiplication rounds

```
public class multiInputFile extends Configured implements Tool
{

    public static class CounterMapper extends Mapper
    {
        public void map(LongWritable key, Text value, Context context)
        throws IOException, InterruptedException
        {
            String[] line=value.toString().split("\t");

            context.write(new Text(line[0]), new Text(line[1]));
        }
    }

    public static class CountertwoMapper extends Mapper
    {
        public void map(LongWritable key, Text value, Context context)
        throws IOException, InterruptedException
        {
            String[] line=value.toString().split("\t");
            context.write(new Text(line[0]), new Text(line[1]));
        }
    }
}
```

Mappers
write first
word as key,
2nd word as
value

```
public static class CounterReducer extends Reducer
{
    String line=null;

    public void reduce(Text key, Iterable values, Context context )
    throws IOException, InterruptedException
    {
        for(Text value:values)
        {
            line = value.toString();

            context.write(key, new Text(line));
        }
    }
}
```

Loop over values
Write each value as
separate record

Hadoop Multiple Input Files – job

```
public int run(String[] args) throws Exception {
    Configuration conf = new Configuration();
    Job job = new Job(conf, "aggprog");
    job.setJarByClass(multiInputFile.class);
    MultipleInputs.addInputPath(job, new Path(args[0]), TextInputFormat.class, CounterMapper.class);
    MultipleInputs.addInputPath(job, new Path(args[1]), TextInputFormat.class, CountertwoMapper.class);

    FileOutputFormat.setOutputPath(job, new Path(args[2]));
    job.setReducerClass(CounterReducer.class);
    job.setNumReduceTasks(1);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(Text.class);

    return (job.waitForCompletion(true) ? 0 : 1);
}

public static void main(String[] args) throws Exception {

    int ecode = ToolRunner.run(new multiInputFile(), args);
    System.exit(ecode);

}
}
```

Multiple input class

Set input file
for each
mapper

- One MR step produces an estimate of v
 - *The file is stored in HDFS*
- At the end of the iteration, we need to compare this with the previous iteration estimate of v
- After that, we use this file as the input for the next step of MR.



THANK YOU

K V Subramaniam, Usha Devi

Dept. of Computer Science and Engineering

subramaniamkv@pes.edu

ushadevibg@pes.edu