



ADVANTAGES

- Reduced environmental impact
- Healthier employees
- Clean products, fewer operational disruptions
- Less cleaning
- Less mold and extended product shelf life
- Reduce heating cost up to 30%

Application

Air purifier for dusty environments and large indoor premises such as pharmaceutical facilities, food factories, paper mills, welding workshops, bakeries, packaging production, printing facilities, processing industry, and other specialist applications such as upgrading of clean room environments and other classified assembly environments

Comment

Power supply: 3-phase 380-480V or 1-phase 230V
 Filter: F7, H13
 Fan: EC fan with adjustable airflow and ModBus connection
 Capacity: 0 - 6000 m³/h
 Connection: 4 standard round (diameter 315mm) or 2 standard round (diameter 315mm) and 2 round (diameter 250mm) with sound reduction
 Installation: Mobile or stationary, floor, wall or ceiling mounting (with wire or suspension arms)

Art. No.	Type	Dimensions WxHxD (mm)	Sound level (dB)	Power Consumption (W)	Weight (kg)	Air Volume (m ³ /h)
94000001	CC 6000 230V, 1 phase	798x1968x820	0-67	0-887	130	6000
94000002	CC 6000 380-400V, 3 phase	798x1968x820	0-67	0-887	130	6000
94000003	CC 6000 230V, 1 phase Horizontal	1262x1359x829	0-67	0-887	130	6000
94000004	CC 6000 380-400V, 3 phase Horizontal	1262x1359x829	0-67	0-887	130	6000

Uses 4 Pre + 2 main filters