



HD 5/11 Cage Classic

The HD 5/11 Cage Classic high-pressure cleaner with 110 bar water pressure, low weight, high mobility, durability and a robust tubular steel frame for the toughest jobs.



1 Durable and robust

- With its brass cylinder heads, the 3-piston axial-piston motor unit ensures an exceptionally long service life.
- The sturdy pipe frame provides protection in continuous heavy-duty use.

3 Easy to service

- Excellent access to all relevant components.

2 Versatile

- The machine can be attached to the floor or the wall.
- Very compact construction style and minimal weight.



HD 5/11 Cage Classic

- Continuous use possible thanks to durable axial pump
- Robust frame protects even in the toughest working conditions
- Ergonomically designed handle

Technical data

Order no.	1.520-204.0	
EAN code	4054278068497	
Current type	Ph / V / Hz	1 / 230 / 50
Flow rate	l/h	500
Working pressure	bar / MPa	110 / 11
Max. pressure	bar	160
Max. inlet temperature	°C	60
Connection load	kW	2.2
Weight	kg	17.8
Dimensions (L × W × H)	mm	475 × 335 × 340

Equipment

Spray gun	standard	
High-pressure hose	m	10 / DN 6, 250 bar
Spray lance	mm	600
Power nozzle	■	
Anti-twist system (AVS)	-	
Pressure cut-off	■	
High-pressure spray lance	■	
Servo Control	-	

■ Included in delivery.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides								
High-pressure hose, 30 m, ID 8, incl. rotary coupling	1	6.390-293.0	ID 8	315 bar	30 m		To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5.	▲
High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling	2	6.390-010.0	ID 8	315 bar	15 m			▲
High-pressure hose, 20 m, ID 8, 315 bar, extension piece	3	6.390-031.0	ID 8	315 bar	20 m			▲
High-pressure hose, 10m, DN 6	4	9.751-035.0					10m high-pressure hose (DN 6) for machines of the HD Classic range. With screw connections at each end M 22 x 1.5.	■
High-pressure hose, 10 m, ID 8, 315 bar, extension	5	6.391-342.0	ID 8	315 bar	10 m		To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5.	□
Longlife 400 with unions on both sides								
High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling	6	6.389-709.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 20 m, ID 8, extension	7	6.390-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling	8	6.390-294.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, ID 8, 400 bar, 1.5 m	9	6.392-282.0	ID 8	400 bar	1.5 m			□
High-pressure hose 1.5 m, ID 8, including connectors	10	6.390-178.0	ID 8	400 bar	1.5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	□
High-pressure hose Longlife 400, 10 m, ID 8, including rotary coupling	11	6.388-083.0	ID 8	400 bar	10 m		10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Flow rate					Price	Description	
Trigger guns										
Standard trigger gun	1	9.751-139.0							High-pressure gun for machines of the HD Classic range. With adapter for high-pressure hoses M 22 x 1.5.	■
EASY!Force Advanced	2	4.118-005.0							Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	□
Quick connect										
Quick coupling	3	6.401-458.0							For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.	□
Male coupling	4	6.401-459.0							Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 x 1.5 external thread.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Nozzle size				Price	Description	
Power nozzle spray angle 25°									
Power nozzle spray angle 25°	1	2.883-821.0	36					Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	■
HP nozzle spray angle 0°									
High-pressure nozzle spray angle 0°	2	2.884-533.0	40					High-pressure nozzle with powerful jet for extremely stubborn dirt.	□
Power nozzle spray angle 15°									
Power nozzle spray angle 15°	3	2.885-225.0	36						□
Power nozzle spray angle 40°									
Power nozzle spray angle 40°	4	2.884-522.0	40					Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0



		Order no.					Price	Description	
Y distributor									
Y distributor	1	4.405-048.0						Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	☐
	2	4.111-024.0							☐

■ Included in delivery.
 ☐ Available accessories.
 ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Flow rate	Nozzle size	Diameter	Price	Description	
FR Classic surface cleaner								
FR Classic surface cleaner	1	2.643-476.0					The ideal entry-level model in the Kärcher surface cleaner range for cleaning surfaces indoors and outdoors. With splash guard and up to 150 bar working pressure.	☐
Hard Surface Cleaner FRV 30								
FRV 30 surface cleaner	2	2.642-999.0					With the integrated and automatic suction of the dirty water, the FRV 30 makes surface cleaning even more efficient. There is no longer a need to rinse the surface after cleaning, as the dirty water can be removed through the 5m suction hose, which is supplied. Additional features include the non-marking steering rollers and double ceramic bearings. Machine specific nozzle kit must be ordered separately.	☐
Rubber lip for FRV 30	3	2.642-910.0					For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	☐
Extension hose 5 m	4	4.440-939.0					5m extension hose for FRV 30. Connection sleeve included.	☐
Hose fastening attachment kit	5	2.642-528.0					Suction cup for fixing the suction hose to smooth surfaces.	☐
Dirt trap attachment kit	6	2.642-532.0					Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	☐
Hard surface cleaner FR 30								
Surface Cleaner FR 30	7	2.642-997.0			300 mm		Up to 10 times greater area coverage compared with the conventional high pressure jet. Plastic casing for optimal manoeuvrability, double ceramic bearing for long working times, flexible connection joint for ergonomic handling and integrated parking position. Machine specific nozzle kit must be ordered separately.	☐
FR 30 Me surface cleaner								
Hard surface cleaner FR 30 Me	8	2.640-355.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	☐
Hard Surface Cleaner FR 50								
Hard surface cleaner FR 50	9	2.640-679.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	☐
Machine-specific nozzle kits for FR								
Nozzle kit for surface cleaners	10	2.640-401.0	500-650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	☐
Machine-specific nozzle kits for FRV								
Nozzle kit 040 - for FRV	11	2.642-431.0		40				☐
Machine-specific nozzle kits for FR Classic								
Nozzle kit for FR Classic 040	12	2.885-312.0		40			Nozzle kit specifically for FR Classic surface cleaner.	☐
FRV 30 Me surface cleaner								
FRV 30 Me	13	2.642-911.0					Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	☐
Extension hose FRV 30 Me and FRV 50 Me	14	4.441-040.0					5 m extension hose for FRV 30 Me. Includes connecting adapter.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0



		Order no.	Flow rate	Nozzle size	Diameter	Price	Description	
Surface Cleaner FR 50 Me								
FRV 50 ME	15	2.643-598.0						☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER


		Order no.						Price	Description	
Rotary coupling										
Rotary coupling	1	4.401-091.0							Reliably prevents twisting of HP hoses. Connection M 22 x 1.5 m. Handle protection	☐
Coupling										
Coupler -2xM22x1,5	2	4.403-002.0							For overriding the dismantled heating coil for cleaning alternative:4.111-029.0 adapter 1 - hose old / hose new	☐
Connector										
Nozzle screws / screw socket	3	4.402-022.0							Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	☐
Adapters										
Sealing cone complete	4	4.424-004.0							In order to install high-pressure hose with male coupling on thread with M22 x 1.5 Alternative:4.111-032.0 Adapter 4 - Device new / Hose old Swivel	☐
EASY!Lock adapter										
Adapter 1 M22AG-TR22AG	5	4.111-029.0							Adapter 1 to connect the old hose with the new hose	☐
Adapter 2 M22IG-TR22AG	6	4.111-030.0							Adapter 2 to connect the old device with the new hose and the old gun with the new hose	☐
Adapter 3 M22IG-TR22AG	7	4.111-031.0							Adapter 3 to connect the old gun with the new spray lance and new servo regulator	☐
Adapter 5 TR22IG-M22AG	8	4.111-033.0							Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	☐
Adapter 6 TR22IG-M22AG	9	4.111-034.0							Adapter 6 to connect the new device with the old hose and the old hose with the new gun	☐
Adapter 7 M18IG-TR20AG	10	4.111-035.0							Adapter 7 to connect the old spray lance with the new nozzle	☐
Adapter 8 TR20IG-M18AG	11	4.111-036.0							Adapter 8 to connect the new spray lance with the old nozzle	☐
Adapter 12 rotary coupling EASY!Lock 22 IG - M22 x 1.8 AG	12	4.111-046.0								☐
Cleaning agent injector										
Cleaning agent injector for high pressure (without nozzle)	13	3.637-170.0							Cleaning agent dosage at high pressure 3 - 5 %	☐
Cleaning agent injector for high and low pressure (without nozzles)	14	3.637-001.0							Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	☐
Machine-specific nozzle kit with order no. 4.637-033.0										
Nozzle kit HD 500-700 l/h	15	4.769-005.0							For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	☐
	16	4.769-045.0								☐
Nozzle insert with order no. 4.637-032.0										
Nozzle insert up to 1,100 l/h - high pressure	17	4.769-003.0							Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	☐
Nozzle insert up to 1,100 l/h - low pressure	18	4.769-001.0							For low pressure with machines up to 1,100 l/h	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Max. working pressure	Nozzle size			Price	Description	
Triple nozzles									
Triple nozzle 036	1	4.767-148.0	300 bar	36				Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For machines with an injector, the low-pressure flat stream is useful for cleaning agent suction and application. Connection M 18 x 1.5.	☐
Dirt Blaster, small									
Dirt blaster - more Performance	2	4.767-231.0	180 bar	40				With rotating point jet for more efficient removal: the new performance dirt blaster with nozzle size 040 achieves up to 50% higher cleaning and area performance than its predecessor.	☐
Dirt blaster, large									
Dirt blaster	3	4.763-252.0	300 bar	40				The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Nozzle size				Price	Description	
Wet blasting attachment (without nozzle)									
Wet blasting attachment with flow control (without nozzles)	1	4.762-010.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	☐
Wet blasting attachment without flow control (nozzles not included)	2	4.762-022.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	☐
Nozzle kits for wet jet unit									
Nozzle kit for wet jet unit 040	3	2.637-900.0	40					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.	☐
Boron carbide nozzle									
Boron carbide nozzle, for machines up to 1,000 l/h	4	6.415-084.0	6 mm					In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Max. working pressure	Nozzle size	Diameter	Price	Description	
Pipe cleaning hose, ID 6								
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	1	6.110-046.0	250 bar				The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	☐
Pipe cleaning hose, DN 6, 20 m, max. 120 bar	2	6.390-028.0	120 bar				The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	☐
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	3	6.110-008.0	250 bar					☐
Pipe cleaning hose, DN 6, 30 m, max. 120 bar	4	6.390-029.0	120 bar				30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	☐
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	5	6.110-047.0	250 bar				The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	☐
Pipe cleaning hose, DN 6, 20 m, max. 250 bar	6	6.390-030.0	250 bar				The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	☐
Pipe cleaning nozzle								
Pipe cleaning dirt blaster D 25 / 040	7	6.415-944.0		40	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	☐
Pipe cleaning dirt blaster D 30 / 040	8	6.415-946.0		40	30 mm			☐
Pipe cleaning dirt blaster D 35 / 040	9	6.415-948.0		40	35 mm			☐
Pipe cleaning nozzle	10	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	☐
	11	5.763-016.0		60	16 mm			☐
	12	5.763-017.0		50	30 mm		Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R 1/8" connection, 3 x 30° backwards, diameter 30 mm.)	☐
Rotating pipe cleaning nozzle	13	6.415-428.0		50	16 mm		Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Flow rate				Price	Description	
Cup foam lance									
Cup foam lance Advanced 042	1	6.394-969.0						Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	☐
1-litre cleaning agent container for foam lance	2	6.414-050.0						Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	☐
Inno Foam Kit									
Inno Foam Set with detergent injector	3	2.640-151.0						High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	☐
Easy Foam Set									
Easy Foam Set with RM injector	4	2.640-691.0						HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	☐
Nozzle kits for Inno/Easy Foam Set									
Nozzle kit 055 for Inno / Easy Set 500-600 l/h	5	2.640-870.0	500-600 l/h					Optimal adaptation to different machine outputs for economic use.	☐
Foam nozzle mounting kit									
Foam nozzle attachment kit	6	2.637-926.0						Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Length					Price	Description	
Automatic, self-winding hose reels for wall mounting										
Automatic stainless steel hose reel	1	6.392-442.0	40 m						Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	☐
Powder-coated swivel holder	2	2.639-931.0							Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	☐
Stainless steel swivel holder	3	2.641-867.0							Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	☐
Automatic hose reel, coated	4	2.639-919.0	20 m						Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	☐
Automatic hose reel, stainless steel, includes swivel holder	5	6.391-421.0	20 m						High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	☐
ABS automatic stainless steel hose drum	6	2.641-866.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	☐
Automatic hose reel, powder-coated steel / plastic	7	6.392-074.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	☐
Automatic stainless steel / synthetic material hose drum	8	6.392-083.0	20 m						Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	☐
Automatic hose reel, coated	9	6.392-106.0	20 m						Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	☐
Hose reel, automatic, basalt grey-coated	10	6.392-105.0	20 m						Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	☐
Automatic hose reel, stainless steel, includes swivel holder	11	6.392-076.0	20 m						High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	☐
Automatic stainless steel hose reel	12	6.392-122.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	☐
Automatic hose reel, powder-coated steel / plastic	13	6.392-975.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	☐
Automatic stainless steel / synthetic material hose drum	14	6.392-965.0	20 m							☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Length	Diameter		Price	Description	
Starting current limiter								
Starting current limiter	1	2.637-495.0					Reduces starting current in single-phase supply and protects line fuse.	☐
Geka coupling								
Geka connector with hose barb, R 3/4"	2	6.388-455.0					with hose liner	☐
Geka connector with inner thread, R 3/4"	3	6.388-473.0					with female thread	☐
Suction filter								
Water suction filter	4	6.414-956.0					Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	☐
Suction filter with check valve	5	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	☐
Water fine filter								
Water fine filter, with adapter	6	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	☐
Water supply hose								
Water supply hose	7	4.440-038.0	7.5 m				NW 13 R1" / R 3/4", up to 30 °C	☐
Backflow check valve								
Backflow preventer	8	2.641-374.0					To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER


		Order no.	Max. working pressure	Length			Price	Description	
Spray lances									
Vibrasoft lance	1	6.415-951.0	250 bar	950 mm				The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster.	☐
Spray lance									
250 mm lance, non-rotatable	2	4.760-667.0		250 mm				250 mm stainless steel lance. With manual coupling. Non-rotatable.	☐
550 mm lance, non-rotatable	3	4.760-665.0		550 mm				550 mm stainless steel lance. With manual coupling. Non-rotatable.	☐
Rotating spray lances									
600 mm spray pipe, rotatable	4	4.760-664.0	300 bar	600 mm				600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 840 mm, rotatable	5	4.760-663.0	300 bar	840 mm				850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
1050 mm spray pipe, rotatable	6	4.760-660.0	300 bar	1050 mm				1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
1550 mm spray pipe, rotatable	7	4.760-661.0	300 bar	1550 mm				1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
2050 mm spray pipe, rotatable	8	4.760-662.0	300 bar	2050 mm				2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Angular spray lance									
Spray lance for toilets and rain gutters	9	4.760-073.0						Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	☐
Flexible spray lance									
Flexible lance 1050 mm	10	6.394-654.0	210 bar	1050 mm				1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	☐
Telescopic spray lance									
Telescopic spray lance	11	6.394-690.0	225 bar					Can be continuously extended from 1.8 to 5.4 m. For cleaning areas that are difficult to reach, such as ceilings or facades. With integrated HD trigger gun, M 22 x 1.5 connection with rotary coupling. Connection for M 18 x 1.5 nozzles.	☐
Strap for telescopic spray pipe	12	6.373-987.0						Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	☐
Gutter cleaner									
Gutter cleaning lance	13	2.642-305.0						The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	☐
Undercarriage spray lance									
Underbody lance	14	4.760-245.0		700 mm				Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 5/11 CAGE CLASSIC

1.520-204.0

KÄRCHER



		Order no.	Flow rate				Price	Description	
Push-on washing brush									
Push-on wash brush	1	4.762-497.0						The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.	☐
Rotating washing brush									
Rotating wash brush for < 800 l/h machines, nylon bristles	2	4.762-561.0	500-800 l/h					The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60°C. (M 18 x 1.5, replaceable brush insert).	☐
Rotating wash brush for < 800 l/h machines, natural bristles	3	4.762-560.0	500-800 l/h					Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 x 1.5 (replaceable brush insert).	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Authorized Distributor



HD 5/11 Cage Classic, 1.520-204.0, 2017-12-30

A : 712 Ansal Chamber II, 6 , Bhikaji Cama Place, New Delhi -110066
T : 9311677446/9350735062 W : www.delta-solutions.in E : contact@delta-solutions.in