HALDIA INSTITUTE OF TECHNOLOGY

(Autonomous under MAKAUT)

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

PROJECT REPORT

"BANKAI : THE ULTIMATE ROBO DOG"

Submitted by Team 6BITS

- **ABHINABA PATRA**
- **SUNAM JANA**
- **SHIRSENDU SENAPATI**
- **AKASH KUMAR BAG**
- **BHABATOSH MAHATO**
- **BANASHREE GAYEN**

Under the Guidance of

Dr. Dibyendu Chowdhury Sir

ACKNOWLEDGEMENT

I would like to express my sincere gratitude to Prof. Dr. Dibyendu Chowdhury sir for their invaluable guidance and continuous support throughout the duration of this project. Their advice and encouragement were crucial in overcoming challenges.

I also thank the faculty and staff of the Department of Electronics and Communication Engineering for their assistance and motivation, which greatly helped me during this work.

Special thanks to my family and friends for their constant encouragement and understanding throughout the project.

Finally, I appreciate the help of my project team members and lab assistants who contributed to the successful completion of this project.

ABSTRACT

This project presents **Bankai**, a high-performance quadruped robot dog developed using the **ESP32 microcontroller** and **Ameba AMB82-MINI AI vision camera**. Designed for agility, intelligence, and real-world functionality, Bankai serves various applications like **security, surveillance, search & rescue, and education**. The robot is equipped with precise **MG995 servo motors**, a **12-bit 16-channel relay driver**, and powered by a **2200mAh LiPo battery**. Its lightweight, modular frame is **3D-printed using Creality Ender 3 V3** with **black and red PLA+ filament**, enabling strong, customizable, and scalable design. Bankai highlights the fusion of robotics, mobility, and edge computing, pushing the boundaries of intelligent robotic companions.

TABLE OF CONTENTS

- **Introduction**
- **Research Objectives**
  - Goals
  - Scope of Study
  - Research Questions
- **Methodology**
  - Design Overview
  - System Components
  - Operation & Workflow
  - Testing & Validation
- **Expected Results**
- **Applications and Use Cases**
- **Vision and Future Scope**
- **Budget and Resources**
- **Conclusion**
- **References**
- **Appendices**

1. INTRODUCTION

1.1 Overview of the Topic

The field of robotics has seen rapid advancements over the last decade, particularly in mobile and autonomous systems. **Quadruped robots**, inspired by the biomechanics of animals, offer exceptional stability, terrain adaptability, and functional versatility. Bankai represents our attempt to build such a robot, integrating modular mechanical design with advanced electronics and vision-based control.

1.2 Background Information

Unlike traditional wheeled or bipedal robots, quadrupeds excel in rough terrains due to their distributed leg structure. Many modern applications, such as military reconnaissance and disaster relief, require such capability. Through this project, we address these needs while building a scalable and affordable prototype suitable for future development.

1.3 Problem Statement

There is a lack of affordable, open-source robotic platforms that provide both mobility and intelligent perception. Commercial quadrupeds are costly and closed-source, limiting accessibility for educational institutions and research. **Bankai** bridges this gap by offering a low-cost, intelligent quadruped robot using widely available components.

1.4 Importance of the Study

This project serves as a foundation for students and engineers to explore robotics in a hands-on, interdisciplinary way. It fosters learning in embedded systems, AI, mechanical design, and control systems. Moreover, its scalability makes it suitable for adaptation in professional and industrial applications.

2. RESEARCH OBJECTIVES

2.1 Goals

- Develop a robust, 4-legged robotic platform capable of dynamic movement.
- Integrate sensors and vision for basic real-time environmental interaction.
- Ensure modularity for future upgrades in AI, autonomy, and mechanical design.
- Test practical applications like surveillance and rescue simulation.

2.2 Scope of Study

This project focuses on the development of a functional prototype using standard hobby electronics and open-source software. Though the current system is manually controlled, the architecture is built to support future wireless and AI integration.

2.3 Research Questions

- Can an affordable quadruped robot achieve stable, lifelike locomotion?
- How well can open-source hardware integrate with AI vision modules?
- What are the limitations of current low-cost components in real-world tasks?

3. METHODOLOGY

3.1 Design Overview

The design of Bankai includes three major systems:

- **Mechanical system** (3D-printed frame, servo mounts)
- **Electronic control system** (MCUs, sensors, relay drivers)
- **Software logic** (locomotion sequences, sensor data processing)

3.2 System Components

Component	**Function**
Arduino Mega 2560	Central control unit for servo management
ESP32	Secondary controller for wireless interfacing
Ameba AMB82 MINI	AI vision and edge processing
MG995 Servo Motors (12x)	Motion of legs (3 per leg)
12-bit 16-Channel Relay	Acts as servo driver interface
LiPo Batteries (5x)	Power source for servos and electronics
HC-SR04 Ultrasonic Sensor	Distance sensing and basic obstacle avoidance
HC-05 Bluetooth Module	Manual remote control capability
MPU6050 IMU Sensor	Measures balance and orientation
PLA+ Filament (2kg)	Material for 3D printing robot body
Creality Ender 3 V3 Printer	Used to fabricate body and parts

3.3System Operation & Workflow

1. **Power-Up:** The robot initializes all servos and sensors.
2. **Command Reception:** Manual or preset movement commands are triggered.
3. **Motion Execution:** Servos respond via relay driver, producing gaits.
4. **Sensor Feedback:** Distance and orientation are monitored in real time.
5. **AI Vision Module:** Processes visuals for obstacle or object tracking.

3.4 Testing & Validation

We tested:

- **Stability during walking** on various surfaces.
- **Servo response delay** under real loads.
- **Battery endurance** under continuous operation.
- **Vision-based tracking** with moving obstacles.

Results showed reliable operation with consistent balance and motion control.

4. EXPECTED RESULTS

4.1 Hypotheses

- Bankai will successfully perform basic quadruped walking and maintain balance.
- The AI camera will detect objects within a 2–3 meter range with good accuracy.
- Sensor integration will support obstacle detection and basic reactive behavior.
- Modular construction will allow quick maintenance and upgrades.

4.2 Predicted Functional Outcomes

- **Locomotion:** Smooth walking and turning on flat and slightly uneven terrain.
- **Vision:** Object recognition and basic gesture tracking using the Ameba AMB82 MINI.
- **Sensor Fusion:** Real-time data from MPU6050 and ultrasonic sensor to support balance and obstacle detection.
- **Modular Performance:** Quick servo replacement and frame part printing as needed.

4.3 Benefits and Impact

- Provides a strong base for future development of autonomous rescue and surveillance bots.
- Ideal for academic use in courses covering robotics, mechatronics, or embedded systems.
- Can be upgraded with machine learning models for advanced decision-making.
- Offers a low-cost alternative to commercial quadruped robots.

5. APPLICATIONS AND USE CASES

Bankai can serve in several real-world applications across multiple domains:

5.1 Search & Rescue

Bankai can navigate rough terrain, locate obstacles, and provide surveillance support during disaster scenarios. Its modularity allows the integration of cameras, microphones, and communication modules.

5.2 Security and Surveillance

With camera integration and mobility, Bankai can be used for routine patrol in restricted or high-security zones, transmitting real-time video feeds via Wi-Fi or Bluetooth.

5.3 Educational Robotics

Bankai serves as a perfect hands-on platform for engineering students. It covers multiple disciplines including electronics, coding, CAD, and artificial intelligence.

5.4 Military Use

In the future, Bankai can assist in tactical scenarios such as reconnaissance missions, terrain mapping, and bomb detection with necessary upgrades.

5.5 Industrial Inspection

In factories or warehouses, Bankai can be programmed to inspect machinery, pipelines, or hazardous areas.

6. VISION AND FUTURE SCOPE

6.1 Long-Term Vision

Bankai is envisioned as a fully autonomous quadruped robot capable of:

- Dynamic path planning
- Real-time decision-making using AI
- Cloud data synchronization for remote monitoring
- Voice command processing

6.2 Planned Enhancements

- **AI Upgrades:** Integrate deep learning models for face/object recognition.
- **Wireless Control:** Add smartphone or web-based interfaces.
- **Path Planning:** Implement SLAM (Simultaneous Localization and Mapping).
- **Solar Charging:** For outdoor use and improved sustainability.
- **GPS Integration:** Enable autonomous outdoor navigation and mapping.

7. BUDGET AND RESOURCES

Overview

The Bankai project is developed using cost-effective and widely available components. The choice of open-source hardware and accessible materials ensures that the robot can be built and replicated in academic and research environments.

7.1 Bill of Materials

Component / Material	Quantity	Unit Cost (INR)	Total Cost (INR)
Arduino Mega 2560	1	₹800	₹800
ESP32 Board	1	₹400	₹400
Ameba AMB82-MINI AI Camera	1	₹2,000	₹2,000
MG995 Servo Motors	12	₹200	₹2,400
12-bit 16-Channel Relay Driver	1	₹350	₹350
LiPo Battery (2200mAh)	5	₹800	₹4,000
PLA+ Filament (Black & Red, 1kg each)	2 kg	₹1,200/kg	₹2,400
HC-SR04 Ultrasonic Sensor	1	₹100	₹100
HC-05 Bluetooth Module	1	₹200	₹200
MPU6050 IMU Sensor	1	₹250	₹250
Misc. Electronics & Wiring	—	—	₹1,000

Total: ₹13,900

7.2 Tools Required

- Creality Ender 3 V3 3D Printer
- Soldering kit
- Arduino IDE
- Creality Slicer
- Digital Multimeter
- Wire cutter, pliers

7.3 Human Resources

Role	**Responsibility**
Hardware Engineer	Assemble components and wiring
Programmer	Develop motion logic, sensor integration
Mechanical Designer	Design and 3D print parts
Tester	Evaluate movement accuracy, balance, response
Documentation Lead	Maintain logs, test results, and prepare reports

8. CONCLUSION

Bankai, the ultimate robo dog, represents a practical and scalable solution in the realm of quadruped robotics. Through intelligent integration of motion control, sensor feedback, and AI vision, it achieves stable locomotion and basic environmental interaction—using affordable and accessible hardware.

The use of the **Arduino Mega 2560**, **Ameba AMB82 MINI**, and **ESP32** ensures both performance and expandability. The hardware-software synergy enables Bankai to perform real-time operations, adapt to commands, and function as an educational tool as well as a research platform.

The 3D-printed body enhances durability while allowing easy reconfiguration. This makes Bankai not just a product, but a prototype that can evolve into more advanced robots capable of autonomous surveillance, search & rescue, and more.

As technology advances, Bankai's foundation allows seamless addition of AI, IoT, GPS, and other intelligent systems. With further development, it has the potential to become a key player in real-world robotic deployment—both in academic and industrial contexts.

9. REFERENCES

- ESP32 Module – www.espressif.com
- Realtek Ameba AMB82 MINI – www.amebaiot.com
- MG995 Servo Motor Specifications – www.robokits.co.in
- HC-05 Bluetooth Module Documentation – www.electronicwings.com
- HC-SR04 Ultrasonic Sensor – www.electronicshub.org
- MPU6050 IMU Sensor – www.invensense.tdk.com
- Creality Ender 3 V3 – www.creality.com
- Creality Slicer Software – Creality Cloud
- Arduino Mega 2560 Datasheet – www.arduino.cc

10. APPENDICES

Appendix A: Pin Mapping Overview

Module	Connected To	Purpose
MG995 Servos	ESP32 PWM Pins	Limb Movement Control
Ameba AMB82 MINI	ESP32 via UART/I2C	Vision Processing & Streaming
HC-SR04	ESP32 GPIO	Distance Measurement
HC-05 Bluetooth Module	ESP32 TX/RX	Wireless Communication
MPU6050 IMU Sensor	ESP32 I2C Pins	Orientation & Balance Control

Appendix B: 3D Printed Part List

Part	Print Time	Material Used
Main Body Frame	6 hrs	PLA+ (Black)
Leg Segments (x4 sets)	4 hrs each	PLA+ (Red)
Servo Brackets (x12)	2 hrs	PLA+ (Black)
Battery Holder	1.5 hrs	PLA+ (Red)

Appendix C : Testing Summary

Test Scenario	**Result**	**Notes**
Forward Walking	Partial success	Stable on tiled and wooden floors
Turning (Left/Right)	Unsuccess	Minor delay at higher servo loads
Vision-based Object Tracking	Partial Success	Works reliably under good lighting
Sensor Fusion with MPU6050	Success	Smooth recovery on small terrain bumps
Power Management	Success	Avg. runtime ~45 minutes per full charge