

Gaussian Mixture Model


Kookjin Lee

(kookjin.Lee@asu.edu)

The contents of this course, including lectures and other instructional materials, are copyrighted materials. Students may not share outside the class, including uploading, selling or distributing course content or notes taken during the conduct of the course. Any recording of class sessions is authorized only for the use of students enrolled in this course during their enrollment in this course. Recordings and excerpts of recordings may not be distributed to others. (see ACD 304 – 06 , “ Commercial Note Taking Services ” and ABOR Policy 5 - 308 F.14 for more information).


K-means clustering

- K=2



K-means clustering

- K=2



Probabilistic ways of assigning centers

- K clusters


- Assign the probability
- Introducing a latent (hidden) variable $z^{(i)}$

$$z^{(i)} \in \{1, \dots, K\}$$

$$z^{(i)} \sim \text{Multinomial}(\phi)$$

$$\phi = (\phi_1, \dots, \phi_K), \quad \sum \phi_i = 1$$

$$p(z^{(i)} = j)$$




Probabilistic ways of assigning centers

- K clusters
 - Assign the probability
 - Introducing a latent (hidden) variable $z^{(i)}$
 - Conditional probability

$$x^{(i)} | z^{(i)} = j \sim \mathcal{N}(\mu_j, \Sigma_j)$$

- All together

$$p(x^{(i)}, z^{(i)}) = p(x^{(i)} | z^{(i)})p(z^{(i)})$$




EM for mixtures of Gaussians in pictures – initialization

41

©2017 Emily Fox

CSE 446: Machine Learning




EM for mixtures of Gaussians in pictures – after 1st iteration


42

©2017 Emily Fox

CSE 446: Machine Learning




EM for mixtures of Gaussians in pictures – after 2nd iteration



43

CSE 446: Machine Learning

EM for mixtures of Gaussians in pictures – converged solution




44

CSE 446: Machine Learning

Examples

Discover groups of similar images

- Ocean
- Pink flower
- Dog
- Sunset
- Clouds
- ...



Simple image representation

Consider average red, green, blue pixel intensities



[R = 0.05, G = 0.7, B = 0.9]




[R = 0.85, G = 0.05, B = 0.35]



[R = 0.02, G = 0.95, B = 0.4]


Distribution over all cloud images

Let's look at just the blue dimension



Distribution over all sunset images

Let's look at just the **blue** dimension




Distribution over all forest images


Let's look at just the **blue** dimension



Distribution over all images




Assume Gaussian distribution





Revisiting Gaussian

- 1D gaussian



Revisiting Gaussian

- 2D Gaussian



Revisiting Gaussian


- 2D Gaussian

Fully specified by **mean** μ and **covariance** Σ



$$\mu = [\mu_{\text{blue}}, \mu_{\text{green}}]$$

$$\Sigma = \begin{pmatrix} \sigma_{\text{blue}}^2 & \sigma_{\text{blue},\text{green}} \\ \sigma_{\text{green},\text{blue}} & \sigma_{\text{green}}^2 \end{pmatrix}$$

covariance determines
orientation + spread





Gaussian per each cluster/group



In reality



- No labels



In reality


- No labels

e.g., forest images are very likely in the collection




Mixture of Gaussian

- Weighting each Gaussian



Mixture of Gaussian

- Characterize each component




Mixture of Gaussian

Without observing the image content, what's the probability it's from cluster k? (e.g., prob. of seeing "clouds" image)

$$p(z_i = k) = \pi_k$$

Given observation \mathbf{x}_i is from cluster k, what's the likelihood of seeing \mathbf{x}_i ?
(e.g., just look at distribution for "clouds")

$$p(x_i | z_i = k, \mu_k, \Sigma_k) = N(x_i | \mu_k, \Sigma_k)$$



Probabilistic ways of assigning centers

- Again, we need to find optimal values of parameters
 - How? Maximum (log) likelihood

$$\ell(\phi, \mu, \Sigma) = \sum_i \log p(x^{(i)}; \phi, \mu, \Sigma)$$

$$\ell(\phi, \mu, \Sigma) = \sum_i \log \sum_{z^{(i)}=1}^K p(x^{(i)}|z^{(i)}; \phi, \mu, \Sigma) p(z^{(i)}; \phi)$$

Assumptions on the values of z

- Assume: we know what the value of $z^{(i)}$ is

$$\ell(\phi, \mu, \Sigma) = \sum_i \log p(x^{(i)} | z^{(i)}; \phi, \mu, \Sigma) p(z^{(i)}; \phi)$$

$$\ell(\phi, \mu, \Sigma) = \sum_i \left(\log p(x^{(i)} | z^{(i)}; \phi, \mu, \Sigma) + \log p(z^{(i)}; \phi) \right)$$

Recall GDA

- Optimal values of parameters?

$$\phi_j = \frac{\sum_{i=1}^{n_{\text{train}}} \mathbb{1}[z^{(i)} = j]}{n_{\text{train}}}$$

$$\mu_j = \frac{\sum_{i=1}^{n_{\text{train}}} \mathbb{1}[z^{(i)} = j] x^{(i)}}{\sum_{i=1}^{n_{\text{train}}} \mathbb{1}[z^{(i)} = j]}$$

$$\Sigma_j = \frac{\sum_{i=1}^{n_{\text{train}}} \mathbb{1}[z^{(i)} = j] (x^{(i)} - \mu_j) (x^{(i)} - \mu_j)^T}{\sum_{i=1}^{n_{\text{train}}} \mathbb{1}[z^{(i)} = j]}$$

Expectation-Maximization algorithm

- EM algorithm

$$\ell(\phi, \mu, \Sigma) = \sum_i \log \sum_{z^{(i)}=1}^K p(x^{(i)}|z^{(i)}; \phi, \mu, \Sigma) p(z^{(i)}; \phi)$$

$$\ell(\phi, \mu, \Sigma) = \sum_i \left(\log p(x^{(i)}|z^{(i)}; \phi, \mu, \Sigma) + \log p(z^{(i)}; \phi) \right)$$

- Expectation: guess the values of $z^{(i)}$
- Maximization: update the model parameter based on the guess

EM algorithm

- Algorithm

- E-step:

$$w_j^{(i)} = p(z^{(i)} = j | x^{(i)}; \phi, \mu, \Sigma)$$

- M-step:

$$\phi_j = \frac{1}{n} \sum_i w_j^{(i)}$$

$$\mu_j = \frac{\sum_i w_j^{(i)} x^{(i)}}{\sum_i w_j^{(i)}}$$

$$\Sigma_j = \frac{\sum_i w_j^{(i)} (x^{(i)} - \mu_j)(x^{(i)} - \mu_j)^T}{\sum_i w_j^{(i)}}$$

Maximum likelihood estimation from soft assignments

Just like in boosting with weighted observations...

R	G	B	r_{i1}	r_{i2}	r_{i3}
$\mathbf{x}_1[1]$	$\mathbf{x}_1[2]$	$\mathbf{x}_1[3]$	0.30	0.18	0.52
$\mathbf{x}_2[1]$	$\mathbf{x}_2[2]$	$\mathbf{x}_2[3]$	0.01	0.26	0.73
$\mathbf{x}_3[1]$	$\mathbf{x}_3[2]$	$\mathbf{x}_3[3]$	0.002	0.008	0.99
$\mathbf{x}_4[1]$	$\mathbf{x}_4[2]$	$\mathbf{x}_4[3]$	0.75	0.10	0.15
$\mathbf{x}_5[1]$	$\mathbf{x}_5[2]$	$\mathbf{x}_5[3]$	0.05	0.93	0.02
$\mathbf{x}_6[1]$	$\mathbf{x}_6[2]$	$\mathbf{x}_6[3]$	0.13	0.86	0.01

Total weight in cluster: **1.242** **2.8** **2.42**
(effective # of obs)

52% chance this obs is in cluster 3

31

©2017 Emily Fox

CSE 446: Machine Learning

Maximum likelihood estimation from soft assignments

R	G	B	r_{i1}	r_{i2}	r_{i3}
$\mathbf{x}_1[1]$	$\mathbf{x}_1[2]$	$\mathbf{x}_1[3]$	0.30	0.18	0.52
$\mathbf{x}_2[1]$	$\mathbf{x}_2[2]$	$\mathbf{x}_2[3]$	0.01	0.26	0.73
$\mathbf{x}_3[1]$	$\mathbf{x}_3[2]$	$\mathbf{x}_3[3]$	0.002	0.008	0.99
$\mathbf{x}_4[1]$	$\mathbf{x}_4[2]$	$\mathbf{x}_4[3]$	0.75	0.10	0.15
$\mathbf{x}_5[1]$	$\mathbf{x}_5[2]$	$\mathbf{x}_5[3]$	0.05	0.93	0.02
$\mathbf{x}_6[1]$	$\mathbf{x}_6[2]$	$\mathbf{x}_6[3]$	0.13	0.86	0.01

32

©2017 Emily Fox

CSE 446: Machine Learning

MLE of cluster proportions $\hat{\pi}_k$

r_{i1}	r_{i2}	r_{i3}
0.30	0.18	0.52
0.01	0.26	0.73
0.002	0.008	0.99
0.75	0.10	0.15
0.05	0.93	0.02
0.13	0.86	0.01

Total weight
in cluster:

1.242	2.8	2.42
-------	-----	------

Total weight
in dataset:

6

$$\hat{\pi}_k = \frac{N_k^{\text{soft}}}{N}$$

$$N_k^{\text{soft}} = \sum_{i=1}^N r_{ik}$$

Total weight in cluster k
= effective # obs

Estimate cluster proportions
from relative weights

35

©2017 Emily Fox

CSE 446: Machine Learning

Defaults to hard assignment case when $r_{ij} \in \{0,1\}$

Hard assignments have:

$$r_{ik} = \begin{cases} 1 & i \text{ in } k \\ 0 & \text{otherwise} \end{cases}$$

R	G	B	r_{i1}	r_{i2}	r_{i3}
$x_1[1]$	$x_1[2]$	$x_1[3]$	0	0	1
$x_2[1]$	$x_2[2]$	$x_2[3]$	0	0	1
$x_3[1]$	$x_3[2]$	$x_3[3]$	0	0	1
$x_4[1]$	$x_4[2]$	$x_4[3]$	1	0	0
$x_5[1]$	$x_5[2]$	$x_5[3]$	0	1	0
$x_6[1]$	$x_6[2]$	$x_6[3]$	0	1	0

Total weight in cluster:

1	2	3
---	---	---

One-hot encoding of
cluster assignment

36

©2017 Emily Fox


CSE 446: Machine Learning

EM for mixtures of Gaussians in pictures – initialization

41

©2017 Emily Fox

CSE 446: Machine Learning




EM for mixtures of Gaussians in pictures – after 1st iteration


42

©2017 Emily Fox

CSE 446: Machine Learning




EM for mixtures of Gaussians in pictures – after 2nd iteration



43

CSE 446: Machine Learning

EM for mixtures of Gaussians in pictures – converged solution



44

CSE 446: Machine Learning

How do we compute E-step?

- Bayes' rule!

$$p(z^{(i)} = j | x^{(i)}; \phi, \mu, \Sigma) = \frac{p(x^{(i)} | z^{(i)} = j; \mu, \Sigma)p(z^{(i)} = j; \phi)}{\sum_l p(x^{(i)} | z^{(i)} = l; \mu, \Sigma)p(z^{(i)} = l; \phi)}$$