Classification

Kookjin Lee

(kookjin.Lee@asu.edu)

The contents of this course, including lectures and other instructional materials, are copyrighted materials. Students may not share outside the class, including uploading, selling or distributing course content or notes taken during the conduct of the course. Any recording of class sessions is authorized only for the use of students enrolled in this course during their enrollment in this course. Recordings and excerpts of recordings may not be distributed to others. (see ACD 304 – 06, "Commercial Note Taking Services" and ABOR Policy 5 - 308 F.14 for more information).

Introduction to classification

- New task!
- Example:

 A flower shop wants to guess
 a customer's purchase from
 similarity to most recent purchase.






What is needed for classification


- Data with
 - Features that can be quantitated
 - Labels that are known → supervised learning
- Method to measure similarity


Your first classification algorithm


• K Nearest Neighbors (KNN) classification





- KNN classification
 - How to make prediction?












What is Needed to Select a KNN Model

- Correct value for 'K'
- How to measure closeness of neighbors?
 - Euclidean distance (L2)


Decision boundary for varying K

K=1 or K=all




Feature scaling

• Features with different numerical scales



Feature scaling (continued)

After scaling



Feature scaling (continued)


• Standard scaler: mean center data and scale to unit variance

Minimum-Maximum Scaler: scale data to fixed range (usually 0–1)

Maximum Absolute Value Scaler: scale maximum absolute value

Regression with KNN

$$y = \frac{1}{k} \sum_{x_i \in N_k(x)} y_i$$



Regression with KNN

$$y = \frac{1}{k} \sum_{x_i \in N_k(x)} y_i$$

