

---

# Git File Lifecycle (Stages)

---

In Git, **every file moves through well-defined stages** from its creation on a developer's machine to being stored on a remote repository such as GitHub. Understanding these stages is **fundamental** to using Git correctly and confidently.

---

## Overview: The Four Main Stages

Working Directory → Staging Area → Local Repository → Remote Repository

Each stage represents a different level of tracking and permanence for your files.

---

## 1. Working Directory (Untracked / Modified)

What is the Working Directory?

- The actual **project folder** on your system
  - Where developers **create, edit, or delete files**
  - This is the default state when you open a project
- 

### File States in the Working Directory

#### 1. Untracked

- A **new file** created in the project
- Git is **not tracking** this file yet
- Git has no record of this file in its history

Example:

```
index.html → untracked
```

---

#### 2. Modified

- File is already **tracked by Git**
- Content has been **changed after the last commit**

Example:

```
style.css → modified
```

---

## Commands Used

```
git status
```

This command shows:

- Untracked files
  - Modified files
  - Staged files
- 

## Key Point

Changes in the working directory are **not saved in Git history** until they are staged and committed.

---

## 2. Staging Area (After `git add`)

What is the Staging Area?

- An **intermediate area** between working directory and local repository
  - Used to **select which changes** will go into the next commit
  - Also called the **Index**
- 

What `git add` Does

```
git add file_name
```

or

```
git add .
```

- Moves selected changes from **Working Directory** → **Staging Area**
  - Does **NOT** create a commit
  - Only marks files as **ready to be committed**
- 

## File State

- **Staged**

---

## Example

```
git add index.html
```

Current state:

```
index.html → staged  
style.css → still modified
```

---

## Why the Staging Area is Important

- Allows **partial commits**
- Helps create **clean and meaningful commit history**
- Widely used in **professional and team-based projects**

---

## 3. Local Repository (After `git commit`)

What is the Local Repository?

- Stored inside the hidden **.git** folder
- Contains the **complete commit history**
- Fully functional **without internet**

---

What `git commit` Does

```
git commit -m "Initial commit"
```

- Takes a **snapshot of staged files**
- Saves them permanently in the local repository
- Generates the following metadata:
  - Commit ID (hash)
  - Author name and email
  - Timestamp
  - Commit message

---

## File State

- **Committed**
-

## Important Rule

Only **staged files** are committed. Unstaged or modified files are ignored during commit.

---

## 4. Remote Repository (After `git push`)

### What is a Remote Repository?

- Repository hosted on platforms like:
    - GitHub
    - GitLab
    - Bitbucket
  - Used for **sharing, collaboration, and backup**
- 

### What `git push` Does

```
git push origin main
```

- Sends local commits to the remote repository
  - Makes the code available to:
    - Team members
    - CI/CD pipelines
    - Code review systems
- 

### File State

- **Published**
- 

## Complete Flow with Commands

```
# Working Directory
vim index.html

# Check current file status
git status

# Stage changes
git add index.html

# Commit to local repository
git commit -m "Add homepage structure"

# Push commits to GitHub
git push origin main
```

---

## Visual Summary (Quick Revision)

```

Edit File
  ↓
Working Directory (Untracked / Modified)
  ↓ git add
Staging Area (Staged)
  ↓ git commit
Local Repository (Committed)
  ↓ git push
Remote Repository (GitHub)
```