

react-router

- It is used to open the required pages depending on the url path
- to install use the below command
- npm install react-router
- to make your react app use the routing mechanism add the APP component inside the BrowserRouter

Why not to use local variables

- Local variables does not help in rerendering

React hooks

- The predefined functions given by react that starts with use
- useState()
- useNavigate()

useState()

- It returns an array which consists of 2 elements
- 0th index -> initial value is stored
- 1st index -> function that helps in changing the value on the 0th index
- the state will help to re-render the page if there are any changes in the state
- whatever state returns can be destructured
- const [email, setEmail] = useState("")

Navigation

- To perform navigation in react we have to first install react-router
- We can perform 2 types of navigation
 1. static navigation
 - this is used by using Link component
 - <Link to='/home'>Home</Link>
 - this is a kind of similar to our anchor tags
 2. dynamic navigation
 - this is used to navigate to the other pages on some conditions
 - to perform dynamic navigation we have to use the hook called as useNavigate()
 - const navigate = useNavigate()
 - navigate('/home')

Axios

- Axios is a promise-based HTTP Client for node.js and the browser.
- used to call the backend api's which returns the promise
- to resolve the promise use the async .. await keywords

```
async function registerUser(name, email, password, mobile) {  
  const URL = 'http://localhost:4000/user/signup'  
  const body = { name, email, password, mobile }  
  const response = await axios.post(URL, body)  
  return response.data  
}
```

```
axios.get()  
axios.post()  
axios.put()  
axios.delete()
```

react-toastify

- React-Toastify allows you to add notifications to your app with ease.
- to add it use the below command
- npm install react-toastify
- to use it in our application first add the ToastContainer inside the App.jsx
-

```
import { ToastContainer } from 'react-toastify'
```

```
function App() {  
  return (  
    <>  
      <Routes>  
        <Route path="/" element={<Login />} />  
        <Route path="/home" element={<Home />} />  
      </Routes>  
  
      <ToastContainer />  
    </>  
  )  
}
```

- To add the toast we can use the below methods.

```
toast.success()
```

```
toast.error()
```

```
toast.warn()
```

