

Data Abstraction

Announcements

Data Abstraction

Data Abstraction

Data Abstraction

- Compound values combine other values together

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)
 - How data are manipulated (as units)

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)
 - How data are manipulated (as units)
- Data abstraction: A methodology by which functions enforce an abstraction barrier between **representation** and **use**

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)
 - How data are manipulated (as units)
- Data abstraction: A methodology by which functions enforce an abstraction barrier between **representation** and **use**

All
Programmers

Great
Programmers

Rational Numbers

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

Rational Numbers

numerator

denominator

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

- `rational(n, d)` returns a rational number `x`

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

Constructor

`rational(n, d)` returns a rational number `x`

- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

Constructor

`rational(n, d)` returns a rational number `x`

Selectors

- `numer(x)` returns the numerator of `x`

- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic

Example

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5}$$

Example

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

Example

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{3}{2} + \frac{3}{5}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{3}{2} + \frac{3}{5} = \frac{21}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{3}{2} + \frac{3}{5} = \frac{21}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{3}{2} + \frac{3}{5} = \frac{21}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

General Form

Rational Number Arithmetic Implementation

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational(numer(x) * numer(y),  
                    denom(x) * denom(y))
```

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational( numer(x) * numer(y),  
                    denom(x) * denom(y) )
```

Constructor

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational(numer(x) * numer(y),  
                   denom(x) * denom(y))
```

Constructor

Selectors

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational(numer(x) * numer(y),  
                    denom(x) * denom(y))
```

Constructor

Selectors

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

These functions implement an abstract representation for rational numbers

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational(numer(x) * numer(y),  
                    denom(x) * denom(y))
```

Constructor

Selectors

```
def add_rational(x, y):  
    nx, dx = numer(x), denom(x)  
    ny, dy = numer(y), denom(y)  
    return rational(nx * dy + ny * dx, dx * dy)
```

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

These functions implement an abstract representation for rational numbers

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational(numer(x) * numer(y),  
                    denom(x) * denom(y))
```

Constructor

Selectors

```
def add_rational(x, y):  
    nx, dx = numer(x), denom(x)  
    ny, dy = numer(y), denom(y)  
    return rational(nx * dy + ny * dx, dx * dy)
```

```
def print_rational(x):  
    print(numer(x), '/', denom(x))
```

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

These functions implement an abstract representation for rational numbers

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational(numer(x) * numer(y),  
                    denom(x) * denom(y))
```

Constructor

Selectors

```
def add_rational(x, y):  
    nx, dx = numer(x), denom(x)  
    ny, dy = numer(y), denom(y)  
    return rational(nx * dy + ny * dx, dx * dy)
```

```
def print_rational(x):  
    print(numer(x), '/', denom(x))
```

```
def rationals_are_equal(x, y):  
    return numer(x) * denom(y) == numer(y) * denom(x)
```

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

These functions implement an abstract representation for rational numbers

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

Representing Rational Numbers

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

```
def numer(x):  
    """Return the numerator of rational number X."""  
    return x[0]
```

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

```
def numer(x):  
    """Return the numerator of rational number X."""  
    return x[0]  
  
def denom(x):  
    """Return the denominator of rational number X."""  
    return x[1]
```

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

```
def numer(x):  
    """Return the numerator of rational number X."""  
    return x[0]
```

```
def denom(x):  
    """Return the denominator of rational number X."""  
    return x[1]
```

Select item from a list

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

```
def numer(x):  
    """Return the numerator of rational number X."""  
    return x[0]
```

```
def denom(x):  
    """Return the denominator of rational number X."""  
    return x[1]
```

Select item from a list

(Demo)

Reducing to Lowest Terms

Example:

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3}$$

Reducing to Lowest Terms


Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

Reducing to Lowest Terms

Example:


$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$


$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2} \qquad \frac{2}{5} + \frac{1}{10}$$


$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from math import gcd
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from math import gcd
```

```
def rational(n, d):
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from math import gcd
```

```
def rational(n, d):
```

```
    """Construct a rational that represents n/d in lowest terms."""
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from math import gcd
```

```
def rational(n, d):
```

```
    """Construct a rational that represents n/d in lowest terms."""
```

```
    g = gcd(n, d)
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from math import gcd
```

```
def rational(n, d):
```

```
    """Construct a rational that represents n/d in lowest terms."""
```

```
    g = gcd(n, d)
```

```
    return [n//g, d//g]
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from math import gcd
```

Greatest common divisor

```
def rational(n, d):  
    """Construct a rational that represents n/d in lowest terms."""  
    g = gcd(n, d)  
    return [n//g, d//g]
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from math import gcd
```

Greatest common divisor

```
def rational(n, d):  
    """Construct a rational that represents n/d in lowest terms."""  
    g = gcd(n, d)  
    return [n//g, d//g]
```

(Demo)

Abstraction Barriers

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

`add_rational, mul_rational`
`rationals_are_equal, print_rational`

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations		

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	<code>rational, numer, denom</code>

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	<code>rational, numer, denom</code>

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	<code>rational, numer, denom</code>
Implement selectors and constructor for rationals		

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	<code>rational, numer, denom</code>
Implement selectors and constructor for rationals	two-element lists	

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	<code>rational, numer, denom</code>
Implement selectors and constructor for rationals	two-element lists	list literals and element selection

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	<code>rational, numer, denom</code>
Implement selectors and constructor for rationals	two-element lists	list literals and element selection

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	<code>rational, numer, denom</code>
Implement selectors and constructor for rationals	two-element lists	list literals and element selection

Implementation of lists

Abstraction Barriers

Parts of the program that...	Treat rationals as...	Using...
Use rational numbers to perform computation	whole data values	<code>add_rational, mul_rational</code> <code>rationals_are_equal, print_rational</code>
Create rationals or implement rational operations	numerators and denominators	<code>rational, numer, denom</code>
Implement selectors and constructor for rationals	two-element lists	list literals and element selection

Implementation of lists

Violating Abstraction Barriers

```
add_rational( [1, 2], [1, 4] )
```

```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```


Violating Abstraction Barriers

Does not use
constructors

```
add_rational( [1, 2], [1, 4] )
```

```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```

Violating Abstraction Barriers

add_rational([1, 2], [1, 4])

Does not use constructors

Twice!

```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```

Violating Abstraction Barriers

Does not use constructors

Twice!

```
add_rational( [1, 2], [1, 4] )
```



```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```

No selectors!

Violating Abstraction Barriers

Does not use constructors

Twice!

```
add_rational( [1, 2], [1, 4] )
```

```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```

No selectors!

And no constructor!

Violating Abstraction Barriers

Data Representations

What are Data?

What are Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior

What are Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d

What are Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d
- Data abstraction uses selectors and constructors to define behavior

What are Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d
- Data abstraction uses selectors and constructors to define behavior
- If behavior conditions are met, then the representation is valid

What are Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d
- Data abstraction uses selectors and constructors to define behavior
- If behavior conditions are met, then the representation is valid

You can recognize an abstract data representation by its behavior

What are Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d
- Data abstraction uses selectors and constructors to define behavior
- If behavior conditions are met, then the representation is valid

You can recognize an abstract data representation by its behavior

(Demo)

Rationals Implemented as Functions

Rationals Implemented as Functions


```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```

Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```



This function represents a rational number

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```


Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

This function represents a rational number

Constructor is a higher-order function

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```

Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

This function represents a rational number

Constructor is a higher-order function

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```

Selector calls x

Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

This function represents a rational number

Constructor is a higher-order function

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```

Selector calls x

```
x = rational(3, 8)  
numer(x)
```

Rationals Implemented as Functions

```
def rational(n, d):
    def select(name):
        if name == 'n':
            return n
        elif name == 'd':
            return d
    return select
```

This
function
represents
a rational
number

Constructor is a higher-order function

```
def numer(x):  
    return x('n')
```

Selector calls x

```
def denom(x):  
    return x('d')
```

