

Li

1 1

* *

4

* *

4

* *

* *

* *

()

()

()

()

()

Wo king i h Li ** ()

Wo king i h Li ** ()



in

in

in

in

in

not in

```
in
in
not in
not( in )
```

```
in
in
not in
not( in )
```

.


Fo Saemen

()

Se ence I e a ion

Se ence I e a ion

Se ence I e a ion



,


•


•


•

Se ence Un acking in Fo S a emen


Se ence Un acking in Fo S a emen









'




'












The Range T


1.

The Range T



k

The Range T




k

The Range T Length

1

The Range T e



Length

Element selection

•

The Range T e

Length

Element selection

 $(\qquad (\qquad))$

(())

*

The Range T Length Element selection ())

1:

The Range T Length Element selection

12

The Range T Length Element selection

1 1 1 1 1 1 1 1

E am le: P omo ed

Fi in Line

```
promoted

s

e

f(e)

def promoted(s, f):

"""Return a list with the same elements as s, but with all elements e for which f(e) is a true value placed first.

>>> promoted(range(10), odd) # odds in front
[1, 3, 5, 7, 9, 0, 2, 4, 6, 8]

"""

return
```

Fi in Line

```
promoted

s

e

f(e)

def promoted(s, f):

"""Return a list with the same elements as s, but with all elements e for which f(e) is a true value placed first.

>>> promoted(range(10), odd) # odds in front
[1, 3, 5, 7, 9, 0, 2, 4, 6, 8]

"""

return [e for e in s if f(e)] + [e for e in s if not f(e)]
```

16