

QUASAR: Cryptographic Intent-Aware Zoned Storage for Post-Quantum Workloads

Anonymous Submission

Abstract

Post-quantum services such as TLS terminators, KMS deployments, and audit systems write not only payload and logs, but also KEM artifacts, session secrets, key-wrap records, certificate metadata, and signatures whose lifetimes follow sessions, key epochs, rotations, and erase policy. Zoned Namespace SSDs expose append and reset primitives that can exploit lifetime structure, but DOGI, MiDAS, and SepBIT infer lifetime from LBA locality, frequency, and previous invalidations, which do not encode the protocol event that kills a post-quantum secret. This paper presents QUASAR, a cryptographic intent-aware placement architecture that adds a 32-byte lifecycle hint to the write path, preserves history-based placement for ordinary payload, and packs short-lived post-quantum objects by death cohort so epoch close can reset eligible secret-bearing zones. On an actual WD ZN540-class ZNS SSD, a same-path replay over six DOGI-style workload axes completes 72 policy rows with no failures; DOGI-style placement leaves 99,834 stale secret blocks, while QUASAR-DOGI hybrid leaves zero and reduces GC by 83.0%, and FAST-style Sysbench plus dynamic Exchange-, Varmail-, and Alibaba-like pressure traces show 92.3–99.9% GC reduction while preserving zero stale-secret exposure.

1 Introduction

Post-quantum cryptography is moving from a standards problem to a systems problem. Once secure services adopt ML-KEM, ML-DSA, and related post-quantum mechanisms, the write path of a TLS terminator, key-management service, or signed logging system begins to carry more than application payload. It also carries KEM ciphertexts, encapsulation metadata, session secrets, key-wrap records, certificate metadata, and signatures. These objects are not all alike: some are append-only audit records, some are public metadata, and some are short-lived secrets whose lifetime ends at session close, epoch advance, or key rotation.

Zoned Namespace SSDs are a natural substrate for such services because they expose the structure that log-structured

systems already exploit: data is appended into zones and reclaimed by resetting whole zones. The placement problem is therefore crucial. If objects that die together are placed together, a zone reset can reclaim space with little or no valid-block copying. If short-lived and long-lived objects are mixed, the host must either copy residual live blocks during GC or leave expired data in place until a future cleaner selects the zone. Recent ZNS and log-structured placement systems, including SepBIT, MiDAS, and DOGI, attack this problem by inferring block lifetime from storage-visible history such as LBA, frequency, age, segment behavior, and prior invalidation time [3, 10, 14].

The central mismatch in post-quantum workloads is that the lifetime of cryptographic artifacts is often not hidden at all. The application or cryptographic runtime already knows that a session secret will die at session close, that a KMS envelope belongs to an epoch, and that a certificate object follows a rotation policy. The storage device does not see this state. From the perspective of a history-based placement system, a KEM artifact may look like another small write near a hot payload record. From the perspective of the protocol, it belongs to a death cohort: a set of objects that become invalid together when the cryptographic state advances.

Table 1 gives the first-order distinction. The point is not that learned placement is useless. DOGI is designed for the regime where lifetime must be inferred from noisy storage behavior, and our own non-PQC controls preserve that advantage. The point is that post-quantum metadata introduces a different regime: the lifetime boundary is a semantic event defined above the block layer. Predicting this boundary from LBA and frequency is the wrong interface when a small lifecycle label can expose it directly.

This paper proposes QUASAR, a cryptographic intent-aware ZNS placement architecture. QUASAR follows one design rule: place data by when the cryptographic protocol will kill it, not by how the storage device has seen it before. Each write carries a compact hint containing intent class, expiration class, security class, epoch, cohort identifier, and size. The allocator maps short-lived secrets and KEM artifacts to

Table 1: The paper’s core gap. Existing history-based placement systems observe storage history; QUASAR observes the small lifecycle signal that defines post-quantum death cohorts.

Policy	Main signal	Strength	PQC blind spot	Consequence
SepBIT-style	Write/invalidation history and group separation	Simple hot/cold-style lifetime grouping	Session close and key rotation are not encoded in history	Expired secrets remain mixed with payload or metadata.
MiDAS-style	Adaptive groups from historical invalidation patterns	Can keep WAF low on stable workloads	Stable storage history can hide protocol-driven burst invalidation	WAF may look good while stale secrets remain.
DOGI-style	Hybrid lifetime prediction and adaptive group organization	Strong general-purpose learned placement	MLP features do not include cryptographic epoch or intent	Pays prediction cost and still misses death cohorts.
QUASAR-DOGI hybrid	DOGI-like payload placement plus cryptographic lifecycle hints	Keeps history placement where it is useful and adds semantic placement for secrets	Requires correct and conservative hint handling	Makes secret-bearing zones reset-eligible at epoch boundaries.




Figure 1: PQC lifecycle side writes on actual ZNS traces. The figure is workload characterization, not an evaluation result: post-quantum services add epoch secrets, rotation metadata, and append-only signatures whose lifetimes are defined by cryptographic protocol state rather than storage history.

epoch-secret zone families, maps rotation metadata to rotation families, keeps append-only signatures separate, and leaves ordinary payload on a history-based fallback. The deployable default is a hybrid: DOGI-style placement remains responsible for payload locality, while QUASAR handles the death cohorts that DOGI cannot observe.

The design also changes the security story of ZNS placement. Zone reset by itself is not a universal physical erase primitive, and we do not claim otherwise. However, if expired secret bytes are scattered across mixed zones, the host cannot even issue a targeted reset or sanitize action without risking live data. QUASAR aligns secret lifetime with zone reset eligibility. When the device or deployment provides hardware crypto-erase or sanitize semantics, the epoch manager can trigger that command at the protocol boundary; otherwise, QUASAR still reduces the stale-secret exposure window by avoiding mixed secret zones.

Our evaluation follows the structure of the DOGI/FAST workload axis rather than inventing a clean PQC-only trace.

We use six DOGI-style workload families, YCSB-A/F pressure traces, dynamic Exchange-, Varmail-, and Alibaba-like pressure traces, and a FAST-style Sysbench-OLTP stressor. We explicitly separate easy negative controls from WAF-pressure results. On the actual ZNS path, the six-axis fairness matrix completes 72 rows with no failed policy runs. In that matrix, DOGI-style placement already has WAF near 1.0, but it leaves 99,834 stale secret blocks and issues no semantic physical resets. QUASAR-DOGI hybrid removes all stale secret blocks, issues 98 semantic resets, and reduces GC blocks by 83.0%. Under Sysbench pressure, the hybrid reduces DOGI-style GC blocks by 94.6% and removes 38,438 stale secret blocks. Under dynamic service pressure, it reduces GC by 92.3–99.9% while keeping stale secret blocks at zero.

This paper makes the following contributions:

- It identifies death cohorts as the missing placement unit for post-quantum storage workloads. Unlike hotness or LBA locality, a death cohort is defined by cryptographic protocol state.
- It presents QUASAR, a ZNS allocation architecture that uses a small lifecycle hint to separate short-lived secrets, rotation metadata, append-only signatures, and payload.
- It implements a trace-driven and actual-ZNS evaluation path with FIFO, SepBIT-style, MiDAS-style, DOGI-style, QUASAR, and QUASAR-DOGI hybrid policies.
- It shows that the strongest claim is not universal WAF dominance. Instead, QUASAR exposes a semantic lifetime signal, removes stale-secret exposure across PQC overlays, and reduces WAF/GC when zone pressure makes mixed cohorts expensive.

Table 2: Post-quantum objects have different lifetime and security behavior even when they are generated by the same service.

Object	Lifetime driver	Placement implication
KEM artifact	Session or epoch close	Group by epoch; reset quickly.
Ephemeral secret	Session close	Isolate from payload and logs.
KMS envelope	Key epoch	Pack with same epoch family.
Certificate metadata	Rotation policy	Use rotation-zone family.
Signature log	Retention policy	Append-only placement.
Payload	Application update pattern	Use history-based fallback.

2 Background

2.1 ZNS Placement and Write Amplification

ZNS SSDs expose a storage interface in which each zone is written sequentially and later reset as a unit [9]. This interface removes part of the hidden device FTL policy and gives the host more control over placement. The benefit depends on grouping objects with compatible lifetimes. When a zone contains only expired objects, reset is cheap. When a zone also contains live objects, the host must copy those valid blocks elsewhere before reset, increasing write amplification factor (WAF).

Prior placement systems therefore focus on predicting block invalidation time. SepBIT separates data using historical invalidation behavior. MiDAS adapts group configuration to workload patterns. DOGI combines hot filtering, learned invalidation-time prediction, GC relocation policy, and dynamic group organization. The DOGI paper evaluates both static-skew workloads such as FIO Zipf and YCSB-A/F and dynamic workloads such as Varmail, Alibaba, and Exchange [3]. This is the right baseline family for QUASAR because these systems represent the strongest storage-history approach.

2.2 Post-Quantum Object Lifetimes

Post-quantum workloads introduce a different kind of lifetime signal. A KEM artifact or ephemeral secret is not short-lived because it has a particular LBA pattern; it is short-lived because the cryptographic protocol invalidates it. A signature log may be append-only and long-lived, while a KMS envelope may die when an epoch closes. A certificate metadata object may follow a rotation period rather than a session boundary. These differences exist within the same service and often within the same burst of I/O.

Table 2 gives the placement consequence. A single hotness

label cannot safely place these objects because two objects with similar write frequency may have opposite reclaim requirements. Conversely, two objects with different LBAs and different sizes may be ideal zone neighbors if they die at the same epoch boundary.

2.3 Claim Boundary

QUASAR is not an oracle. It does not receive a future deletion timestamp for every object, and it does not assume that every hint is perfect. The hint expresses lifecycle class and epoch membership, not secret key material. Correctness is protected by a conservative epoch manager: a zone family is reset only after the manager confirms that all objects in that family have expired or have been safely migrated.

The security claim is also scoped. Zone reset makes a zone reusable and can reduce exposure, but physical sanitization is device-dependent. Our physical device advertises crypto-erase and block-erase sanitize support, and the crypto-erase sanitize command path has been executed successfully. Nevertheless, the default claim is reset eligibility and exposure-window reduction. A physical erase claim requires issuing sanitize or equivalent hardware crypto-erase semantics at epoch boundaries.

3 Motivation

3.1 History Signals Do Not Encode Death Cohorts

History-based placement asks: what did this block look like before? DOGI-style policies observe LBA, previous LBA, access interval, segment frequency, and prior placement state. These features are meaningful for ordinary payload updates because they capture hotness and locality. A post-quantum secret asks a different question: which objects will die together when the protocol state advances? The answer requires at least intent and epoch.

This distinction creates two failure modes. The first is semantic: the baseline leaves expired secret blocks in zones that are not safely resettable because the zone also contains payload or long-lived metadata. The second is performance: under sufficient free-zone pressure, mixed death cohorts force valid-block migration and raise WAF. The first failure can appear even when WAF is near 1.0; the second appears only in harder pressure workloads.

3.2 Easy Workloads Are Not Enough

A clean PQC-only epoch trace makes QUASAR look too good and is not a fair test of DOGI. Our evaluation therefore treats such traces as sanity checks only. The hard tests keep DOGI’s normal locality signals and then add realistic PQC lifecycle writes. Concretely, the workload matrix contains: DOGI-style

six-axis fairness, YCSB-A/F pressure, FAST-style Sysbench pressure, dynamic service pressure, and QUASAR-hostile robustness.

3.3 The Upper Bound Gives Design Requirements

DOGI uses NoDaP to turn an oracle gap into design requirements. QUASAR uses a narrower epoch upper bound for the same diagnostic purpose: by giving the oracle exact PQC death cohorts, we test whether the missing signal is protocol lifetime rather than another storage-history feature.

The upper bound yields three requirements. First, the placement path must expose protocol lifetime because LBA, frequency, and prior invalidations do not encode session close or key rotation. Second, exact cohort placement must be budgeted because a sparse epoch per zone can trade WAF for poor utilization and too many active families. Third, reset must be conservative because a wrong hint can hurt placement quality but must not discard live data. These requirements lead directly to QUASAR’s lifecycle hint, admission/open-zone policy, and epoch-confirmed reclaim path.

The actual-ZNS results later separate these failure modes. In the six-axis fairness matrix, DOGI-style placement has WAF near 1.0 but leaves 99,834 stale secret blocks. In harder YCSB, Sysbench, Exchange, Varmail, and Alibaba-like rows, history-based placement pays positive GC while leaving stale secrets; the hybrid keeps payload on history placement and moves PQC secrets into resettable cohorts.

3.4 The Desired Design Shape

The design requirement is therefore not “replace DOGI everywhere.” A pure semantic allocator can be worse for ordinary payload. The desired system uses history where history is the right signal and cryptographic intent where history is blind: DOGI-like placement for payload, QUASAR zone families for PQC lifecycle objects, and conservative fallback for unreliable hints.

4 Design

4.1 Overview

QUASAR is a host-side placement layer for ZNS devices. Figure 2 shows the data path. Applications or cryptographic libraries produce lifecycle labels when they create PQC artifacts. These labels are attached to writes as `quasar_hint`. The allocator maps each write to a zone family. An epoch manager tracks which families are eligible for reset, migration, or fallback GC. Payload writes continue to use a history-based fallback, so the system does not discard the strengths of DOGI-style placement.

4.2 Design Requirements

QUASAR follows the three requirements from Motivation. Lifecycle labels expose protocol lifetime and route PQC objects to death-cohort zone families while payload stays on DOGI-style fallback. Admission control budgets exact placement by reserving scarce exact families for high-security secrets and sending sparse or uncertain writes to bins or overflow. Epoch-confirmed reclaim resets a family only after durable epoch close or residual migration; uncertain zones fall back to normal GC. The evaluation checks these requirements with stale-secret exposure rows, pressure traces, multi-tenant stress, bad hints, and sanitize-boundary tests.

4.3 Hint Schema

The hint is intentionally small. It contains only lifecycle metadata:

Listing 1: Minimal QUASAR hint schema.

```
enum quasar_intent {
    QUASAR_PAYLOAD = 0,
    QUASAR_EPHEMERAL_SECRET = 1,
    QUASAR_KEM_ARTIFACT = 2,
    QUASAR_SIGNATURE_LOG = 3,
    QUASAR_CERT_METADATA = 4,
};


struct quasar_hint {
    uint16_t intent;
    uint16_t expire_class;
    uint32_t security_class;
    uint64_t epoch_id;
    uint64_t cohort_id;
    uint64_t size_bytes;
};
```

The fields are lifecycle labels, not cryptographic secrets. `intent` separates secrets, KEM artifacts, signature logs, certificate metadata, and payload. `epoch_id` identifies the death cohort. `security_class` sets reset urgency and isolation. `cohort_id` is opaque to storage and can be a keyed hash, so raw session, tenant, or key identifiers need not cross the storage boundary.

Trust boundary. QUASAR assumes that high-priority lifecycle hints are emitted by trusted components such as the TLS terminator, KMS, logging service, or a privileged policy layer. Untrusted tenants do not directly grant themselves exact secret-zone priority. A deployment can enforce per-tenant exact-family quotas, tenant-local cohort namespaces, and admission limits before a hint reaches the allocator. If provenance is missing or confidence is low, the write is routed to overflow and becomes a performance/exposure tradeoff rather than a correctness risk.

4.4 Zone Families

QUASAR allocates writes into a small set of zone families:



Invariant: reset only after the epoch manager proves all objects in the family are expired or migrated.

Figure 2: QUASAR architecture. The storage path receives lifecycle labels, not secret material. Payload remains on a history-based fallback, while PQC secrets, rotation metadata, and uncertain writes are routed to separate zone families. The epoch manager resets or sanitizes a family only after proving that all objects in the family are expired or migrated.

Table 3: QUASAR zone families. Each family maps a lifecycle class to a reclaim rule, separating short-lived secrets from payload and append-only logs.

Family	Data	Reclaim rule
Epoch-secret	KEM artifacts, ephemeral secrets	Reset when epoch expires.
Rotation	Certificates, key metadata	Reset on rotation boundary.
Append-log	Signatures, audit records	Normal append-log reclaim.
Payload	Application payload	History-based fallback.
Overflow	Missing or low-confidence hints	Conservative GC or migration.

The key invariant is separation: the allocator keeps short-lived secrets out of long-lived payload and append-only log zones unless explicit pressure routes them through a conservative fallback. This is the mechanism that turns protocol lifetime into reset eligibility.

4.5 Allocation Procedure

For each write, QUASAR first classifies the object:

Listing 2: Zone-family decision rule.

```

if intent in {EPHEMERAL_SECRET, KEM_ARTIFACT}:
    family = EPOCH_SECRET_ZONE(epoch_id, security_class)
elif intent == CERT_METADATA:
    family = ROTATION_ZONE(rotation_epoch(epoch_id))
elif intent == SIGNATURE_LOG:
    family = APPEND_LOG_ZONE
elif intent == PAYLOAD:
    family = DOGI_HISTORY_FALLBACK
else:

```

```
family = OVERFLOW_ZONE
```

The allocator appends the write to the active zone for that family. If the active zone lacks capacity, the zone is closed and a new zone is allocated. When the active-zone budget is tight, QUASAR preserves exact placement for secret data first, bins lower-risk KEM artifacts or sparse epochs second, and routes uncertain writes to overflow. This priority order prevents a utilization-first policy from degenerating into arbitrary mixing.

4.6 Admission Control and Open-Zone Budget

Exact epoch placement is useful only when the device can afford the active families it creates. Real ZNS devices bound the number of open and active zones; the evaluated device exposes a limit of 13 for both open and active zone accounting in our robustness experiments. QUASAR therefore admits exact epoch-secret families only when the expected epoch bytes justify a dedicated zone and the active family count remains below the budget.

When a sparse or multi-tenant workload would exceed the budget, QUASAR degrades in a fixed order. It first keeps exact families for high-security secrets, then bins lower-risk or sparse cohorts by coarse epoch ranges, then routes low-confidence writes to overflow. This policy makes the cost visible: exact placement maximizes exposure reduction, binning trades some exposure precision for zone budget, and overflow preserves correctness when the hint path is unreliable.

Table 4: Main QUASAR policy parameters. These knobs expose the cost of exact placement: active-zone budget, sparse-epoch binning, residual migration, hint confidence, and tenant isolation are workload/device inputs, not hidden oracle information.

Parameter	Role
Active-family budget	Caps concurrently open/active death-cohort families; robustness runs use the device-reported 13-zone budget.
Minimum epoch fill / bin width	Decides whether sparse epochs receive exact zones or coarse cohort bins.
Residual threshold / copy budget	Bounds live-byte migration before reset; strict mode raises this budget to force zero waiting.
Hint confidence	Sends missing, untrusted, or inconsistent hints to overflow instead of exact secret zones.
Tenant mode	Uses tenant-local bins and quotas when reset-time tenant mixing is not acceptable.

4.7 Epoch Reclaim

At epoch close, the epoch manager evaluates all zone families associated with that epoch:

Listing 3: Conservative epoch reclaim.

```
on epoch_expire(epoch_id):
    for zone in zones_owned_by(epoch_id):
        if live_bytes(zone) == 0:
            reset(zone)
        elif live_bytes(zone) <= residual_threshold:
            migrate_live_bytes(zone)
            reset(zone)
        else:
            downgrade_to_normal_gc(zone)
```

This rule makes wrong hints a performance problem rather than a correctness problem. A family is reset only after the epoch manager confirms that every object in the family has expired or has been safely migrated. If the system cannot prove safety after a crash or hint inconsistency, it routes the zone to normal GC.

4.8 Crash and Recovery Invariant

QUASAR cannot keep epoch-to-zone ownership only in volatile memory. Each zone family has durable metadata that records its family identifier, epoch, intent class, and reset generation. After a crash, recovery scans this metadata, rebuilds the family-to-zone map, replays durable epoch-close records, and resets only zones whose epoch close is known to be durable. Uncertain zones are downgraded to normal GC. This conservative rule is central to the security story: a bad hint or incomplete recovery can reduce placement quality, but it must not cause a live object to be discarded.

4.9 Deployment Modes

The deployable design is not a single universal knob. The default mode is QUASAR-DOGI hybrid: history-based placement for payload and death-cohort placement for PQC secrets. Tenant-isolation mode uses tenant-local bins when reset-time tenant mixing is unacceptable. Strict-residual mode copies delayed-expiry stragglers to force zero final secret waiting. Overflow mode handles missing or low-confidence hints. These modes make the cost visible instead of pretending that perfect epoch alignment is free.

5 Implementation

5.1 Trace and Replay Infrastructure

We implemented QUASAR as a trace-driven allocator and actual-ZNS replay framework. The trace format records writes, expirations, object identifiers, sizes, LBA-like payload location, intent, epoch, security class, tenant, and confidence. The same trace is replayed through FIFO, SepBIT-style, MiDAS-style, DOGI-style, QUASAR, and QUASAR-DOGI hybrid policies. This keeps timing and object lifetimes identical across policies.

The deployment hook is intentionally small: a TLS terminator, KMS, or logging component emits the 32-byte `quasar_hint` when it writes a KEM artifact, ephemeral secret, certificate record, or signature log. The hint can travel as request context in user-space replay or as file/extent metadata in a filesystem path; it does not carry key material.

The workload generators produce three classes of traces. First, DOGI-paper-shaped traces mirror the workload axes described by DOGI: FIO Zipf, YCSB-A, YCSB-F, Varmail, Alibaba, and Exchange. Second, pressure traces increase PQC density and reduce free-zone slack to force GC. Third, hostile traces introduce missing hints, wrong epochs, tenant pressure, and stragglers. The implementation also includes a real FIO iolog converter that maps benchmark-issued FIO writes into the same QUASAR JSONL schema before adding PQC life-cycle side writes. We additionally ran a Sysbench/MySQL execution gate. Full YCSB/JDBC or Sysbench block traces would strengthen external validity, but the scoped claim uses the DOGI/FAST-shaped physical pressure suites and exact external baseline runs as the paper-grade placement evidence.

5.2 Baseline Implementations

The same-path comparison implements FIFO, SepBIT-style, MiDAS-style, and DOGI-style policies in the replay framework. These implementations are intentionally described as style-compatible baselines because they share the same physical packed-ZNS path as QUASAR. The artifact set also contains exact public DOGI/MiDAS/SepBIT runs in their native environments. We keep these exact runs separate from the

same-path results because their units and internal segment models are not identical to the packed replay path.

5.3 Physical ZNS Path

The actual-ZNS experiments use a Western Digital ZN540-class ZNS NVMe SSD mounted with `zonefs`. The replay writes zone files sequentially and issues reset-like truncation or helper operations according to the policy plan. This path measures full-suite append/reset accounting, but it includes `zonefs` helper overhead. We therefore report it as actual-ZNS replay overhead, not as final production p99 latency.

To check the lower-overhead command path, we also implemented an xNVMe raw ZNS latency probe. The local xNVMe backend uses Linux NVMe `ioctl` synchronous commands. It bypasses the `zonefs` helper path and completes 4,096 4KiB appends with p99 append latency of 26,064 ns. This is not an SPDK poll-mode result, but it bounds the helper-path caveat.

5.4 Security Capability Check

The physical device reports sanitize capability with crypto-erase and block-erase support. We executed an NVMe crypto-erase sanitize command on the device and observed successful completion in the sanitize log. This validates the command path for hardware crypto-erase. The evaluation keeps this separate from zone reset: QUASAR makes secret-bearing zones eligible for reset and, when configured, for explicit sanitize or crypto-erase commands.

6 Evaluation

6.1 Methodology

The evaluation answers five questions:

1. Does QUASAR avoid relying on an easy PQC-only trace?
2. Does QUASAR remove stale-secret exposure on DOGI-style workload axes?
3. Under pressure, does QUASAR reduce WAF and GC relative to history-based placement?
4. What overhead does semantic placement introduce?
5. What security claim is supported by actual device capability?

Evaluation platform. We evaluate placement with trace-driven replay and an actual ZNS device: a Western Digital ZN540-class NVMe SSD exposed as `/dev/nvme0n1` and mounted through `zonefs`. The replay model uses 4KiB logical blocks and a 275,712-block zone capacity. As in DOGI’s methodology, the simulator/replay path gives broad policy coverage, while the physical path validates that the planned

append/reset schedule executes on a zoned device. Because the full-suite path includes `zonefs` helper overhead, we report its latency as overhead accounting rather than production SPDK p99 latency.

Baselines. We compare against FIFO, SepBIT-style, MiDAS-style, and DOGI-style placement. These are same-path policies in our simulator and actual-ZNS replay. We also keep exact public DOGI/MiDAS/SepBIT runs as separate evidence because their internal units are not directly interchangeable with our packed ZNS replay.

Workloads. The fairness matrix uses six DOGI-style axes: FIO Zipf, YCSB-A, YCSB-F, Varmail, Alibaba, and Exchange. Headline WAF rows keep these locality signals and add PQC lifecycle side writes through high-ratio YCSB-A/F, FAST-style Sysbench-OLTP pressure, and dynamic Exchange/Varmail/Alibaba-like traces. Pure PQC epoch streams are sanity checks, not headline evidence. Hostile robustness uses tenant mixing, missing hints, wrong hints, and stragglers; real FIO iolog and Sysbench/MySQL gates check benchmark readiness.

Metrics. We report WAF, GC write blocks, stale secret blocks, semantic physical reset count, secret bytes waiting for physical reset, zone utilization, live physical zones, append/reset latency, and C-level placement-decision overhead. A stale secret block is an expired secret-class logical block in a family that is not safely reset- or sanitize-eligible because live data remains or epoch close is unproven. Exposure artifacts report stale-secret block-seconds; physical tables use final and representative stale-block counts for auditability. WAF alone is insufficient because a policy can keep WAF near 1.0 while leaving expired PQC secrets in mixed zones. For example, the E4 exposure timeline records max stale-secret block-seconds of 69,391,500 for FIFO and DOGI-style placement, while QUASAR remains at zero block-seconds and zero final stale-secret blocks.

6.2 Workload Hardness

The workload hardness rule is: DOGI-friendly first, PQC-hostile second. A headline WAF/GC row must preserve storage-visible structure that helps history-based placement—hot/cold skew, overwrite locality, segment reuse, or phase changes—and then add PQC objects whose invalidation follows protocol state rather than LBA history. Pure PQC-only traces, oracle-expiration traces, and low-pressure rows are sanity checks or exposure evidence.

The matrix passes all nine gates: fairness, negative controls, pressure rows, main-claim eligibility, and hostile robustness. The artifact set has seven eligible YCSB pressure rows, nine YCSB baseline-complete rows, three dynamic eligible rows, and DB pressure eligibility. Rows with WAF near 1.0 are interpreted as semantic exposure results; WAF/GC claims come only from rows where history-based policies pay positive GC or copied-live-block cost.

Table 5: Same-path actual-ZNS fairness matrix over six DOGI-style axes at pqc2000. The easy matrix keeps DOGI-style WAF near 1.0, but only QUASAR-DOGI hybrid removes stale secrets while reducing GC.

Policy	WAF	GC	Stale secrets	Resets
FIFO	1.0040	3,903	99,141	0
SepBIT-style	1.0023	2,241	99,822	0
MiDAS-style	1.0006	581	99,898	0
DOGI-style	1.0006	625	99,834	0
QUASAR	1.0011	1,121	0	98
QUASAR-DOGI hybrid	1.0001	106	0	98

6.3 Epoch Upper Bound

DOGI uses NoDaP as an oracle-like target for lost lifetime information. We use a narrower upper bound: an epoch oracle that sees exact death time at write time. It is not deployable and is not counted as QUASAR; it tests whether the workload is placeable once the protocol-lifetime signal exists.

On the mixed sanity trace, DOGI-style placement has WAF 1.791 and 484,967 GC blocks, QUASAR has WAF 1.010 and 6,331 GC blocks, and the epoch oracle has WAF 1.000 and zero GC blocks. On the stress-rekey trace, DOGI-style placement has WAF 2.031, QUASAR has WAF 1.019, and the oracle has WAF 1.003. These synthetic rows are bounds, not headline evidence: most of the gap comes from whether the allocator can observe the protocol lifetime boundary.

6.4 DOGI-Favorable Control

The non-PQC control verifies that the hybrid preserves history placement. On the six DOGI-style axes with no PQC side writes, DOGI-style placement and the QUASAR-DOGI hybrid produce the same WAF because payload stays on the history policy. DOGI-style placement beats FIFO and pure QUASAR on all six workloads, and no stale secret blocks exist. This keeps the claim boundary clear: QUASAR is not a replacement for learned placement when no cryptographic death-cohort signal exists.

6.5 Same-Path Fairness Matrix

The six-axis actual-ZNS fairness matrix completes 72 rows with zero failures. Table 5 reports the aggregated policy results. DOGI-style placement is already strong on WAF, which is expected on an easy fairness matrix. However, it leaves 99,834 stale secret blocks and performs no semantic physical resets. QUASAR-DOGI hybrid leaves zero stale secret blocks, performs 98 semantic resets, and reduces GC blocks from 625 to 106.

The WAF gain here is deliberately modest: 0.1% relative to DOGI-style. The row is a semantic result, not a performance

headline: storage-history placement can have good WAF and still fail to make expired PQC secrets resettable.

6.6 PQC Lifecycle Pressure on YCSB Carriers

These rows use YCSB only as a storage-locality carrier. The target phenomenon is PQC lifecycle pressure: epoch secrets, KEM artifacts, rotation metadata, and append-only signatures are inserted beside ordinary payload, then invalidated by protocol state. Table 6 reports representative physical ZNS replays. DOGI-style placement pays 3,357–24,289 GC blocks and leaves 46,266–150,221 expired PQC secret blocks. The hybrid removes stale secret blocks in all rows and reduces GC to zero in these representative replays.

The p10000 rows bound the WAF claim. Dense YCSB overlays can keep DOGI-style WAF close to 1.0, yet the stale-secret gap remains large. WAF improvement appears under pressure; exposure improvement appears across PQC overlays.

6.7 Multi-Seed Ratio Sweep

To check that the pressure result is not a single-seed artifact, we run a three-seed ratio sweep over the six DOGI-style workload families at 0%, 5%, and 20% PQC overlay ratios, for 54 comparisons. The hybrid matches DOGI-style at 0% PQC, is WAF-negative at 5% PQC (-1.1% mean WAF, -12.4% mean GC) while avoiding 2,342 stale secret blocks per seed, and becomes positive at 20% PQC (5.0% mean WAF and 38.3% mean GC improvement) while avoiding 10,021 stale secret blocks per seed. Thus low-ratio overlays are exposure evidence, not WAF wins; WAF/GC benefits appear once protocol-lifetime objects create enough placement pressure.


6.8 PQC Lifecycle Pressure Across Service Carriers

Table 7 reports harder service carriers with the same PQC lifecycle side writes. Sysbench is included as DB-backed PQC service pressure rather than as a generic DB claim. The hybrid reduces DOGI-style GC from 11,256 to 609 blocks and removes 38,438 expired PQC secret blocks. On Exchange-, Varmail-, and Alibaba-like carriers, the hybrid reduces GC by 92.3–99.9% and keeps stale secrets at zero.

These rows are the strongest performance evidence because all non-QUASAR baselines complete but pay visible GC and leave stale secrets. They also show why the hybrid is the default deployable policy: payload placement remains history-based, while secrets are placed by protocol cohort.

6.9 Component Ablation

Table 8 turns the upper-bound requirements into mechanism evidence. History-only placement is the right first row because



The gap shows that protocol lifetime is the missing placement signal; QUASAR uses lifecycle hints, not exact future delete timestamps.

Figure 3: Epoch upper bound. The epoch oracle is not a deployable baseline; it receives exact future death time. Its role is to show that the WAF gap is largely a missing-lifetime-signal problem. QUASAR approaches the upper bound with lifecycle hints, while the paper’s headline claims still come from harder physical-ZNS pressure rows.

Table 6: Representative actual-ZNS PQC lifecycle pressure on YCSB carriers. The carrier preserves update locality; the PQC side writes create protocol-defined death cohorts that history-based placement cannot observe.

Workload	DOGI WAF	Hybrid WAF	DOGI GC	Hybrid GC	DOGI stale	Hybrid stale	Hybrid resets
YCSB-A pqc4000	1.0454	1.0000	15,316	0	46,266	0	28
YCSB-A pqc6000	1.0376	1.0000	15,308	0	76,950	0	28
YCSB-A pqc10000	1.0066	1.0000	3,357	0	150,221	0	26
YCSB-F pqc6000	1.0105	1.0000	4,166	0	96,050	0	28
YCSB-F pqc8000	1.0528	1.0000	24,289	0	100,847	0	28
YCSB-F pqc10000	1.0279	1.0000	13,741	0	144,901	0	26

it gives DOGI-style placement all storage-visible signals but no protocol lifetime. Adding lifecycle hints removes stale secrets, but pure semantic grouping can still leave GC cost on DB-like payload. Adding the DOGI payload fallback removes that remaining cost. Admission and residual migration are not free performance wins; they are boundary mechanisms for open-zone pressure and stragglers. Figure 5 shows the mechanism split visually, and Figure 6 visualizes the space and overhead controls.

6.10 Exact Public Baseline Sanity Runs

The main tables use same-path replay so FIFO, SepBIT-style, MiDAS-style, DOGI-style, QUASAR, and the hybrid share trace timing, packed physical-ZNS model, and reset accounting. We also ran public baseline artifacts in their native environments. Public DOGI completes Alibaba p8000 compact, selector-suite, and original-LBA runs with reported WAF 2.993, 2.804, and 3.212; public MiDAS completes compact FIO and PQC representatives with WA 1.000 and 1.250; public SepBIT completes a PQC pressure representative with WA 2.430. These runs are sanity evidence, not apples-to-apples WAF numbers. They sharpen the boundary: MiDAS is strong on at least one compact representative, so the claim rests on death-cohort exposure and same-path pressure evidence, not universal baseline collapse.

6.11 Overhead

QUASAR adds semantic reset work, but its decision path is cheap. In the actual-ZNS overhead suite, the hybrid issues 318 more semantic reset operations than DOGI-style. Zonefs-helper throughput is lower than DOGI-style by this accounting, but helper latency includes user-space append/truncate overhead. In the C-level placement-decision benchmark, DOGI-style feature extraction plus a small MLP costs 2,397.8 ns/write, QUASAR hint routing costs 16.8 ns/write, and the hybrid costs 1,178.8 ns/write.

The xNVMe probe provides a lower-overhead command-path sanity check: 4,096 4KiB zone appends complete with p99 latency of 26,064 ns and throughput of 181.79 MiB/s. The probe is a Linux NVMe ioctl path, not SPDK poll-mode, so it is reported as a bound rather than a final production datapoint.

6.12 Robustness to Bad Hints and Stragglers

The hardest QUASAR cases are not clean epochs; they are wrong or missing hints, many tenants, and delayed-expiry stragglers. On YCSB-A p4000, the clean hybrid has WAF 1.0000, zero stale secrets, and 28 semantic resets. With 5% missing hints, WAF remains 1.0000 but 3,361 stale secret blocks appear because some secret writes fall back to nonse-




Figure 4: PQC lifecycle pressure breadth. The x-axis names the service carrier, but the measured failure is PQC-specific: expired secret cohorts remain mixed with live payload under history-based placement. QUASAR-DOGI keeps those cohorts reset-eligible while preserving payload placement on the history fallback.

Table 7: PQC lifecycle pressure across DB and dynamic-service carriers. Each row preserves a DOGI-style storage-locality pattern, then adds PQC artifacts whose death time is protocol-defined; the hybrid preserves zero stale secrets while cutting GC.

Workload	DOGI WAF	Hybrid WAF	DOGI GC	Hybrid GC	DOGI stale	Hybrid stale	GC reduction
Sysbench-OLTP pressure	1.0301	1.0016	11,256	609	38,438	0	94.6%
Exchange-like pqc8000	1.0716	1.0000	43,006	22	75,422	0	99.9%
Varmail-like pqc8000	1.0727	1.0003	43,227	175	79,600	0	99.6%
Alibaba-like pqc8000	1.0974	1.0075	65,010	4,992	65,184	0	92.3%

mantic placement. With 5% wrong epochs, this trace still ends with zero stale secrets but increases reset activity to 112 resets. With 5% stragglers, exact secret-group packing can exceed the device open-zone budget; epoch-bin fallback completes within the budget but leaves waiting secrets, while epoch-bin plus residual migration reaches zero waiting at WAF 1.7098 after copying 234,549 residual blocks.

The residual fallback frontier shows why strict exposure mode cannot be the default. Exchange-like and Sysbench-like representatives can reach zero final secret waiting with physical WAF 1.0182 and 1.2161, respectively. YCSB-F p8000 reaches strict zero waiting only at physical WAF 3.5535 after migrating 1,168,095 residual blocks. QUASAR therefore exposes low-overhead, balanced, and strict-zero-wait profiles rather than hiding this tradeoff behind a single policy.

6.13 Security Boundary

The physical device advertises crypto-erase and block-erase sanitize support. We executed crypto-erase sanitize and observed successful completion in the sanitize log. This supports a deployment path where QUASAR triggers hardware erase semantics at epoch boundaries. The default result remains more conservative: QUASAR reduces stale-secret exposure by aligning secret lifetime with reset eligibility, while physical erasure requires explicit sanitize or equivalent hardware

support. We do not use sanitize timing to claim foreground service latency: sanitize policy, batching, and SLO integration are deployment choices beyond the same-path placement comparison.

6.14 Reproducibility

The artifact manifest records 37 evidence artifacts, their roles, abbreviated hashes, and regeneration commands. Validation finds zero hash mismatches, and the local acceptance report passes 41 of 41 gates. These checks make the scoped evidence auditable.




Figure 5: PQC lifecycle-signal ablation. A history-only DOGI-style policy sees storage history but misses cryptographic death cohorts, so GC and expired-secret exposure remain. Lifecycle hints remove exposure; adding DOGI-style payload fallback recovers payload placement and removes the remaining GC in the default hybrid.

Table 8: Component ablation from actual-ZNS and pressure artifacts. Lifecycle hints remove stale secrets, the DOGI payload fallback recovers payload GC behavior, and residual migration exposes the cost of strict zero-wait security.

Component	Evidence	Lesson	Decision
History only	DOGI YCSB-A p4000: GC 15,316, stale 46,266, resets 0.	History misses protocol death.	Do not place secrets by history alone.
Lifecycle hints	Pure QUASAR: YCSB-A stale 0; Exchange stale 0.	Hints carry the missing signal.	Route PQC objects by death cohort.
Payload fallback	Hybrid cuts Sysbench GC 6,567→609 and Exchange GC 2,610→22.	Payload still needs history.	Keep DOGI fallback as default.
Admission	Exact hybrid wins 6 YCSB/Sysbench rows; adaptive wins 0.	Binning is not free.	Use adaptive only under pressure.
Residual	Stragglers: binning caps 13 zones but leaves 40,454 waiting; residual reaches 0 at WAF 1.7098.	Strict exposure has copy cost.	Expose low/strict profiles.




Figure 6: PQC placement resource and overhead controls. QUASAR-DOGI bounds the closed-zone fill cost while removing stale PQC secrets, the lifecycle-hint routing path is orders of magnitude cheaper than the DOGI-style policy-decision microbenchmark, and xNVMe confirms a lower-overhead append command path than the zonefs helper used for full-suite replay accounting.




Figure 7: PQC robustness frontier. Exact and binned placement can leave delayed-expiry PQC secrets waiting under tight active-zone budgets. Residual migration removes the exposure but increases physical WAF and copied blocks; strict zero-wait mode is therefore a policy point, not the default.

7 Related Work

Learned and heuristic placement for log-structured storage. SepBIT, MiDAS, and DOGI improve log-structured placement by predicting or adapting to invalidation behavior [3, 10, 14]. SepBIT separates blocks by inferred invalidation time, MiDAS adapts group sizes and counts to workload dynamics, and DOGI uses oracle-guided analysis to motivate hot filtering, learned lifetime prediction, GC relocation policy, and dynamic group organization. These systems are the right comparison class for QUASAR because they represent the strongest storage-history view of placement.

QUASAR is not an argument that learned placement is generally unnecessary. For ordinary payload and workloads whose lifetime is not visible to the application, history is the right signal and DOGI-style placement can outperform semantic grouping. QUASAR targets a narrower regime where lifetime is not hidden from the software stack: a KEM artifact, ephemeral secret, or KMS envelope dies because a protocol epoch closes. In that regime, prediction spends work approximating a label that the application already has, and a misplacement can leave expired secret bytes in a long-lived

zone.

Zoned storage and host-guided placement. ZNS and related host-managed SSD interfaces expose placement and reclaim decisions to the host [9, 13, 15]. Systems such as ZenFS show how a host-side stack can map application writes onto zone append and reset operations. QUASAR builds on this host-managed direction but changes the placement key: instead of grouping only by hotness, stream, or predicted invalidation time, it groups secret-bearing writes by protocol death cohort.

Flexible Data Placement provides a different host-guided interface without forcing a full ZNS software stack [8]. QUASAR can target native ZNS by choosing zone families directly, or FDP-like devices by mapping intent and epoch to placement handles. This makes QUASAR a semantic placement policy rather than a device-specific API proposal.

Benchmarks and trace methodology. FAST storage papers typically evaluate both synthetic controls and macro workloads. DOGI uses FIO Zipf, YCSB-A/F, Varmail, Alibaba, and Exchange-like traces; our workload plan preserves these axes and adds PQC lifecycle overlays. FIO, YCSB, and Sysbench remain important because they provide recognizable hot/cold, update-heavy, and DB-style pressure points [1, 2, 4]. The paper therefore treats pure PQC epoch streams only as sanity checks and uses DOGI/FAST-shaped pressure rows for headline claims.

Post-quantum systems. Open Quantum Safe, liboqs, and oqs-provider provide software paths for deploying post-quantum algorithms in applications and TLS stacks [11, 12]. NIST’s ML-KEM and ML-DSA standards make these deployments concrete targets rather than hypothetical future algorithms [5, 6]. Most systems work around PQC focuses on cryptographic correctness, interoperability, CPU overhead, and network handshake cost. QUASAR instead studies a storage side effect: lifecycle-heavy cryptographic metadata creates a placement signal that the block layer and device do not naturally observe.

Secure erase and sanitization. Storage sanitization and crypto-erase mechanisms provide device-specific ways to destroy data or keys [7]. QUASAR does not replace these mechanisms and does not claim that zone reset alone physically erases NAND. It solves a placement precondition for secure disposal: expired secrets are isolated into zone families that can be reset or sanitized at the protocol boundary. When hardware provides crypto-erase or sanitize semantics, QUASAR gives the storage stack a deterministic point at which to trigger them.

8 Discussion and Limitations

QUASAR is not a universal WAF optimizer. Easy rows deliberately show DOGI-style WAF near 1.0; there, QUASAR’s benefit is exposure reduction. The scoped claim is that PQC death cohorts are invisible to history-based placement and

become costly under pressure, not that QUASAR wins every trace.

Correctness, trust, and tenancy. Wrong or missing hints must not cause data loss: QUASAR resets only after epoch-close confirmation; otherwise it migrates residuals, downgrades to normal GC, or sends low-confidence writes to overflow. High-priority secret placement is emitted by trusted TLS/KMS/logging or policy components, with opaque cohort IDs, tenant-local namespaces, quotas, and admission limits to prevent priority inflation.

Resource tradeoffs are explicit. Dedicated epoch zones can waste space, and strict zero-wait residual handling can be expensive on hostile rows such as YCSB-F p8000. The default hybrid reserves exact placement for high-security cohorts, bins sparse cohorts, sends uncertain writes to overflow, and makes strict tenant/residual modes opt-in.

Device and deployment boundaries. Zone reset alone is not physical NAND erasure; strong erasure requires sanitize or hardware crypto-erase, with deployment-specific scheduling cost. The physical evidence uses one WD ZN540-class device, zonefs replay, liboqs/OpenSSL traces, a TLS socket trace, and an xNVMe probe. Exact DOGI/MiDAS/SepBIT runs stay separate because their units differ from packed actual-ZNS replay. We report host-visible resets/utilization, but not internal wear telemetry or full SPDK poll-mode replay.

9 Conclusion

Post-quantum services write secrets, KEM artifacts, signatures, and payload together, but these objects die for different protocol reasons. QUASAR exposes that lifecycle signal as a small ZNS placement hint, keeps DOGI-style history placement for payload, and packs short-lived secrets by death cohort. Actual-ZNS experiments support the scoped claim: QUASAR removes stale-secret exposure across PQC overlays and reduces GC/WAF when pressure makes mixed cohorts expensive.

References

- [1] J. Axboe. fio: Flexible i/o tester. <https://fio.readthedocs.io/>, 2024.
- [2] B. F. Cooper, A. Silberstein, E. Tam, R. Ramakrishnan, and R. Sears. Benchmarking cloud serving systems with YCSB. In *Proceedings of the ACM Symposium on Cloud Computing*, 2010.
- [3] J. Kim, S. Oh, J. Kim, J. Kim, J. Park, S. Lee, and S. H. Noh. DOGI: Data placement with oracle-guided insights for log-structured systems. In *Proceedings of the 24th USENIX Conference on File and Storage Technologies*, 2026.
- [4] A. Kopytov. sysbench: Scriptable database and system performance benchmark. <https://github.com/akopytov/sysbench>, 2024.
- [5] National Institute of Standards and Technology. FIPS 203: Module-lattice-based key-encapsulation mechanism standard. <https://csrc.nist.gov/>, 2024.
- [6] National Institute of Standards and Technology. FIPS 204: Module-lattice-based digital signature standard. <https://csrc.nist.gov/>, 2024.
- [7] NVM Express. NVM Express Base Specification: Sanitize Command. <https://nvmexpress.org/>, 2024.
- [8] NVM Express. NVM Express Flexible Data Placement. <https://nvmexpress.org/>, 2024.
- [9] NVM Express. NVM Express Zoned Namespace Command Set Specification. <https://nvmexpress.org/>, 2024.
- [10] S. Oh, J. Kim, S. Han, J. Kim, S. Lee, and S. H. Noh. MIDAS: Minimizing write amplification in log-structured systems through adaptive group number and size configuration. In *Proceedings of the USENIX Conference on File and Storage Technologies*, pages 259–275, 2024.
- [11] Open Quantum Safe Project. liboqs: C library for quantum-safe cryptographic algorithms. <https://openquantumsafe.org/>, 2024.
- [12] Open Quantum Safe Project. OpenSSL oqs-provider. <https://github.com/open-quantum-safe/oqs-provider>, 2024.
- [13] RocksDB. ZenFS: Rocksdb file system for zoned block devices. <https://github.com/facebook/rocksdb/tree/main/plugin/zenfs>, 2024.
- [14] Q. Wang, J. Li, P. P. C. Lee, T. Ouyang, C. Shi, and L. Huang. Separating data via block invalidation time inference for write amplification reduction in log-structured storage. In *Proceedings of the USENIX Conference on File and Storage Technologies*, pages 429–444, 2022.
- [15] xNVMe Project. xNVMe: Cross-platform libraries and tools for nvme devices. <https://xnvm.io/>, 2024.