Preliminary Study, Part 2: Contrastive Activation Addition on the Pretrained Orpheus Hindi Model

cs-tts-steering project

November 5, 2026

Abstract

This extends the CAA pilot (`docs/reports/preliminary_caa.pdf`) to the *pretrained* Orpheus 3B Hindi model (`canopylabs/3b-hi-pretrain-research_release`, "PT"), which has no named voices. Positives are the 100 natural TV recordings of `Listening_Examples_100`; negatives are the model's own (on-policy) generations from the same Devanagari/English transcripts. The steering vector $v = \bar{h}_{\text{natural}} - \bar{h}_{\text{PT}}$ was built from 69 training pairs. Evaluation is a three-way comparison with one model: Natural vs. PT base vs. PT steered. As in the pilot, a linear natural-vs-PT direction exists at every site (held-out AUC median 1.0, permutation 95th percentile ≤ 0.63). The selected configuration (layer 27 attention output, mean-pooled v, $\alpha^* = 1$) moves an external natural-vs-PT classifier (M1) beyond a random vector of the same norm on the 19 test utterances (+0.79 log-odds, $p = .023$), but **not significantly beyond the unsteered baseline** (+0.40, 95% CI $[-0.49, 1.28]$). Similarity to the paired natural clip (M2) and prosody distance (M3) move in the right direction but are not significant. In-sample on all 100 utterances, M1 improves clearly (+0.84, $p = 5 \times 10^{-5}$) and M2/M3 trend better ($p \approx .08$), while voice quality worsens (HNR -1.1 dB, jitter and shimmer up) and NISQA is unchanged. The pre-registered failure guardrail admitted no configuration; we recalibrated it to the measured sampling variance of the unsteered model. On test the steered model still fails the failure-rate and WER guardrails, the latter because of one clip. The objective verdict is **no-go**, with a weak positive signal worth a listening check.

1 Question and design changes from the pilot

The pilot steered fine-tuned models with a fixed voice and used their default outputs as negatives. Here we ask whether the same mechanism improves the *pretrained* Orpheus checkpoint, whose baseline output is the model's own unprompted delivery. The changes from the pilot are:

- **Model:** Orpheus Hindi PT, revision b813fee6, bf16. Text-only prompt (no voice prefix), so the speaker varies per clip.
- **Negatives:** on-policy PT generations, one sample per transcript at seed 1234 (decoding $t = 0.6$, top-p 0.9, repetition penalty 1.1, batch size 1). These same clips are the "PT base" condition.
- **Input:** Devanagari/English transcripts only.
- **Split:** the pilot's split, reused as is (76 train including 16 dev, 19 test, 5 excluded; seed 20261029).
- **Evaluation:** one model, three groups (Natural, PT base, PT steered), plus a random-vector control on test. Metrics are the partner summary's figure set (`preliminary_summary.pdf`), NISQA-TTS, and the pilot's M1–M3.

The listening package is a new folder with the same per-utterance layout as `Listening_Examples_100` (§7).

2 Method

2.1 Teacher forcing and the PT prefix

In all 100 base generations, the PT model emitted the same start-of-audio prefix as the fine-tuned model, `[128261, 128257]`, and no non-audio tokens inside or after the audio. Teacher forcing therefore uses `128259` + tok(text) + `128009, 128260, 128261, 128257` + SNAC audio tokens + `128258`. Natural clips were mixed to mono, resampled to 24 kHz and SNAC-encoded; PT clips were re-encoded from their wavs, so both classes go through the same encoder. A SNAC round trip on 9 real clips was exact.

2.2 Base generations and contrast set

Of the 100 base generations, 10 ran to the token budget without ending speech (7 train, 1 test, 2 of the excluded utterances). Several are short inputs at the 8 s minimum budget, so they are runaways, not truncation. The 7 failed train negatives were dropped together with their natural clip, leaving **69 train pairs** for v.

2.3 Diagnostics, selection and test

Sites, pooling, norm-preserving injection ($\tilde{h} = h + \alpha v$, rescaled to $\|h\|$) and statistics are the pilot's. Following option (a) of the plan, we ran the lean diagnostics (probes, held-out projection AUC against a permutation control, audio-token NLL) and then a dev sweep restricted to attention `o_proj`, mean-pooled sites, the only family usable in the pilot:

- Sweep 1: the 6 shortlisted layers, each at $\alpha \in \{0.5, 1, 2\}$, on the 16 dev utterances.
- Sweep 2: the top-2 and top-3 layers combined, at the same α values.

The selection rule and composite score are the pilot's. A clip counts as a failure if it has no end-of-speech token, hits the budget, or lasts less than half or more than twice its seed-1234 base clip. The selected vector was then applied to all 100 utterances, and a random vector of the same norm at the same site and α to the 19 test utterances.

2.4 Metrics

- **Summary figure metrics**, computed with the partner's code: Whisper-large-v3 WER/CER and ASR speaking rate, Praat prosody and voice quality, syllable-nucleus rate, WavLM-SV within-group speaker consistency.
- **NISQA-TTS:** official repository at commit fe84f0f2, run in a separate environment. The checkpoint pickle was inspected before loading and also loads with `weights_only=True`.
- **M1:** log-odds of a logistic natural-vs-PT classifier on WavLM-base-plus embeddings, trained on the train utterances (held-out AUC 1.000).
- **M2:** WavLM cosine similarity to the paired natural clip.
- **M3:** IQR-scaled prosody distance to the paired natural clip (lower is better).
- **Guardrails:** WER/CER, S-SIM to the base clip, failure rate.

The 19 test utterances are the primary result. All-100 numbers are reported as *in-sample*, because v and the M1 classifier used the train utterances.

3 Results

3.1 Diagnostics

	Orpheus PT	Pilot Orpheus FT
Sites with probe accuracy = 1.0	78/112	82/112
Probe accuracy, permuted labels	0.475	0.49
Held-out projection AUC, min / median	0.743 / 1.0	0.89 / –
Permutation AUC, mean / max 95th pct.	0.494 / 0.625	0.49 / 0.62
Cohen's d, median (resid. / attn.)	4.4 / 4.5	5.7 / 5.8
$\|v\|/\|h\|$, median (resid. / attn.)	0.31 / 0.67	0.28 / 0.73
Audio-token NLL, natural vs. synthetic (nats)	5.69 vs. 2.69	5.93 vs. 3.17

The direction is far above chance at every site. As in the pilot, separation is close to trivial: natural audio is about twice as surprising to the model, and speaker and channel differ. Diagnostics alone therefore cannot choose a site. The shortlist (all AUC 1.0) was layers 24, 20, 27, 23, 22 and 26.

3.2 Selection

Under the pre-registered rule, no configuration was admissible (0 of 27). The dev base failed on 0 of 16 clips, so the failure threshold was 5%, and every steered configuration failed on at least 12.5%. To test whether this reflects steering or sampling, we resampled the *unsteered* model at seeds 1235 and 1236 on the same 16 utterances. By the same definition it failed on **7/32 = 21.9%** (3 runaways, 4 duration ratios), on the same utterances that fail under steering. Because PT draws a new speaker for every sample, the duration-ratio test against a single base clip mostly measures sampling variance. We therefore recalibrated the threshold to max(5%, base, 21.9%). This is a post-hoc deviation; the strict outcome is reported alongside it.

Config (dev)	Fail	WER	CER	S-SIM	ΔM1	ΔM2	ΔM3	Admissible
L20, $\alpha = 0.5$	.188	.741	.606	.838	+0.88	−.005	−.121	yes
L27, $\alpha = 1$	**.125**	**.767**	**.614**	**.876**	**+0.95**	**+.027**	**−.163**	**yes, selected**
L27, $\alpha = 2$	.250	.800	.629	.895	+1.47	+.014	−.053	no (fail)
L27+L20, $\alpha = 0.5$	.125	.704	.519	.882	+0.61	+.006	−.190	yes
L27+L20+L24, $\alpha = 0.5$	.188	.794	.604	.908	+1.09	+.022	+.030	yes
L26, $\alpha = 0.5$	.188	.878	.680	≈.86	+1.27	≈+.02	−.15	no (WER)
Dev PT base	0	.814	.602	–	–	–	–	

Four configurations passed the recalibrated rule, and **layer 27 attention output at $\alpha^* = 1$** had the best composite score (0.527). Stronger or multi-layer steering raised either failures or WER. Across sweep-1 sites, steering effect and diagnostic separation were not positively related (correlation −0.26). The full table is in the run's `report.md`.

3.3 Test set (19 utterances)

Metric (median unless noted)	Natural	PT base	PT steered	Random control
Failures (of 19)	0	1	5	3
WER corpus	.945	.718	1.235 (.717 w/o outlier)	.725
CER corpus	.877	.602	.843 (.573 w/o outlier)	.614
Syllable-nucleus rate (/s)	4.20	3.20	3.23	3.60
Duration (s)	5.49	6.40	6.57	5.46
Median F0 (Hz)	220	129	149	137
F0 range (st)	19.9	6.3	9.3	7.3
Internal pause (%)	17.6	18.8	21.3	19.7
HNR (dB)	8.7	15.5	15.0	14.7
NISQA-TTS	2.94	3.62	3.57	3.58
Speaker consistency (mean pair cosine)	.732	.834	.848	.838
M1 logit (mean)	5.38	−4.25	−3.85	−4.64
M2 (mean)	–	.676	.696	.661
M3 (mean, lower better)	–	1.015	.951	1.097
S-SIM to PT base (mean)	–	–	.883	.889

Paired differences, mean [95% bootstrap CI], Wilcoxon p, $n = 19$:

	Steered − base	Random − base	Steered − random
M1	+0.40 [−0.49, 1.28], $p = .44$	−0.39 [−1.01, 0.24], $p = .42$	**+0.79 [0.18, 1.34],** $p = .023$
M2	+0.020 [−0.038, 0.084], $p = .83$	−0.014, $p = .54$	+0.034, $p = .33$
M3	−0.064 [−0.28, 0.12], $p = .89$	+0.082, $p = .52$	−0.147, $p = .20$
NISQA	−0.06 [−0.34, 0.25], $p = .74$	−0.15, $p = .54$	+0.09, $p = .74$
Median F0 (Hz)	+9.0 [−8.3, 23.8], $p = .12$	−2.5, $p = .47$	+11.5, $p = .11$
Failure	+0.21 [0.05, 0.42]	+0.11 [0, 0.26]	+0.11

The only steered-minus-base interval that excludes zero is the failure rate. Steering beats a random vector on M1, so the effect is specific to v, but it is too small to separate from the baseline on 19 utterances. Guardrails on test: S-SIM passes. WER and CER fail because of a single clip, `train_1693_0`: the steered clip ends properly but runs 16.0 s against 5.9 s for base (clip WER 8.1). Without it, steered WER/CER are .717/.573 against .726/.606 for base. The failure rate fails, at 26% against the 21.9% threshold. Only 1 of the 5 steered failures is a runaway; the other 4 are duration-ratio flags. One of them, `train_1753_4`, is a properly ended 1.6 s steered clip whose *base* was the runaway.




Figure 1: M1–M3 on the test set. M2 and M3 compare each generated clip with its paired natural clip, so Natural has no bar.




Figure 2: Prosody on the test set (medians).

3.4 All 100 utterances (in-sample)

Metric	Natural	PT base	PT steered
Failures / runaways only	0 / 0	10 / 10	18 / 3
WER median / corpus	.750 / .880	.750 / .817	.756 / .988
Syllable-nucleus rate (/s)	4.02	3.23	3.68
Median F0 (Hz) / F0 range (st)	225 / 19.8	141 / 7.4	142 / 8.2
Internal pause (%)	18.3	19.6	14.8
Jitter / shimmer / HNR (dB)	.024 / .127 / 8.6	.019 / .081 / 14.8	.020 / .088 / 13.5
NISQA-TTS	3.15	3.69	3.72
Speaker consistency	.776	.853	.855
M1 / M2 / M3 (means)	5.69 / – / –	−4.87 / .655 / 1.049	−4.03 / .680 / .983

Steered − base, $n = 100$: M1 +0.84 [0.50, 1.21], $p = 5 \times 10^{-5}$; M2 +0.025 [−0.000, 0.052], $p = .085$;

M3 -0.066 [-0.139, 0.008], $p = .072$; syllable-nucleus rate $+0.43$/s, $p = .003$; HNR -1.08 dB, $p = 5 \times 10^{-4}$; jitter and shimmer up, $p < .02$; NISQA $+0.11$, $p = .10$. Runaways drop from 10 to 3, but duration-ratio flags rise, so total failures go from 10 to 18. These numbers are biased upward by in-sample use but are consistent in sign with the test set.

3.5 Go/no-go

Criterion	Test (19)	Verdict
Direction exists (AUC vs. permutation)	1.0 vs. 0.63	pass
M1 specific to v (vs. random)	$+0.79$, $p = .023$	pass
M1 better than base	$+0.40$, CI includes 0	fail
M2 / M3 better than base	n.s.	fail
S-SIM guardrail	.883	pass
WER/CER guardrail	fails (one clip)	fail
Failure guardrail (recal.)	26% vs. 21.9%	fail
Overall		**no-go (weak positive signal)**

4 Discussion

Same picture as the pilot, with one difference. The direction exists, is causal, and is specific to v. But on the test set it does not bring output measurably closer to the paired natural recording. Unlike the pilot, M2 and M3 here move in the right direction in-sample, with $p \approx .08$, so the PT model may be somewhat more steerable toward natural delivery than the fine-tuned models.

What the vector changes. Steering raises F0 level and range and the syllable rate, moving toward the natural pool. It also lowers HNR and raises jitter and shimmer. Natural TV audio has lower HNR and higher jitter than TTS, so these changes may partly be steering toward the TV channel rather than toward delivery. NISQA, a learned quality score, is flat: it neither rewards nor penalises the change.

Sampling variance dominates the guardrails. PT draws a new speaker for each sample, and even unsteered resamples fail the duration-ratio test 22% of the time. Single-seed comparisons against one base clip are therefore noisy. A fair test needs several seeds per utterance and failure criteria that do not depend on one reference clip.

WER is a weak proxy. Natural speech has a higher WER than PT (corpus .945 vs. .718), as in the partner summary, so higher WER does not necessarily mean less intelligible speech.

Transcripts. The caveat from the pilot applies: the Devanagari/English inputs went through lossy romanization and transliteration, so they do not fully match what was said in the natural clips.

5 Limitations

- 19 test utterances, one seed per utterance and condition, and a random speaker per clip. Small effects cannot be resolved.
- The failure guardrail was recalibrated after sweep 1. Under the strict rule, nothing would have been selected.
- Several metric deviations from the partner summary: natural audio resampled with torchaudio rather than `resample_poly`; NISQA run with newer library versions than its pins, with clips under 0.3 s left unscored (1 clip); small stand-ins for two scipy functions used only by unreported features.
- The mechanistic projection check from the pilot was not run.
- No human listening yet. Naturalness is judged only by bilingual listeners (`AGENTS.md`).

6 Next steps

1. Blind A/B listening on `Listening_Examples_100_PT`, test utterances first. Include `train_1693_0`.
2. Re-run base and steered with 3–5 seeds per utterance to separate steering from sampling variance, and define failure relative to the base distribution rather than one clip.
3. Reduce the channel confound, for example by building v from natural clips matched to PT on loudness and band-limiting, or by subtracting a speaker/channel direction.

7 Listening package

On kedi at `/local/speech/users/sp4050/Listening_Examples_100_PT/`. It has the same 100 folder names as `Listening_Examples_100`. Each folder holds a copy of the natural clip, `TRANSCRIPT.txt`, `02_OrpheusPT_base.wav` and `03_OrpheusPT_steered.wav`, and is tagged with its split (19 test, 60 train, 16 dev, 5 excluded). The top level has `manifest.csv` (with SHA-256 per file), `utterances_100.csv`, `READ_ME.txt` and `listen.html` (three players per utterance).

A Provenance

- Run: `/local/speech/users/sp4050/outputs/caa_pt/20261105-1232_listening100/` (`report.md`, `report_phase1.md`, `config.yaml`, `generations.jsonl`, `tables/`, `selection/`, `figures/`, `provenance/`).
- Code: base commit a5240e0 plus the CAA-PT changes (`configs/caa_pt/pt.yaml`, `scripts/caa_pt_report.py`, and the config-driven pilot scripts). 11 unit tests pass.
- Model revisions: Orpheus PT b813fee6, SNAC d73ad176. NISQA fe84f0f2, `nisqa_tts.tar` sha256 c556a954....
- Key numbers in this report were recomputed from `metrics/clips_pt.csv` and match the run's `stats.json`.