



P550HVN06.6 2500nit EC Comparison Table

Faway Lan

ADP PM

2023/12/06

P550HVN06.6 _ Comparison Table

Model name	P550HVN06.6 (Before EC)	P550HVN06.6 (After EC)
ADP Part No.	97.55P09.600	97D55P09.601
Resolution/Frame Rate	1920 x 1080	←
Frame rate	60Hz	←
Brightness	2500nit	←
Display Color	8bit + FRC	←
Contrast Ratio	4000 : 1	←
Color Gamut	72%	←
Color Temp	10,000K	6500K
Color Coordinate	(0.28, 0.29)	(0.313, 0.329)
LC	High Temp(-20°~110°)	Wide Temp(-40°~110°)
POL surface treatment	AG 28%	←
Active Area	1209 (H) x 680 (V)	←
Outline (mm)	1235.6 (H) x 706.4 (V)	←
Thickness(mm)	58.2 (FB to DB)	←
Bezel width U/L/R/D (mm)	9.8 / 9.8 / 9.8 / 9.8	←
Bezel color	SECC Original color	Black
BLU structure	D-LED	D-LED
Operation Temperature	-20°C ~ 60°C	←
Power Consumption	285W	226 W
LED Lifetime (min)	50K hrs MTTF MDL	←

Product Key Upgrade:

- Color Temp. Changed from CCT 10,000K to 6,500K
- Wide temperature LC Introduced
- Power Consumption : 20% Power Saving. (New DB)

Schedule

1. Drawing 2D/3D : Ready
2. 1st Sample Schedule : 7/26
3. 2nd Sample Schedule : 8/18

P550HVN06.6 EC Comparison



Model name	P550HVN06.6(Before EC)	P550HVN06.6(After EC)
UDM	Keeps the same	Keeps the same
Packing	5pcs/Box	5pcs/Box(Keeps the same)
DB size	Keeps the same	Keeps the same
Weight	Keeps the same	Keeps the same

P550HVN06.6 EC Comparison_ Pin Assignment(LVDS)

PIN	Symbol	Description	Note	PIN	Symbol	Description	Note
1	N.C.	No connection (for AUO test only. Do not connect)	2	28	N.C.	No connection (for AUO test only. Do not connect)	2
2	N.C.	No connection (for AUO test only. Do not connect)	2	27	N.C.	No connection (for AUO test only. Do not connect)	2
3	N.C.	No connection (for AUO test only. Do not connect)	2	28	CH2_0	LVD 8 Channel 2, Signal 0	2
4	N.C.	No connection (for AUO test only. Do not connect)	2	29	CH2_0	LVD 8 Channel 2, Signal 0	2
5	BITSEL	LVD 8 2/10bit Input Selection: Open/Low(0ND) : 2bits High(3.3V) : 10bits	2	30	CH2_1	LVD 8 Channel 2, Signal 1	2
8	N.C.	No connection (for AUO test only. Do not connect)	2	31	CH2_1	LVD 8 Channel 2, Signal 1	2
7	LVD_8_SEL	High(3.3V) for N8 Open/Low(0ND) for JEIDA	2	32	CH2_2	LVD 8 Channel 2, Signal 2	2
8	N.C.	No connection (for AUO test only. Do not connect)	2	33	CH2_2	LVD 8 Channel 2, Signal 2	2
9	N.C.	No connection (for AUO test only. Do not connect)	2	34	GND	Ground	2
10	N.C.	No connection (for AUO test only. Do not connect)	2	35	CH2_CLK	LVD 8 Channel 2, Clock	2
11	GND	Ground	2	36	CH2_CLK	LVD 8 Channel 2, Clock	2
12	CH1_0	LVD 8 Channel 1, Signal 0	2	37	GND	Ground	2
13	CH1_0	LVD 8 Channel 1, Signal 0	2	38	CH2_3	LVD 8 Channel 2, Signal 3	2
14	CH1_1	LVD 8 Channel 1, Signal 1	2	39	CH2_3	LVD 8 Channel 2, Signal 3	2
15	CH1_1	LVD 8 Channel 1, Signal 1	2	40	CH2_4	LVD 8 Channel 2, Signal 4	2
16	CH1_2	LVD 8 Channel 1, Signal 2	2	41	CH2_4	LVD 8 Channel 2, Signal 4	2
17	CH1_2	LVD 8 Channel 1, Signal 2	2	42	N.C.	No connection (for AUO test only. Do not connect)	2
18	GND	Ground	2	43	N.C.	No connection (for AUO test only. Do not connect)	2
19	CH1_CLK	LVD 8 Channel 1, Clock	2	44	GND	Ground	2
20	CH1_CLK	LVD 8 Channel 1, Clock	2	45	GND	Ground	2
21	GND	Ground	2	46	GND	Ground	2
22	CH1_3	LVD 8 Channel 1, Signal 3	2	47	N.C.	No connection (for AUO test only. Do not connect)	2
23	CH1_3	LVD 8 Channel 1, Signal 3	2	48	VDD	Power Supply, +12V DC Regulated	2
24	CH1_4	LVD 8 Channel 1, Signal 4	2	49	VDD	Power Supply, +12V DC Regulated	2
25	CH1_4	LVD 8 Channel 1, Signal 4	2	50	VDD	Power Supply, +12V DC Regulated	2
				51	VDD	Power Supply, +12V DC Regulated	2

PIN	Symbol	Description	Note	PIN	Symbol	Description	Note
1	N.C.	No connection (for AUO test only. Do not connect)	2	28	N.C.	No connection (for AUO test only. Do not connect)	2
2	N.C.	No connection (for AUO test only. Do not connect)	2	27	N.C.	No connection (for AUO test only. Do not connect)	2
3	N.C.	No connection (for AUO test only. Do not connect)	2	28	CH2_0	LVD 8 Channel 2, Signal 0	2
4	N.C.	No connection (for AUO test only. Do not connect)	2	29	CH2_0	LVD 8 Channel 2, Signal 0	2
5	BITSEL	LVD 8 2/10bit Input Selection: Open/Low(0ND) : 2bits High(3.3V) : 10bits	2	30	CH2_1	LVD 8 Channel 2, Signal 1	2
8	N.C.	No connection (for AUO test only. Do not connect)	2	31	CH2_1	LVD 8 Channel 2, Signal 1	2
7	LVD_8_SEL	High(3.3V) for N8 Open/Low(0ND) for JEIDA	2	32	CH2_2	LVD 8 Channel 2, Signal 2	2
8	N.C.	No connection (for AUO test only. Do not connect)	2	33	CH2_2	LVD 8 Channel 2, Signal 2	2
9	N.C.	No connection (for AUO test only. Do not connect)	2	34	GND	Ground	2
10	N.C.	No connection (for AUO test only. Do not connect)	2	35	CH2_CLK	LVD 8 Channel 2, Clock	2
11	GND	Ground	2	36	CH2_CLK	LVD 8 Channel 2, Clock	2
12	CH1_0	LVD 8 Channel 1, Signal 0	2	37	GND	Ground	2
13	CH1_0	LVD 8 Channel 1, Signal 0	2	38	CH2_3	LVD 8 Channel 2, Signal 3	2
14	CH1_1	LVD 8 Channel 1, Signal 1	2	39	CH2_3	LVD 8 Channel 2, Signal 3	2
15	CH1_1	LVD 8 Channel 1, Signal 1	2	40	CH2_4	LVD 8 Channel 2, Signal 4	2
16	CH1_2	LVD 8 Channel 1, Signal 2	2	41	CH2_4	LVD 8 Channel 2, Signal 4	2
17	CH1_2	LVD 8 Channel 1, Signal 2	2	42	N.C.	No connection (for AUO test only. Do not connect)	2
18	GND	Ground	2	43	N.C.	No connection (for AUO test only. Do not connect)	2
19	CH1_CLK	LVD 8 Channel 1, Clock	2	44	GND	Ground	2
20	CH1_CLK	LVD 8 Channel 1, Clock	2	45	GND	Ground	2
21	GND	Ground	2	46	GND	Ground	2
22	CH1_3	LVD 8 Channel 1, Signal 3	2	47	N.C.	No connection (for AUO test only. Do not connect)	2
23	CH1_3	LVD 8 Channel 1, Signal 3	2	48	VDD	Power Supply, +12V DC Regulated	2
24	CH1_4	LVD 8 Channel 1, Signal 4	2	49	VDD	Power Supply, +12V DC Regulated	2
25	CH1_4	LVD 8 Channel 1, Signal 4	2	50	VDD	Power Supply, +12V DC Regulated	2
				51	VDD	Power Supply, +12V DC Regulated	2

Pin Assignment :
No Change

P550HVN06.6 EC Comparison_ Pin Assignment(DB)

Pin ⁽¹⁾	Symbol ⁽²⁾	Description ⁽³⁾	Note ⁽⁴⁾
1 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
2 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
3 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
4 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
5 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
6 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
7 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
8 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
9 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
10 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
11 ⁽¹⁾	DET ⁽²⁾	BLU status detection: ⁽³⁾	1 ⁽⁴⁾
12 ⁽¹⁾	VBLO ⁽²⁾	BLU On-Off control: ⁽³⁾	2,3 ⁽⁴⁾
13 ⁽¹⁾	NC ⁽²⁾	NC ⁽³⁾	4 ⁽⁴⁾
14 ⁽¹⁾	PDIM ⁽²⁾	External PWM ⁽³⁾	2, 5 ⁽⁴⁾

Pin ⁽¹⁾	Symbol ⁽²⁾	Description ⁽³⁾	Note ⁽⁴⁾
1 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
2 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
3 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
4 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
5 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
6 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
7 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
8 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
9 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
10 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
11 ⁽¹⁾	NC ⁽²⁾	NC ⁽³⁾	4 ⁽⁴⁾
12 ⁽¹⁾	NC ⁽²⁾	NC ⁽³⁾	4 ⁽⁴⁾

Pin ⁽¹⁾	Symbol ⁽²⁾	Description ⁽³⁾	Note ⁽⁴⁾
1 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
2 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
3 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
4 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
5 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
6 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
7 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
8 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
9 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
10 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
11 ⁽¹⁾	DET ⁽²⁾	BLU status detection: ⁽³⁾	1 ⁽⁴⁾
12 ⁽¹⁾	VBLO ⁽²⁾	BLU On-Off control: ⁽³⁾	2,3 ⁽⁴⁾
13 ⁽¹⁾	NC ⁽²⁾	NC ⁽³⁾	4 ⁽⁴⁾
14 ⁽¹⁾	PDIM ⁽²⁾	External PWM ⁽³⁾	2, 5 ⁽⁴⁾

Pin ⁽¹⁾	Symbol ⁽²⁾	Description ⁽³⁾	Note ⁽⁴⁾
1 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
2 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
3 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
4 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
5 ⁽¹⁾	VDDB ⁽²⁾	Power Supply Input Voltage ⁽³⁾	⁽⁴⁾
6 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
7 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
8 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
9 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
10 ⁽¹⁾	GND ⁽²⁾	Ground ⁽³⁾	⁽⁴⁾
11 ⁽¹⁾	NC ⁽²⁾	NC ⁽³⁾	4 ⁽⁴⁾
12 ⁽¹⁾	NC ⁽²⁾	NC ⁽³⁾	4 ⁽⁴⁾

Pin Assignment :
No Change

Tap Into The Possibilities