



G156HAN02.000 to G156HAN02.001 LED Driver IC & BLUEC notice

2024.07.18

AUO Display Plus LED Driver IC & BLU EC

- **Purpose :** In order to maintain product competitiveness, we would like to adopt new PCBA circuit with new LED driver IC (BD9276) and change to new BLU.

- **Change Items:**

Key parts of PCBA

No.	Function	<u>Before:</u> Type Name, Vender	<u>After:</u> Type Name, Vender
1	LED Driver IC	NT50508 *2, NVT	BD9276*1, ROHM

Key parts of BLU


No.	Function	<u>Before:</u> Type Name, Vender	<u>After:</u> Type Name, Vender
1.	Light guide plate	PMMA print, vendor A	PMM thermoforming, vendor B
2.	LED	PT40XXX XX, Lextar , 50ea	01.JP.ZC4014XXXXXX, JF, 45ea
3.	Optical films	----	Suppliers and type are different

- **Implement date & method:**

Running Change from 2024.Q4

AUO Display Plus LED Driver IC & BLU EC

➤ Schedule:



AUO Display Plus LED Driver IC & BLU EC

➤ Optical:

Optical Measurement Report												
Originator	chongfeng			Model/PCS		G156HAN02.0/5PCS			Date	2024/4/4		
Test Condition	Lum.,CR,Chromaticity,Uniformity,Gary Scale,V-T,View Angle,RT,Cross Talk,Flicker											
Test System	Detector	Inverter			DC Voltage				Warm up time			
FPM-510	SR-UL2	NA			12V				30 min			
【Test Reason】												
G156HAN02.001 DVT												
【Judgement】												
PASS												
Test Items	unit	PSS								-4σ	mean	+4σ
					4B1WX3BKZZZS01	4B1WX7W1ZZZS01	4B1WX3BFZZZS01	4B1WX5DCZZS01	4B1WX7WTZZS01			
		min	typ	max	5G2500342640201701	5G2500342640201701	5G2500342640201701	5G2500342640201701	5G2500342640201701			
Center Brightness	cd/m ²	400	500		485.4	470.0	487.0	482.0	490.2	451.8	482.9	514.0
Darkness (L0)					0.35	0.40	0.45	0.43	0.56	0.125	0.44	0.748
Contrast Ratio(CR)		700	1000		1399.7	1163.0	1085.2	1132.8	877.7	384.7	1131.7	1878.7
Brightness(5P Ave.)	cd/m ²				442.0	442.4	453.7	447.1	459.2	419.0	448.9	478.7
Chromaticity												
Wx	---	0.263	0.313	0.363	0.311	0.311	0.313	0.313	0.312	0.307	0.312	0.317
Wy	---	0.279	0.329	0.379	0.318	0.319	0.322	0.323	0.322	0.312	0.321	0.329
Rx	---	0.589	0.639	0.689	0.649	0.648	0.648	0.649	0.648	0.647	0.649	0.650
Ry	---	0.283	0.333	0.383	0.331	0.331	0.332	0.332	0.331	0.331	0.331	0.332
Gx	---	0.252	0.302	0.352	0.297	0.296	0.299	0.298	0.299	0.292	0.298	0.304
Gy	---	0.574	0.624	0.674	0.608	0.611	0.606	0.608	0.607	0.600	0.608	0.616
Bx	---	0.107	0.157	0.207	0.148	0.148	0.148	0.148	0.149	0.148	0.148	0.149
By	---	0.008	0.058	0.108	0.057	0.055	0.059	0.058	0.059	0.052	0.058	0.063
NTSC	---	---	72		74.3	74.9	73.4	74.0	73.5	71.611	74.020	76.428

AUO Display Plus LED Driver IC & BLU EC

➤ RA:

RA Test Summary Report

保管單位 Storage	RA
保存年限 Retention Period	依產品適用範圍保存(參照： AWQP-05-002 紀錄管制流程)

Product No	G156HAN02.0	Part No	97.15G25.001	Applicant/Dept	群智/RPPE3	Judgement					
Test Purpose	G156HAN02.001 DVT 1-2			Application Date	2024/04/02	PASS					
RA No	D240403008	Product Stage	DVT	Input Date	2024/04/05						
Test Item	Test Condition	Test Panel		Issue Date	2024/04/17	Test Result					
THB	50°C 80% 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500★	Judgement	Judgement
		D2404030080001		6E3B93474EZZS0101	OK	OK	OK	OK	OK	PASS	PASS
		D2404030080002		6e3b92w8mtzzs0101	OK	OK	OK	OK	OK	PASS	
		D2404030080003		6e4b1wx5cpzzzs0101	OK	OK	OK	OK	OK	PASS	
LTO	-20°C 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500★	Judgement	Judgement
		D2404030080004		6e4b1wx7wjzzzs0101	OK	OK	OK	OK	OK	PASS	PASS
		D2404030080005		6e4b1wx7wbzzzs0101	OK	OK	OK	OK	OK	PASS	
		D2404030080006		6l3bcw9amzzzs0101	OK	OK	OK	OK	OK	PASS	
LTS	-20°C 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500★	Judgement	Judgement
		D2404030080007		6e4b1wx5czzzs0101	OK	OK	OK	OK	OK	PASS	PASS
		D2404030080008		6e4b1wx5btzzzs0101	OK	OK	OK	OK	OK	PASS	
		D2404030080009		6e4b1wx5brzzzs0101	OK	OK	OK	OK	OK	PASS	
HTO	70°C 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500★	Judgement	Judgement
		D2404030080010		6l3bbl15tzzzs0101	OK	OK	OK	OK	OK	PASS	PASS
		D2404030080011		6e4b1wx5cazzzs0101	OK	OK	OK	OK	OK	PASS	
		D2404030080012		6e4b1wx7wezss0101	OK	OK	OK	OK	OK	PASS	
HTS	70°C 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500★	Judgement	Judgement
		D2404030080013		6e3b92w8pazzzs0101	OK	OK	OK	OK	OK	PASS	PASS
		D2404030080014		6h3btj80tzzzs0101	OK	OK	OK	OK	OK	PASS	
		D2404030080015		6e4b1wx7wazzzs0101	OK	OK	OK	OK	OK	PASS	
TST	-20°C/30min, 60°C/30min, 100 cycles Judge 100cycles	No	Chip_Id	Shipping_No	C0★	C100★				Judgement	Judgement
		D2404030080016		6e4b1wx5dlzzzs0101	OK	OK				PASS	PASS
		D2404030080017		6e3b92w8mbzzzs0101	OK	OK				PASS	
		D2404030080018		6e4b1wx7whzzzs0101	OK	OK				PASS	

AUO Display Plus LED Driver IC & BLU EC

➤ RA:

AUO

Test Result (Summary)

Test Item	Test Condition	Qty	Test Date	Judge
Vibration	Acceleration: 1.5 Grms Wave: Random Frequency: 10 - 200 Hz Sweep: 30 Minutes each Axis (X, Y, Z)	3	2024-2-15	PASS

Test Item	No.	S/N	Before test (T0)	After test
Vibration	1	6H3BBJ80XBZZS0101	OK	PASS
	2	6H3BBJ80LDZZS0101	OK	PASS
	3	6L3BBL15YMZZS0101	OK	PASS

AUO

Test Result (Summary)

Test Item	Test Condition	Qty	Test Date	Judge
Shock	Acceleration: 50 G Wave: Half-sine Active Time: 20 ms Direction: $\pm X, \pm Y, \pm Z$ (one time for each Axis)	3	2024-2-2	PASS

Test Item	No.	S/N	Before test (T0)	After test
Shock	1	6H3BBJ80WRZZS0101	OK	PASS
	2	6H3BBJ80LCZZS0101	OK	PASS
	3	6H3BBJ80XCZZS0101	OK	PASS

Tap Into The Possibilities

AUO Display Plus Confidential for Internal Use Only