

 AUO Display+ AUO Display Plus Corporation		Engineering Change Notice																						
Document No: GT37P-03-3-0006		Requested by																						
Product Type: P370IVN02.2		Signature <u>紀曉真 陳正欣</u>																						
Model Name: P370IVN02.2		Date <u>2024/12/09</u>																						
Issued Date: 2024/07/20		Name <u>紀曉真 陳正欣</u>																						
		Title <u>交通產品行銷部</u>																						
1. Purpose Utilize lock type connector for enhanced stability and fixation 2. Changes DB connector, DB to LB Wire Connector EC Proposal ■ Purpose : Utilize lock type connector for enhanced stability and fixation. ■ EC item : DB connector, DB to LB Wire ■ EC date & mode : 2025/1 running change ■ EC comparison: shown as below pictures, The EC will be converted from normal type to lock type. <table><tr><th>EC item</th><th>P/N</th></tr><tr><td>DB</td><td>P/N unchanged, version updated</td></tr><tr><td>Wire</td><td>New P/N</td></tr></table><table><tr><th>Connector</th><th>Before</th><th>After (Lock type)</th></tr><tr><td>DB Receptacle</td><td></td><td></td></tr><tr><td>Wire Plug</td><td></td><td></td></tr></table> ■ RA test item: Vehicle Vibration Test(Follow EN 61373) <table><tr><th>RA test item</th><th>Condition</th><th>Result</th></tr><tr><td>Vibration</td><td>Random (0.21Grms 5-150Hz), 5hr / X axis Random (0.434Grms 5-150Hz), 5hr / Y axis Random (0.281Grms 5-150Hz), 5hr / Z axis * One time each direction</td><td>PASS</td></tr></table> Figure : P370IVN02.2.jpg				EC item	P/N	DB	P/N unchanged, version updated	Wire	New P/N	Connector	Before	After (Lock type)	DB Receptacle			Wire Plug			RA test item	Condition	Result	Vibration	Random (0.21Grms 5-150Hz), 5hr / X axis Random (0.434Grms 5-150Hz), 5hr / Y axis Random (0.281Grms 5-150Hz), 5hr / Z axis * One time each direction	PASS
EC item	P/N																							
DB	P/N unchanged, version updated																							
Wire	New P/N																							
Connector	Before	After (Lock type)																						
DB Receptacle																								
Wire Plug																								
RA test item	Condition	Result																						
Vibration	Random (0.21Grms 5-150Hz), 5hr / X axis Random (0.434Grms 5-150Hz), 5hr / Y axis Random (0.281Grms 5-150Hz), 5hr / Z axis * One time each direction	PASS																						
3. Desired Implementation Method & Date 2025/01/01 ; RUNNING CHANGE ;																								
4. Attachment																								
Customer (PROMATE) Feedback																								
Disposition ☐ Agree ☐ Disagree, Comment: Note: Please kindly reply to ADP within 14 calendar days upon receipt. This ECR will be regarded as "Agree" if ADP does not receive feedback within 14 calendar days.		Agreed by: Signature _____ Date _____ Name _____ Title _____																						