




G240HW01 V100 Engineering Change Request



Felix Lee
2023/09

G240HW01 V100 EC Notice

Purpose :

Since Tcon IC (12304 Z03) will be EOL. In order to keep supply smoothly, ADP will Change Original Tcon IC (12304 Z03) to new Tcon IC (12303 Z09), for longevity support.

Replacement model :

G240HW01 V100=> G240HW01 V104, new product specification need to be changed as below.

- Display Characteristics: Only the Model Name would be changed, the other part of spec would not be different.
- EC Change

Items	Before (G240HW01 V100)	After (G240HW01 V104)
Tcon IC	AUO 12304 Z03	AUO 12303 Z09
Protection Film	Hard Protection Film	Soft Protection Film

Verification schedule:

1. Verification samples will come out at the 2023/07.
2. RA / EMI / ESD all test passed
3. Phase in => 2024/Q1


General Display Characteristics

Panel supplier	MP (now)	EC model
Mode	VA	VA
Model name	G240HW01 V100	G240HW01 V104
Resolution	1920 x 1080	1920 x 1080
Active Area(mm)	531.36 x 298.89	531.36 x 298.89
Outline dimension(mm) (W x H x D)	430.4 x 254.6 x 12	430.4 x 254.6 x 12
Treatment	Anti-Glare, (3H)	Anti-Glare, 3H
Contrast Ratio (Typ.)	5000: 1	5000: 1
Viewing Angle (CR≥10) (Typ.)	89/89/89/89	89/89/89/89
Response Time (Tr+Td) (Typ.)	25ms	25ms
Brightness (cd/m ²) (Typ.)	300	300
NTSC	72%	72%
Weight (g)	2,130	2,130
Interface	Dual channel LVDS	Dual channel LVDS
Operating Temperature	-20~70 °C	-20 to +70
Storage Temperature	-30 to +80	-30 to +80
LED life time	50K	50K
LED driver board	Y	Y
Color Coordinates	x:0.313 ; Wy:0.329	x:0.313 ; Wy:0.329


Hard Protection Film Changed to Soft Protection Film

- Soft Protection Film could decrease particle effect and scratch rate.,

Current LCD protective film:





New LCD protective film



RA report

Product No	G240HW01 V1		Part No	97.24G01.104		Applicant/Dept		郑习习/RRPBF3		Judgement	
Test Purpose	G240HW01 V104 RA					Application Date		2023/08/15		PASS	
						Input Date		2023/08/16			
RA No	D230816001		Product Stage	DVT		Issue Date		2023/08/16			
Test Item	Test Condition	Test Panel			Test Result						
THB	50°C 80% 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500	Judgement	
		D2308160010001		U13A6EX3TKZZS0104	OK	OK	OK	OK	OK	PASS	PASS
		D2308160010002		U13A6EX3TFZZS0104	OK	OK	OK	OK	OK	PASS	
		D2308160010003		U13A6EX32DZZS0104	OK	OK	OK	OK	OK	PASS	
THB	60°C 90% 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500	Judgement	
		D2308160010004		U13A6EX4Y GZZS0104	OK	OK	OK	OK	OK	PASS	PASS
		D2308160010005		U13A6EX61GZZS0104	OK	OK	OK	OK	OK	PASS	
		D2308160010006		U13A6EX3ZEZZS0104	OK	OK	OK	OK	OK	PASS	
HTO	70°C 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500	Judgement	
		D2308160010007		U13A6EX4Y JZZS0104	OK	OK	OK	OK	OK	PASS	PASS
		D2308160010008		U13A6EX4Y JZZS0104	OK	OK	OK	OK	OK	PASS	
		D2308160010009		U13A6EX3PCZZS0104	OK	OK	OK	OK	OK	PASS	
LTO	-20°C 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500	Judgement	
		D2308160010010		U13A6EX3TMZZS0104	OK	OK	OK	OK	OK	PASS	
		D2308160010011		U13A6EX32HZZS0104	OK	OK	OK	OK	OK	PASS	
		D2308160010012		U13A6EX32CZZS0104	OK	OK	OK	OK	OK	PASS	
TST	-20°C(30min) ~ 60°C(30min), 100 cycles judge, 200 cycles reference 200cycles	No	Chip_Id	Shipping_No	C0★	C100★	C200★			Judgement	
		D2308160010013		U13A6EX32AZZZS0104	OK	OK	OK			PASS	PASS
		D2308160010014		U13A6EX32BZZS0104	OK	OK	OK			PASS	
		D2308160010015		U13A6EX3HKZZS0104	OK	OK	OK			PASS	
HTS	80°C 300h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★		Judgement	
		D2308160010016		u13a6ex3nhzzzs0104	OK	OK	OK	OK		PASS	
		D2308160010017		u13a6ex3thzzzs0104	OK	OK	OK	OK		PASS	
		D2308160010018		u13a6ex2lezzzs0104	OK	OK	OK	OK		PASS	
LTS	-30°C 300h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★		Judgement	
		D2308160010019		u13a5jv0qbzzzs0104	OK	OK	OK	OK		PASS	
		D2308160010020		u13a6ex4ykzzzs0104	OK	OK	OK	OK		PASS	
		D2308160010021		u13a6ex3zfzzzs0104	OK	OK	OK	OK		PASS	

EMI/ESD Report



	Freq	Read Level	Over Level	Limit	Line Remark
	MHz	dBuV	dBuV/m	dB	dBuV/m
1	208.480	21.89	22.76	-7.24	30.00
2 PP	555.740	17.04	29.76	-7.24	37.00
3	764.290	13.72	28.95	-8.05	37.00

	Freq	Read Level	Over Level	Limit	Line Remark
	MHz	dBuV	dBuV/m	dB	dBuV/m
1 PP	195.870	15.71	22.84	-7.16	30.00
2	485.900	16.14	27.75	-9.25	37.00
3	764.290	14.19	29.25	-7.75	37.00
4	903.000	12.44	29.70	-7.30	37.00

File Name: 20230901-5D2390002-G240HW01 V1		Test Ambient: 26 °C / 49% RH	
Application Sec: RRCAC3	User: 黄泓儒	Ext: 86-503004	Sample Received: 2023/9/19
Model Name: G240HW01 V1	Quantity (pcs): 3	Panel S/N: U13A6EX34KZZ-ZS0104	(#1)
		U13A6EX32FZZ-ZS0104	(#2)
		U13A6EX34KZZ-ZS0104	(#3)
Examiner: 王源源	Ext: 504202	Date Tested: 2023/9/20	Date Completed: 2023/9/20
☒ AUO Fixed Point Position Rules ☐ AUO IC Nearly Point Position Rules ☐ Customer Rules			
Stage: TEST	Resolution: 1920 X 1080	Frame rate (Hz):	Color depth (bit):
XPCB Part No:	Layout No:	PCB Vendor:	N/A
YPCB Part No:	Layout No:	PCBA Vendor:	N/A
C/B Part No:	Layout No:	ASIC:	
Inverter Part No: NA	Inverter Vendor:	SOURCE IC:	
		GATE IC:	
Purposes: 其他, 新產品驗證			
Test Specification: Test Level Requirement: B			Results: PASS
Test Standard: AUO Fixed Point Position Rules (8 points, 25 times/point)			



Tap Into The Possibilities