



G190ETN01.001 LDO ECN

2024/11/05



ECN Notice



Purpose:

1. Because the GMT LDO G933T24 EOL, AUO Display Plus (ADP) will replace GMT LDO G933T24 with UTC LR180IG-33-AB3-C-R for this model.
2. AUO has G190ETN01.002, which has been mass-produced. The only difference between the design structure and G190ETN01.001 are the LDO & LB CNT color. It is recommended that customers directly EC to G190ETN01.002

Changes:


- LDO change from GMT LDO G933T24 to UTC LR180IG-33-AB3-C-R.
- BLU Connector change from Cvilux CII406MIHRN-NH(Black) to Cvilux CII406MIHRN-NH(White)

Change Items:


- LDO
- BLU Connector

Schedule

- a. G190ETN01.002 sample is available.
- b. G190ETN01.002 RA/Optical/ESD test results are all pass



GMT LDO G933T24



UTC LR180IG-33-AB3-C-R

Specs	G190ETN01.0	G190ETN01.0
Part No.	97.19G04.001	97.19G04.002
POL Surface Treatment (AG/HC...)	AG	AG
Outline Dimensions (mm)	396x324x11.2	396x324x11.2
Active Area (mm)	376.32x301.06	376.32x301.06
Resolution (dots)	1280x1024	1280x1024
Pixel Pitch (mm)	0.294x0.294	0.294x0.294
Mode	TN	TN
Contrast Ratio (typ.)	1000:1	1000:1
Brightness (typ.)	350 nits	350 nits
Response Time (ms)	5	5
Viewing Angle-CR>10 (L/R/U/D)	85/85/80/80	85/85/80/80
LED Life (hrs)	30K(typ)	30K(typ)
Support Color	6-bit + HL_FRC	6-bit + HL_FRC
Color Gamut	85% NTSC	85% NTSC
Typ. (Wx.y) or Color Temperature	(0.313, 0.329)	(0.313, 0.329)
Weight (g)	1800(typ)	1800(typ)
Power Supply Input Voltage-LCD (V)	5	5
Interface	LVDS	LVDS
Power Consumption (W)	13.9(typ)	13.9(typ)
Operation Temp	0~50°C	0~50°C
Storage Temp	-20~60°C	-20~60°C
Connector - BLU 廠商/型號	Cvilux CII406MIHRN-NH(Black)	Cvilux CII406MIHRN-NH(White)
Remark	LDO: G933T24	LDO: LR180IG-33-AB3-C-R

AUO Display+

Summary items and result for New LDO IC product evaluation

1. Optical measurement result : Pass
2. ESD Result : Pass
3. RA Test : Pass
4. Product spec no change

Evaluation result



Result : Pass

				RA Test Summary Report				<table border="1"> <tr> <td>保管単位 Storage</td> <td>RA</td> </tr> <tr> <td>保管年数 Retention Period</td> <td>監視期間内監視保存(標準) AC900-05-092 監視監視 期</td> </tr> </table>		保管単位 Storage	RA	保管年数 Retention Period	監視期間内監視保存(標準) AC900-05-092 監視監視 期
保管単位 Storage	RA												
保管年数 Retention Period	監視期間内監視保存(標準) AC900-05-092 監視監視 期												
Product No.	G1908TM01-B		Part No.	97-19304-002		Applicant Dept.	品質部/品質課		Judgement				
Test Purpose	2023 mar wk4 G1908TM01-002/97-19304-002/ORT Test				Appication Date	2023/03/24		PASS					
RA No.	Q230324007		Product Stage	MP		Input Date	2023/03/25						
Test Item	Test Condition	Test Panel		Test Panel		Test Result							
Cold-start	0°C 5	No	Chip Id	Shipping No	TO★	T145★		Judgement	Judgement				
		Q2303240070001		252B91U58AZZS0102	OK	OK		PASS					
		Q2303240070002		252B91U58AZZS0102	OK	OK		PASS	PASS				
		Q2303240070003		252B91J7UCZZS0102	OK	OK		PASS					
LTD	0°C 300h	No	Chip Id	Shipping No	TO★	T168★	T300	Judgement	Judgement				
		Q2303240070001		252B91U58AZZS0102	OK	OK	OK	PASS					
		Q2303240070002		252B91U58AZZS0102	OK	OK	OK	PASS	PASS				
		Q2303240070003		252B91J7UCZZS0102	OK	OK	OK	PASS					
THB	60°C 90% 300h	No	Chip Id	Shipping No	TO★	T168★	T300	Judgement	Judgement				
		Q2303240070004		252B91U3WAZZS0102	OK	OK	OK	PASS					
		Q2303240070005		252B91U58CZZS0102	OK	OK	OK	PASS	PASS				
		Q2303240070006		252B91U58HZZS0102	OK	OK	OK	PASS					
HTD	50°C 300h	No	Chip Id	Shipping No	TO★	T168★	T300	Judgement	Judgement				
		Q2303240070007		252B91U58AZZS0102	OK	OK	OK	PASS					
		Q2303240070008		252B91J7UJZZS0102	OK	OK	OK	PASS	PASS				
		Q2303240070009		252B91C8WZZS0102	OK	OK	OK	PASS					
TST	(-20~100.5h)-60°C (0.5h) 100cycles	No	Chip Id	Shipping No	CO★	C100★		Judgement	Judgement				
		Q2303240070010		252B91J7VFZZS0102	OK	OK		PASS					
		Q2303240070011		252B91U2BQZZS0102	OK	OK		PASS	PASS				
		Q2303240070012		252B91J7VCZZS0102	OK	OK		PASS					
Remark	* ★ 為 Judge Point 非 Judge Point 的 Defect Alarm 請參考以下 Defect Description												
Comment													

Note: Check Point T: meaning Hour, C: meaning Cycles

Approve By: 劉小松

Prepare By: 張嘉怡

Check By: 劉小松

Defect Status Description:

AUO Display+

Evaluation result

Originator	chongfeng				Model/PCS		G190ETN01.0/5pcs			Date	2023/3/27						
Test Condition	Lum.,CR,Chromaticity,Uniformity,Gary Scale,V-T,View Angle,RT																
Test System	Detector		Inverter			DC Voltage				Warm up time							
FPM-520-2	SR-UL1R		NA			12V				30 min							
【Test Reason】																	
2023 mar wk4 G190ETN01-002(97.19G04.002)ORT Test																	
【Judgement】																	
PASS																	
Test Items	unit	PSS			23.3°C		23.3°C		23.3°C		23.3°C		23.3°C		-4σ	mean	+4σ
					2023/3/26 20:22		2023/3/26 20:40		2023/3/26 21:08		2023/3/26 21:27		2023/3/26 21:47				
					2B91U3WAZZS01		2B91U5MHZZS01		2B91U5BCZZS01		2B91U5XAZZS01		2B91U7UJZZS01				
		min	typ	max													
Center Brightness	cd/m ²	280	350		686.2	699.7	692.3	686.3	728.0	628.922	698.5	768.078					
Darkness (L0)					1.02	0.69	0.95	0.76	0.83	0.303	0.85	1.397					
Contrast Ratio(CR)	---	600	1000		670.1	1020.3	730.9	900.9	875.8	280.126	839.6	1399.078					
Brightness(5P Ave.)	cd/m ²				635.3	650.9	643.7	631.9	658.5	600.246	644.1	687.866					
Chromaticity																	
	Wx	---	0.263	0.313	0.363	0.320	0.319	0.320	0.321	0.321	0.316	0.320	0.324				
	Wy	---	0.279	0.329	0.379	0.345	0.337	0.340	0.340	0.343	0.328	0.341	0.354				
	Rx	---	0.629	0.679	0.729	0.668	0.670	0.668	0.670	0.669	0.666	0.669	0.673				
	Ry	---	0.263	0.313	0.363	0.319	0.319	0.319	0.319	0.319	0.318	0.319	0.320				
	Gx	---	0.235	0.285	0.335	0.292	0.291	0.292	0.292	0.292	0.290	0.292	0.293				
	Gy	---	0.609	0.659	0.709	0.664	0.665	0.664	0.664	0.665	0.662	0.664	0.667				
	Bx	---	0.099	0.149	0.199	0.156	0.156	0.156	0.156	0.156	0.155	0.156	0.156				
	By	---	0.012	0.062	0.112	0.055	0.052	0.054	0.053	0.055	0.049	0.054	0.058				
	NTSC	---		85		87.3	88.2	87.4	87.9	87.7	86.269	87.686	89.103				
	CCT	---				6046	6165	6093	6049	6008	5832.377	6072.315	6312.254				

Evaluation result



ESD Test Report

☐ Record ☒ ESD check ☐ Customer check

File number 2023 mar wk4 G190ETN01-002(97.19604.002)ORT Test			
申請單位 :MQMCA4	姓名 :张进	分機 : 1298	送測日期 : 2023-03-25
Model Name: G190ETN01.0	送測數量 : 3	Panel S/N :RA00000001 RA00000002 RA00000003	
測試人員 :张进	分機 :1298	測試日期 :2023-03-30	完成日期 :2023-03-30
Test standard: ☒ AUO固定點位 ☐ AUO IC對應點位 ☐ Other:			
階段: ☐ (EVT) ☐ (DVT) ☒ (MVT/MP) ☐ TEST	1280X1024	Frame rate (Hz): 60Hz	Color depth (bit): 8Bit
Pixel clock (MHz): 53.98MHz			
XPCB料號: NA	Layout No: NA	PCB Vendor:	NA
YPCB料號: NA	Layout No: NA	PCBA Vendor:	NA
C/B料號: NA	Layout No: NA	ASIC:	NA
Inverter料號: NA	Inverter料號: NA	SOURCE IC:	NA
測試需求等級 : Class B	判定結果 : PASS	GATE IC:	NA
目的: 抗ESD能力測試			
Test Specification:			
Test standard:			
Acceptance Definition:			
Class A : Normal operation. No degradation. No failures.			
Class B : Some performance degradation allowed.			
Class C : Temporary performance degradation. Recovery by operator (Reset) is acceptable. No Hardware failures			
Operation Model:		Non-operation Model:	
Contact discharge	Class	Air discharge	Class
+/- 8 KV	B	+/- 15 KV	B
Contact discharge	Class	Air discharge	Class
+/- 8 KV	B	+/- 15 KV	B

AUO Display+



Tap Into The Possibilities

