

GI56HAN03.0

EC for Source IC

2024/7/3

Source IC EC



- **Cause:** The Source IC OTD 7116A of G156HAN03.0 will be EOL. In order to keep supply smoothly, we would like to change source IC from OTD 7116A to OTD 7116D.

- **Change item:**

Item	Before	After
Model Name	G156HAN03.0	G156HAN03.0
Model Number	97.15G38.000	97D15G38.001
Source IC	OTD 7116A (FocalTech)	OTD 7116D (FocalTech)

- **Spec:** The LCM spec will be kept the same as the table below:

Items	Unit	Specifications			
Screen Diagonal	[mm]	15.6"			
Active Area	[mm]	344.16 x 193.59			
Resolution		1920 x 3(RGB) x 1080			
Pixel Pitch	[mm]	0.17925 x 0.17925			
Pixel Arrangement		R.G.B. Vertical Stripe			
Display Mode		AHVA, Normally Black			
Nominal Input Voltage VDD	[Volt]	+3.3 (Typ.)			
LCD Power Consumption	[Watt]	0.8W (Max.)			
LED Power Consumption	[Watt]	4.0W (Max.)			
Weight	[Grams]	370 (Max)			
Physical Size Include bracket	[mm]		Min.	Typ.	Max.
		Length	350.36	350.66	350.96
		Width	215.65	216.15	216.65
		Thickness			3.2
Electrical Interface		2 Lane eDP1.2			
Surface Treatment		Anti-glare, 3H			
Support Color		16.2M colors			
Temperature Range					
Operating	[°C]	-0 to +50			
Storage (Non-Operating)	[°C]	-20 to +60			
RoHS Compliance		Yes, RoHS Compliance			

- **Implement data and method:** Cutting change from 2024/11/B

AUO Display+

Source IC EC – Optical Measurement Report



Optical Measurement Report													
Originator	yongde			Model/PCS		G156HAN03.0/5PCS			Date	2024/3/22			
Test Condition Lum.,CR,Chromaticity,Uniformity,Gary Scale,V-T,View Angle,RT,CrossTalk,Flicker													
Test System		Detector		Inverter		DC Voltage				Warm up time			
FPM-510		SR-UL2		NA		12V				30 min			
【Test Reason】													
G156HAN03.001 DVT1-1 RA													
【Judgement】													
PASS													
Test Items	unit	PSS				Y3BBLC23AZZS010Y3BBLC2THZZS010Y3BBLC23CZZS010Y3BBLC2QCZZS010Y3BBLC2UQZZS010				-4σ	mean	+4σ	
		min	typ	max									
Center Brightness	cd/m ²	255				314.9	313.8	294.7	325.9	323.1	265.5	314.5	363.4
Darkness (L0)						0.23	0.24	0.37	0.30	0.32	0.065	0.29	0.522
Contrast Ratio(CR)		700	800			1363.7	1293.1	800.4	1075.3	994.8	193.1	1105.4	2017.6
Brightness(5P Ave.)	cd/m ²					301.0	301.3	291.8	322.2	314.9	257.7	306.2	354.8
Chromaticity													
	Wx	---	0.283	0.313	0.343	0.313	0.319	0.318	0.317	0.313	0.305	0.315	0.327
	Wy	---	0.299	0.329	0.359	0.331	0.339	0.339	0.338	0.331	0.315	0.336	0.353
	Rx	---	0.534	0.574	0.604	0.585	0.588	0.587	0.585	0.586	0.581	0.586	0.591
	Ry	---	0.314	0.344	0.374	0.341	0.343	0.344	0.342	0.343	0.338	0.342	0.347



Image sticking Test Report

保存單位 Storage	RA
保存年限 Retention Period	依產品適用範圍保存(參照：AUQP-05-002 紀錄管制流程)

RA No	D240315021		Applicant/Dept		2024/3/22/RRPSEJ		Test temperature		25℃	
Product No	G156HAN03.0		Application Date		2024/03/13		Issue Date		2024/03/26	
Test Purpose	G156HAN03.001 DVT1-1 RA						Judgement		PASS	
No	D240315021002?		D2403150210023		D2403150210024		D2403150210025		D2403150210026	
Chip ID	-		-		-		-		-	
S / N	5Y3BBLC23AZZS0101		5Y3BBLC23CZZS0101		5Y3BBLC2THZZS0101		5Y3BBLC2UQZZS0101		5Y3BBLC2QCZZS0101	
IC DM_Before(V)	-		-		-		-		-	
IC DM_After(V)	-		-		-		-		-	
Cbv. pattern	50%Gray		50%Gray		50%Gray		50%Gray		50%Gray	
觀察時間	S	L	S	L	S	L	S	L	S	L
TO	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

AUO Display+

Source IC EC – RA Result



➤ RA test Result

ITEMS	Required Condition	Result
Temperature Humidity Bias	Ta= 40°C , 90%RH, 300hours	Pass
High Temperature Operation	Ta= 50°C, 300hours	Pass
Low Temperature Operation	Ta= 0°C, 300hours	Pass
High Temperature Storage	Ta= 60°C, 300hours	Pass
Low Temperature Storage	Ta= -20°C, 300hours	Pass
Thermal Shock Test	-20°C/30min, 60°C/30min, 100 cycles	Pass
Hot Start	50°C, 300hours	Pass
Cold Start	0°C, 300hours	Pass
ESD	Contact Discharge: $\pm 8\text{KV}$, 150pF(330 Ω) 1sec, 8 points, 25 times/ point. Air Discharge: $\pm 15\text{KV}$, 150pF(330 Ω) 1sec 8 points, 25 times/ point.	Class B Pass

splay+



NUO

Innovating Life