



G213UAN01.0 ECR

ADP

2024/05/07



Summary

➤ Plan schedule:



Item	EC item	Current	New	Background and Purpose
1	Color Resistance	T7G	C7G	The current material EOL. To keep supply smoothly, we would like to adopt new color resistance (T7G→C7G).

RA Test Result

7. Reliability Test Criteria

Items	Required Condition
Temperature Humidity Bias (THB)	Ta= 50°C, 80%RH, 300hours
High Temperature Operation (HTO)	Ta= 50°C, 300hours
Low Temperature Operation (LTO)	Ta= 0°C, 300hours
High Temperature Storage (HTS)	Ta= 60°C, 300hours
Low Temperature Storage (LTS)	Ta= -20°C, 300hours

Product No	G213UAN01.1		Part No	97.21G07.101		Applicant/Dept		许垂/RRPBF3		Judgement	
Test Purpose	G213UAN01.101 RA test report					Application Date		2024/04/08		PASS	
						Input Date		2024/04/12			
RA No	R240409001		Product Stage	MVT		Issue Date					
Test Item	Test Condition	Test Panel									
HTO	50°C 6500h	No	Chip_Id	Shipping_No		T0★	T100★	T200★	T300★	T500	
		R2404090010001		zt4h1lk3eezzzs0101		OK	OK	OK	OK	OK	
		R2404090010002		zt4h1lk3eczzzs0101		OK	OK	OK	OK	OK	
		R2404090010003		zt4h1gm0rezzzs0101		OK	OK	OK	OK	OK	
THB	50°C 80% 500h	No	Chip_Id	Shipping_No		T0★	T100★	T200★	T300★	T500	
		R2404090010004		zt4h1lk3fdzzzs0101		OK	OK	OK	OK	OK	
		R2404090010005		zt4h1lk3bczzzs0101		OK	OK	OK	OK	OK	
		R2404090010006		zt4h1lk3lezzzs0101		OK	OK	OK	OK	OK	
TST	-20°C(30min) ~ 60°C(30min), 100cycles judge, 200cycles reference 200cycles	No	Chip_Id	Shipping_No		C0★	C100★	C200			
		R2404090010013		Zt4H1LK3BbZzZS0101		OK	OK	OK			
		R2404090010014		Zt4H1LK3RCZZZS0101		OK	OK	OK			
		R2404090010015		ZT4H1LK3BDZZZS0101		OK	OK	OK			

Test Item	Test Condition	Test Panel			Test Result							
LTO	0°C 500h	No	Chip_Id	Shipping_No	T0★	T100★	T200★	T300★	T500	Judgement	PASS	
		D2311030050001		zt3h6m9hdzzzs0101	OK	OK	OK	OK	OK	PASS		
		D2311030050002		zt3h6m9dezzzs0101	OK	OK	OK	OK	OK	PASS		
		D2311030050003		zt3h6m8jezzzs0101	OK	OK	OK	OK	OK	PASS		


- For reliability test, G213UAN01.0 refer to G213UAN01.I. G213UAN01.I RA PASS.

Optical Test Result

Optical Measurement Report													
Originator	chongfeng		Model/PCS		G213UAN01.0/5pcs				Date	2024/4/10			
Test Condition	Lum.,CR,Chromaticity,Uniformity,Gary Scale,V-T,View Angle,RT,CrossTalk												
Test System	Detector	Inverter			DC Voltage					Warm up time			
FPM-520-1	SR-UL1R	NA			24V					30 min			
【 Test Reason 】													
G213UAN01.001 RA test report C7G													
【 Judgement 】													
PASS													
Test Items	unit	PSS			23.6℃	23.6℃	23.6℃	23.6℃	23.6℃	-4σ	mean	+4σ	
					24/4/9 下午 03:54	24/4/9 下午 04:23	24/4/9 下午 04:55	24/4/9 下午 05:39	24/4/9 下午 06:08				
					4H1LK3DCZZZ80	4H1GM0NFZZZ80	4H1GM0NDZZZ80	4H1GM0RBZZZ80	4H1LK3UEZZZ80				
		G0700443GBF4P01	G0700443GBF4P01	G0700443GBF4P01	G0700443GBF4P01	G0700443GBF4P01							
Center Brightness	cd/m²	min	typ	max	660.7	670.1	652.5	660.0	664.7	635.674	661.6	687.526	
Darkness (L0)					0.44	0.37	0.44	0.41	0.44	0.305	0.42	0.534	
Contrast Ratio(CR)	---	1260	1800		1514.67	1796.51	1477.58	1608.58	1525.24	1073.25	1584.52	2095.787	
Brightness(5P Ave.)	cd/m²				635.6	638.3	633.3	643.2	635.4	621.872	637.2	652.448	
Chromaticity													
	Wx	---	0.269	0.299	0.329	0.306	0.304	0.303	0.303	0.304	0.299	0.304	0.309
	Wy	---	0.285	0.315	0.345	0.327	0.321	0.320	0.321	0.321	0.310	0.322	0.333
	Rx	---	0.626	0.656	0.686	0.656	0.653	0.655	0.656	0.653	0.650	0.655	0.660
	Ry	---	0.300	0.330	0.360	0.331	0.331	0.331	0.331	0.331	0.330	0.331	0.331
	Gx	---	0.285	0.315	0.345	0.314	0.315	0.313	0.314	0.315	0.311	0.314	0.317
	Gy	---	0.610	0.640	0.670	0.642	0.642	0.643	0.642	0.641	0.639	0.642	0.645
	Bx	---	0.120	0.150	0.180	0.151	0.152	0.152	0.152	0.152	0.151	0.151	0.152
	By	---	0.029	0.059	0.089	0.060	0.057	0.058	0.059	0.058	0.054	0.058	0.062
	SRGB	%		100		99.1%	98.7%	99.1%	98.9%	98.5%	0.979	0.989	0.999
	CCT	---				6926	7106	7202	7163	7113	6679.197	7101.920	7524.642

- For the validation of G213UAN01.0 with EC Color Resistance: Optical Result PASS.

IS result for G213UAN01.0: PASS



Display pattern

SN (至少2位)	殘影 類型	1min-30sec.					1.5hour-10min				
		L255	L127	L64	L32	L0	L255	L127	L64	L32	L0
ZT4H1LK3DCZZS0101	S	无	无	无	无	无	无	无	无	无	无
	L	无	无	无	无	无	无	无	无	无	无
ZT4H1GM0RBZZS0101	S	无	无	无	无	无	无	无	无	无	无
	L	无	无	无	无	无	无	无	无	无	无
ZT4H1GM0NDZZS0101	S	无	无	无	无	无	无	无	无	无	无
	L	无	无	无	无	无	无	无	无	无	无
ZT4H1GM0NFZZS0101	S	无	无	无	无	无	无	无	无	无	无
	L	无	无	无	无	无	无	无	无	无	无
ZT4H1LK3UEZZS0101	S	无	无	无	无	无	无	无	无	无	无
	L	无	无	无	无	无	无	无	无	无	无

Test Results:	PASS
Model Type:	G213UAN01.0
Issue date	2024/04/13
Remark	NA

SN (至少2位)	固定patternL127,8hrs 立即判				
	殘影 類型	L128	L64	L32	L0
ZT2H9AF0CCZZS0101	S	无	无	无	无
	L	无	无	无	无
ZT2H9AF2FEZZS0101	S	无	无	无	无
	L	无	无	无	无
ZT2H9B31BEZZS0101	S	无	无	无	无
	L	无	无	无	无
ZT2H9AG4KBZZS0101	S	无	无	无	无
	L	无	无	无	无
ZT2H9AG3HDZZS0101	S	无	无	无	无
	L	无	无	无	无

Test Results:	PASS
Model Type:	G213UAN01.0
Issue date	2023/05/15
Remark	NA

Remark : G213UAN01.0 IS showed the **PASS** result both in short time and long time.



Tap Into The Possibilities

