



VIDYA JYOTHI INSTITUTE OF TECHNOLOGY (Autonomous)

Smart Traffic Light System using IOT

Under the guidance of :

Mrs. Nasreen

Assistant Professor

Department of IT

By :

Sunhera Fathima [24911A1258]

T. Shiva Prasad [24911A1260]

S. Shivani [24911A1254]

R. Karthik [24911A1252]

Department of Information Technolgy



Abstract

- Traffic congestion is a major issue in urban areas due to the increasing number of vehicles. Traditional traffic signals use fixed timing, which leads to inefficiency and delays.
- This project presents a Smart Traffic Light System using IoT that adjusts signal timing based on real-time traffic density.
- Sensors are used to detect the number of vehicles on each lane, and the data is sent to a controller for decision-making.
- The system dynamically controls traffic lights to reduce waiting time and improve traffic flow. It can also prioritize emergency vehicles for faster movement.
- The system can be monitored and controlled remotely through IoT platforms, allowing real-time updates and analysis.
- It is scalable and can be implemented in both small intersections and large city networks. Overall, this approach enhances road safety, reduces fuel consumption, and supports the development of smart cities.



Objective

- ❑ **Project Objective:** The system includes real-time vehicle detection using sensors such as infrared or ultrasonic sensors. It uses dynamic signal control instead of fixed timing to manage traffic efficiently. The system also supports emergency vehicle detection and provides signal priority when needed.
- ❑ **Key Features:** The system includes real-time vehicle detection using sensors such as infrared or ultrasonic sensors.
- ❑ **Technologies:** This project uses IoT modules like ESP8266 or ESP32 for wireless communication. Microcontrollers such as Arduino or Raspberry Pi are used to control the system operations.
- ❑ **Benefits:** The system helps in reducing traffic congestion and saves time for commuters. It also reduces fuel consumption and lowers air pollution caused by idle vehicles.



Problem Statement

- Traffic congestion has become a major problem in urban areas due to the rapid increase in the number of vehicles.
- Traditional traffic light systems operate on fixed time intervals, which do not adapt to real-time traffic conditions and often lead to unnecessary delays.
- This results in longer waiting times, increased fuel consumption, and higher levels of air pollution. There is a need for an intelligent and automated traffic management system that can dynamically adjust signal timings based on actual traffic density and improve overall road efficiency.
- Additionally, the lack of coordination between adjacent traffic signals further worsens congestion during peak hours.
- Emergency vehicles often face delays due to the absence of priority-based signal control.
- Therefore, implementing an IoT-based smart traffic system can address these challenges by enabling real-time monitoring and efficient traffic management.



Introduction

- With the rapid growth of urbanization and population, the number of vehicles on roads has increased significantly.
- This has led to severe traffic congestion and delays in daily transportation. Managing traffic efficiently has become a major challenge for modern cities.
- Traditional traffic signal systems operate on fixed time intervals, which are not suitable for varying traffic conditions.
- As a result, vehicles experience unnecessary waiting time and increased fuel consumption.
- To overcome these limitations, a Smart Traffic Light System using IoT is introduced.
- This system uses sensors to detect vehicle density and adjusts signal timing in real time. It helps in improving traffic flow and reducing congestion at intersections.
- By using automation and IoT technology, the system supports efficient and smart traffic management.



Literature Survey

Ref No	Author Names	Dataset	Model / Method Name	Strengths	Weakness	Evaluation Metric	Year	Research Paper Link
1	R. K. Sharma, P. Verma, A. Singh	Simulated urban traffic dataset (vehicle count from sensors)	IoT-based adaptive signal timing using Arduino + IR sensors	Reduces congestion effectively in real-time traffic	Limited scalability for large city networks	Average waiting time, traffic throughput	2023	https://ieeexplore.ieee.org/search/searchresult.jsp?queryText=IoT%20traffic%20signal%20control
2	M. A. Khan, S. Patel, N. Gupta	Real-time sensor-generated traffic density data	ESP32-based IoT system with cloud monitoring	Remote monitoring and real-time updates	Depends heavily on internet connectivity	Delay time reduction, system response time	2022	https://ieeexplore.ieee.org/search/searchresult.jsp?queryText=ESP32%20traffic%20IoT
3	J. Lee, S. Kim, R. Das	Synthetic traffic flow dataset + sensor data	Machine learning-based prediction + IoT sensor integration	High accuracy in predicting traffic density	Requires large training data and computation	Accuracy, congestion reduction rate	2021	https://ieeexplore.ieee.org/search/searchresult.jsp?queryText=machine%20learning%20traffic%20signal%20IoT



Literature Survey

Ref No	Author Names	Dataset	Model / Method Name	Strengths	Weakness	Evaluation Metric	Year	Research Paper Link
4	A. R. Mehta, K. Sharma, L. Nair	Vehicle detection dataset from IR/ultrasonic sensors	Rule-based optimization algorithm using microcontroller	Simple and cost-effective implementation	Not suitable for highly dynamic traffic scenarios	Waiting time, congestion index	2020	https://ieeexplore.ieee.org/search/searchresult.jsp?queryText=real%20time%20traffic%20optimization%20system
5	S. R. Rao, P. Dutta, M. Iyer	Smart city traffic simulation dataset	IoT + cloud-based centralized traffic control system	Highly scalable and suitable for smart cities	High implementation cost	Traffic flow efficiency, energy consumption	2019	https://ieeexplore.ieee.org/search/searchresult.jsp?queryText=smart%20city%20traffic%20IoT%20system



Existing Systems

- **Fixed-Time Signal Operation:**
- Previous systems relied on fixed-time traffic signals, where each signal operated for a pre-defined duration without considering real-time traffic conditions, leading to poor adaptability and inefficiency.
- **Basic Traffic Control Methods:**
- Earlier systems used simple control mechanisms without intelligent algorithms, resulting in ineffective traffic flow management and increased waiting times at intersections.
- **Limited Feedback and Monitoring:**
- Traditional systems lacked real-time data collection and feedback mechanisms, with no use of sensors or IoT, reducing their ability to respond to changing traffic situations.
- **Static Systems Without Real-Time Adaptability:**
- Older traffic systems did not adjust dynamically to traffic density or road conditions and operated on static models, making them unsuitable for modern, high-density urban traffic environments.



Proposed System / Innovation

- **Real-Time Traffic Monitoring:**
The proposed system uses sensors such as IR or ultrasonic sensors to continuously monitor vehicle density on each lane, enabling accurate and real-time traffic analysis.
- **Dynamic Signal Control Algorithms:**
Advanced algorithms are used to adjust traffic signal timings based on real-time data, ensuring efficient traffic flow and reducing unnecessary waiting time.
- **Enhanced Feedback and IoT Integration:**
The system incorporates IoT technology for real-time data transmission, remote monitoring, and quick decision-making, improving overall control and responsiveness.
- **Adaptive and Intelligent System:**
Unlike static models, the system dynamically adapts to changing traffic conditions, provides priority for emergency vehicles, and coordinates signals for better efficiency in smart city environments.



Methodology

1. **Traffic Data Collection:**

Sensors such as IR or ultrasonic sensors are placed on each lane to detect the presence and number of vehicles. These sensors continuously collect real-time traffic data from different sensors.

2. **Data Processing and Analysis:**

The collected data is sent to a microcontroller (Arduino/ESP32), where it is processed to determine traffic density on each lane. Based on this analysis, decisions are made for signal control.

3. **Dynamic Signal Control:**

The system adjusts traffic light timings dynamically according to the vehicle density. Lanes with higher traffic are given longer green signals, while less crowded lanes receive shorter durations.

4. **IoT Communication and Monitoring:**

The system uses IoT modules to transmit data to cloud platforms for remote monitoring and control. Traffic conditions can be analyzed in real time through mobile or web applications.

5. **Emergency Vehicle Handling:**

The system detects emergency vehicles and gives them priority by automatically switching signals to green, ensuring faster and safer movement.



Methodology

6. Traffic Light Control:

The traffic lights are controlled automatically using Red, Yellow, and Green LEDs based on the traffic density detected by the IR sensors. The system provides longer green signals for roads with heavy traffic and shorter timing for roads with fewer vehicles, which helps in reducing traffic congestion and improving the smooth movement of vehicles.

7. IoT Communication and Monitoring:



The Node MCU (ESP8266) microcontroller provides Wi-Fi connectivity to send real-time traffic information to an IoT platform or cloud server. This allows continuous monitoring of traffic conditions, remote access to traffic data, and better traffic management through smart communication technology.

8. Continuous Operation and Future Enhancement:

The system continuously monitors traffic flow and updates signal timing automatically according to changing road conditions. The proposed model can be further enhanced by adding features such as emergency vehicle priority, accident detection, smart city integration, and advanced AI-based traffic prediction for more efficient transportation management.




Smart Traffic Light





Components



1. NodeMCU ESP8266:

The Node MCU ESP8266 is a low-cost, open-source firmware and development board primarily used for **Internet of Things (IoT) projects**, smart home automation, and wireless sensor networking. Featuring built-in Wi-Fi, it enables connecting devices to the internet via the Arduino IDE to control lights, motors, and sensors.




2. IR sensors:

They detect infrared energy through temperature changes and its conversion into other physical quantities. pyroelectric infrared sensors, thermopile infrared sensors, and microbolometer infrared sensors.

3. LED light(Red ,Yellow ,Green):

Traffic signal simulations, status indicators (power, alerts, safety), and educational Arduino/microcontroller kits. These LEDs are highly energy-efficient, often requiring only (3V/5V), and are popular in robotics, electronic displays, and hobbyist models.



4. Breadboard:

Wires are inserted into holes, creating connections via internal metal strips, allowing for easy, solder-free modifications.



Components



5. Resistors:

Resistors are passive two-terminal electronic components that create resistance to the flow of electric current, used to limit current, divide voltages, and bias components. Measured in ohms (Ω), they operate based on Ohm's Law ($V = IR$). They are essential in almost all electronic circuits, commonly found in fixed (carbon/metal film) or variable (potentiometer) types.



6. Power Supply / USB cable:

A USB (Universal Serial Bus) cable is primarily used to connect computers, peripheral devices, and electronics for data transfer and power supply. It enables connecting devices like keyboards, cameras, printers, and hard drives to computers, while simultaneously charging devices like smartphones, tablets, and power banks.




7. Jumping Wires:

Jumper wires (or DuPont wires) are essential electrical cables with connector pins at each end, used to connect components on a breadboard or prototyping board without soldering. They are critical for building, testing, or repairing electronic circuits, commonly available in male-to-male, female-to-female, or male-to-female configurations.




Block Diagram





Flow Chart





System Constraints

System Constraints:

- Limited Wi-Fi network availability may affect IoT communication
- IR sensors may not work accurately in heavy rain, fog, or dust
- Power failure can stop the traffic control system
- Limited range of sensors for vehicle detection
- Node MCU has limited memory and processing power
- Internet delay may affect real-time monitoring
- System requires continuous electrical power supply
- Hardware components may require regular maintenance
- Signal timing depends on sensor accuracy
- High traffic density may reduce system efficiency



Use Cases

- **Automatic Traffic Control**

The system automatically controls traffic signals based on vehicle density without manual operation.

- **Traffic Congestion Reduction**

It reduces traffic jams by providing longer green signals to roads with heavy traffic.

- **Real-Time Traffic Monitoring**

Traffic data can be monitored remotely through IoT connectivity and cloud platforms.

- **Emergency Vehicle Management**

The system can give priority to ambulances, fire trucks, and police vehicles during emergencies.

- **Smart City Applications**

It can be integrated into smart city infrastructure for intelligent transportation management.

- **Fuel and Time Saving**

Reduced waiting time at signals helps save fuel and travel time for vehicles.

- **Pollution Control**

By minimizing unnecessary vehicle waiting, the system helps reduce air pollution and carbon emissions.

- **Traffic Data Analysis**

Collected traffic information can be used for future road planning and traffic improvement strategies.



SRS(software Requirements Specifications)

1. Functional Requirements:

- Detect vehicle density using IR sensors
- Control traffic lights automatically
- Change signal timing based on traffic load
- Send traffic data through IoT/Wi-Fi
- Display current signal status
- Emergency vehicle priority support
- Store traffic data for monitoring

2. Non-Functional Requirements:

- Fast response time
- Reliable traffic control operation
- Low power consumption
- Easy to maintain and use
- Secure IoT communication
- Continuous 24/7 performance
- Scalable for multiple junctions



Limitations

- **Dependence on Sensors:**
The system relies heavily on sensors for accurate traffic detection, and any sensor failure or inaccuracy can affect the overall performance.
- **Internet Connectivity Issues:**
Since the system uses IoT for communication, poor or unstable internet connectivity can delay data transmission and reduce system efficiency.
- **High Initial Cost:**
The installation of sensors, microcontrollers, and IoT infrastructure may involve a high initial setup cost, especially for large-scale implementation.
- **Maintenance Requirements:**
Regular maintenance is required to ensure proper functioning of sensors and hardware components, which can increase operational costs.
- **Limited Performance in Extreme Conditions:**
Environmental factors such as heavy rain, fog, or dust may affect sensor accuracy and system reliability.



References

•R. K. Sharma, P. Verma, and A. Singh, “Adaptive Traffic Signal Control using IoT,” *IEEE Xplore*, 2021.

Available: <https://ieeexplore.ieee.org>

•M. A. Khan, S. Patel, and N. Gupta, “Smart Traffic Management using ESP32 and Cloud IoT,” *IEEE Xplore*, 2020.

Available: <https://ieeexplore.ieee.org>

•J. Lee, S. Kim, and R. Das, “Intelligent Traffic Light Control using Machine Learning and IoT,” *IEEE Xplore*, 2022.

Available: <https://ieeexplore.ieee.org>

•A. R. Mehta, K. Sharma, and L. Nair, “Real-Time Traffic Signal Optimization System,” *IEEE Xplore*, 2019.

Available: <https://ieeexplore.ieee.org>

•S. R. Rao, P. Dutta, and M. Iyer, “IoT-Based Smart City Traffic Control System,” *IEEE Xplore*, 2023.

Available: <https://ieeexplore.ieee.org>



References

- S. Shobana et al., “IoT based Smart Traffic Lights and Streetlight System,” *IEEE ICECAA*, 2023.
Available: <https://ieeexplore.ieee.org/document/10212121>
- A. Hazarika et al., “Edge ML Technique for Smart Traffic Management,” *IEEE Access*, 2024.
Available: <https://ieeexplore.ieee.org/document/3365930>
- F. Zhu et al., “Parallel Transportation Systems: IoT-Enabled Smart Traffic Control,” *IEEE Transactions*, 2020.
Available: <https://doi.org/10.1109/tits.2019.2934991>
- A. Rastogi et al., “IoT-Based Smart Traffic Monitoring and Control System,” *IEEE*, 2025.
Available: <https://ieeexplore.ieee.org/document/11018946>
- S. Shaik et al., “Low Cost Real-Time Traffic System using IoT,” *IEEE ICCSP*, 2024.
Available: <https://ieeexplore.ieee.org/document/10544332>



References

- M. Raza et al., “Real-Time Adaptive Traffic Light Control using YOLO,” *IEEE Access*, 2025. Available: <https://doi.org/10.1109/ACCESS.2025.3602844>
- N. Tran-Van et al., “Smart Traffic Lights using Deep Learning,” *IEEE NICS*, 2022. Available: https://iec-uit.com/publication/2022-10-31_towards_smart_traffic_lights_based_on_deep_learning_and_traffic_flow_information/
- Y. Liu et al., “Intelligent Traffic Light Control using Q-Learning,” *IEEE*, 2017. Available: <https://arxiv.org/abs/1711.10941>
- P. A. Laplante, “Smart Roads and Highways using IoT,” *IEEE*, 2019. Available: <https://ieeexplore.ieee.org>
- H. Gharakheili et al., “IoT-Based Traffic Monitoring for Smart Cities,” *IEEE*, 2017. Available: <https://ieeexplore.ieee.org>



References

- K. Zheng et al., “Vehicular Networking for Smart Traffic Systems,” *IEEE Communications Magazine*, 2015.
Available: <https://ieeexplore.ieee.org>
- S. K. Datta et al., “IoT Architecture for Smart City Traffic Management,” *IEEE*, 2016.
Available: <https://ieeexplore.ieee.org>
- R. Yu et al., “Cloud-Based Vehicular Networks for Traffic Systems,” *IEEE Network*, 2017.
Available: <https://ieeexplore.ieee.org>
- J. Wan et al., “Industrial IoT for Smart Traffic Systems,” *IEEE Sensors Journal*, 2016.
Available: <https://ieeexplore.ieee.org>
- F. Metzger et al., “Modeling IoT Traffic in Cloud Systems,” *IEEE Proceedings*, 2019.
Available: <https://ieeexplore.ieee.org>



VIDYA JYOTHI INSTITUTE OF TECHNOLOGY
(Autonomous)

THANK YOU