## Assignment-3 (operators) (each question carries 5 marks).

```
1. What is binary equivalent of
i)char ch='5'; ii) short int s = -520; iii) int i = -2; iv) float f = 45.6; v)double d = -45.6;
2. What is the range of char, short int, int, long int, float.
3. main() {
unsigned char a:
a = 0xFF + 1;
printf("%u\n", a);
4. main() { int x=10, y=20, z=5, i;
                i = x < y < z;
                printf("%d\n", i);}
      main(){ unsigned int x=022,y=0x22, z=022; printf("%d",x+y+z); }
5.
6. main() { int a = 123, b = 456;
                a \land = b \land = a \land = b;
                printf(" %d %d", a,b); }
7. List 6 number of unary operators.
8. main() {
                        int a=10,b;
                        b=a>=5?100:200;
                        printf("%d",b);
                                                          }
9. main(){
printf("%d\n", -1<<4);
printf(" %d\n", -1 >>2);
printf("%x\n", 1<<10);
printf("%x\n", 0xFF<<4);
printf("%o\n", 034<<2); }
10. main()
                printf("%d\n", 1<<4>>4);
        {
                printf("%d\n", 1<<31>>30); }
11. main() { double f = 33.3; int x;
                x = (f > 33.3) + (f = 33.3); printf("%d",x);}
12. main() { unsigned int res;
                res = (64 >> (2+1-2)) & (\sim (1 << 2));
                printf("%d", res); }
13. main() {
                int z,x=5,y=-10,a=4,b=2;
                z=x++ - --y * --b / a;
                printf("%d\n",z);  }
14. main(){
                printf("%lu\n",sizeof('\n'));
                printf("%lu\n",sizeof("5"));
                printf("%lu\n",sizeof(5.0));
                printf("%lu\n",sizeof(23.4f));
                printf("%lu\n",sizeof("23.4f")); }
                printf("%d\n",(0x11>11) && (11>011));
15. main() {
                printf("%d\n", sizeof(-1) > 10); printf("%d\n", 23.0>23); }
```

```
16. main() {
               int a=-1,b=0, c=5;
               char ch='a';
               printf("%d\n", (ch>=97)&&(ch<=122));
               printf("%d\n",(a==0) || (b==0) ||(c==0));
               printf("%d\n", (a\leqb)&&(b\leqc));
}
17. main(){
                       printf("%d\n",-1&3456);
                       printf("%d\n", -1| 456);
                       printf("%d\n", -1 \(^{789}\);
                       printf("%d\n", 0&789);
                       printf("%d\n",0&234);
               }
18. main(){ int bitMask=1;
               printf("%d\n", 50 & bitMask);
               bitMask=32;printf("%d\n",50 & bitMask);
                       printf("%d\n",60 & bitMask);
                       printf("%d\n",70 & bitMask);
                       bitMask=512;
                       printf("%d\n",525&bitMask); }
19.
main(){
               int var=50,bit=3;
               printf("%d\n",var&(1<<3));
               printf("%d\n",var&(1<<4));
               printf("%d\n",var&(1<<5));
       }
20. main(){ int a=2,b=4,c=5;
a+=b*=c-=10;
printf("%d %d %d\n",a,b,c);
```