Status	Finished
Started	Thursday, 29 October 2026, 4:31 PM
Completed	Thursday, 29 October 2026, 4:40 PM
Duration	8 mins 35 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. An error is raised

b. Hello

c. Hello, world! ✓

d. world

The correct answer is: Hello, world!

Question **2**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. The operation is ignored

b. An error is raised ✓

c. A new file is created

d. An empty file object is returned

The correct answer is: An error is raised

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for writing in binary format?

a. r+
b. rb
c. w
d. wb ✓

The correct answer is: wb

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

a. read()
b. insert()
c. write() ✓
d. append()

The correct answer is: write()

Question **5**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

a. Binary file
b. Both text and binary file ✓
c. Text file
d. none of the given choices

The correct answer is: Both text and binary file

Question **6**

Correct

Mark 1.00 out of 1.00

What is the purpose of the with statement in Python file handling?

- a. To automatically close the file after its suite finishes ✓
- b. To read data from a file
- c. To write data to a file
- d. To delete a file

The correct answer is: To automatically close the file after its suite finishes

Question **7**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

- a. writelines() ✓
- b. write()
- c. write_list()
- d. write_all()

The correct answer is: writelines()

Question **8**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

- a. truncate() ✓
- b. resize()
- c. shrink()
- d. reduce()

The correct answer is: truncate()

Question **9**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

a. file.closed()
b. file.isclosed()
c. file.is_closed()
d. file.closed ✓

The correct answer is: file.closed

Question **10**

Incorrect

Mark 0.00 out of 1.00

Which method is used to sets the position of a file pointer

a. fseek() ✗
b. ftell()
c. seek()
d. tell()

The correct answer is: seek()

Question **11**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

a. openfile()
b. open_file()
c. open() ✓
d. file()

The correct answer is: open()

Question **12**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use _____

a. outfile = open("c:\scores.txt", "w")

b. outfile = open(file = "c:\scores.txt", "w")

c. outfile = open(file = "c:\\scores.txt", "w")

d. outfile = open("c:\\scores.txt", "w") ✓

The correct answer is:
outfile = open("c:\\scores.txt", "w")

Question **13**

Correct

Mark 1.00 out of 1.00

What is the difference between r+ and w+ modes in file handling?

a. r+ is for read and write, w+ is for append only

b. r+ is for read and append, w+ is for read and write

c. r+ is for read and write without truncating, w+ is for read and write with truncating ✓

d. r+ is for binary read and write, w+ is for text read and write

The correct answer is: r+ is for read and write without truncating, w+ is for read and write with truncating

Question **14**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

True ✓

False

The correct answer is 'True'.

Question **15**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. • Move file pointer five characters ahead from the current position. ✓

b. • Move file pointer five characters behind from the current position.

c. • Move file pointer five characters behind ahead from the end of a file.

d. Move file pointer five characters ahead from the beginning

The correct answer is:

- Move file pointer five characters ahead from the current position.