

STOCKTON STREET
MERIT K.S. REG. S.P.
710 (PC)

Effective Date: July 31, 1980

CIGARETTE DESCRIPTIVE FOR MERIT K.S. REGULAR S.P.

Length - 84.4mm

Circumference - 25.0mm

Filter - 25.0mm

COPY

Cigarette Rod:

Filler - High Burley - Basic Merit Formula

Cuts - 30/Inch

Paper - Schwelzer 110-6/DeMauduit Ref. 110-6/Ecusta 12753; 27.5mm x 6500m;
P.M. Material Code 10-123-A

or DeMauduit Ref. 110-6; 27.5mm x 7000m; P.M. Material Code 10-145-A

Print Die - None

Ink - None

Circumference - 25.0mm

Length - 59.4mm

Cigarette:

Tipping - 64mm x 2700m DGL Merit Laser; P.M. Material Code 12-508-A USE UP AND
REPLACE WITH 64mm x 3200m DGL Merit Laser (GSR-156); P.M. Material
Code 12-702-B

Tipping Adhesive - Ajax 563-6; P.M. Material Code 61-001-A
Ajax 563-8; P.M. Material Code 61-002-A

Rod Moisture - 13.10%

Total R.T.D. - 5.40 inches of water (Diluted)

Plug R.T.D. - 4.50 - 4.70 inches of water (Undiluted)

-OR Q.A. APPROVED
EQUAL

Dilution Target - $28\% \pm 5\%$

Prepared By: Glenn E. Barnett

Approved By: *J. J. M. Grace*
Operations Services

/dyd

2031315222

This supersedes specification dated July 18, 1980. Reason for change:
Dilution target changed from $30\% \pm 5\%$ to $28\% \pm 5\%$.