

SAR OSC Test — Field Report

Date: 2026-07-29 Status:  Pass

Summary

Ethernet link and OSC comms between Mac (Python) and Windows (TouchDesigner) confirmed working end to end.

Results

- **Ping:** bidirectional, 0% packet loss, ~2-4ms

```
C:\Users\ubiqu>ping 192.168.50.10

Pinging 192.168.50.10 with 32 bytes of data:
Reply from 192.168.50.10: bytes=32 time=4ms TTL=64
Reply from 192.168.50.10: bytes=32 time=2ms TTL=64
Reply from 192.168.50.10: bytes=32 time=2ms TTL=64
Reply from 192.168.50.10: bytes=32 time=2ms TTL=64

Ping statistics for 192.168.50.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 4ms, Average = 2ms

C:\Users\ubiqu>|
```

- **OSC receive:** /hello 1 received correctly in oscin1

The screenshot shows the TouchDesigner interface. On the left, a small window titled '0' contains the text '0 message' and '1 /hello 1'. Below it, a larger window titled 'oscin1' contains a Python script for handling OSC messages. On the right, a settings panel for 'Messaging (UDP)' is visible, showing 'Network Address' as 'localhost' and 'Port' as '9000'. The 'Shared Connection' is set to 'On'. The 'OSC Address Scope' is set to '*'. Other options like 'Include Type Tag', 'Split Bundle into Messages', 'Split Message into Columns', and 'Bundle Timestamp Column' are all set to 'Off'. At the bottom, a timeline shows a 'Timecode' of '00:00:03:47' and a 'Beats' value of '228'. The 'Range Limit' is set to 'Loop'.

```

1 """
2 OSC In DAT Callbacks
3
4 me - this DAT
5
6 peer - a Peer object describing the originating message
7 peer.close() #close the connection
8 peer.owner #the operator to whom the peer belongs
9 peer.address #network address associated with the peer
10 peer.port #network port associated with the peer
11 """
12
13 from typing import List, Any
14
15 def onReceiveOSC(dat: oscinDAT, rowIndex: int, message: str,
16                 byteData: bytes, timeStamp: float, address: str,
17                 args: List[Any], peer: Peer):
18     """
19     Called when an OSC message is received.
20
21     Args:
22         dat: The DAT that received a message
23         rowIndex: The row number the message was placed into
24         message: ASCII representation of the data
  
```

End: 600
REnd: 600
Tempo: 120.0
T Sig: 4 4

Timecode: 00:00:03:47
Beats: 228
Range Limit: Loop Once

- **Burst test:** 500-message send (`/test/index`) received in TouchDesigner with no dropped or out-of-order messages

The screenshot shows the TouchDesigner interface during a burst test. The 'oscin1' window displays a list of 10 messages, all starting with '/test/index' followed by an index value from 490 to 499. The settings panel on the right shows 'Include Type Tag' set to 'Off', and other options like 'Split Bundle into Messages', 'Split Message into Columns', and 'Bundle Timestamp Column' are also set to 'Off'. The timeline at the bottom shows a 'Timecode' of '00:00:03:47' and a 'Beats' value of '228'. The 'Range Limit' is set to 'Loop'.

```

0 message
1 /test/index 490
2 /test/index 491
3 /test/index 492
4 /test/index 493
5 /test/index 494
6 /test/index 495
7 /test/index 496
8 /test/index 497
9 /test/index 498
10 /test/index 499
  
```

Include Type Tag: Off
Split Bundle into Messages: Off
Split Message into Columns: Off
Bundle Timestamp Column: Off

Timecode: 00:00:03:47
Beats: 228
Range Limit: Loop Once

- **Firewall:** UDP 9000 inbound rule resolved the initial block
- **Internet over Wi-Fi:** retained throughout on both machines

Bonus

Also confirmed working in a separate TouchDesigner OSC patch (switch/select routing into kantanMapper → window output).



Outcome

Exit gate criteria met. Cleared to move on to SAR pipeline integration planning.