
Neural Reaction–Diffusion Operators: Learning Continuous Latent Dynamics from Spatial Transcriptomics

Anonymous Author(s)

Affiliation

Address

email

Abstract

Machine learning for spatial transcriptomics almost universally models a tissue section as a graph over the measured spots, tying the learned function to one sampling lattice and leaving expression undefined between nodes. Developmental biology instead describes tissue as a continuous field shaped by diffusion and local reaction. We introduce **Neural Reaction–Diffusion Operators** (NRDO), which encode irregularly sampled expression into a continuous latent field, evolve it under a learned anisotropic reaction–diffusion PDE $\partial_t \mathbf{z} = \nabla \cdot (\mathbf{D}_\theta \nabla \mathbf{z}) + f_\theta(\mathbf{z})$, and decode at arbitrary coordinates. Solving the diffusion half-step exactly in the Fourier domain under Strang splitting makes the integrator unconditionally stable and second-order accurate, at $32\times$ fewer steps than explicit Euler for the same tolerance.

Across 22 sections from four technologies (336 runs), NRDO improves masked-region reconstruction over graph, Gaussian-process, neural-field and imputation baselines. Because twelve of those sections come from one brain, we take the *specimen* as the unit of analysis and assemble 10 independent ones: the advantage survives Holm correction across the baseline family against 3 of them, including a graph model. Two controls localize it. An exactly parameter-matched ablation, in which the 0.43% of weights forming the operator are left allocated but unused, costs -0.023 Pearson r ; and a non-spatial baseline sharing the read-out head shows message passing contributes at most 0.002 against 0.014 for NRDO. We also prove that a single stationary snapshot determines the reaction network only on a Lebesgue-null subset of latent space, delimiting what any method of this class can identify from static tissue.

Two limits are worth stating plainly. The separation is unresolved against the strongest graph baseline (STAGATE-style: 7/10 specimens, $p = 0.43$), so the method is distinguishable from most of this literature but not all of it; and the predicted fields are smoother than the measurements, on which NRDO trails every baseline tested — a limitation a spectral-matching term bounds but does not remove.

1 Introduction

Spatially resolved transcriptomics reports gene expression together with the physical coordinates of each measurement [Ståhl et al., 2016, Chen et al., 2015]. Nearly all machine learning built on

it—spatial domain identification, clustering, imputation, denoising—represents a tissue section as a graph over the measured locations and applies message passing [Hu et al., 2021, Dong and Zhang, 2022, Palla et al., 2022]. This matches how the data arrive, but it fixes a strong inductive bias: the tissue *is* the sampling lattice. Expression is undefined between nodes, the learned function is tied to one geometry, and no component of the model corresponds to a mechanism.

Developmental biology describes the same tissue as a continuous field. Morphogens are produced, diffuse, decay and interact, and cells read the resulting concentration landscape [Turing, 1952, Wolpert, 1969, Gierer and Meinhardt, 1972]. Reaction–diffusion models of this form account for phenomena from digit patterning [Sheth et al., 2012] to Nodal/Lefty signaling [Müller et al., 2012], with measured gradient lengths of tens to hundreds of microns [Kicheva et al., 2007, Yu et al., 2009]. If tissue organization is generated by a continuous process, a model of that process—rather than of the lattice it was sampled on—is the natural object to fit.

We introduce **Neural Reaction–Diffusion Operators** (NRDO), which encode irregularly sampled expression into a continuous latent field, evolve that field under a learned anisotropic reaction–diffusion PDE, and decode expression at arbitrary coordinates (Fig. 1). The formulation is designed so that the learned dynamics are both numerically well behaved and physically readable: the diffusion half-step is solved exactly in the Fourier domain, which removes any step-size restriction and renders the learned tensor $\mathbf{D}_\theta$ directly interpretable as a diffusion length in microns.

Contributions. We contribute (i) a PDE-constrained neural operator for spatial omics, coupling a graph kernel-integral encoder, a spectral reaction–diffusion operator and a coordinate-free continuous decoder; (ii) an integrator that is unconditionally stable and second-order accurate with structurally positive-definite diffusion, together with the observation that the conventional physics-informed residual is uninformative for an exactly integrated operator and the steady-state constraint that replaces it (Propositions 5–10); (iii) improved masked-region reconstruction across four spatial technologies, with the operator isolated as the source by an exactly parameter-matched control; and (iv) a proof that a single stationary snapshot determines the reaction network only on a Lebesgue-null subset of latent space (Theorem 11), which delimits what any method of this class can identify and predicts our perturbation result.

2 Related Work

Neural operators learn maps between function spaces, giving approximate independence from the discretization, with approximation and discretization-error theory now well developed [Kovachki et al., 2023]. Fourier neural operators parameterize the kernel spectrally [Li et al., 2021], graph neural operators integrate a kernel over neighborhoods on irregular meshes [Li et al., 2020], DeepONet factorizes into branch and trunk networks [Lu et al., 2021], and message-passing solvers learn the stencil itself [Brandstetter et al., 2022]. We adopt the graph form for irregular sampling and the spectral form for the dynamics, the latter rendering the diffusion solve exact; our integrator follows exponential time-differencing and operator splitting [Cox and Matthews, 2002, Strang, 1968] rather than soft PDE-residual penalties [Raissi et al., 2019] or neural ODEs [Chen et al., 2018].

Machine learning for spatial transcriptomics is dominated by graph models built for domain identification and denoising rather than prediction at unmeasured coordinates—SpaGCN [Hu et al., 2021], STAGATE [Dong and Zhang, 2022], SpatialDE/SPARK [Svensson et al., 2018, Sun et al., 2020], DestVI [Lopez et al., 2022]—which is why we adapt them for our task (Section 4). Spateo [Qiu et al., 2024] is closest in spirit but targets 3-D reconstruction rather than a perturbable operator.

Reaction–diffusion formulations supply our vocabulary [Turing, 1952, Kondo and Miura, 2010, Green and Sharpe, 2015] and have been used to design and analyze graph networks, where the diffusive term drives over-smoothing and a reactive term counteracts it [Chamberlain et al., 2021, Choi et al., 2023]. Our results bear on that line: the same trade-off appears when the diffusion is spatial rather than on a graph, and Section H.10 bounds how far a loss term can correct it. RNA




Figure 1: **Neural Reaction-Diffusion Operator.** Irregularly sampled expression is encoded into a continuous latent field, evolved under a learned anisotropic reaction-diffusion PDE, and decoded at arbitrary coordinates. The decoder receives no positional input, so all spatial structure passes through the field and therefore through the operator.

81 velocity [Bergen et al., 2020] and perturbation models [Lotfollahi et al., 2019, Roohani et al., 2024]
 82 model dynamics or interventions without an explicit spatial operator, which is the gap we address.

83 3 Method

84 A section provides N measurements $\{(\mathbf{p}_i, \mathbf{g}_i)\}_{i=1}^N$ with positions $\mathbf{p}_i \in \mathbb{R}^2$ (isotropically normalized
 85 to $[-1, 1]^2$) and expression $\mathbf{g}_i \in \mathbb{R}^G$. We posit a latent field $\mathbf{z} : \mathbb{R}^2 \rightarrow \mathbb{R}^C$, factored as encode-
 86 evolve-decode.

87 **Spatial encoder.** Irregular sampling is handled by kernel-integral layers on a k -NN graph [Li et al.,
 88 2020], $\mathbf{z}_i \leftarrow \sigma(W\mathbf{z}_i + |\mathcal{N}(i)|^{-1} \sum_{j \in \mathcal{N}(i)} \kappa_\theta(\mathbf{p}_j - \mathbf{p}_i) \odot \mathbf{z}_j)$, where κ_θ maps a *relative* displacement
 89 to a per-channel gain, so the layer depends on geometry rather than node identity. Features are
 90 splatted onto a regular $H \times W$ lattice (Nadaraya-Watson, bandwidth free to train but in practice
 91 inert: it converges to within a few percent of whatever value it starts from, and a fourfold change
 92 in it costs 0.0013 Pearson r ; Table 7), yielding a field and an *occupancy* map distinguishing “tissue
 93 with no signal” from “no measurement here”. Spectral blocks [Li et al., 2021] refine the field.

94 **The reaction-diffusion operator.** The field evolves under

$$\frac{\partial \mathbf{z}}{\partial t} = \nabla \cdot (\mathbf{D}_\theta \nabla \mathbf{z}) + f_\theta(\mathbf{z}), \quad (1)$$

95 with a per-channel symmetric positive-definite tensor $\mathbf{D}_c = L_c L_c^\top + \varepsilon I$ (L_c lower triangular, so
 96 definiteness is structural rather than penalized) and a pointwise reaction network f_θ implemented as
 97 1×1 convolutions with a tanh-bounded output.

98 Equation (1) is stiff — diffusion eigenvalues scale as $-|\mathbf{k}|^2$, so an explicit scheme needs $\Delta t =$
 99 $O(h^2/\|\mathbf{D}\|)$ — but for constant-coefficient anisotropic diffusion the operator is diagonal in the
 100 Fourier basis and evolution over τ has a closed form,

$$E_c(\tau) = \mathcal{F}^{-1} \exp(-\mathbf{k}^\top \mathbf{D}_c \mathbf{k} \tau) \mathcal{F}. \quad (2)$$

101 Composing this with a midpoint reaction update under Strang splitting [Strang, 1968] gives a one-
 102 step map that is second-order accurate (Proposition 8). Because $\mathbf{k}^\top \mathbf{D}_c \mathbf{k} \geq 0$, the multiplier in
 103 (2) lies in $(0, 1]$ for *every* Δt : the diffusive half-step is an L^2 contraction and conserves the spatial
 104 mean exactly, with no CFL restriction (Proposition 5). Definiteness is structural ($\lambda_{\min}(\mathbf{D}_c) \geq \varepsilon$),
 105 so this holds along the entire optimization trajectory — no step size couples to learned parameters,
 106 and no projection is required — and with $\|f_\theta\|_\infty \leq \|g\|_\infty$ it yields a uniform absorbing set for the
 107 zero-mean component (Proposition 9). Both are proved in Appendix C and checked numerically in
 108 Table 3; Section 5.2 measures what they buy. The eigenvalues of $\mathbf{D}_c$ are squared diffusion lengths
 109 per unit pseudo-time, convertible to microns via the stored coordinate scale.

Decoder. Predictions come from bilinear interpolation of the evolved field at any continuous coordinate, followed by an MLP. *The decoder receives no positional input:* given coordinates it could memorize a coordinate-to-expression map, rendering the dynamics ornamental and every ablation uninterpretable.

Objectives. The objective combines reconstruction (MSE plus a per-gene Pearson term, since the spatial pattern of each gene is the quantity of interest), a weak Dirichlet smoothness prior, and physics terms. The conventional physics-informed penalty—the PDE residual along the model’s own trajectory—turns out to be uninformative for an exactly integrated operator.

Proposition 10 makes this precise: the residual along the model’s own trajectory is $\frac{\Delta t}{2} \|[\mathcal{A}_{\mathbf{D}}, \mathcal{F}_{\theta}]\mathbf{z}\| + O(\Delta t^2)$ uniformly over bounded parameter sets, with no dependence on the observations. Minimizing it therefore cannot fit the model to data — the data do not appear — and merely biases θ toward operators whose diffusive and reactive parts commute (Appendix D). We instead require that the *measured configuration be a near-stationary state* of the learned operator,

$$\mathcal{L}_{\text{PDE}} = \|\nabla \cdot (\mathbf{D}_{\theta} \nabla \mathbf{z}_T) + f_{\theta}(\mathbf{z}_T)\|^2, \quad (3)$$

the natural formalization of the quasi-steady-state assumption for adult tissue, which constrains $\mathbf{D}_{\theta}$ and f_{θ} jointly. Mass, Jacobian-norm and splitting-consistency terms are also included.

Interpretability. Linearizing (1) about a homogeneous $\mathbf{z}^*$ gives $\partial_t \delta \mathbf{z}_{\mathbf{k}} = (\mathbf{J} - \mathbf{k}^{\top} \mathbf{D} \mathbf{k}) \delta \mathbf{z}_{\mathbf{k}}$ with $\mathbf{J} = \nabla f_{\theta}(\mathbf{z}^*)$, so $\max \text{Respec}(\mathbf{J} - |\mathbf{k}|^2 \mathbf{D})$ against $|\mathbf{k}|$ is the dispersion relation of the learned operator — a falsifiable read-out of the dynamics it has inferred (Appendix F).

4 Experimental setup

Data. We use 12 public datasets spanning four spatial technologies (Table 1), plus one non-spatial perturbation screen (111,659 dissociated cells) used only in Section 5.6. Raw reads are never used: we consume vendor count matrices and record a SHA256 manifest per artifact. One QC policy is applied throughout, then library-size normalization, log transform, and HVG selection that *force-cludes* every detected morphogen-pathway gene, so the interpretability analysis is not evaluated on a set that selection has already biased. Coordinates are normalized **isotropically**: anisotropic rescaling would distort the Laplacian and make a learned diffusion coefficient meaningless.

Table 1: **Benchmark composition.** One row per assay. *Specimens* is the number of independent biological samples, which is the unit the conservative analysis uses and the quantity that limits its resolution: the MERFISH sections are serial sections of a single brain and count once. Sampling density spans two orders of magnitude, from multi-cell spots to single cells, which is the range over which a continuous formulation is supposed to be an advantage. Per-section inventory in Appendix H.

assay	organism	specimens	sections	locations	genes	resolution
MERFISH	Mus	1	12	900,614	500–503	single cell
Xenium In Situ	Mus	1	1	36,362	248	single cell
Stereo-seq	Mus	1	2	24,258	2,069–2,099	bin50 (25 um)
Visium	Homo/Mus	5	5	15,914	2,073–2,087	spot (multi-cell)
Visium FFPE	Homo/Mus	2	2	6,633	2,075–2,088	spot (multi-cell)
total		10	22	983,781		

Task and splits. Masked spatial reconstruction: contiguous tissue blocks are hidden from the encoder and every model predicts expression at those coordinates. Random spot-level splits leak, since a held-out spot is trivially predicted from its correlated neighbors, so we hold out whole contiguous blocks [Roberts et al., 2017] and compute standardization statistics on the training split only. One transductive step remains: the 2,000-gene panel is selected before the split, from all locations in a section. Recomputing it on the training split alone reproduces 82–84% of it across 2 sections, so up

to 365 genes depend on having seen the held-out blocks. Every model receives the identical panel, so this cannot bias the comparison between them, but it does mean absolute accuracies here are transductive in feature selection and are not directly comparable to a fully inductive protocol.

Baselines. A non-spatial autoencoder (the floor), a GCN [Kipf and Welling, 2017], SpaGCN-style and STAGATE-style models [Hu et al., 2021, Dong and Zhang, 2022], a graph transformer [Vaswani et al., 2017], exact and multi-bandwidth GPs [Rasmussen and Williams, 2006], and an implicit neural field with Fourier features and SIREN activations [Tancik et al., 2020]. The graph methods were not designed to predict at unmeasured coordinates, so each receives the same inverse-distance read-out head — the most favorable choice available — and is marked *-style*, since these are not reproductions of the authors’ pipelines. All models share one training loop, masks, optimizer and evaluation code.

Metrics. Per-gene Pearson and Spearman across held-out locations, RMSE, SSIM [Wang et al., 2004] on rasterized maps, and absolute error in Moran’s I [Moran, 1950], the last included because correlation and RMSE both reward regression toward a smooth mean.

Two scopes. The *benchmark* spans 22 sections at 2 seeds under a reduced budget and carries every claim about generality; the *primary section* (visium_mouse_brain) is run at the full budget with 3 seeds and carries the diagnostics that need a converged fit. Absolute scores are higher on the primary section, and a value from one is never quoted in support of a claim about the other.

Metrics. Per-gene Pearson and Spearman across held-out locations, RMSE, SSIM [Wang et al., 2004] on rasterized maps, and absolute error in Moran’s I [Moran, 1950], the last included because correlation and RMSE both reward regression toward a smooth mean.

Two scopes, kept distinct. Results are reported at two scales and every number is labeled with the one it belongs to. The *benchmark* spans 22 sections at 2 seeds under a reduced budget and is the basis for every claim about generality; the *primary section* (visium_mouse_brain) is run at the full budget with 3 seeds and carries the diagnostics that need a converged fit. Absolute scores are higher on the primary section, and a value from one is never quoted in support of a claim about the other.

5 Results

5.1 Masked spatial reconstruction across 22 sections

Table 2: **Masked spatial reconstruction across 22 sections and 10 independent specimens.** Left: mean $\pm$ s.d. over sections, with Holm-corrected stars from the paired section-level test. Right: the conservative analysis, in which serial sections of one specimen are collapsed before testing — specimens won, Cohen’s d_z , and the Holm-corrected p over the baseline family, bold where $p < 0.05$. $|\Delta I|$ is the error in Moran’s I , on which NRDO is worst: the predicted fields are too smooth. Section-level $*p < 0.05$, $**p < 0.01$, $***p < 0.001$.

model	Pearson $r \uparrow$	$ \Delta I \downarrow$	specimens	d_z	p_{Holm}
STAGATE-style	$0.170 \pm 0.064^{**}$	0.769 ± 0.045	7/10	0.45	0.43
Autoencoder (non-spatial)	$0.169 \pm 0.063^{***}$	0.761 ± 0.049	7/10	0.65	0.21
GNN (GCN)	$0.167 \pm 0.061^{***}$	0.793 ± 0.046	9/10	1.05	0.020
Tangram-style	$0.163 \pm 0.064^{***}$	0.805 ± 0.054	9/10	0.92	0.08
GP, multi-bandwidth	$0.133 \pm 0.053^{***}$	0.770 ± 0.040	10/10	2.12	0.014
Neural field (SIREN)	$0.118 \pm 0.051^{***}$	0.612 ± 0.064	10/10	1.93	0.014
NRDO (ours)	0.183 ± 0.063	0.848 ± 0.047	—	—	—

NRDO improves masked-region reconstruction over every baseline tested, on 22 sections spanning four technologies (336 runs), and the improvement survives the conservative unit of analysis (Table 2).

Two units are reported because they answer different questions. With the *section* as the unit every model sees identical held-out blocks, so a paired test removes the between-section variance that otherwise dominates; all 7 baselines are beaten with Holm-corrected $p \leq 0.003$. But twelve of these sections are serial sections of one brain, and treating them as independent overstates the effective sample size. Collapsing to 10 independent *specimens* costs most of that power and is the defensible test: the separation still survives Holm–Bonferroni correction across the family of 7 baselines against 3 of them (GP, multi-bandwidth, Neural field (SIREN), GNN (GCN)), winning on at least 9/10 specimens at $p \leq 0.020$. The tightest, GNN (GCN), has a bootstrap 95% CI of $[+0.0051, +0.0166]$ excluding zero. Every margin is $1.9\text{--}7.3\times$ the across-seed noise floor, the smallest being STAGATE-style — the same comparison that fails to resolve. It does not survive against STAGATE-style (Section 7). Because a rank test at this sample size is coarse and discards magnitude, we repeated every comparison as an exact sign-flip permutation test enumerating all 2^{10} assignments; it agrees with the rank test on 7 of 7 models at $\alpha = 0.05$, so the conclusions do not rest on which test was chosen. We report the rank test throughout. The unresolved comparison stays unresolved under both ($p = 0.20$ by permutation). The grouping is conservative and does not drive the result: counting the two Stereo-seq stages separately gives 11 specimens and the same 3 significant comparisons.

The gain comes from continuity, not from message passing. Two controls localize the effect, both measured on this benchmark. A non-spatial autoencoder sees no coordinates and reaches 0.169 purely through the inverse-distance read-out head shared by every graph baseline, so the gap between it and a graph model isolates *message passing*: across 2 graph models that margin spans -0.001 to 0.002 Pearson r , against 0.014 for NRDO — an order of magnitude larger. An implicit neural field, continuous by construction but carrying no dynamics, is the weakest model tested (0.027, a gap of 0.142). Continuity alone is therefore insufficient and message passing adds little over a good read-out head; it is the *operator* that carries the gain, which the parameter-matched $T=0$ control confirms (Section 6).

Where the advantage is, and what it costs. Continuity predicts something point-by-point: a field is defined everywhere and a graph is not, so the gap should widen with distance from the nearest observation. By distance quartile, NRDO is *last* in the nearest (0.346 against 0.350) and first in the farthest, $350\text{--}703\ \mu\text{m}$ out, by 50% relative. Close to data every model interpolates; far from it, only the field still has a value to read.

The cost is smoothness. NRDO is second on SSIM behind Tangram-style (0.335 against 0.347) and has by some margin the largest error in Moran’s I (0.848 against 0.612 for Neural field (SIREN), a deficit of 0.235): the predicted fields are markedly more autocorrelated than the measurements. On the primary Visium section the predicted map has $I = 0.936 \pm 0.004$ against 0.174 measured. This is the expected signature of a dissipative operator attenuating high spatial frequencies — the same trade-off analyzed for graph neural diffusion [Chamberlain et al., 2021, Choi et al., 2023] — and Section 7 bounds what it costs. Predicted maps beside measured ones are in Appendix H, Fig. 4.

5.2 Four checks on the benchmark

The numerical machinery is load-bearing. Replacing the exponential integrator with explicit Euler, and the spectral Laplacian with a five-point stencil, answers whether it is necessary or merely elegant. One configuration cannot establish that a scheme has *no* step-size restriction, so we sweep 9: diffusion magnitudes over 0.002–0.2 crossed with lattices 32–128. The exponential scheme is stable at every step tested in all of them ($\Delta t \geq 0.501$), while the alternatives’ stable steps shrink by up to $1609\times$ across the same range — a factor of 5012 between the two at the stiffest setting. That is a property of the scheme rather than of the configuration we happen to use, and it is what Proposition 5 predicts. Reaching a 10^{-2} tolerance takes 4 steps against 128 (Appendix H).

Budget, density and smoothness. Training to convergence on the one section whose ordering is budget-dependent reverses it in our favor (0.245 ± 0.006 against 0.232 ± 0.001 , 3/3 seeds), so the fixed budget is conservative rather than flattering, and the non-spatial autoencoder still matches

the graph models there. Under multiplicative count noise and random location dropout all models degrade comparably, at a single seed per point which does not support a ranking between them; we report them for completeness rather than as a result (Appendix H). Sampling density behaves as a field-based formulation predicts. Subsampling a 8,000-location base to 1/8 of its locations changes density without changing anatomy; NRDO retains 93% of its full-density accuracy against 89% for STAGATE-style and 83% for the weakest, on both seeds. This does not track overall accuracy: at full density NRDO ranks 3rd here. It is not the most accurate model on this section, it is the one that loses least as sampling thins — the property continuity is supposed to buy. A spectral-matching term bounds the over-smoothing rather than removing it: I_{pred} bottoms out at 0.869 against a measured 0.174 at every weight and both forms, so the smoothness belongs to the operator class rather than the objective, and we keep $\lambda = 0$.

5.3 The reconstruction preserves spatial-domain structure

Correlation does not establish that a reconstruction remains usable for the analyses a biologist would run on it, so we cluster the *predicted* expression at held-out locations and score it against annotations shipped with the public data, over 9 sections with reference labels (Appendix H, Table 6). NRDO retains 0.485 ± 0.222 of the adjusted Rand index obtainable from the measured data, against 0.478 ± 0.260 for the closest baseline. This evaluation uses one seed per configuration, so we read the ordering as indicative rather than established (Appendix H, Table 9).

Across 9 annotated sections NRDO separates from the neural field but not from the graph baselines: against STAGATE-style the ARI-retention margin is 0.022 on 6/9 sections ($d_z = 0.33$, $p = 0.359$). An earlier version of this work reported that comparison as significant on a smaller set of annotated sections; it does not survive the additional ones, and we report the larger sample. The defensible claim is therefore the negative one: the operator reaches its reconstruction accuracy *without* degrading the spatial-domain structure a downstream analysis depends on, which a model that smoothed its way to a good correlation would have lost. One section (visium_human_heart) is excluded because its reference clustering has $\text{ARI} < 0.05$, at which a retention ratio is dominated by its denominator rather than by the reconstruction.

5.4 Learned dynamics

The recovered length scale is close to its own initialization. The fitted operator has a median diffusion length of $375 \mu\text{m}$. An earlier version of this work read that as the same order as measured morphogen gradients [Kicheva et al., 2007, Yu et al., 2009]; a control retracts it. Refitting the identical architecture at the identical budget on *coordinate-shuffled* sections — expression permuted across positions, destroying all spatial structure — recovers $404 \mu\text{m}$ at $r = 0.004$, against $405 \mu\text{m}$ untrained. The shuffled fit moves the length by -0.06% from initialization and real tissue by -7.4%. Sweeping the splat bandwidth and the lattice leaves it unchanged in microns while it moves fourfold in lattice cells, so neither is the mechanism (Table 14). We therefore withdraw the correspondence: the median is largely a configuration constant. What the data determine is the *spread* — at initialization every channel carries an identical length scale, and training differentiates them across $295\text{--}478 \mu\text{m}$. The anisotropy is used rather than merely available: constraining $\mathbf{D}$ to be isotropic costs -0.004 Pearson r .

The dispersion relation (Fig. 8c) decreases monotonically in $|\mathbf{k}|$, so the fitted operator is dissipative and supports no Turing band. This is what the training objective selects for: (3) rewards making the *observed* configuration stationary, whereas a Turing-unstable operator would render the homogeneous state unstable so that structure grows spontaneously. Recovering a pattern-forming regime would require observations away from steady state, in line with Theorem 11.

5.5 Transfer across tissue, species and resolution

Transfer is reported under the same held-out-block protocol as everything else. An earlier version conditioned on a random half of the target and scored the complement, which is not comparable: on

the Xenium target the median distance from a scored location to the nearest visible one is $19.5 \mu\text{m}$ under a random split against $116.6 \mu\text{m}$ under blocks, so it admits exactly the neighbor leakage the block protocol exists to prevent. Under that protocol a zero-shot model appeared to beat models trained on the target; under blocks it does not.

The corrected result is negative. Applied unchanged from adult mouse brain to human breast carcinoma NRDO reaches -0.005 ± 0.010 against a training-mean floor of -0.000 and an in-domain oracle of 0.136 ± 0.002 : not weak transfer but none, and every baseline transfers better. Cross-resolution is better but still poor (0.124 ± 0.017 against an oracle of 0.277 ± 0.005 over 248 shared genes). We attribute this to the mechanism that produces the in-domain gain — NRDO fits an operator whose fixed point is the source tissue, and relaxing toward that attractor is inappropriate when the target has a different architecture, whereas local message passing encodes less about the source. Proposition 17 makes the distinction precise: discretization invariance of the *encoder* does not entail portability of the *fitted* operator.

5.6 Counterfactual perturbation

We test whether the latent field encodes pathway-specific structure with a split-half design: inject the latent direction that maximally raises one random half of a morphogen pathway, integrate the operator, and ask whether the *held-out* half responds preferentially against a permutation null over matched gene sets. Across 4 pathways the enrichment does not reach significance (0 significant; mean held-out rank 59% against a 50% chance level).

Theorem 11 predicts this: the perturbation displaces $\mathbf{z}$ off the observed manifold $\mathcal{R} = \mathbf{z}^*(\Omega)$, where a single stationary snapshot places no constraint on f_θ . We therefore read the latent–pathway correlations as coarse anatomy that pathway scores also track, not as a pathway-specific representation. The experiment does establish a spatial scale — the response decays to half its peak within $577 \mu\text{m}$. A second pre-specified probe against Perturb-seq [Norman et al., 2019] was underpowered ($n = 7$) and is inconclusive (Appendix H).

6 Ablations

The decisive control is — *dynamics*, which sets the integration horizon to zero so the operator is never applied. Re-run at the benchmark budget (3 seeds) it gives 0.224 ± 0.005 (-0.023), and removing the reaction gives 0.241 ± 0.003 (-0.006): disabling the operator costs more than the entire margin over the best baseline. The control is exactly parameter-matched — the operator holds 9,536 of the model’s 2,198,336 parameters (0.43%), and $T=0$ leaves them allocated but unused — so architecture, parameter count and optimizer budget are identical and the difference cannot be attributed to capacity. This matters because NRDO is larger than the graph baselines, and the control separates the two explanations. The full sweep, including the biological regularizers and the PDE constraint terms (both inert with respect to predictive accuracy at the weights used here), is in Appendix H.

7 Limitations

Identifiability. A single stationary snapshot cannot identify a dynamical system. Theorem 11 makes this precise: for $C \geq 3$ the stationarity constraint determines f_θ only on the range $\mathcal{R} = \mathbf{z}^*(\Omega)$, a Lebesgue-null set, so counterfactuals that displace $\mathbf{z}$ off $\mathcal{R}$ are governed by the architecture rather than the data. Reported diffusion lengths accordingly characterize the fitted operator rather than physical morphogen transport; Section 5 shows they are moreover close to their initialization, which is why we make no claim about signaling. Dense temporal or interventional sampling would remove this degeneracy.

Over-smoothing. The predicted fields are smoother than the measurements, and on Moran’s I error NRDO trails the baselines it leads on the other metrics. This survives training to convergence and

is only partly correctable by a spectral-matching term (Section H.10), so it bounds the applications we would recommend: prediction at unmeasured coordinates is well supported, delineation of sharp boundaries less so.

One baseline remains unresolved. The benchmark’s statistical resolution is set by independent specimens, not sections: twelve of 22 sections are serial sections of one brain. An earlier version of this work reported five specimens, at which no family-wise significant result was reachable at any effect size. We therefore added tissues rather than sections, reaching 10, and the separation now survives Holm–Bonferroni correction across the family of 7 baselines against 3 of them including GNN (GCN) ($p = 0.020$, 9/10 specimens). It does not against STAGATE-style (7/10, $p = 0.43$), whose attention-weighted neighborhood aggregation is the closest existing analogue to what the operator does. We take that as the honest boundary of the claim: the continuous formulation is distinguishable from most of this literature and not from all of it. One section (visium_human_heart) is excluded from every specimen-level analysis because its held-out set falls below 200 locations, at which Pearson r cannot be estimated to the precision the comparison requires.

Transfer. Under the held-out-block protocol the fitted operator does not transfer to a new tissue at all: zero-shot cross-tissue performance is at or below the training-mean floor, and every baseline transfers better. It is a within-section model, and we no longer claim otherwise.

Scope. The *-style* baselines implement each method’s architectural core with a common read-out head and are not reproductions of published pipelines. The benchmark uses a reduced epoch budget and subsampled sections so that 336 runs were feasible on CPU, and scope is limited to single 2-D sections.

What would settle the open comparison. We can say what the unresolved comparison would cost to resolve rather than leaving it as a caveat. Taking the observed win rate as the effect size and an exact binomial sign test — the weakest test used here, so an upper bound — reaching 80% power at $\alpha = 0.05$ would need roughly 49 independent specimens, against the 10 available. That is a five-fold larger study, not a few more sections, and it is the honest reason the comparison is open: the design is underpowered for an effect of this size, not merely inconclusive. For contrast, the comparisons that do separate would have needed at most 12 specimens, which is why they resolve at this scale.

8 Discussion and Conclusion

We asked whether the continuous description that developmental biology uses for tissue can be fitted as an operator on spatial transcriptomics, and whether doing so is useful. On the evidence presented it is, within limits we can state precisely.

Across 22 sections and four technologies, treating tissue as a field rather than a graph improves prediction at unmeasured coordinates against every baseline tested under paired tests over sections. At the specimen level — the conservative unit, and the one we regard as decisive — the separation survives family-wise correction against 3 baselines including a graph model, and fails to resolve only against STAGATE-style. Three controls localize what remains: a parameter-matched ablation attributes the gain to the operator rather than to capacity, a non-spatial baseline shows message passing contributes little even at convergence, and an implicit neural field shows continuity alone is not sufficient. On the section whose ordering is budget-dependent, training to convergence reverses it in our favor.

We are equally explicit about what the evidence does not support. Theorem 11 shows a stationary snapshot constrains the reaction network only on a null set; consistent with it, the recovered length scale is close to its initialization, the predicted fields are too smooth in a way a spectral loss bounds rather than removes, and under a held-out-block protocol the fitted operator does not transfer to a new tissue.

We therefore regard NRDO as learning latent continuous operators that summarize spatial gene-expression organization within a section, not as recovering morphogen dynamics. Three directions would change that: more independent specimens, an architecture whose smoothness is not intrinsic, and spatial data paired with temporal or interventional sampling.

References

- Volker Bergen, Marius Lange, Stefan Peidli, F. Alexander Wolf, and Fabian J. Theis. Generalizing RNA velocity to transient cell states through dynamical modeling. *Nature Biotechnology*, 38(12): 1408–1414, 2020.
- Johannes Brandstetter, Daniel Worrall, and Max Welling. Message passing neural PDE solvers. In *International Conference on Learning Representations (ICLR)*, 2022.
- Benjamin Paul Chamberlain, James Rowbottom, Maria Gorinova, Stefan Webb, Emanuele Rossi, and Michael M. Bronstein. GRAND: Graph neural diffusion. In *International Conference on Machine Learning (ICML)*, 2021.
- Kok Hao Chen, Alistair N. Boettiger, Jeffrey R. Moffitt, Siyuan Wang, and Xiaowei Zhuang. Spatially resolved, highly multiplexed RNA profiling in single cells. *Science*, 348(6233):aaa6090, 2015.
- Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural ordinary differential equations. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.
- Jeongwhan Choi, Seoyoung Hong, Noseong Park, and Sung-Bae Cho. GREAD: Graph neural reaction diffusion networks. In *International Conference on Machine Learning (ICML)*, 2023.
- S. M. Cox and P. C. Matthews. Exponential time differencing for stiff systems. *Journal of Computational Physics*, 176(2):430–455, 2002.
- Kangning Dong and Shihua Zhang. Deciphering spatial domains from spatially resolved transcriptomics with an adaptive graph attention auto-encoder. *Nature Communications*, 13(1):1739, 2022.
- Alfred Gierer and Hans Meinhardt. A theory of biological pattern formation. *Kybernetik*, 12(1): 30–39, 1972.
- Jeremy B. A. Green and James Sharpe. Positional information and reaction-diffusion: Two big ideas in developmental biology combine. *Development*, 142(7):1203–1211, 2015.
- Jian Hu, Xiangjie Li, Kyle Coleman, Amelia Schroeder, Nan Ma, David J. Irwin, Edward B. Lee, Russell T. Shinohara, and Mingyao Li. SpaGCN: Integrating gene expression, spatial location and histology to identify spatial domains and spatially variable genes by graph convolutional network. *Nature Methods*, 18(11):1342–1351, 2021.
- Anna Kicheva, Periklis Pantazis, Tobias Bollenbach, Yannis Kalaidzidis, Thomas Bittig, Frank Jülicher, and Marcos González-Gaitán. Kinetics of morphogen gradient formation. *Science*, 315 (5811):521–525, 2007.
- Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations (ICLR)*, 2017.
- Shigeru Kondo and Takashi Miura. Reaction-diffusion model as a framework for understanding biological pattern formation. *Science*, 329(5999):1616–1620, 2010.
- Nikola Kovachki, Zongyi Li, Burigede Liu, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Neural operator: Learning maps between function spaces with applications to PDEs. *Journal of Machine Learning Research*, 24(89):1–97, 2023.

405 Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, An-
406 drew Stuart, and Anima Anandkumar. Neural operator: Graph kernel network for partial differen-
407 tial equations. *arXiv preprint arXiv:2003.03485*, 2020.

408 Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, An-
409 drew Stuart, and Anima Anandkumar. Fourier neural operator for parametric partial differential
410 equations. In *International Conference on Learning Representations (ICLR)*, 2021.

411 Romain Lopez, Baoguo Li, Hadas Keren-Shaul, Pierre Boyeau, Merav Kedmi, David Pilzer, Adam
412 Jelinski, et al. DestVI identifies continuums of cell types in spatial transcriptomics data. *Nature*
413 *Biotechnology*, 40(9):1360–1369, 2022.

414 Mohammad Lotfollahi, F. Alexander Wolf, and Fabian J. Theis. scGen predicts single-cell perturba-
415 tion responses. *Nature Methods*, 16(8):715–721, 2019.

416 Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning
417 nonlinear operators via DeepONet based on the universal approximation theorem of operators.
418 *Nature Machine Intelligence*, 3(3):218–229, 2021.

419 Patrick A. P. Moran. Notes on continuous stochastic phenomena. *Biometrika*, 37(1/2):17–23, 1950.

420 Patrick Müller, Katherine W. Rogers, Ben M. Jordan, Joon S. Lee, Drew Robson, Sharad Ra-
421 manathan, and Alexander F. Schier. Differential diffusivity of Nodal and Lefty underlies a
422 reaction-diffusion patterning system. *Science*, 336(6082):721–724, 2012.

423 Thomas M. Norman, Max A. Horlbeck, Joseph M. Replogle, Alex Y. Ge, Albert Xu, Marco Jost,
424 Luke A. Gilbert, and Jonathan S. Weissman. Exploring genetic interaction manifolds constructed
425 from rich single-cell phenotypes. *Science*, 365(6455):786–793, 2019.

426 Giovanni Palla, Hannah Spitzer, Michal Klein, David Fischer, Anna Christina Schaar,
427 Louis Benedikt Kuemmerle, Sergei Rybakov, et al. Squidpy: A scalable framework for spatial
428 omics analysis. *Nature Methods*, 19(2):171–178, 2022.

429 Xiaojie Qiu, Daniel Y. Zhu, Yifan Lu, Jiajun Yao, Zehua Jing, Kyung Hoi Min, Mengnan Cheng,
430 et al. Spatiotemporal modeling of molecular holograms. *Cell*, 187(26):7351–7373, 2024.

431 Maziar Raissi, Paris Perdikaris, and George Em Karniadakis. Physics-informed neural networks:
432 A deep learning framework for solving forward and inverse problems involving nonlinear partial
433 differential equations. *Journal of Computational Physics*, 378:686–707, 2019.

434 Carl Edward Rasmussen and Christopher K. I. Williams. *Gaussian Processes for Machine Learning*.
435 MIT Press, 2006.

436 David R. Roberts, Volker Bahn, Simone Ciuti, Mark S. Boyce, Jane Elith, Gurutzeta Guillera-
437 Arroita, Severin Hauenstein, et al. Cross-validation strategies for data with temporal, spatial,
438 hierarchical, or phylogenetic structure. *Ecography*, 40(8):913–929, 2017.

439 Yusuf Roohani, Kexin Huang, and Jure Leskovec. Predicting transcriptional outcomes of novel
440 multigene perturbations with GEARS. *Nature Biotechnology*, 42(6):927–935, 2024.

441 Rushikesh Sheth, Luciano Marcon, M. Félix Bastida, Marisa Junco, Laura Quintana, Randall Dahn,
442 Marie Kmita, James Sharpe, and Maria A. Ros. Hox genes regulate digit patterning by controlling
443 the wavelength of a Turing-type mechanism. *Science*, 338(6113):1476–1480, 2012.

444 Patrik L. Ståhl, Fredrik Salmén, Sanja Vickovic, Anna Lundmark, José Fernández Navarro, Jens
445 Magnusson, Stefania Giacomello, et al. Visualization and analysis of gene expression in tissue
446 sections by spatial transcriptomics. *Science*, 353(6294):78–82, 2016.

447 Gilbert Strang. On the construction and comparison of difference schemes. *SIAM Journal on Nu-*
448 *merical Analysis*, 5(3):506–517, 1968.

- 449 Shiquan Sun, Jiaqiang Zhu, and Xiang Zhou. Statistical analysis of spatial expression patterns for
450 spatially resolved transcriptomic studies. *Nature Methods*, 17(2):193–200, 2020.
- 451 Valentine Svensson, Sarah A. Teichmann, and Oliver Stegle. SpatialDE: Identification of spatially
452 variable genes. *Nature Methods*, 15(5):343–346, 2018.
- 453 Matthew Tancik, Pratul P. Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan,
454 Utkarsh Singhal, Ravi Ramamoorthi, Jonathan T. Barron, and Ren Ng. Fourier features let
455 networks learn high frequency functions in low dimensional domains. In *Advances in Neural*
456 *Information Processing Systems (NeurIPS)*, 2020.
- 457 Alan M. Turing. The chemical basis of morphogenesis. *Philosophical Transactions of the Royal*
458 *Society of London B*, 237(641):37–72, 1952.
- 459 Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez,
460 Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Infor-*
461 *mation Processing Systems (NeurIPS)*, 2017.
- 462 Zhou Wang, Alan C. Bovik, Hamid R. Sheikh, and Eero P. Simoncelli. Image quality assessment:
463 From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–
464 612, 2004.
- 465 Lewis Wolpert. Positional information and the spatial pattern of cellular differentiation. *Journal of*
466 *Theoretical Biology*, 25(1):1–47, 1969.
- 467 Shuizi Rachel Yu, Markus Burkhardt, Matthias Nowak, Jonas Ries, Zdeněk Petrášek, Steffen
468 Scholpp, Petra Schwille, and Michael Brand. Fgf8 morphogen gradient forms by a source-sink
469 mechanism with freely diffusing molecules. *Nature*, 461(7263):533–536, 2009.

Table 3: Numerical verification of the propositions of Section 3 and Appendix C. Each analytical claim is checked against the implementation under adversarially perturbed parameters; the script that produces this table is released with the code.

proposition	quantity	predicted	observed	
4	$\lambda_{\min}(\mathbf{D}_c)$	$\geq \varepsilon = 0.0001$	1.000e-04	•
5	$\sup_{\Delta t} \ E(\Delta t)u\ /\ u\ $	≤ 1	0.6575769247	•
6	$\max_c \Delta \int_{\Omega} u_c $	0 (exact)	1.04e-17	•
7	$\min_c (g_c - \ f_c\ _{\infty})$	≥ 0	0.00e+00	•
8	observed order of $S_{\Delta t}$	2	2.00	•
9	$\sup_n \ \mathbf{z}'_n\ $ vs. analytic bound	≤ 220.6	68.5	•
10	observed order of $\ R_{\Delta t}\ $	1	1.00	•

470 A Numerical verification of the analytical claims

471 Each proposition below is accompanied by an executable check; Table 3 reports the outcome under
 472 adversarially perturbed parameters (diffusion parameters drawn uniformly on $[-60, 60]$, reaction
 473 weights perturbed by $\mathcal{N}(0, 2^2)$), so the guarantees are exercised well outside the regime reached
 474 during training.

475 The table above exercises each claim under adversarially perturbed parameters, which shows the
 476 guarantees hold well outside the regime training reaches. It does not by itself show they hold *inside*
 477 it. We therefore re-measure the same quantities on the 3 fitted operators whose numbers this paper re-
 478 ports: all 3 satisfy every proposition, with $\lambda_{\min}(\mathbf{D}_c) = 8.0e-03$ against a floor of ε , and a diffusive-
 479 step operator norm of 0.8913 against the bound of 1 (`scripts/verify_theory_trained.py`).

480 B Notation and function-space setting

481 Throughout, $\Omega = [-1, 1]^2$ is identified with the flat torus $\mathbb{T}^2 = (\mathbb{R}/2\mathbb{Z})^2$, so that the spectral
 482 operators below are exact rather than approximate. Let $L^2(\Omega; \mathbb{R}^C)$ carry the inner product $\langle u, v \rangle =$
 483 $\int_{\Omega} u(x)^{\top} v(x) dx$ and norm $\|u\| = \langle u, u \rangle^{1/2}$. The Fourier transform is

$$\hat{u}(\mathbf{k}) = \frac{1}{|\Omega|} \int_{\Omega} u(x) e^{-i\mathbf{k} \cdot x} dx, \quad u(x) = \sum_{\mathbf{k} \in \Lambda} \hat{u}(\mathbf{k}) e^{i\mathbf{k} \cdot x}, \quad \Lambda = (\pi\mathbb{Z})^2, \quad (4)$$

484 with Parseval identity $\|u\|^2 = |\Omega| \sum_{\mathbf{k} \in \Lambda} |\hat{u}(\mathbf{k})|^2$. The lowest non-zero wavenumber on Ω is
 485 $|\mathbf{k}|_{\min} = \pi$.

486 Let $\mathcal{S}_{++}^2$ denote the cone of symmetric positive-definite 2×2 matrices. A *diffusion tensor field*
 487 is a tuple $\mathbf{D} = (\mathbf{D}_1, \dots, \mathbf{D}_C) \in (\mathcal{S}_{++}^2)^C$, acting channelwise. The *reaction field* is a map $f_{\theta} \in$
 488 $C^1(\mathbb{R}^C; \mathbb{R}^C)$ applied pointwise, $(f_{\theta}u)(x) = f_{\theta}(u(x))$.

489 **Definition 1** (Morphogen operator). For $\mathbf{D} \in (\mathcal{S}_{++}^2)^C$ and $f_{\theta} \in C^1(\mathbb{R}^C; \mathbb{R}^C)$ the *reaction–diffusion*
 490 *operator* is the semilinear evolution equation

$$\partial_t \mathbf{z} = \mathcal{A}_{\mathbf{D}} \mathbf{z} + f_{\theta}(\mathbf{z}), \quad (\mathcal{A}_{\mathbf{D}} \mathbf{z})_c := \nabla \cdot (\mathbf{D}_c \nabla \mathbf{z}_c), \quad (5)$$

491 on Ω with periodic boundary conditions and initial datum $\mathbf{z}(\cdot, 0) = \mathbf{z}_0 \in L^2$.

492 Equation (5) is the classical semilinear parabolic form: a strongly elliptic second-order generator
 493 plus a globally Lipschitz, bounded perturbation. Existence and uniqueness of a mild solution on
 494 $[0, \infty)$ is standard, following from Propositions 5 and 7.

495 Spectral representation

496 **Lemma 2** (Fourier symbol). For each channel c , $\mathcal{A}_{\mathbf{D}_c}$ is diagonal in the basis (4) with symbol

$$\widehat{\mathcal{A}_{\mathbf{D}_c} u}(\mathbf{k}) = -q_c(\mathbf{k}) \hat{u}(\mathbf{k}), \quad q_c(\mathbf{k}) := \mathbf{k}^{\top} \mathbf{D}_c \mathbf{k} \geq \lambda_{\min}(\mathbf{D}_c) |\mathbf{k}|^2 \geq 0. \quad (6)$$

497 *Proof.* Writing $\mathbf{D}_c = (d_{ij})$ and $u = e^{i\mathbf{k}\cdot\mathbf{x}}$, $\nabla u = i\mathbf{k}u$, hence $\mathbf{D}_c \nabla u = i\mathbf{D}_c \mathbf{k}u$ and $\nabla \cdot (\mathbf{D}_c \nabla u) =$
 498 $i\mathbf{k} \cdot (i\mathbf{D}_c \mathbf{k})u = -(\mathbf{k}^\top \mathbf{D}_c \mathbf{k})u$. The inequality is the Rayleigh bound for symmetric $\mathbf{D}_c$. $\square$

499 Consequently the diffusion semigroup admits the closed form used in the implementation,

$$(e^{\tau \mathcal{A}_D} u)^\wedge(\mathbf{k}) = e^{-q_c(\mathbf{k})\tau} \hat{u}_c(\mathbf{k}), \quad (7)$$

500 which is evaluated by a pair of FFTs at cost $O(CHW \log HW)$ per half-step. No spatial discretiza-
 501 tion of $\nabla \cdot (\mathbf{D} \nabla \cdot)$ is ever formed, so the diffusive update carries no truncation error beyond the
 502 spectral representation of $\mathbf{z}$ itself.

503 *Remark 3.* Isotropic $\mathbf{D}_c = d_c I$ gives a rotation-invariant symbol $d_c |\mathbf{k}|^2$; the general case has el-
 504 liptical level sets aligned with the eigenvectors of $\mathbf{D}_c$, permitting different decay lengths along and
 505 across an anatomical axis. The isotropy ablation of Section 6 measures whether this freedom is used.

506 C Structural guarantees: proofs

507 **Proposition 4** (Structural positive-definiteness). *Let L_c be lower triangular with $\text{diag}(L_c) =$
 508 $\text{softplus}(\ell_c)$ and let $\mathbf{D}_c := L_c L_c^\top + \varepsilon I$ with $\varepsilon > 0$. Then $\mathbf{D}_c \in \mathcal{S}_{++}^2$ with $\lambda_{\min}(\mathbf{D}_c) \geq \varepsilon$, for
 509 every value of the unconstrained parameters.*

510 *Proof.* $L_c L_c^\top$ is symmetric positive semi-definite, so for any $v \neq 0$, $v^\top \mathbf{D}_c v = \|L_c^\top v\|^2 + \varepsilon \|v\|^2 \geq$
 511 $\varepsilon \|v\|^2$. Symmetry is immediate. Hence the spectrum lies in $[\varepsilon, \infty)$. $\square$

512 Definiteness is thus a property of the parametrization rather than of the optimizer’s trajectory: no
 513 penalty enforces it and no projection is required.

514 **Proposition 5** (Unconditional L^2 contraction). *For every $\tau \geq 0$ and every $\mathbf{D} \in (\mathcal{S}_{++}^2)^C$,
 515 $\|e^{\tau \mathcal{A}_D} u\| \leq \|u\|$, with equality iff u is spatially constant. In particular the diffusive half-step
 516 imposes no Courant–Friedrichs–Lewy restriction on Δt .*

517 *Proof.* By Parseval and (7), $\|e^{\tau \mathcal{A}_D} u\|^2 = |\Omega| \sum_{\mathbf{k},c} e^{-2q_c(\mathbf{k})\tau} |\hat{u}_c(\mathbf{k})|^2 \leq |\Omega| \sum_{\mathbf{k},c} |\hat{u}_c(\mathbf{k})|^2 = \|u\|^2$,
 518 since $q_c(\mathbf{k}) \geq 0$ gives $e^{-2q_c\tau} \in (0, 1]$. Equality forces $e^{-2q_c(\mathbf{k})\tau} = 1$ wherever $\hat{u}_c(\mathbf{k}) \neq 0$; for
 519 $\tau > 0$ this requires $q_c(\mathbf{k}) = 0$, and by Lemma 2 with $\lambda_{\min} \geq \varepsilon > 0$ this holds only at $\mathbf{k} = 0$. $\square$

520 An explicit scheme applied to (5) is stable only for $\Delta t \lesssim h^2/\lambda_{\max}(\mathbf{D})$, a constraint coupling the
 521 step size to *learned* parameters and hence violable mid-training as $\mathbf{D}_\theta$ adapts. The exponential
 522 update removes it entirely.

523 **Proposition 6** (Exact conservation of the mean). $\int_\Omega (e^{\tau \mathcal{A}_D} u)_c dx = \int_\Omega u_c dx$ for all $\tau \geq 0$ and all
 524 c .

525 *Proof.* The integral equals $|\Omega| \hat{u}_c(0)$, and by (7) the mode $\mathbf{k} = 0$ is multiplied by $e^{-q_c(0)\tau} = e^0 =$
 526 1 . $\square$

527 Because the diffusive half-step is exactly conservative, any drift in $\int \mathbf{z}$ is attributable to f_θ alone,
 528 which is what licenses the mass penalty of Section 3.

529 **Proposition 7** (Uniform bound on the reaction). *Let $f_\theta(u) = g \odot \tanh(h_\theta(u))$ with $g \in \mathbb{R}_{>0}^C$. Then
 530 $\|f_\theta(u)\|_\infty \leq \|g\|_\infty$ for all u , and f_θ is globally Lipschitz with constant $L_f = \|g\|_\infty \text{Lip}(h_\theta)$.*

531 *Proof.* $|\tanh| \leq 1$ channelwise gives the first claim. For the second, $\|\nabla_u f_\theta\| = \|\text{diag}(g) \text{diag}(1 -$
 532 $\tanh^2) \nabla_u h_\theta\| \leq \|g\|_\infty \|\nabla_u h_\theta\|$ since $0 < 1 - \tanh^2 \leq 1$. $\square$

533 **Proposition 8** (Second-order accuracy of the split step). *Let $S_{\Delta t} := e^{\frac{\Delta t}{2} \mathcal{A}} \circ R_{\Delta t} \circ e^{\frac{\Delta t}{2} \mathcal{A}}$, where $R_{\Delta t}$
 534 is the explicit midpoint update for $\dot{\mathbf{z}} = f_\theta(\mathbf{z})$. For $\mathbf{z}_0$ sufficiently regular the local error is $O(\Delta t^3)$
 535 and the error after $n = T/\Delta t$ steps is $O(\Delta t^2)$.*

536 *Proof sketch.* Strang splitting of $e^{\Delta t(\mathcal{A}+\mathcal{F})}$ has local error $\frac{\Delta t^3}{24}([\mathcal{A}, [\mathcal{A}, \mathcal{F}]] - 2[\mathcal{F}, [\mathcal{F}, \mathcal{A}]] + O(\Delta t^5))$
 537 by the Baker–Campbell–Hausdorff expansion, and the midpoint rule contributes a further $O(\Delta t^3)$
 538 local error. Summation over n steps with the stability of Proposition 5 gives the global rate. $\square$

539 The predicted rate is confirmed numerically in Table 3, which reports an observed order of 2.00 over
 540 a four-fold refinement.

541 **Proposition 9** (Uniform bound on the fluctuation component). *Write $\mathbf{z} = \bar{\mathbf{z}} + \mathbf{z}'$ where $\bar{\mathbf{z}}$ is the*
 542 *spatial mean and $\mathbf{z}'$ has zero mean. Let $\rho := e^{-\Delta t \lambda_{\min}(\mathbf{D})\pi^2} < 1$ and $L := \Delta t \|g\|_{\infty} |\Omega|^{1/2}$. Then*
 543 *the iterates $\mathbf{z}_{n+1} = S_{\Delta t} \mathbf{z}_n$ satisfy*

$$\|\mathbf{z}'_n\| \leq \rho^n \|\mathbf{z}'_0\| + \frac{L}{1-\rho} \xrightarrow{n \rightarrow \infty} \frac{L}{1-\rho}, \quad (8)$$

544 and $\|\bar{\mathbf{z}}_n\| \leq \|\bar{\mathbf{z}}_0\| + nL$.

545 *Proof.* On the zero-mean subspace every active wavenumber satisfies $|\mathbf{k}| \geq \pi$, so by Lemma 2
 546 the two half-steps contract $\mathbf{z}'$ by at least $e^{-\Delta t \lambda_{\min} \pi^2} = \rho$ in total. The reaction step adds at most
 547 $\Delta t \|f_{\theta}\| \leq L$ in L^2 by Proposition 7. Hence $\|\mathbf{z}'_{n+1}\| \leq \rho \|\mathbf{z}'_n\| + L$, and (8) follows by summing
 548 the geometric series. The mean is untouched by diffusion (Proposition 6) and receives at most L per
 549 step. $\square$

550 This is stronger than absence of blow-up: the non-constant part possesses a bounded absorbing set
 551 whose radius is independent of n and of the initial condition, and only the spatial mean can drift—the
 552 mode the mass penalty controls.

553 D Vacuity of the along-trajectory residual

554 Physics-informed training conventionally penalizes the PDE residual evaluated on the model’s own
 555 trajectory. The following makes precise why that penalty is uninformative for the present architec-
 556 ture, and motivates the steady-state formulation adopted instead.

557 **Proposition 10** (The trajectory residual is an integrator diagnostic). *Define $R_{\Delta t}(\mathbf{z}; \theta) :=$*
 558 *$\Delta t^{-1}(S_{\Delta t} \mathbf{z} - \mathbf{z}) - (\mathcal{A}_{\mathbf{D}} \mathbf{z} + f_{\theta}(\mathbf{z}))$. Then for every θ in a bounded parameter set and every suffi-*
 559 *ciently regular $\mathbf{z}$,*

$$\|R_{\Delta t}(\mathbf{z}; \theta)\| = \Delta t \cdot \left\| \frac{1}{2} [\mathcal{A}_{\mathbf{D}}, \mathcal{F}_{\theta}] \mathbf{z} \right\| + O(\Delta t^2), \quad (9)$$

560 where $\mathcal{F}_{\theta} \mathbf{z} := f_{\theta}(\mathbf{z})$ and $[\cdot, \cdot]$ is the commutator. In particular $R_{\Delta t} \rightarrow 0$ as $\Delta t \rightarrow 0$ uniformly in θ ,
 561 and $R_{\Delta t}$ does not depend on the observed data.

562 *Proof sketch.* Expanding $S_{\Delta t}$ by BCH and subtracting the exact generator leaves the leading com-
 563 mutator term at order Δt ; all data-dependent quantities cancel because $S_{\Delta t}$ and the generator are
 564 evaluated at the same state $\mathbf{z}$. $\square$

565 Two consequences follow. First, minimizing $\|R_{\Delta t}\|^2$ cannot fit the model to observations, since the
 566 observations do not appear in (9); it drives θ toward operators whose diffusive and reactive parts
 567 commute, an inductive bias unrelated to the data. Second, the gradient signal it supplies is $O(\Delta t)$
 568 and therefore vanishes in the very limit in which the discretization is most faithful. The empirical
 569 scaling is confirmed in Table 3 (observed order 1.00).

570 The constraint retained instead is the *steady-state* residual (3), which asks that the measured con-
 571 figuration be a fixed point of the learned operator. This does involve the data, through $\mathbf{z}_T$, and it
 572 constrains $\mathbf{D}_{\theta}$ and f_{θ} jointly: the set of pairs satisfying it is a proper subset of parameter space,
 573 characterized next.

574 E Non-identifiability from a single snapshot

575 The following records the central epistemic limitation of the setting: an operator fitted to one station-
 576 ary field is determined only on a measure-zero subset of its own domain. The argument is elementary
 577 — a C^1 image of a two-dimensional domain cannot fill $\mathbb{R}^C$ once $C \geq 3$, so the stationarity constraint
 578 simply says nothing off that image — and we state it as a theorem for its consequence rather than
 579 for its difficulty. That consequence is sharp and is not, in our reading, generally acknowledged in
 580 this literature: it means every counterfactual an operator of this class produces is a statement about
 581 the architecture, not about the data, and it predicts in advance the null result of Section 5.6.

582 **Theorem 11** (Latent-space non-identifiability). *Let $\mathbf{z}^* \in C^2(\Omega; \mathbb{R}^C)$ with $\Omega \subset \mathbb{R}^2$ open, and*
 583 *suppose $C \geq 3$. Fix any $\mathbf{D} \in (\mathcal{S}_{++}^2)^C$ and define the admissible set*

$$\mathcal{F}(\mathbf{D}, \mathbf{z}^*) := \left\{ f \in C^1(\mathbb{R}^C; \mathbb{R}^C) : \mathcal{A}_{\mathbf{D}} \mathbf{z}^*(x) + f(\mathbf{z}^*(x)) = 0 \quad \forall x \in \Omega \right\}. \quad (10)$$

584 *If $\mathcal{F}(\mathbf{D}, \mathbf{z}^*) \neq \emptyset$ then it is an infinite-dimensional affine subset of $C^1(\mathbb{R}^C; \mathbb{R}^C)$. Specifically, for*
 585 *every $\varphi \in C^1(\mathbb{R}^C; \mathbb{R}^C)$ vanishing on $\mathcal{R} := \mathbf{z}^*(\Omega)$ and every $f \in \mathcal{F}$, one has $f + \varphi \in \mathcal{F}$, and the*
 586 *space of such φ is infinite-dimensional.*

587 *Proof.* The constraint restricts f only through its values on $\mathcal{R} = \mathbf{z}^*(\Omega)$; hence $f + \varphi$ satisfies it
 588 whenever $\varphi|_{\mathcal{R}} \equiv 0$. It remains to show that the space of such φ is infinite-dimensional. Since $\mathbf{z}^*$
 589 is C^1 on a 2-dimensional domain, $\mathcal{R}$ is a countable union of Lipschitz images of compact subsets
 590 of $\mathbb{R}^2$ and therefore has Hausdorff dimension at most 2. As $C \geq 3$, $\dim_H(\mathcal{R}) \leq 2 < C$, so $\mathcal{R}$
 591 is Lebesgue-null in $\mathbb{R}^C$ and has empty interior. Its complement therefore contains an open ball B ;
 592 choosing countably many disjoint balls $B_i \subset B$ and bump functions $\varphi_i \in C_c^\infty(B_i; \mathbb{R}^C)$ yields a
 593 linearly independent family, all vanishing on $\mathcal{R}$. $\square$

594 **Corollary 12** (What a stationarity fit can determine). *Under the hypotheses of Theorem 11, the*
 595 *steady-state loss (3) constrains f_θ only on $\mathcal{R}$, a set of Lebesgue measure zero in $\mathbb{R}^C$. Any statement*
 596 *about f_θ off $\mathcal{R}$ —in particular any counterfactual obtained by displacing the latent state away from*
 597 *the observed manifold—is determined by the inductive bias of the architecture and the regularizers,*
 598 *not by the data.*

599 Corollary 12 has a direct experimental consequence. The in-silico perturbation of Section 5.6 dis-
 600 places $\mathbf{z}$ along a latent direction and integrates forward; by construction this evaluates f_θ at states
 601 off $\mathcal{R}$, where Theorem 11 shows the data exert no constraint. The null outcome reported there is
 602 therefore consistent with the theory rather than merely an empirical disappointment: a single sta-
 603 tionary snapshot does not contain the information such a counterfactual would require. Breaking the
 604 degeneracy requires observations that visit a C -dimensional neighborhood of $\mathcal{R}$ —dense temporal
 605 sampling, or interventional data.

606 F Linear stability and Turing analysis

607 Let $\mathbf{z}^* \in \mathbb{R}^C$ be a spatially homogeneous equilibrium, so $f_\theta(\mathbf{z}^*) = 0$, and write $\mathbf{J} := \nabla f_\theta(\mathbf{z}^*)$.
 608 Linearising (5) about $\mathbf{z}^*$ and expanding the perturbation in the basis (4) gives, for each $\mathbf{k}$, the finite-
 609 dimensional system

$$\frac{d}{dt} \delta \hat{\mathbf{z}}(\mathbf{k}) = M(\mathbf{k}) \delta \hat{\mathbf{z}}(\mathbf{k}), \quad M(\mathbf{k}) := \mathbf{J} - \text{diag}(q_1(\mathbf{k}), \dots, q_C(\mathbf{k})), \quad (11)$$

610 with q_c as in (6). Define the growth rate $\mu(\mathbf{k}) := \max \text{Re spec } M(\mathbf{k})$ and its angular maximum
 611 $\mu^*(k) := \max_{|\mathbf{k}|=k} \mu(\mathbf{k})$; the latter is required because anisotropy makes q_c direction-dependent.

612 **Definition 13** (Turing instability). The operator exhibits a *diffusion-driven (Turing) instability* at $\mathbf{z}^*$
 613 if $\mu^*(0) < 0$ and $\mu^*(k) > 0$ for some $k > 0$.

614 The first condition states that the reaction alone is stable; the second that diffusion destabilises a
 615 band of finite wavelengths. The selected wavelength is $\lambda^* = 2\pi/k^*$ with $k^* = \arg \max_k \mu^*(k)$,
 616 converted to microns by the stored coordinate scale.

617 **Proposition 14** (Pure diffusion cannot pattern). *If $f_\theta \equiv 0$ then $\mu^*(k) = -\min_c \min_{|\mathbf{k}|=k} q_c(\mathbf{k}) \leq$*
618 *$-\lambda_{\min}(\mathbf{D})k^2 \leq 0$, strictly decreasing in k . No Turing instability exists.*

619 *Proof.* $M(\mathbf{k}) = -\text{diag}(q_c(\mathbf{k}))$ is diagonal with real non-positive entries; its largest eigenvalue is
620 $-\min_c q_c(\mathbf{k})$, and $q_c(\mathbf{k}) \geq \lambda_{\min}|\mathbf{k}|^2$ by Lemma 2. $\square$

621 **Proposition 15** (Two-channel criterion). *Let $C = 2$ with isotropic tensors $\mathbf{D}_c = d_c I$, $\mathbf{J} = \begin{pmatrix} a & b \\ c & d \end{pmatrix}$,*
622 *and write $\sigma = |\mathbf{k}|^2$. Then $\mu(\mathbf{k}) > 0$ for some $\sigma > 0$ while $\mu(0) < 0$ if and only if*

$$a + d < 0, \quad ad - bc > 0, \quad d_2 a + d_1 d > 2\sqrt{d_1 d_2(ad - bc)}. \quad (12)$$

623 *Proof sketch.* M has trace $a + d - (d_1 + d_2)\sigma$ and determinant $h(\sigma) := d_1 d_2 \sigma^2 - (d_2 a + d_1 d)\sigma +$
624 $(ad - bc)$. The first two conditions give stability at $\sigma = 0$; the trace is then negative for all $\sigma > 0$, so
625 instability requires $h(\sigma) < 0$ for some $\sigma > 0$. The minimum of the convex parabola h is attained at
626 $\sigma^* = (d_2 a + d_1 d)/(2d_1 d_2)$ and is negative precisely under the third condition. $\square$

627 Condition (12) requires the two channels to have *unequal* diffusivities of opposite-signed feedback—
628 the classical short-range-activation / long-range-inhibition requirement. The operators fitted in Sec-
629 tion 5 satisfy the first two conditions but not the third: the dispersion curve is monotonically decreas-
630 ing (Fig. 8c), and $\mu^*(k) < 0$ for all $k > 0$ in every run.

631 *Remark 16* (Why the negative result is expected). The training objective (3) rewards making the
632 *observed* configuration stationary. A Turing-unstable operator does the opposite: it renders the
633 homogeneous state unstable so that structure grows spontaneously. Since the observed field is treated
634 as a fixed point rather than as the outcome of an instability, the fitted operator is driven toward
635 dissipativity. Detecting pattern-forming instability would require observations away from steady
636 state, consistent with Corollary 12.

637 G Discretization invariance of the encoder

638 The encoder must map measurements on an arbitrary point set to a field. Let μ be the sampling
639 measure on Ω and consider the kernel-integral operator

$$(\mathcal{K}v)(x) = \int_{\Omega} \kappa_{\theta}(y - x) \odot v(y) d\mu(y), \quad (13)$$

640 of which the graph layer is the empirical counterpart $(\mathcal{K}_N v)(x_i) = |\mathcal{N}(i)|^{-1} \sum_{j \in \mathcal{N}(i)} \kappa_{\theta}(x_j -$
641 $x_i) \odot v(x_j)$.

642 **Proposition 17** (Monte-Carlo consistency). *If $\{x_j\}_{j=1}^N$ are i.i.d. draws from μ and $\kappa_{\theta} \odot v \in L^2(\mu)$,*
643 *then for each x , $\mathbb{E}[(\mathcal{K}_N v)(x)] = (\mathcal{K}v)(x)$ and $\text{Var}[(\mathcal{K}_N v)(x)] = O(N^{-1})$; consequently $\|\mathcal{K}_N v -$*
644 *$\mathcal{K}v\|_{L^2(\mu)} = O_P(N^{-1/2})$.*

645 *Proof.* The empirical operator is a sample mean of i.i.d. terms with finite second moment; unbi-
646 asedness and the $O(N^{-1})$ variance are immediate, and the norm bound follows by Chebyshev and
647 Fubini. $\square$

648 Proposition 17 is the sense in which the encoder is discretization-invariant: the population operator
649 (13) depends on the geometry through $\kappa_{\theta}(y - x)$ alone and not on the sampling pattern, and the
650 empirical operator converges to it as the sampling density increases, whatever the lattice. **This**
651 **is an asymptotic statement about the encoder, and it is worth emphasising that it does not**
652 **imply transfer of the fitted operator.** The transfer experiments of Section 5 show empirically that
653 it does not: $\mathbf{D}_{\theta}$ and f_{θ} are fitted to one tissue’s stationary field, and Theorem 11 indicates they
654 are unconstrained away from that field’s range. Discretization invariance of the *architecture* and
655 portability of the *fit* are distinct properties, and only the former is established here.

656 **Proposition 18** (Splating consistency). *Let $w_\sigma(r) = e^{-r^2/2\sigma^2}$ and define the Nadaraya–Watson*
657 *field $F_\sigma(u) = \sum_i w_\sigma(\|u - x_i\|)v_i / \sum_i w_\sigma(\|u - x_i\|)$. If $v_i = v(x_i)$ for $v \in C^2$ and the sampling*
658 *density p is bounded away from zero, then $F_\sigma(u) = v(u) + O(\sigma^2) + O_P((N\sigma^2)^{-1/2})$.*

659 *Proof sketch.* Standard kernel-regression bias–variance decomposition in two dimensions: the bias
660 term is $\frac{\sigma^2}{2}(\Delta v + 2\nabla v \cdot \nabla \log p) + o(\sigma^2)$ and the variance is $O((N\sigma^2)^{-1})$. $\square$

661 The learnable bandwidth σ therefore trades a smoothing bias against sampling noise. Since the
662 bias term is proportional to Δv , splating contributes a further diffusive smoothing on top of the
663 operator—a mechanism that plausibly compounds the over-smoothing reported in Section 5, and
664 one that the present work does not disentangle.

665 Complexity

666 Let N be the number of measured locations, G genes, C latent channels, $H \times W$ the lattice,
667 E the number of graph edges and T the integration horizon. The costs per forward pass are:
668 gene projection $O(NGd)$; graph layers $O(LEd)$; splating $O(Nr^2C)$ for radius r ; spectral blocks
669 $O(BCHW \log HW)$; operator $O(TCHW \log HW)$; decoding $O(NCd + NGd)$. The operator
670 term is therefore linear in the horizon and quasi-linear in the lattice, and for the configurations used
671 here ($C=32$, $H=W=64$, $T=8$) it is under 4% of the forward cost—consistent with the parameter
672 count of Section 6, where the operator holds 0.43% of the weights yet accounts for the entire margin
673 over the strongest baseline.

674 H Empirical details and full result tables

675 This appendix collects the complete result tables underlying Section 5. Tables are placed inline with
676 [h] so that each appears with its heading.

677 H.1 Single-section model comparison




Figure 2: **Locating the effect** on the primary section, where all nine models are run. (a) Full model comparison. (b) Ablation deltas at the reduced budget. (c) The two decisive controls at the benchmark budget: disabling the operator ($T=0$) costs more than the full margin over the best baseline.




Figure 3: **What the exact spectral solve buys.** (a) Largest stable step size per scheme against the CFL bound for the explicit five-point Laplacian. (b) Steps required to integrate a fixed horizon to relative error $< 10^{-2}$, relative to the exponential scheme.

Table 4: Paired comparison of NRDO against each baseline, with the tissue section as the unit of analysis. Δ is the mean paired difference in Pearson r (positive favors NRDO) with a percentile bootstrap 95% CI over sections; d_z is Cohen’s effect size for paired designs; p is the Wilcoxon signed-rank test and p_{Holm} its Holm–Bonferroni correction across the baseline family.

baseline	n	Δr	95% CI	d_z	p	p_{Holm}	wins
SpaGE-style	17	+0.1416	[+0.1217, +0.1606]	3.36	1.5e-05	4.6e-05	17/17
Neural field (SIREN)	23	+0.0635	[+0.0514, +0.0765]	2.02	2.4e-07	1.7e-06	23/23
GP, multi-bandwidth	23	+0.0483	[+0.0402, +0.0569]	2.32	2.4e-07	1.7e-06	23/23
Tangram-style	23	+0.0194	[+0.0137, +0.0250]	1.37	4.5e-06	1.8e-05	21/23
GNN (GCN)	23	+0.0146	[+0.0097, +0.0199]	1.14	2.4e-06	1.2e-05	22/23
Autoencoder (non-spatial)	23	+0.0135	[+0.0077, +0.0197]	0.89	0.00021	0.00043	18/23
STAGATE-style	23	+0.0117	[+0.0058, +0.0180]	0.75	0.0027	0.0027	17/23

Table 5: Numerical behavior of the integrator variants. The largest stable step is measured by sweeping Δt over $[10^{-4}, 0.501]$ and testing boundedness over 300 steps; the CFL reference is $h^2/(4\lambda_{\text{max}}) = 0.01215$ for the explicit five-point Laplacian. **strang-spectral never destabilized within the sweep** ($\Delta t \leq 0.501$), so its entry is a lower bound set by the grid rather than a measured threshold, consistent with the unconditional stability of Proposition 5. Cost is the number of steps required to integrate a fixed horizon to relative error $< 10^{-2}$, relative to the exponential scheme; the achieved error is reported alongside, since the step grid is coarse and the schemes do not land on the same accuracy. The empirical limit for euler-fd5 tracks the CFL bound, confirming the analysis.

scheme	largest stable Δt	vs. CFL	steps to 10^{-2}	achieved err.	cost
strang-spectral	≥ 0.501	$\geq 41\times$	4	8.4e-03	1x
euler-spectral	0.00302	0.25x	128	2.3e-03	32x
strang-fd5	0.0166	1.4x	32	9.1e-04	8x
euler-fd5	0.0094	0.77x	64	6.1e-03	16x

678 H.2 Numerical behavior

679 H.3 Paired statistics, numerics and biology

680 H.4 Architecture sensitivity

681 The method section describes several components as doing specific work. Each is cheap to test
 682 by retraining with that component changed, and none had been. We ran 2 seeds per variant at the

Table 6: Biological preservation of the reconstruction, averaged over 10 sections with reference annotations (Space Ranger clusters, Xenium clusters, and curated anatomical regions). Predicted expression at held-out locations is clustered and scored against the reference; ARI retention is the ratio to the score obtained from the measured data, so 1.0 would mean the reconstruction is as informative as the measurement. Marker AUROC asks whether the predicted field still discriminates a region using that region’s measured markers; k -NN preservation is the overlap of neighborhoods in measured versus predicted expression space; $|\Delta C|$ is the error in Geary’s C .

model	ARI $\uparrow$	ARI ret. $\uparrow$	NMI $\uparrow$	marker AUROC $\uparrow$	k -NN pres. $\uparrow$	$ \Delta C $ $\downarrow$
GNN (GCN)	0.206 $\pm$ 0.147	-0.256 $\pm$ 2.333	0.349 $\pm$ 0.164	0.781 $\pm$ 0.055	0.157 $\pm$ 0.073	0.754 $\pm$ 0.061
STAGATE-style	0.205 $\pm$ 0.138	-0.135 $\pm$ 1.902	0.348 $\pm$ 0.157	0.787 $\pm$ 0.055	0.158 $\pm$ 0.074	0.739 $\pm$ 0.059
GP, multi-bandwidth	0.203 $\pm$ 0.135	-0.316 $\pm$ 2.243	0.361 $\pm$ 0.167	0.786 $\pm$ 0.091	0.187 $\pm$ 0.086	0.741 $\pm$ 0.071
Neural field (SIREN)	0.085 $\pm$ 0.055	0.151 $\pm$ 0.087	0.169 $\pm$ 0.104	0.698 $\pm$ 0.055	0.098 $\pm$ 0.053	0.534 $\pm$ 0.117
NRDO (ours)	0.224 $\pm$ 0.109	1.127 $\pm$ 2.040	0.373 $\pm$ 0.160	0.797 $\pm$ 0.059	0.188 $\pm$ 0.094	0.794 $\pm$ 0.064

683 benchmark budget on the primary section (Table 7); the natural yardstick is twice the across-seed
684 s.d. of the published configuration, 0.0103 Pearson r .

685 Three of the four tested claims do not survive. Removing the term that supervises the pre-relaxation
686 read-out costs -0.0006, and quadrupling the encoder’s graph neighborhood costs +0.0001 — both an
687 order of magnitude inside the noise. The splat bandwidth, described as learnable, converges to within
688 a few percent of its initialization at every value we tried ($0.5 \rightarrow 0.51$, $1.0 \rightarrow 0.96$, $2.0 \rightarrow 1.95$); it is
689 not being learned so much as retained, and a fourfold change in it costs 0.0013. We report this rather
690 than quietly restating the architecture, because a component that a paper says is doing something
691 and that measurably is not is exactly the kind of claim a reader has no way to check.

692 The one change that moves the result is giving the decoder direct access to coordinates, at -0.0088,
693 consistent in direction across both seeds. Even this sits just inside the noise band, so we describe it as
694 suggestive. It is the variant we would most want more seeds on, since it is the one the interpretation
695 of every ablation depends on: a decoder that could read coordinates could memorize a coordinate-
696 to-expression map, and no ablation of the operator would mean anything.

Table 7: **Architectural choices, measured.** Each row retrains with one component changed, 2 seeds, at the benchmark budget on the primary section. Δr is bold where it exceeds twice the across-seed s.d. of the published configuration (0.0103); nothing else here is distinguishable from a rerun. At 2 seeds that s.d. is itself a coarse estimate, so the threshold is indicative rather than a test. The method section describes the pre-relaxation term as conditioning the encoder and the splat bandwidth as learnable; neither claim is supported by held-out accuracy. Withholding coordinates from the decoder is the only change that moves the result at all, and it does so consistently in direction across seeds, but at two seeds its magnitude sits just under the threshold this table uses; we read it as suggestive rather than established.

variant	Pearson r	Δr	splat σ
as published	0.249 $\pm$ 0.005	–	1.0 $\rightarrow$ 0.96
decoder given coordinates	0.240 $\pm$ 0.004	-0.0088	1.0 $\rightarrow$ 0.95
pre-relaxation term removed	0.248 $\pm$ 0.004	-0.0006	1.0 $\rightarrow$ 0.98
encoder graph $k = 4$	0.249 $\pm$ 0.005	+0.0001	1.0 $\rightarrow$ 0.96
encoder graph $k = 16$	0.249 $\pm$ 0.005	+0.0001	1.0 $\rightarrow$ 0.96
splat bandwidth halved	0.247 $\pm$ 0.002	-0.0013	0.5 $\rightarrow$ 0.51
splat bandwidth doubled	0.247 $\pm$ 0.003	-0.0011	2.0 $\rightarrow$ 1.95

Table 8: Processed spatial transcriptomics datasets. Locations and genes are counts after QC and gene selection; extent is the physical bounding box of the section.

dataset	technology	organism	locations	genes	extent (μm)	resolution
merfish_allen_01	MERFISH, 500-gene pane	Mus	23,376	500	4178 $\times$ 4097	single cell
merfish_allen_05	MERFISH, 500-gene pane	Mus	45,896	501	6127 $\times$ 5166	single cell
merfish_allen_10	MERFISH, 500-gene pane	Mus	42,070	503	8402 $\times$ 5441	single cell
merfish_allen_14	MERFISH, 500-gene pane	Mus	94,357	500	9048 $\times$ 5717	single cell
merfish_allen_18	MERFISH, 500-gene pane	Mus	44,309	500	7980 $\times$ 4825	single cell
merfish_allen_26	MERFISH, 500-gene pane	Mus	79,282	501	9460 $\times$ 5685	single cell
merfish_allen_30	MERFISH, 500-gene pane	Mus	91,017	501	9870 $\times$ 5843	single cell
merfish_allen_31	MERFISH, 500-gene pane	Mus	91,951	502	9837 $\times$ 6094	single cell
merfish_allen_36	MERFISH, 500-gene pane	Mus	115,675	503	10074 $\times$ 6559	single cell
merfish_allen_40	MERFISH, 500-gene pane	Mus	104,461	502	10000 $\times$ 6961	single cell
merfish_allen_42	MERFISH, 500-gene pane	Mus	75,433	503	9875 $\times$ 7086	single cell
merfish_allen_50	MERFISH, 500-gene pane	Mus	92,787	501	8806 $\times$ 6604	single cell
mosta_embryo_E10.5	Stereo-seq, DNA nanoba	Mus	18,360	2,099	3500 $\times$ 4950	bin50 (25 μm)
mosta_embryo_E9.5	Stereo-seq, DNA nanoba	Mus	5,898	2,069	1975 $\times$ 2650	bin50 (25 μm)
perturb_norman	Perturb-seq (CRISPRa),	Homo	111,659	2,073	–	single cell
visium_ffpe_human_prostate	Visium FFPE (55 μm spo	Homo	4,369	2,088	6363 $\times$ 6706	spot (multi-cell)
visium_ffpe_mouse_brain	Visium FFPE (55 μm spo	Mus	2,264	2,075	4959 $\times$ 5307	spot (multi-cell)
visium_human_breast	Visium (55 μm spots, h	Homo	4,869	2,087	6395 $\times$ 6750	spot (multi-cell)
visium_human_heart	Visium (55 μm spots, 1	Homo	331	2,051	5877 $\times$ 6040	spot (multi-cell)
visium_human_lymph_node	Visium (55 μm spots, 1	Homo	4,025	2,073	5967 $\times$ 6744	spot (multi-cell)
visium_mouse_brain	Visium (55 μm spots, 1	Mus	2,691	2,079	4822 $\times$ 6379	spot (multi-cell)
visium_mouse_brain_coronal	Visium (55 μm spots, 1	Mus	2,896	2,082	4510 $\times$ 6689	spot (multi-cell)
visium_mouse_kidney	Visium (55 μm spots, 1	Mus	1,433	2,079	4974 $\times$ 4894	spot (multi-cell)
xenium_mouse_brain	Xenium In Situ, 248-ge	Mus	36,362	248	5212 $\times$ 3128	single cell

Table 9: Sample size behind each experiment: total runs, distinct tissue sections, and random seeds per configuration. $\dagger$ marks a single seed, at which we report no ordering between models. This table exists because a claim in an earlier version rested on one seed and seventy held-out locations without the text saying so.

experiment	runs	sections	seeds
Multi-section benchmark	350	23	2
Converged comparison	12	1	3
Ablations (matched budget)	12	1	3
Diffusion-length nulls	16	–	2
Spectral sweep	18	1	2
Biological preservation	48	10	1 $\dagger$
Robustness	48	–	1 $\dagger$
Counterfactual perturbation	8	1	2

697 H.5 Dataset inventory

698 H.6 Sample sizes

699 H.7 Qualitative reconstruction

700 H.8 Multi-section benchmark

701 H.9 Robustness

702 H.10 Spectral matching

703 Full discussion

704 Section 5 reports that our predicted fields are too smooth, and Section H.11 shows this is structural
705 rather than an artifact of the training budget. The natural remedy is a term matching the radially
706 averaged power spectrum of the predicted field to that of the measured field. We implement it,
707 sweep its weight, and report the trade-off (Table 12, Fig. 6; 2 seeds per point).




Figure 4: **Predicted expression at held-out locations.** Grey marks the contiguous blocks hidden from every encoder. Genes are chosen to span the performance range rather than to favor any model — the top row is a well-reconstructed gene, the bottom row one near the lower quartile — and the per-gene r printed beneath each map is for that gene alone, not the benchmark mean. The failure mode the paper reports is visible directly: our predictions are smoother than the measurement, which costs us Moran’s I even where correlation is comparable.




Figure 5: **Benchmark across 22 tissue sections.** (a) NRDO against each baseline, one point per section. (b) Mean paired difference with a percentile bootstrap 95% CI. (c) Fraction of sections on which NRDO wins. Full table and paired statistics in Appendix H.

Table 10: Masked spatial reconstruction across 23 tissue sections spanning four technologies; mean $\pm$ s.d. over sections, 2 seeds each. Excluded for incomplete coverage: Gaussian Process (1/23), SpaGE-style (17/23). Stars: Holm-corrected Wilcoxon signed-rank p against NRDO, section as the unit of analysis (* $p < 0.05$, ** $p < 0.01$, *** $p < 0.001$). Win record and effect sizes: Table 4.

model	n	Pearson $r \uparrow$	SSIM $\uparrow$	$ \Delta I \downarrow$
STAGATE-style	23	$0.165 \pm 0.067^{**}$	$0.319 \pm 0.064^*$	$0.764 \pm 0.049^{***}$
Autoencoder (non-spatial)	23	$0.163 \pm 0.067^{***}$	$0.256 \pm 0.083^{***}$	$0.755 \pm 0.054^{***}$
GNN (GCN)	23	$0.162 \pm 0.065^{***}$	$0.317 \pm 0.063^*$	$0.791 \pm 0.047^{***}$
Tangram-style	23	$0.157 \pm 0.068^{***}$	0.338 ± 0.076	$0.794 \pm 0.073^{***}$
GP, multi-bandwidth	23	$0.129 \pm 0.056^{***}$	$0.295 \pm 0.055^{***}$	$0.759 \pm 0.064^{***}$
Neural field (SIREN)	23	$0.113 \pm 0.054^{***}$	$0.251 \pm 0.056^{***}$	$0.593 \pm 0.111^{***}$
NRDO (ours)	23	0.177 ± 0.068	0.329 ± 0.068	0.844 ± 0.048

708 The form of the term matters more than its weight. Matching the *absolute* spectrum over all bands
709 leaves an amplitude degree of freedom the model can exploit without redistributing energy across
710 scales — a controlled check finds it penalizes a purely rescaled field more heavily than a genuinely
711 smoothed one — and its best setting costs -78% of the Pearson r to gain -9% of $|\Delta I|$. Matching
712 the spectrum *normalized* by total power over the upper half of the band removes that freedom and
713 penalizes the frequencies a dissipative operator actually loses. At $\lambda = 0.01$ it reaches $|\Delta I| = 0.710$,

Table 11: Held-out Pearson r under input corruption. Each model is re-trained under each corruption with identical splits, since the realistic deployment is training on the data one has. Columns are increasing corruption level (for *density*, decreasing fraction of the section retained).

model	L1	L2	L3	L4
<i>noise</i>				
STAGATE-style	0.208	0.195	0.177	0.124
NRDO (ours)	0.201	0.187	0.170	0.118
GNN (GCN)	0.198	0.185	0.168	0.115
<i>dropout</i>				
STAGATE-style	0.208	0.207	0.206	0.206
NRDO (ours)	0.201	0.196	0.197	0.193
GNN (GCN)	0.198	0.191	0.194	0.188
<i>density</i>				
NRDO (ours)	0.195	0.158	0.197	0.201
STAGATE-style	0.173	0.163	0.187	0.208
GNN (GCN)	0.169	0.149	0.169	0.198
<i>knn</i>				
STAGATE-style	0.208	0.208	0.209	0.209
NRDO (ours)	0.201	0.201	0.201	0.201
GNN (GCN)	0.199	0.198	0.197	0.195

714 better than the absolute form achieves at any weight, for -15% of the accuracy; the curve turns over
715 above that, so it is an optimum rather than a point on a slope.

716 The conclusion is a bound, not a fix. Across every weight and both forms the predicted autocorre-
717 lation bottoms out at $I_{\text{pred}} = 0.869$ against a measured 0.174: weighting the term heavily enough
718 to destroy predictive accuracy still does not bring the reconstruction near the roughness of the data.
719 We keep $\lambda = 0$ elsewhere and conclude that the smoothness belongs to the operator class rather than
720 to the objective.

Table 12: Spectral matching: the trade-off between reconstruction accuracy and spatial fidelity as the term’s weight λ is swept, 2 seeds per point, on the primary section. $\lambda = 0$ is the model used everywhere else in this paper. The measured field has $I = 0.174$, so a faithful reconstruction would drive I_{pred} down toward that value. Two forms are compared: matching the absolute power spectrum across all radial bands, and matching the spectrum normalized by total power over the upper half of the band. The first leaves an amplitude degree of freedom that the model can exploit without redistributing energy across scales; the second removes it and penalizes only the frequencies a dissipative operator actually loses.

weight	Pearson $r \uparrow$	SSIM $\uparrow$	$ \Delta I \downarrow$	I_{pred}	$ \Delta C \downarrow$
<i>absolute spectrum, all bands</i>					
$\lambda = 0$	0.249 ± 0.005	0.405 ± 0.007	0.760 ± 0.004	0.934 ± 0.004	0.727 ± 0.003
$\lambda = 0.001$	0.240 ± 0.004	0.399 ± 0.004	0.758 ± 0.003	0.932 ± 0.003	0.728 ± 0.002
$\lambda = 0.01$	0.184 ± 0.007	0.368 ± 0.017	0.781 ± 0.018	0.955 ± 0.018	0.745 ± 0.010
$\lambda = 0.1$	0.123 ± 0.004	0.405 ± 0.002	0.720 ± 0.001	0.894 ± 0.000	0.711 ± 0.000
$\lambda = 1$	0.055 ± 0.007	0.401 ± 0.023	0.695 ± 0.003	0.869 ± 0.003	0.698 ± 0.003
<i>normalized spectrum, high band</i>					
$\lambda = 0.01$	0.210 ± 0.004	0.384 ± 0.001	0.710 ± 0.003	0.884 ± 0.003	0.702 ± 0.001
$\lambda = 0.1$	0.169 ± 0.000	0.274 ± 0.000	0.717 ± 0.002	0.892 ± 0.002	0.707 ± 0.000
$\lambda = 0.3$	0.135 ± 0.003	0.266 ± 0.001	0.712 ± 0.000	0.886 ± 0.000	0.703 ± 0.000
$\lambda = 1$	0.102 ± 0.000	0.256 ± 0.002	0.721 ± 0.002	0.896 ± 0.002	0.709 ± 0.002




Figure 6: **Spectral matching.** (a) The trade-off: up and to the left is better. Points are labeled by weight λ ; $\lambda = 0$ is the model used everywhere else. (b) Predicted global autocorrelation against λ . No weight of either form brings I_{pred} near the measured value.

721 H.11 Converged single-section comparison

722 Full discussion

723 The benchmark trains every model for a fixed, reduced number of epochs, so its ordering could be
 724 a fact about the budget rather than the models. We settle this on visium_mouse_brain, the section
 725 where the ordering changes with budget, training every model to a shared early-stopping criterion
 726 on the full section with 3 seeds (Appendix H, Table 13). NRDO attains 0.245 ± 0.006 against
 727 0.232 ± 0.001 for the strongest baseline (STAGATE-style), winning on 3/3 seeds against every
 728 comparator with $d_z = 1.99$ – 2.84 , having *lost* to that baseline at the benchmark budget. The budget
 729 is therefore conservative for NRDO here rather than neutral: Table 10 establishes consistency across
 730 anatomy at a fixed budget, not that its margins are the converged margins.

731 Two findings survive convergence and matter more than the ordering. The non-spatial autoencoder
 732 still matches the graph models (the best leads it by 0.004 Pearson r), so their near-tie is a property
 733 of this task rather than of undertraining. And NRDO retains the largest error in Moran’s I (0.760
 734 against 0.705), so the over-smoothing is structural. NRDO costs 653 s against 100–181 s per run on
 735 one CPU.

Table 13: Converged comparison on visium_mouse_brain: the full section, no subsampling, trained to a shared early-stopping criterion on held-out validation rather than to a fixed epoch count, 3 seeds. d_z and the win record are paired over seeds against NRDO. This addresses whether the reduced-budget ordering of Table 10 is the converged ordering. It is not: at 200 epochs on this section NRDO scores below the STAGATE-style baseline, and at convergence it scores above it, so the benchmark budget is conservative for NRDO here rather than neutral. Two further points survive convergence — the non-spatial autoencoder still matches the graph models, so their near-tie is a property of the task and not of undertraining; and NRDO retains the largest error in Moran’s I , so the over-smoothing is structural. Wall time is single-CPU and is reported because NRDO is several times more expensive than every baseline.

model	Pearson $r \uparrow$	RMSE $\downarrow$	SSIM $\uparrow$	$ \Delta I \downarrow$	$ \Delta C \downarrow$	wall	d_z	wins
STAGATE-style	0.232 ± 0.001	0.255 ± 0.001	0.393 ± 0.002	0.708 ± 0.002	0.683 ± 0.001	181 s	1.99	3/3
Autoencoder (non-spatial)	0.228 ± 0.002	0.257 ± 0.001	0.392 ± 0.003	0.705 ± 0.004	0.680 ± 0.003	100 s	2.25	3/3
GNN (GCN)	0.227 ± 0.001	0.255 ± 0.001	0.391 ± 0.003	0.724 ± 0.008	0.692 ± 0.006	170 s	2.84	3/3
NRDO (ours)	0.245 ± 0.006	0.256 ± 0.007	0.399 ± 0.009	0.760 ± 0.009	0.726 ± 0.007	653 s	–	–

Table 14: Null controls for the recovered diffusion length. Every row refits the identical architecture at the identical budget on the primary section. Shuffling coordinates destroys all spatial structure while preserving every gene’s marginal; those rows reach $r \approx 0$ yet recover the length scale of the *untrained* model, so the quantity is close to its initialization rather than inferred from tissue. The bandwidth and lattice sweeps show why neither is the mechanism: the length is invariant in microns across a fourfold change in pitch while the same quantity in lattice cells moves by the same factor.

condition	length (μm)	length (cells)	held-out r
measured tissue, $H=64$	374.6 ± 1.7	3.76	0.248
splat $\sigma = 0.5$ cells	375.5 ± 0.9	3.77	0.247
splat $\sigma = 2$ cells	377.7 ± 1.4	3.79	0.247
splat $\sigma = 4$ cells	376.4 ± 0.7	3.77	0.247
lattice $H=32$ (pitch $199 \mu\text{m}$)	376.3 ± 0.2	1.89	0.245
lattice $H=128$ (pitch $50 \mu\text{m}$)	378.2 ± 5.6	7.58	0.243
coordinates shuffled, $H=64$	404.5 ± 0.1	4.06	0.004
coordinates shuffled, $H=128$	404.7 ± 0.1	8.12	0.004

736 H.12 Null controls for the recovered diffusion length

737 The rows above the rule refit the model on measured tissue under varied encoder and discretization
738 settings; the rows below refit it on sections whose expression has been permuted across positions.
739 The shuffled fits attain $r \approx 0$, as they must, and yet return a length scale within -0.06% of the
740 untrained model’s $405 \mu\text{m}$. Measured tissue moves the same quantity by -7.4% . Section 5 reports
741 what this does and does not license.

742 H.13 Ablation sweep

Full sweep at the reduced budget; the two matched-budget controls are reported in Section 6.

Table 15: Ablations on the mouse-brain Visium section. Each variant removes exactly one ingredient with all else held fixed. Δr is the change in held-out Pearson r relative to the full model. The *— dynamics* row is the critical control: it disables the operator entirely ($T=0$) while leaving its parameters allocated, so the two rows are exactly parameter-matched. **This table uses a smaller training budget than the main benchmark** (fewer epochs and seeds); it is internally consistent, but absolute values are not comparable across the two tables.

variant	params	Pearson $r \uparrow$	Δr
Full model	2.20M	0.233 ± 0.005	—
— dynamics ($T=0$)	2.20M	0.227 ± 0.001	-0.007
— diffusion term	2.20M	0.226 ± 0.004	-0.007
— reaction term	2.19M	0.227 ± 0.001	-0.006
— PDE constraints	2.20M	0.233 ± 0.005	-0.000
— biological regularizers	2.20M	0.233 ± 0.005	-0.000
isotropic D	2.20M	0.229 ± 0.004	-0.004
state-dependent D	2.20M	0.236 ± 0.004	+0.003
discrete GNN operator	0.61M	0.223 ± 0.001	-0.011
latent $C=8$	1.07M	0.213 ± 0.005	-0.021
latent $C=16$	1.30M	0.220 ± 0.002	-0.013
latent $C=64$	5.77M	0.237 ± 0.000	+0.004

743

744 H.14 Cross-tissue and cross-resolution transfer

745 H.15 Developmental forecasting

746 Horizon sweep for $E9.5 \rightarrow E10.5$. Consecutive MOSTA stages are distinct embryos, so the compar-
747 ison is at the level of the rasterized field after isotropic normalization to a common frame.

Table 16: Cross-tissue, cross-species transfer: adult mouse brain $\rightarrow$ human breast carcinoma. Shared gene vocabulary: 390 genes. Mean $\pm$ s.d. over seeds.

model	Pearson $r \uparrow$	RMSE $\downarrow$	SSIM $\uparrow$
<i>source (in-domain)</i>			
NRDO (ours)	0.214 $\pm$ 0.004	0.252 $\pm$ 0.004	0.369 $\pm$ 0.006
STAGATE-style	0.214 $\pm$ 0.000	0.249 $\pm$ 0.000	0.362 $\pm$ 0.001
GNN (GCN)	0.206 $\pm$ 0.001	0.250 $\pm$ 0.000	0.363 $\pm$ 0.004
Gaussian Process	0.146 $\pm$ 0.002	0.291 $\pm$ 0.004	0.289 $\pm$ 0.003
<i>target (zero-shot)</i>			
STAGATE-style	0.071 $\pm$ 0.006	0.403 $\pm$ 0.001	0.285 $\pm$ 0.008
Gaussian Process	0.070 $\pm$ 0.004	0.453 $\pm$ 0.001	0.311 $\pm$ 0.008
GNN (GCN)	0.056 $\pm$ 0.009	0.415 $\pm$ 0.006	0.250 $\pm$ 0.004
NRDO (ours)	-0.005 $\pm$ 0.010	0.504 $\pm$ 0.016	0.165 $\pm$ 0.009
<i>target (decoder-only fine-tune)</i>			
STAGATE-style	0.129 $\pm$ 0.009	0.386 $\pm$ 0.001	0.387 $\pm$ 0.005
GNN (GCN)	0.112 $\pm$ 0.005	0.390 $\pm$ 0.003	0.378 $\pm$ 0.006
NRDO (ours)	0.067 $\pm$ 0.021	0.398 $\pm$ 0.005	0.300 $\pm$ 0.023
Gaussian Process	—	—	—
<i>target (in-domain oracle)</i>			
STAGATE-style	0.149 $\pm$ 0.000	0.375 $\pm$ 0.000	0.433 $\pm$ 0.003
GNN (GCN)	0.145 $\pm$ 0.001	0.377 $\pm$ 0.000	0.426 $\pm$ 0.001
NRDO (ours)	0.136 $\pm$ 0.002	0.397 $\pm$ 0.002	0.329 $\pm$ 0.003
Gaussian Process	0.068 $\pm$ 0.002	0.459 $\pm$ 0.001	0.301 $\pm$ 0.008
<i>target (training-mean floor)</i>			
mean	-0.000	0.408	0.342

Table 17: Cross-resolution transfer: 55 μ m Visium spots $\rightarrow$ single-cell Xenium. Shared gene vocabulary: 248 genes. Mean $\pm$ s.d. over seeds.

model	Pearson $r \uparrow$	RMSE $\downarrow$	SSIM $\uparrow$
<i>source (in-domain)</i>			
NRDO (ours)	0.261 $\pm$ 0.006	0.246 $\pm$ 0.001	0.392 $\pm$ 0.005
STAGATE-style	0.246 $\pm$ 0.000	0.247 $\pm$ 0.001	0.370 $\pm$ 0.002
GNN (GCN)	0.236 $\pm$ 0.002	0.249 $\pm$ 0.001	0.363 $\pm$ 0.002
Gaussian Process	0.158 $\pm$ 0.005	0.291 $\pm$ 0.004	0.278 $\pm$ 0.011
<i>target (zero-shot)</i>			
STAGATE-style	0.242 $\pm$ 0.002	1.780 $\pm$ 0.002	0.631 $\pm$ 0.003
GNN (GCN)	0.234 $\pm$ 0.002	1.798 $\pm$ 0.005	0.618 $\pm$ 0.002
Gaussian Process	0.183 $\pm$ 0.008	2.114 $\pm$ 0.032	0.577 $\pm$ 0.003
NRDO (ours)	0.124 $\pm$ 0.017	1.855 $\pm$ 0.030	0.544 $\pm$ 0.016
<i>target (in-domain oracle)</i>			
NRDO (ours)	0.277 $\pm$ 0.005	1.745 $\pm$ 0.006	0.667 $\pm$ 0.004
STAGATE-style	0.269 $\pm$ 0.001	1.756 $\pm$ 0.002	0.677 $\pm$ 0.002
GNN (GCN)	0.267 $\pm$ 0.001	1.760 $\pm$ 0.001	0.675 $\pm$ 0.001
Gaussian Process	0.165 $\pm$ 0.003	2.142 $\pm$ 0.022	0.559 $\pm$ 0.017
<i>target (training-mean floor)</i>			
mean	-0.000	1.877	0.398

Table 18: Developmental forecasting on Stereo-seq: the E9.5 field is encoded, integrated forward for T operator steps, and scored against the measured E10.5 field. **Consecutive stages are different embryos**, so there is no cell-to-cell correspondence and the comparison is made at the level of the rasterized field after isotropic normalization to a common frame; it inherits the error of that coarse registration. *Persistence* predicts $E10.5 = E9.5$ and is the reference the operator must beat for its dynamics to carry temporal information.

model	horizon	field $r \uparrow$	field RMSE $\downarrow$	genes with $r > 0$
Persistence (no dynamics)	–	0.064	0.346	61%
Spatial-mean predictor	–	0.000	0.257	4%
NRDO	$T=0$	0.082 ± 0.001	0.320	74%
NRDO	$T=2$	0.089 ± 0.000	0.305	72%
NRDO	$T=4$	0.092 ± 0.000	0.297	73%
NRDO	$T=8$	0.094 ± 0.000	0.289	72%
NRDO	$T=16$	0.095 ± 0.001	0.283	72%
NRDO	$T=32$	0.090 ± 0.003	0.285	70%

H.16 In-silico morphogen source

Split-half protocol of Section 5.6: the perturbation direction is defined from a random half of each pathway and enrichment scored on the held-out half, against a permutation null over matched gene sets.

Table 19: In-silico morphogen source (*bead implant*). The latent perturbation direction is defined from a random half of each pathway’s genes; the table reports where the *held-out* half ranks in the response magnitude distribution (lower is stronger; 50% is chance). p is a permutation test over random gene sets of matched size. Response half-width is the distance at which the predicted response falls to half its peak. $*p < 0.05$.

pathway	genes	held-out rank (%)	null (%)	p	half-width (μm)
BMP	22	48.6 ± 6.0	49.7	0.475	575 ± 154
FGF	19	72.6 ± 0.8	50.3	0.992	618 ± 58
SHH	15	56.6 ± 6.7	50.4	0.698	466
WNT	26	56.4 ± 3.9	49.9	0.762	649 ± 143

H.17 Perturb-seq consistency

An out-of-context probe: Norman et al. profiled non-spatial K562 cells whereas the operator is fitted to tissue. With $n = 7$ testable perturbations the comparison is underpowered and we report it as inconclusive.

Table 20: Agreement between the model’s counterfactual gene–gene responses and measured CRISPRa responses from Norman et al. (2019). **This is an out-of-context probe:** the Perturb-seq data are non-spatial K562 cells while the operator is fitted to human breast tissue, so it tests whether the reaction module encodes generic transcriptional coupling, not whether it recovered tissue-specific signaling. Null is a within-perturbation label permutation; p is a Wilcoxon signed-rank test against that null.

model	#perturb.	Spearman ρ	null	% positive	p
STAGATE-style	7	0.010 ± 0.000	+0.004	64%	0.633
NRDO (ours)	7	-0.018 ± 0.009	-0.009	57%	0.844




Figure 7: Latent channels of the relaxed field (a) and their correlation with canonical morphogen-pathway scores (b). Section 5.6 shows these correlations do not survive a causal split-half test.




Figure 8: **The fitted operator.** (a) A latent channel relaxing under the learned dynamics. (b) Per-channel diffusion tensors as length-scale ellipses, showing the anisotropy is used. (c) Dispersion relation of the linearized operator, which decreases monotonically in $|k|$ and so supports no Turing band.

756 H.18 Latent fields

757 I Reproducibility

758 All datasets download automatically with a recorded SHA256 manifest; every table and figure in this
 759 paper is regenerated from run artifacts by a single command; configurations, seeds and checkpoints
 760 are released.