# ZERO HOUR

## DEFUSAL MANUAL

The defuser describes what they see. You find the matching rule and say what to do. Don't look at the bomb.

New to the bomb? Bomb basics, at the end, shows how the case is built and what its parts look like.

Revision 575058f6

# CONTENTS

**1 Wires ..... 2**
1.1 3 wires ..... 2
1.2 4 wires ..... 2
1.3 5 wires ..... 2
1.4 6 wires ..... 2
1.5 Rear plate ..... 2

**2 Button ..... 3**
2.1 Holding the button ..... 3

**3 Glyphs ..... 4**
3.1 Rear plate ..... 4

**4 Simon ..... 5**
4.1 Serial number contains a vowel (A, E, I, O, U) ..... 5
4.2 Serial number has no vowel ..... 5
4.3 Rear plate ..... 5

**5 Password ..... 6**

**6 Switches ..... 7**
6.1 Rear plate ..... 7

**7 Morse ..... 8**

**8 Memory ..... 9**

**9 Knob ..... 10**

**10 Breaker ..... 11**
10.1 Rear plate ..... 11

**11 Combination ..... 12**

**12 Fuses ..... 13**
12.1 Rear plate ..... 13

**13 Gears ..... 14**
13.1 Rear plate ..... 14

**A Bomb basics ..... 15**
A.1 The case ..... 15
A.2 Parts on the side panels ..... 16
A.3 Rotary encoders ..... 16
A.4 Knife switch ..... 17
A.5 Modules and strikes ..... 18

# 1 WIRES

Cut exactly one wire. Count wires from the top. Use the section that matches the number of wires and take the first rule that applies.

## 1.1 3 wires

1. If there are no red wires, cut the second wire.
2. Otherwise, if the last wire is white, cut the last wire.
3. Otherwise, if there is more than one blue wire, cut the last blue wire.
4. Otherwise, cut the last wire.

## 1.2 4 wires

1. If the encoders add up to 12 or more and the last wire is red, cut the last wire.
2. Otherwise, if there is more than one red wire and the last digit of the serial number is odd, cut the last red wire.
3. Otherwise, if the last wire is yellow and there are no red wires, cut the first wire.
4. Otherwise, if there is exactly one blue wire, cut the first wire.
5. Otherwise, if there is more than one yellow wire, cut the last wire.
6. Otherwise, cut the second wire.

## 1.3 5 wires

1. If the last wire is black and the last digit of the serial number is odd, cut the fourth wire.
2. Otherwise, if there is exactly one red wire and more than one yellow wire, cut the first wire.
3. Otherwise, if there are two coin cells, cut the third wire.
4. Otherwise, if there are no black wires, cut the second wire.
5. Otherwise, cut the first wire.

## 1.4 6 wires

1. If there are no yellow wires and the last digit of the serial number is odd, cut the third wire.
2. Otherwise, if there is exactly one yellow wire and more than one white wire, cut the fourth wire.
3. Otherwise, if there are no red wires, cut the last wire.
4. Otherwise, if the coin cells add up to 3 volts or more, cut the second wire.
5. Otherwise, cut the fourth wire.

## 1.5 Rear plate

The rear plate is the harness plug the wires run into. It has as many brass pins as the last digit of the serial number: an odd number of pins means the last digit is odd. An empty plug means the digit is 0, which is even. It saves searching the sides of the bomb for the serial.

# 2 BUTTON

Tell the defuser to hold the button or tap it. Take the first rule that applies.

1. If the button is blue and the label says ABORT, hold it.
2. If there is more than one battery and the label says DETONATE, press and immediately release it.
3. If the button is white and there is a lit indicator labeled CAR, hold it.
4. If there are more than two batteries and there is a lit indicator labeled FRK, press and immediately release it.
5. If the button is yellow, hold it.
6. If there is a coin cell marked CR2016, press and immediately release it.
7. If the button is red and the label says HOLD, press and immediately release it.
8. If the encoders add up to an odd number and the label says PRESS, press and immediately release it.
9. Otherwise, hold it.

## 2.1 Holding the button

A colored light bar glows beside the button once it is held. Check its color, then tell the defuser to release when the countdown timer shows the matching digit in *any* position.

| Light bar color | Release when the timer shows |
|---|---|
| blue | 4 |
| white | 1 |
| yellow | 5 |
| Any other color | 1 |

"Press and immediately release" means a quick tap, well under half a second.

# 3 GLYPHS

The four glyphs on the module all appear in exactly one of the columns below. Press them in the order they appear in that column, top to bottom. A wrong press is a strike; glyphs already pressed stay lit.

| I | II | III | IV |
|---|---|---|---|
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |

## 3.1 Rear plate

The rear plate is stamped with four numerals, I to IV. One is raised and amber: that is the column to use, counted left to right in the table above. It saves you searching all four columns.

# 4 SIMON

The ring flashes a growing sequence of colors. The defuser does *not* repeat the flashes: for each flash, press the color shown in the table instead. The table depends on the serial number and the current number of strikes.

After each correct stage the sequence grows by one flash and replays from the start. Press the translated colors for the whole sequence each time. If the defuser pauses, the sequence repeats. The dots in the center fill in as stages are completed.

## 4.1 Serial number contains a vowel (A, E, I, O, U)

| Strikes | red flashes | blue flashes | green flashes | yellow flashes |
|---|---|---|---|---|
| 0 | blue | red | yellow | green |
| 1 | yellow | green | blue | red |
| 2 | green | red | yellow | blue |

## 4.2 Serial number has no vowel

| Strikes | red flashes | blue flashes | green flashes | yellow flashes |
|---|---|---|---|---|
| 0 | blue | yellow | green | red |
| 1 | red | blue | yellow | green |
| 2 | yellow | green | blue | red |

## 4.3 Rear plate

The rear plate is the back of the toy: a round speaker grille with a label on the cone. The label lists the vowels in the serial number, or shows a dash when there are none, which picks the table above.

# 5 PASSWORD

The module shows five columns of letters. Ask the defuser to read out the six letters available in each column (use the arrow keys to cycle through them). Exactly one word from the list below can be spelled using one letter from each column in order. Tell the defuser which word to spell, then press Submit.

| | | | | |
|---|---|---|---|---|
| about | found | place | still | three |
| after | great | plant | study | water |
| again | house | point | their | where |
| below | large | right | there | which |
| could | learn | small | these | world |
| every | never | sound | thing | would |
| first | other | spell | think | write |

# 6 SWITCHES

Each switch has a lamp above it. A switch should be **up** (tilted toward the top of the module) when its lamp is lit and **down** when it is dark, but some switches are reversed. Work out each switch from the list below, tell the defuser which ones to set up, then have them press Confirm.

1. Switch 1: flip it if the last digit of the serial number is odd.
2. Switch 2: flip it if any indicator is lit.
3. Switch 3: flip it if there are two or more batteries (the AA and D cells, not coin cells).
4. Switch 4: flip it if there is at least one coin cell.
5. Switch 5: flip it if the encoders add up to an odd number. With no encoders the sum is 0, which counts as even.

"Flip it" means the opposite of the lamp: dark means up, lit means down. Rule 5 reads the encoders as they are at the moment of pressing Confirm.

## 6.1 Rear plate

The rear plate is the switch bank's memory backup. Its window reads BACKUP FITTED when the bomb has any coin cells and BACKUP EMPTY when it has none, which is what switch 4 needs. The window is a printed flag, not a coin cell: don't count it as one.

# 7 MORSE

The lamp flashes a word in Morse code, then pauses and repeats. A short flash is a dot, a long flash is a dash, and a longer dark gap separates letters. Decode the word with the chart, find its frequency in the table, tell the defuser to tune to it with the arrow keys and press Transmit.

| | | | |
|---|---|---|---|
| A ·– | B –··· | C –·–· | D –·· |
| E · | F ··–· | G ––· | H ···· |
| I ·· | J ·––– | K –·– | L ·–·· |
| M –– | N –· | O ––– | P ·––· |
| Q ––·– | R ·–· | S ··· | T – |
| U ··– | V ···– | W ·–– | X –··– |
| Y –·–– | Z ––·· | | |

| Word | Frequency (MHz) |
|---|---|
| fuse | 3.505 |
| volt | 3.515 |
| coil | 3.522 |
| bolt | 3.532 |
| grid | 3.535 |
| relay | 3.542 |
| laser | 3.545 |
| diode | 3.552 |

# 8 MEMORY

Five stages. Each stage the display shows a number from 1 to 4 and the four keys carry the labels 1 to 4 in a new order. Positions are counted left to right. Look up the stage and the displayed number below and tell the defuser which key to press. **Write down the position and the label of every key pressed**, because later stages refer back to them. A wrong press is a strike and sends the module back to stage 1.

| Stage | Shows 1 | Shows 2 | Shows 3 | Shows 4 |
|---|---|---|---|---|
| 1 | press the key in position 2 | press the key in position 1 | press the key in position 4 | press the key in position 3 |
| 2 | press the key labeled 3 | press the key in the same position as in stage 1 | press the key in position 1 | press the key with the same label as in stage 1 |
| 3 | press the key with the same label as in stage 2 | press the key in position 4 | press the key in the same position as in stage 1 | press the key labeled 1 |
| 4 | press the key in position 3 | press the key with the same label as in stage 3 | press the key in the same position as in stage 2 | press the key labeled 2 |
| 5 | press the key in the same position as in stage 4 | press the key with the same label as in stage 1 | press the key with the same label as in stage 4 | press the key in the same position as in stage 3 |

# 9 KNOB

Six lamps (two rows of three) show a pattern. Find it in the table to learn where the red notch of the knob must point, then tell the defuser to click the knob round (each click turns it a quarter clockwise) and press Lock. Filled circles are lit lamps. "Up" is the top of the module.

| Pattern | Notch points |
|---|---|
| ● ○ ○<br>● ● ○ | up |
| ○ ● ●<br>○ ○ ● | up |
| ● ● ○<br>○ ● ● | right |
| ○ ○ ●<br>● ○ ○ | right |
| ● ○ ●<br>○ ● ○ | down |
| ○ ● ○<br>● ○ ● | down |
| ● ● ●<br>○ ○ ○ | left |
| ○ ○ ○<br>● ● ● | left |

# 10 BREAKER

This module is linked to the double-throw knife switch on the left or right panel of the bomb: silver blades on a centre hinge with a ribbed black handle. Thrown up (blades in the top contacts) is ON, and thrown a full half turn down (blades in the bottom contacts) is OFF. A green lamp at the top and a red lamp at the bottom show which. The defuser must put the lever in the right position and then press Latch. Work out the position from the displayed number and the lamp:

1. Add the two digits of the displayed number. If the sum is even the switch should be ON (thrown up). If it is odd it should be OFF (thrown down).
2. If the last digit of the serial number is odd, swap: ON becomes OFF and OFF becomes ON.
3. If the lamp is red, swap again. A green lamp changes nothing.

Drag the handle up or down (or just click it) to throw the switch. A wrong Latch is a strike, and the switch can be moved again afterwards.

## 10.1 Rear plate

The rear plate is the breaker's rating plate. Its trip coil number is the last digit of the serial number; rule 2 needs to know whether it is odd.

# 11 COMBINATION

The three digits on the display are a code for the rotary encoders engraved **A**, **B** and **C** on the side panels of the bomb. Each encoder has to be turned to the reading below, then the defuser presses Verify.

1. Encoder A: the first digit plus the number of lit indicators.
2. Encoder B: the second digit plus the number of batteries (the AA and D cells, not coin cells).
3. Encoder C: the third digit plus the number of coin cells.

Only the last digit of each sum counts, so 13 becomes 3. To set an encoder, click the right half of its knob to raise the reading by one and the left half to lower it (9 wraps to 0).

# 12 FUSES

Five fuses sit side by side. Pull exactly one: the one that feeds the circuit named by the first rule that applies. A wrong fuse is a strike.

1. If the serial number contains a vowel, pull the fuse that feeds RADIO.
2. Otherwise, if there are two or more batteries, pull the fuse that feeds SPARK.
3. Otherwise, if any indicator is lit, pull the fuse that feeds LAMPS.
4. Otherwise, pull the fuse that feeds CLOCK.

Which fuse feeds which circuit is only written on the back, so the defuser has to turn the bomb. The amp ratings on the fuses don't matter.

## 12.1 Rear plate

The rear plate is the fuse block's wiring: five terminals, each labelled with its circuit. Seen from behind, the labels run the other way: the first label from the right on the back belongs to the first fuse from the left on the front.

# 13 GEARS

The defuser turns a crank on the front, one full turn per press, then presses Release. The front shows the load: **LIFT** or **DROP**.

1. Direction. LIFT needs the winch drum to turn clockwise, DROP anticlockwise, both as seen from the front. Neighbouring gears turn opposite ways, so count every gear on the back, from the crank's gear to the drum's gear: with an odd number the drum turns the same way as the crank, with an even number the opposite way.
2. Turns. Turn the crank as many times as there are gears with a red dot.

A turn the wrong way is a strike and starts the count again. Release with the wrong number of turns is a strike too.

## 13.1 Rear plate

The rear plate is the gear train: a chain of three to six gears from the crank to the winch drum, some with a red dot. The drawing does not move, so count the gears rather than watch them. Seen from behind the chain runs the other way; that does not change the count.

# A BOMB BASICS

## A.1 The case





Figure 1. The case unfolded. Modules sit in the front bays. A rear plate sits directly behind its module, so seen from behind the columns swap: the plate for module 1 is on the right.

- **Rotate the case.** Modules sit on the front. Everything else is on the other sides, and the positions change on every bomb. The left, right and top panels can carry any component. The bottom only ever carries plates: the serial number plate, and sometimes plain name plates (model or rating) that mean nothing. If a rule needs a component, ask the defuser to turn the bomb and look.
- **Rear plates.** Some modules have a steel rear plate on the back of the bomb, directly behind the module. Seen from behind, left and right swap: a module in the left column on the front has its plate in the right column on the back. Some rear plates repeat a clue from elsewhere on the bomb; others are part of the puzzle, and their module cannot be solved without them. A module without a rear plate has a blank panel behind it. Each module's section says what its plate shows.

## A.2 Parts on the side panels





Figure 2. Parts on the side panels: the serial number plate, battery holders, a coin cell, indicators, and a plain name plate.

- **Serial number.** A white steel plate with a barcode. Rules refer to the last digit (odd or even) and to whether the serial contains a vowel: A, E, I, O or U.
- **Batteries.** Count the individual cells in all battery holders (a single large D cell, or a pair of AA cells). There may be none at all. Coin cells are not batteries.
- **Coin cells.** Flat silver discs in small black holders with a steel clip. The model is stamped on top: CR2032, CR2025 and CR2016 are 3 volt lithium cells (in that order they get thinner), and LR44 is a small, thick 1.5 volt alkaline cell. A bomb can have none, one or two.
- **Indicators.** Small labeled plates with a lens. A lit indicator has a glowing lens and bright text. An unlit one is dark.

## A.3 Rotary encoders





Figure 3. Rotary encoder A, reading 3: the red pointer aims at the reading. Clicking the right half of the knob raises the reading by one, the left half lowers it.

- **Rotary encoders.** Some bombs have up to three: a knurled aluminium knob on a dial numbered 0 to 9, with a letter (A, B, C) and a colored cap. The reading is the digit the red pointer line aims at, and the digits are printed around the knob. Click the right half of a knob to turn it one step clockwise (the reading goes up, 9 wraps to 0) or the left half to turn it back one step. The mouse wheel and right-click also turn it. Rules read the encoders as they are at the moment you act, so turning one changes the answer. "The encoders add up" means the sum of all readings, and a bomb without encoders adds up to 0. A bomb can carry encoders that no rule uses.

## A.4 Knife switch





Figure 4. The knife switch. ON: thrown up, blades in the top contacts, handle above the base, green lamp lit. OFF: thrown a half turn down, blades in the bottom contacts, handle below the base, red lamp lit.

- **Knife switch.** Some bombs have a double-throw knife switch on the left or right panel: a dark graphite base with two silver blades on a centre hinge, silver contacts and terminal blocks with socket-head screws at the top and the bottom, and a ribbed black handle with an orange collar. Thrown up, with the blades in the top contacts and the handle above the base, it is ON. Thrown a full half turn down, with the blades in the bottom contacts and the handle below the base, it is OFF. A green lamp at the top and a red lamp at the bottom show which. Drag the handle up or down, or click it to throw it. Only the Breaker module reads it; on any other bomb it is a decoy.

## A.5 Modules and strikes





Figure 5. A module on the front and its rear plate on the back. Some modules have no rear plate; then the panel behind them is blank.

- **Modules.** Each module is independent. Defuse them all before the clock reaches zero. A module's status light turns green when it is safe.
- **Strikes.** Every mistake is a strike, and each strike makes the clock run 25% faster. The third strike detonates the bomb.