

更改导入快件的取件人手机号

更改导入快件的取件人手机号以**POST**方式请求，内容以**JSON**形式在**BODY**里传送

request

path:

```
http://host:port/api/v1/express/modifyPhoneNumber
```

header:

参数	说明
userToken	API使用者的Token,需要同公司快递员权限,获取方法用户API文档说明

body:

参数	必须	说明
expressNumber	Y	快递单号
takeUserPhoneNumber	Y	修改后的取件人手机号
previousPhoneNumber	Y	当前的取件人手机号
logisticsCompany	N	快递公司ID(JSON 格式)

reponse

返回结果以**HttpCode**说明请求结果

状态码	说明
200	格口状态返回成功
400	用户提交参数有误

403	用户没有相关权限
404	快件运单号不存在或快件状态不为 <i>IMPORTED</i> 或 <i>IN_STORE</i>

example

request path:

```
http://localhost:8080/api/v1/express/modifyPhoneNumber
```

header:

```
Content-Type:application/json
userToken:aff1e89da06d45d4b087b4dc51b6f411
```

body:

```
{
  "expressNumber":"TEST0001",
  "takeUserPhoneNumber":"18500000000",
  "previousPhoneNumber":"18600000000",
  "logisticsCompany":{
    "id":"c05b25f809a811e5b6c90610400f8d97"
  }
}
```

response:

```
status:200 OK

{
  "expressNumber": "TEST0001",
  "logisticsCompany": {
    "id": "c05b25f809a811e5b6c90610400f8d97"
  },
  "takeUserPhoneNumber": "18500000000",
  "previousPhoneNumber": "18600000000"
}
```

