

In [1]:

```
import pandas as pd
from sklearn.feature_extraction import DictVectorizer
import matplotlib.pyplot as plt
import seaborn as sns
%matplotlib inline
from pandas.plotting import scatter_matrix
```

In [3]:

```
data = pd.read_csv("bank-additional-full.csv", sep=';')
```

In [4]:

```
data.head()
```

Out[4]:

	age	job	marital	education	default	housing	loan	contact	month
0	56	housemaid	married	basic.4y	no	no	no	telephone	may
1	57	services	married	high.school	unknown	no	no	telephone	may
2	37	services	married	high.school	no	yes	no	telephone	may
3	40	admin.	married	basic.6y	no	no	no	telephone	may
4	56	services	married	high.school	no	no	yes	telephone	may

5 rows × 21 columns

In [5]:

```
data_dict = data.T.to_dict().values()
```

In [6]:

```
vec = DictVectorizer()
signal_array = vec.fit_transform(data_dict).toarray()
feature_names = vec.get_feature_names()
```

In [7]:

```
df = pd.DataFrame(signal_array, columns=feature_names)
df.head()
```

Out[7]:

	age	campaign	cons.conf.idx	cons.price.idx	contact=cellular	contact=telephone
0	56.0	1.0	-36.4	93.994	0.0	1.0
1	57.0	1.0	-36.4	93.994	0.0	1.0
2	37.0	1.0	-36.4	93.994	0.0	1.0
3	40.0	1.0	-36.4	93.994	0.0	1.0
4	56.0	1.0	-36.4	93.994	0.0	1.0

5 rows × 65 columns

In [8]:

```
import numpy as np
import matplotlib.pyplot as plt

from sklearn.datasets import make_classification
from sklearn.ensemble import RandomForestClassifier

X = signal_array[:, :-2]
X = np.hstack((X[:, :14], X[:, 15:]))
y = signal_array[:, -1]
# Build a forest and compute the feature importances
forest = RandomForestClassifier(n_estimators=250,
                               random_state=0)

forest.fit(X, y)
importances = forest.feature_importances_
std = np.std([tree.feature_importances_ for tree in forest.estimators_],
             axis=0)
indices = np.argsort(importances)[::-1]

# Print the feature ranking
print("Feature ranking:")


for f in range(X.shape[1]):
    print("%d. feature %s (%f)" % (f + 1, feature_names[indices[f]], importances[
indices[f]]))

# Plot the feature importances of the forest
plt.figure()
plt.title("Feature importances")
plt.bar(range(X.shape[1]), importances[indices],
        color="r", yerr=std[indices], align="center")
plt.xticks(range(X.shape[1]), indices)
plt.xlim([-1, X.shape[1]])
plt.show()
```

Feature ranking:

1. feature age (0.164047)
2. feature emp.var.rate (0.117021)
3. feature campaign (0.083560)
4. feature month=sep (0.049478)
5. feature nr.employed (0.034052)
6. feature cons.conf.idx (0.027570)
7. feature cons.price.idx (0.023012)
8. feature poutcome=nonexistent (0.022943)
9. feature education=unknown (0.022474)
10. feature euribor3m (0.021194)
11. feature housing=unknown (0.021185)
12. feature housing=yes (0.017653)
13. feature marital=divorced (0.016720)
14. feature education=basic.9y (0.016283)
15. feature education=professional.course (0.016191)
16. feature marital=married (0.014782)
17. feature day_of_week=mon (0.014618)
18. feature day_of_week=wed (0.014473)
19. feature poutcome=success (0.014427)
20. feature day_of_week=thu (0.014243)
21. feature day_of_week=tue (0.014166)
22. feature job=student (0.014008)
23. feature job=unknown (0.014003)
24. feature loan=unknown (0.013831)
25. feature day_of_week=fri (0.013753)
26. feature education=illiterate (0.011851)
27. feature job=admin. (0.011798)
28. feature education=basic.6y (0.011275)
29. feature loan=yes (0.010415)
30. feature job=housemaid (0.009447)
31. feature job=self-employed (0.009024)
32. feature contact=telephone (0.008300)
33. feature duration (0.008157)
34. feature contact=cellular (0.007694)
35. feature pdays (0.007676)
36. feature poutcome=failure (0.007590)
37. feature default=unknown (0.007252)
38. feature default=no (0.007184)
39. feature job=management (0.007027)
40. feature education=basic.4y (0.006778)
41. feature education=university.degree (0.006760)
42. feature job=retired (0.006212)
43. feature job=blue-collar (0.005778)
44. feature month=nov (0.005462)
45. feature job=services (0.005384)
46. feature job=technician (0.004991)
47. feature month=mar (0.004532)
48. feature job=entrepreneur (0.004431)
49. feature month=jun (0.004220)
50. feature marital=unknown (0.003309)

51. feature month=jul (0.003013)
52. feature month=dec (0.002521)
53. feature month=apr (0.002500)
54. feature loan=no (0.002475)
55. feature housing=no (0.002460)
56. feature month=oct (0.002417)
57. feature job=unemployed (0.002256)
58. feature month=may (0.002140)
59. feature month=aug (0.000844)
60. feature marital=single (0.000843)
61. feature education=high.school (0.000297)
62. feature default=yes (0.000001)




In [9]:

```
ax = sns.regplot(x="age", y="y=yes", order=3, data=df, truncate=True)
```


C:\Users\sunny sharma\Anaconda\lib\site-packages\scipy\stats\stats.p
y:1713: FutureWarning: Using a non-tuple sequence for multidimensiona
l indexing is deprecated; use `arr[tuple(seq)]` instead of `arr[seq]
`. In the future this will be interpreted as an array index, `arr[np.
array(seq)]`, which will result either in an error or a different res
ult.

```
return np.add.reduce(sorted[indexer] * weights, axis=axis) / sumval
```



In [11]:

```
ax = sns.regplot(x="campaign", y="y=yes", order=1, data=df, truncate=True)
```



In [12]:

```
df.loc[(df['campaign'] > 15) & (df['y=yes'] == 1)]
```


Out[12]:

	age	campaign	cons.conf.idx	cons.price.idx	contact=cellular	contact=telep
3219	39.0	23.0	-36.4	93.994	0.0	
10162	44.0	17.0	-41.8	94.465	0.0	
17284	59.0	17.0	-42.7	93.918	1.0	
17655	50.0	17.0	-42.7	93.918	0.0	
29980	31.0	17.0	-47.1	93.075	0.0	

5 rows × 65 columns


In [13]:

```
x = sns.regplot(x="emp.var.rate", y="y=yes", order=1, data=df, truncate=True)
```




In [14]:

```
ax = sns.regplot(x="nr.employed", y="y=yes", order=1, data=df, truncate=True)
```




In [15]:

```
ax = sns.regplot(x="age", y="y=yes", order=1, data=df, truncate=True)
```




In [16]:

```
ax = sns.regplot(x="duration", y="y=yes", order=1, data=df, truncate=True)
```




In [17]:

```
ax = sns.regplot(x="contact=telephone", y="y=yes", order=1, data=df, truncate=True)
```




In [18]:

```
ax = sns.regplot(x="month=sep", y="y=yes", order=1, data=df, truncate=True)
```




In [19]:

```
ax = sns.regplot(x="cons.conf.idx", y="y=yes", order=1, data=df, truncate=True)
```




In [20]:

```
ax = sns.regplot(x="poutcome=nonexistent", y="y=yes", order=1, data=df, truncate=True)
```




In [21]:

```
ax = sns.regplot(x="education=unknown", y="y=yes", order=1, data=df, truncate=True)
```




In [22]:

```
ax = sns.regplot(x="euribor3m", y="y=yes", order=1, data=df, truncate=True)
```




In [23]:

```
ax = sns.regplot(x="housing=unknown", y="y=yes", order=1, data=df, truncate=True)
```



In [24]:

```
ax = sns.regplot(x="housing=yes", y="y=yes", order=1, data=df, truncate=True)
```



In [25]:

```
sum(df['y=yes'])/sum(df['campaign'])
```

Out[25]:

0.043875408967982296

In [28]:

```
print ("Nth Call \t Efficiency")
for i in range(1,30):
    goo = sum(df.loc[df['campaign']==i]['y=yes']) / float(df.loc[df['campaign'] >
= i].shape[0])
    print (str((i))+ " \t\t "+str(goo))
```

Nth Call	Efficiency
1	0.05584150723511702
2	0.05143124097511254
3	0.04423551171393342
4	0.03261296660117878
5	0.024077046548956663
6	0.022156573116691284
7	0.015793848711554447
8	0.009566685424873381
9	0.012345679012345678
10	0.010968921389396709
11	0.01380897583429229
12	0.004335260115606936
13	0.007054673721340388
14	0.002105263157894737
15	0.0049261083743842365
16	0.0
17	0.013157894736842105
18	0.0
19	0.0
20	0.0
21	0.0
22	0.0
23	0.008620689655172414
24	0.0
25	0.0
26	0.0
27	0.0
28	0.0
29	0.0

In [30]:

```

print("For age upto 30")
print ("Nth Call \t Efficiency")
for i in range(1,30):
    num = float(df[(df['age'] <= 30) & (df['campaign']==i) & (df['y=yes']==1)].shape[0])
    den = 1+float(df[(df['age'] <= 30) & (df['campaign'] >= i)].shape[0])
    print (str((i))+ " \t\t "+str(num/den))

```

For age upto 30

Nth Call	Efficiency
1	0.07502708559046588
2	0.07100309745055992
3	0.06274509803921569
4	0.04447739065974796
5	0.03882352941176471
6	0.02058319039451115
7	0.030805687203791468
8	0.006493506493506494
9	0.012875536480686695
10	0.005376344086021506
11	0.013888888888888888
12	0.0
13	0.010869565217391304
14	0.0
15	0.014705882352941176
16	0.0
17	0.0
18	0.0
19	0.0
20	0.0
21	0.0
22	0.0
23	0.0
24	0.0
25	0.0
26	0.0
27	0.0
28	0.0
29	0.0

In [31]:

```

print("For age between 30-40")
print ("Nth Call \t Efficiency")
for i in range(1,30):
    num = float(df[(df['age'] <= 40) & (df['age'] > 30) & (df['campaign']==i) & (
df['y=yes']==1)].shape[0])
    den = 1+float(df[(df['age'] <= 40) & (df['age'] > 30) & (df['campaign'] >= i
)]) .shape[0])
    print (str((i))+ " \t\t "+str(num/den))

```

For age between 30-40

Nth Call	Efficiency
1	0.04882216526302942
2	0.042643923240938165
3	0.04005444293214078
4	0.028093645484949834
5	0.02048131080389145
6	0.024279210925644917
7	0.007494646680942184
8	0.008746355685131196
9	0.011538461538461539
10	0.011990407673860911
11	0.015015015015015015
12	0.0076045627376425855
13	0.009523809523809525
14	0.0
15	0.0
16	0.0
17	0.009259259259259259
18	0.0
19	0.0
20	0.0
21	0.0
22	0.0
23	0.02040816326530612
24	0.0
25	0.0
26	0.0
27	0.0
28	0.0
29	0.0

In [32]:

```

print("For age between 40-50")
print ("Nth Call \t Efficiency")
for i in range(1,30):
    num = float(df[(df['age'] <= 50) & (df['age'] > 40) & (df['campaign']==i) & (
df['y=yes']==1)].shape[0])
    den = 1+float(df[(df['age'] <= 50) & (df['age'] > 40) & (df['campaign'] >= i
)])shape[0])
    print (str((i))+ " \t\t "+str(num/den))

```

For age between 40-50

Nth Call	Efficiency
1	0.03925397910360316
2	0.036345108695652176
3	0.03047676523838262
4	0.027820710973724884
5	0.020737327188940093
6	0.016853932584269662
7	0.008012820512820512
8	0.008368200836820083
9	0.005333333333333333
10	0.013888888888888888
11	0.017316017316017316
12	0.005434782608695652
13	0.006622516556291391
14	0.007936507936507936
15	0.0
16	0.0
17	0.023529411764705882
18	0.0
19	0.0
20	0.0
21	0.0
22	0.0
23	0.0
24	0.0
25	0.0
26	0.0
27	0.0
28	0.0
29	0.0

In [33]:

```

print("For age between 50-60")
print ("Nth Call \t Efficiency")
for i in range(1,30):
    num = float(df[(df['age'] <= 60) & (df['age'] > 50) & (df['campaign']==i) & (
df['y=yes']==1)].shape[0])
    den = 1+float(df[(df['age'] <= 60) & (df['age'] > 50) & (df['campaign'] >= i
)])shape[0])
    print (str((i))+ " \t\t "+str(num/den))

```

For age between 50-60

Nth Call	Efficiency
1	0.050709615691277306
2	0.05120481927710843
3	0.040806293018682396
4	0.024681528662420384
5	0.016766467065868262
6	0.02120141342756184
7	0.022004889975550123
8	0.013559322033898305
9	0.024489795918367346
10	0.009900990099009901
11	0.0
12	0.0
13	0.0
14	0.0
15	0.011363636363636364
16	0.0
17	0.016129032258064516
18	0.0
19	0.0
20	0.0
21	0.0
22	0.0
23	0.0
24	0.0
25	0.0
26	0.0
27	0.0
28	0.0
29	0.0

In [34]:

```

print("For age above 60")
print ("Nth Call \t Efficiency")
for i in range(1,30):
    num = float(df[(df['age'] > 60) & (df['campaign']==i) & (df['y=yes']==1)].shape[0])
    den = float(df[(df['age'] > 60) & (df['campaign'] >= i)].shape[0])+1
    print (str((i))+ " \t\t "+str(num/den))

```

For age above 60

Nth Call	Efficiency
1	0.24807903402854006
2	0.25806451612903225
3	0.20512820512820512
4	0.19230769230769232
5	0.12244897959183673
6	0.12121212121212122
7	0.18181818181818182
8	0.06666666666666667
9	0.0
10	0.0
11	0.16666666666666666
12	0.0
13	0.0
14	0.0
15	0.0
16	0.0
17	0.0
18	0.0
19	0.0
20	0.0
21	0.0
22	0.0
23	0.0
24	0.0
25	0.0
26	0.0
27	0.0
28	0.0
29	0.0

In [35]:

```

total_calls = sum(df['campaign'])
print(total_calls)

```

105754.0

In [36]:

```
extra_calls = sum(df[df['campaign']>6]['campaign']) - 6*df[df['campaign']>6].shape[0]
print(extra_calls)
```

12040.0

In [37]:

```
reduction=100*extra_calls/total_calls
print(reduction)
```

11.384912154622993

In [38]:

```
total_sales=float(df[df['y=yes']==1].shape[0])
print(total_sales)
```

4640.0

In [39]:

```
less_costly_sales=float(df[(df['campaign'] <= 6) & (df['y=yes']==1)].shape[0])
print(less_costly_sales)
```

4529.0

In [40]:

```
sales_percent=100*less_costly_sales/total_sales
print(sales_percent)
```

97.60775862068965

In []: