

FABRICATION TOLERANCES UNLESS OTHERWISE SPECIFIED (2)

WELDMENT/FAB. & ASSY. (1)		CASTING		MACHINING/GENERAL			
DIMENSION	TOL	DIMENSION	TOLERANCE	DIMENSION	TOLERANCE		
			ALL PLACES		1PL	2PL	3PL
ABV 0.0 TO 12.0	±.1	ABV 0.0 TO 2.0	+.06 -.06	ABV 0.00 TO 6.00	±.1	±.02	±.005
ABV 12.0 TO 24.0	±.2	ABV 2.0 TO 5.0	+.10 -.06	ABV 6.00 TO 18.00	±.1	±.04	±.010
ABV 24.0	±.3	ABV 5.0 TO 8.0	+.14 -.10	ABV 18.00 TO 36.00	±.1	±.06	±.015
		ABV 8.0 TO 12.0	+.20 -.12	ABV 36.00	±.1	±.08	±.020
DECK THICKNESS	±.2	ABV 12.0 TO 15.0	+.26 -.18	FILLETS & RADII TO BE .06 TO .14			
		ABV 15.0	+.26 -.26	SURFACE TEXTURE SYMBOLS: ANSI Y14.36-1978			
		FILLETS & RADII TO BE .06 TO .26		THREADS TO BE IN ACCORDANCE WITH FED-STD-H2B			

ANGULAR: ± 1° FOR PIPING AND VENTILATION DUCTING
 ± .5° ANGLE BETWEEN HANGER MOUNTS (60°MIN-120°MAX)
 ± .5° FOR ALL OTHER APPLICATIONS