

**For any Custom made items, please submit a copy of your invoice from the Manufacturer or a list/catalog price document with your quote for review purposes.**

**Please note, the equipment, and freight (if applicable), is line 1 of the solicitation and installation is line 2. Please make sure to quote the installation separately from the equipment.**

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0    | 1 ea | <b>WSSF2</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 1    | 1 ea | <b>CONVECTION OVEN, ELECTRIC</b><br> Vulcan VC4ED<br>Convection Oven, electric, single-deck, standard depth, solid state controls, 60 minute timer, (5) nickel plated racks, 23-3/4"H legs with foot, stainless steel front, top & sides, stainless steel door with window, 1/2 HP, 12.5kW, NSF, cUL, UL, ENERGY STAR®<br>1 ea 1 year limited parts & labor warranty, standard<br>1 ea 208v/60/3-ph, 35 amps, standard<br>1 ea Simultaneous doors |
| 2    | 1 ea | <b>HOT FOOD WELL UNIT, DROP-IN, ELECTRIC</b><br>Delfield N8663-FWH<br>DriTec Dry Hot Well, Drop-in, 63", (4) 12"x20" pan capacity, standard flush mount pans, thermostatic temperature controls, top one-piece stainless steel, galvanized steel exterior, dry operation only, standard push in flange gasket, adapter bars, R290, 8 amps, (4) 500W, 208Y-240V/1ph, UL, cUL, NSF                                                                                                                                                    |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3    | 1 ea | <b>HEAT LAMP</b><br> Hatco GRAL-60<br>Glo-Ray® Infrared Strip Heater, 60" W, standard wattage with lights, tubular metal heater rod, aluminum construction, 1350 watts, NSF, CE, cULus, Made in USA<br><br>1 ea NOTE: Sale of this product must comply with Hatco's Minimum Resale Price Policy; consult order acknowledgement for details<br>1 ea NOTE: Includes 24/7 parts & service assistance, call 414-671-6350<br>1 ea One year on-site parts & labor warranty, plus one additional year parts only warranty on all Glo-Ray metal sheathed elements<br>1 ea 120v/60/1-ph<br>1 ea REM TOG-2 (2) Remote toggle switches in lieu of standard built-in toggle, shipped loose (max. 15 amp) (available at time of purchase only)<br>1 ea Note: INCLUDES THE STANDARD TOGGLE FOR LAMP CONTROL<br>1 ea STANDARD Clear Anodized Aluminum housing, finish, standard (available at time of purchase only) |
| 4    | 1 ea | <b>COFFEE BREWER</b><br> BUNN 38700.0043<br>38700.0043 AXIOM®-15-3 Single Coffee Brewer, 200 oz. capacity tank, brews 4.5 gallon per hour, brews 1/2 gallon and 1 gallon batches, BrewWIZARD™ technology LCD display, touch pad to set pot level and tank temperature, BrewLOGIC™ technology, hot water faucet, digital temperature control, includes (1) GPR server (20950.0004), SplashGard® funnel, 120v/60/1-ph, 1600w, 13.3amps, cord attached, UL, NSF<br><br>1 ea Prices include applicable tariffs<br>2 ea 20950.0004 20950.0004 1.5GPR-FF Coffee Server, 1.5 gallon, top handles, fast flow faucet, stainless decor, NSF                                                                                                                                                                                                                                                                    |
| 5    | 1 ea | <b>MILK DISPENSER</b><br> Silver King SKMAJ1-ESAM3<br>Majestic Series Milk Dispenser, refrigerated, single spring-loaded valve, 6 gallon capacity, (accommodates 3, 5, or 6 gallon bags), includes (1) crate, stainless steel interior & exterior with galvanized bottom, shipboard legs, bottom-mounted self-contained refrigeration, R290 Hydrocarbon refrigerant, 1/10 HP, 230v/50/60/1-ph, .83A amps, NEMA 6-15P, cETLus, ETL-Sanitation                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 0    | 1 ea | <b>WSSF1</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 6    | 1 ea | <b>REACH-IN REFRIGERATOR</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

| Item                                                                              | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------------------------------------------------------------------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |      | True Mfg. - General Foodservice T-49-HC<br>Refrigerator, reach-in, two-section, (2) stainless steel doors, (6) PVC coated adjustable wire shelves, interior lighting, stainless steel front, aluminum sides, aluminum interior with stainless steel floor, 4" castors, R290 Hydrocarbon refrigerant, 1/2 HP, 115v/60/1-ph, 5.4 amps, NEMA 5-15P, cULus, UL EPH Classified, Made in USA, ENERGY STAR®                                                                                                                                            |
|                                                                                   | 1 ea | 7 year compressor warranty, 7 years parts warranty, 7 year labor warranty, standard. Visit <a href="http://www.truemfg.com">www.truemfg.com</a> for specifics.                                                                                                                                                                                                                                                                                                                                                                                  |
|                                                                                   | 1 ea | Self-contained refrigeration standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                                                                   | 1 ea | Left door hinged left, right door hinged right standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|                                                                                   | 1 ea | 4" stem castors, standard (adds 5" to OA height)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 7                                                                                 | 1 ea | <b>CONVECTION OVEN, ELECTRIC</b><br>Vulcan VC44ED<br>Convection Oven, electric, double-deck, standard depth, solid state controls, temperature range 150° to 500°F, 60 minute timer with audible alarm per oven, oven cool switch for rapid cool down, independently operated stainless steel doors with double pane windows, porcelain enamel on steel oven interiors, (5) nickel plated racks per oven, stainless steel front, top, sides & 8"H legs, (2) 1/2 HP two speed oven blower-motors, 12 kW each section, NSF, cUL, UL, ENERGY STAR® |
|                                                                                   | 1 ea | 1 year limited parts & labor warranty, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                                                                                   | 1 ea | (2) 208v/60/3-ph, 70 amps total, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|                                                                                   | 2 ea | Simultaneous doors, both ovens                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 8                                                                                 | 1 ea | <b>COFFEE BREWER</b><br>BUNN 38700.0043<br>38700.0043 AXIOM®-15-3 Single Coffee Brewer, 200 oz. capacity tank, brews 4.5 gallon per hour, brews 1/2 gallon and 1 gallon batches, BrewWIZARD™ technology LCD display, touch pad to set pot level and tank temperature, BrewLOGIC™ technology, hot water faucet, digital temperature control, includes (1) GPR server (20950.0004), SplashGard® funnel, 120v/60/1-ph, 1600w, 13.3amps, cord attached, UL, NSF                                                                                     |
|                                                                                   | 1 ea | Prices include applicable tariffs                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|                                                                                   | 2 ea | 20950.0004 20950.0004 1.5GPR-FF Coffee Server, 1.5 gallon, top handles, fast flow faucet, stainless decor, NSF                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 0                                                                                 | 1 ea | <b>LA</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 9                                                                                 | 1 ea | <b>CONVECTION OVEN, ELECTRIC</b><br>Vulcan VC44ED<br>Convection Oven, electric, double-deck, standard depth, solid state controls, temperature range 150° to 500°F, 60 minute timer with audible alarm per oven, oven cool switch for rapid cool down, independently operated stainless steel doors with double pane                                                                                                                                                                                                                            |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |      | <p>windows, porcelain enamel on steel oven interiors, (5) nickel plated racks per oven, stainless steel front, top, sides &amp; 8"H legs, (2) 1/2 HP two speed oven blower-motors, 12 kW each section, NSF, cUL, UL, ENERGY STAR®</p> <p>1 ea 1 year limited parts &amp; labor warranty, standard</p> <p>1 ea (2) 208v/60/3-ph, 70 amps total, standard</p> <p>2 ea Simultaneous doors, both ovens</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 10   | 1 ea | <p><b>KETTLE, ELECTRIC, COUNTERTOP</b></p> <p>Groen TDBC-20A</p>  <p>Kettle, electric, table top, 20 quart capacity, 2/3 jacket, IPX6 water rated electronic Advanced controls with digital display, 1 minute to 10 hour timer, low (2) and high (7) preset intensities with manual capability, 304 stainless steel liner, crank tilt, faucet bracket, support console on right, stainless steel construction, cULus, NSF, Made in USA</p> <p>1 ea (1) year parts &amp; labor, (10) year hemisphere warranty, standard</p> <p>1 ea Start-up Program, included at customer's request (See start-up request form document)</p> <p>1 ea 208v/60/3-ph, 6.3kw, 18.0 amps</p> <p>1 ea Please verify proper operating voltage prior to submitting an order for this equipment</p> <p>1 ea 155237 316 Stainless Steel Liner, in lieu of standard 304 stainless steel</p> <p>1 ea Etch Marks, 1 gallon increments</p> <p>1 ea 128003 Cover, lift-off, for 20 &amp; 24 quart table top kettle</p> <p>1 ea 104278 Brush Set, 2", includes drain valve brush &amp; paddle, for 2" TDO</p> |
| 11   | 1 ea | <p><b>COFFEE BREWER</b></p> <p>BUNN 38700.0043</p> <p>38700.0043 AXIOM®-15-3 Single Coffee Brewer, 200 oz. capacity tank, brews 4.5 gallon per hour, brews 1/2 gallon and 1 gallon batches, BrewWIZARD™ technology LCD display, touch pad to set pot level and tank temperature, BrewLOGIC™ technology, hot water faucet, digital temperature control, includes (1) GPR server (20950.0004), SplashGard® funnel, 120v/60/1-ph, 1600w, 13.3amps, cord attached, UL, NSF</p> <p>1 ea Prices include applicable tariffs</p> <p>2 ea 20950.0004 20950.0004 1.5GPR-FF Coffee Server, 1.5 gallon, top handles, fast flow faucet, stainless decor, NSF</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| 0    | 1 ea | <b>AUX</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 12   | 1 ea | <b>COMBI OVEN, ELECTRIC (this make and model is required)</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

| Item                                                                              | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------------------------------------------------------------------------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |      | <p>Blodgett (Middleby) INVOQ 62BE/102BE <b>(this make and model is required)</b></p> <p>Blodgett INVOQ Model No. 62BE/102BE, Combi Oven Steamer, Electric, boiler, 62BE stacked on 102BE, (7) + (10) full size 18" x 26" sheet pan or (34) 12" x 20" hotel pan capacity, Stacking kit included, (2) + (2) side racks with non-tilt support rails, (5) + (8) wire shelves, touch screen controls, multiple cooking modes, SmartChef, MenuPlanner, CombiSpeed/CombiSense, stores up to 1,500 recipes, built-in hand shower, HybridSteam: Injection Steam &amp; Boiler Steam, external temperature probe, Delta-T cooking, Cook &amp; Hold, USB port, Cloud Connectivity (optional), HACCP, CareCycle Tablet-based automatic cleaning system, heat protection with triple-pane glass door, stainless steel exterior &amp; interior on casters, cULus, NSF, CE, ENERGY STAR®</p>                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|                                                                                   |      | <p>1 ea 1 year parts &amp; labor warranty, standard</p> <p>1 ea It is the sole responsibility of the customer/purchaser of this equipment to verify that the incoming water supply is comprehensively tested and, if required, provide a means of water treatment that would meet the compliance requirements with the manufacturers water quality standards published on the product spec sheet. Non-compliance with these minimum standards will potentially damage this equipment and/or components and VOID the original equipment manufacturers warranty</p> <p>1 ea CHEF TRAINING 1 hour chef training assistance on-site, included for each new location, to be coordinated with local Middleby rep chef once combi installation has been successfully completed</p> <p>1 ea 208v/60/3-ph, standard</p> <p>1 ea Installation Kit only (NET)</p> <p>1 ea 2.76" (70mm) spacing, standard</p> <p>1 ea Top Oven: Door hinged on left, standard</p> <p>1 ea Bottom Oven: Door hinged on left, standard</p> <p>1 ea Legs in lieu of casters</p> <p>1 ea TruH2O RO500 with TruH2O ST15 (recommended for poor quality water) (NET)</p> <p>1 bx 63768 Blodgett INVOQ CareCycle Clean tab for oven interior wash (150 PER BOX)</p> <p>1 bx 63769 Blodgett INVOQ CareCycle Descale tab for oven descaling (150 PER BOX)</p> |
| 13                                                                                | 1 ea | <p><b>COFFEE BREWER</b></p> <p>BUNN 38700.0043</p> <p>38700.0043 AXIOM®-15-3 Single Coffee Brewer, 200 oz. capacity tank, brews 4.5 gallon per hour, brews 1/2 gallon and 1 gallon batches, BrewWIZARD™ technology LCD display, touch pad to set pot level and tank temperature, BrewLOGIC™ technology, hot water faucet, digital temperature control, includes (1) GPR server (20950.0004), SplashGard® funnel, 120v/60/1-ph, 1600w, 13.3amps, cord attached, UL, NSF</p> <p>1 ea Prices include applicable tariffs</p> <p>2 ea 20950.0004 20950.0004 1.5GPR-FF Coffee Server, 1.5 gallon, top handles, fast flow faucet, stainless decor, NSF</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 14   | 1 ea | <b>COUNTER REFRIGERATOR</b><br> <p>True Mfg. - General Foodservice GDM-05-S-HC~FGD01<br/> Refrigerated Merchandiser, countertop, True standard look version 01,<br/> (2) shelves, (1) Low-E thermal glass hinged door, LED interior lighting,<br/> sign decal, stainless steel exterior, white aluminum interior with<br/> stainless steel floor, leg levelers, R290 Hydrocarbon refrigerant, 1/5<br/> HP, 115v/60/1-ph, 2.7 amps, NEMA 5-15P, cULus, UL EPH Classified,<br/> Made in USA, ENERGY STAR®</p> <p>1 ea 7 year compressor warranty, 7 years parts warranty, 7 year labor<br/> warranty, standard. Visit <a href="http://www.truemfg.com">www.truemfg.com</a> for specifics.</p> <p>1 ea Self-contained refrigeration standard</p> <p>1 ea Exterior: Stainless steel, standard</p> <p>1 ea Door hinged right standard</p> <p>1 ea Illuminated sign decal: S-TS-02 "TRUE Stripe" graphic, standard</p> |
| 15   | 1 ea | <b>SALAD BAR</b><br><p>Custom 4 Well Salad Bar. Includes (4) well mechanically cooled cold<br/> pan, stainless steel top with enclosed stainless steel base, Lighted self<br/> serve sneeze guard, and soup well.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 0    | 1 ea | <b>INSTALLATION</b><br><p>Installation includes:</p> <ul style="list-style-type: none"> <li>-receive all items at base warehouse, and inspect for damage</li> <li>-transport items to galley</li> <li>-Run new electric, plumbing and drains as needed</li> <li>-uncrate, assemble, set in place and connect to utilities within 4 feet.</li> <li>-remove debris</li> <li>-start up</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 16   | 1 ea | <b>REACH-IN FREEZER</b><br> Traulsen RLT232WUT-HHS<br>Spec-Line Freezer, Reach-in, two-section, 51.6 cu. ft., self-contained refrigeration, StayClear™ Condenser, variable speed compressor, stainless steel exterior and interior, standard depth, wide half-height doors with EZ-Clean Gaskets, (3) adjustable wire shelves per section, microprocessor controls, unit can be programmed to operate at -10° F, R-290 Hydrocarbon refrigerant, 1-1/4 HP, cETLus, ETL-Sanitation, ENERGY STAR®<br>1 ea 6-year parts & labor and 7 year compressor, standard. Visit <a href="http://www.traulsen.com">www.traulsen.com</a> for details<br>1 ea 115v/60/1-ph, 13.5 amps, cord with NEMA 5-15P, standard<br>1 ea Left door hinged left/right hinged right, standard<br>1 st Casters, 6" high (set of 4)                                                                                                                                                                                                                                  |
| 17   | 1 ea | <b>REACH-IN FREEZER</b><br> Traulsen RLT332WUT-HHS<br>Spec-Line Freezer, Reach-in, three-section, 79.0 cu. ft., self-contained refrigeration, StayClear™ Condenser, stainless steel exterior & interior, standard depth, wide half-height doors with EZ-Clean Gaskets, (3) adjustable wire shelves per section, microprocessor controls, unit can be programmed to operate at -10° F, R-290 Hydrocarbon refrigerant, 1-1/4 HP, cETLus, ETL-Sanitation, ENERGY STAR®<br>1 ea Oversized units with crated shipping dimensions greater or equal to 72" in length and/or 90" in height. If delivery is to a facility without a standard height dock, additional shipping charges will apply, depending on the service requested (consult factory for details)<br>1 ea 6-year parts & labor and 7 year compressor, standard. Visit <a href="http://www.traulsen.com">www.traulsen.com</a> for details<br>1 ea 115v/60/1-ph<br>1 ea Left door hinged left/center & right doors hinged right, standard<br>1 st Casters, 6" high (set of 4) |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 18   | 2 ea | <b>PASS-THRU REFRIGERATOR</b><br> Traulsen RHT232WPUT-FHG<br>Spec-Line Refrigerator, Pass-thru Display, two-section, self-contained refrigeration, StayClear™ Condenser, variable speed compressor, stainless steel exterior and interior, standard depth, wide full-height glass door or doors with EZ-Clean Gaskets, interior lights, (3) adjustable wire shelves per section, microprocessor controls, 6" adjustable stainless steel legs, R-290 Hydrocarbon refrigerant, 1/2 HP, cETLus, ETL-Sanitation, ENERGY STAR® |
|      | 2 ea | 6-year parts & labor and 7 year compressor, standard. Visit <a href="http://www.traulsen.com">www.traulsen.com</a> for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|      | 2 ea | 115v/60/1-ph, 7.6 amps, cord with NEMA 5-15P, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|      | 2 ea | Thermometer side: Left door hinged left/right hinged right, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|      | 2 ea | Rear: Left door hinged left/right hinged right, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|      | 2 st | Casters, 6" high (set of 4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 19   | 1 ea | <b>PASS-THRU HEATED CABINET</b><br> Traulsen RHF332WP-FHS<br>Spec-Line Heated Cabinet, Pass-thru, three-section, stainless steel exterior and interior, standard depth cabinet, full-height doors, with EZ-Clean Gaskets, (3) clear coated adjustable shelves per section, microprocessor controls, 6' adjustable stainless steel legs, cETLus, ETL-Sanitation                                                                                                                                                           |
|      | 1 ea | Oversized units with crated shipping dimensions greater or equal to 72" in length and/or 90" in height. If delivery is to a facility without a standard height dock, additional shipping charges will apply, depending on the service requested (consult factory for details)                                                                                                                                                                                                                                                                                                                              |
|      | 1 ea | 6-year parts & labor, standard. Visit <a href="http://www.traulsen.com">www.traulsen.com</a> for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|      | 1 ea | 208-230/115v/60/1-ph, hard wired, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|      | 1 ea | Front full height solid door(s) - L, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|      | 1 ea | Front full height solid door(s) - C, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|      | 1 ea | Front full height solid door(s) - R, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|      | 1 ea | Rear full height glass door(s) in lieu of full height solid door, per door - L                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|      | 1 ea | Rear half height glass door(s) in lieu of full height solid door, per door - C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|      | 1 ea | Rear full height glass door(s) in lieu of full height solid door, per door - R                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|      | 3 ea | Additional coated shelf                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 20   | 1 ea | <b>TILTING SKILLET BRAISING PAN, ELECTRIC</b><br> Crown (Middleby) ES-40<br>Tilting Skillet, electric, 40 gallon capacity, manual tilt, spring assisted cover, removable lip strainer, etched interior markings, stainless steel construction, open frame, adjustable flanged feet, 18.0kW, cCSAus, NSF (maximum quantity = 2 per order)                                                                                                                                                                                |
|      | 1 ea | Quick Ship items have limited configurations & that standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |




| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |      | configuration may not apply. Contact factory for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|      | 1 ea | Domestic Shipping, inside of North America                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|      | 1 ea | Standard one year limited warranty                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|      | 1 ea | ESVS-2 440v/60/3-ph, 460v/60/3-ph or 480v/60/3-ph (specify)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|      | 1 ea | NOTE: Choose option PT-SK power tilt for ELTS replacement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|      | 1 ea | LMS-151 Permanent etched interior markings, litre, for 40 gallon braising pan                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|      | 1 ea | DF-12 Double pantry faucet with 12" swing spout                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 21   | 1 ea | <b>SPEED LINE COUNTER</b><br><br>240" L. X X 46" W.<br>- 3 CM Stone top, Premium series.<br>Top extends past counter base on front of counter providing an integral tray slide.<br>- 16/304 Stainless steel cabinet body/structure.<br>- Operator side of counter to be open with bottom shelves as applicable.<br>- Electrical load center<br>- Internal utility chase, compartmentalized<br>- Counter pre-wired to load center<br>- Customer side of counter front to include stainless steel sub fascia with laminated raised panels installed on stand-offs and LED back lighting behind panels.<br>- Includes, from left to right (from customer side), provision for installation of (1) 5-pan hot food drop-in food well (hot wells NOT included, supplied by others). Includes (1) 4 pan, self contained refrigerated cold well located in center section of counter and flat top section of counter on right end.<br>- Sneeze guard(s), convertible style. All welded stainless steel tubular construction with 3/8" tempered glass panels. LED lighting. Any required heat lamps are NOT included, to be supplied by dealer.<br>- Stainless steel legs with adjustable feet<br>- Stainless steel, removable, toe kick on all customer exposed sides. |
| 22   | 1 ea | <b>MAIN LINE COUNTER</b><br><br>420" L. X X 46" W.<br>- 3 CM Stone top, Premium series.<br>Top extends past counter base on front of counter providing an integral tray slide.<br>- 16/304 Stainless steel cabinet body/structure.<br>- Operator side of counter to be open with bottom shelves as applicable.<br>- Electrical load center<br>- Internal utility chase, compartmentalized<br>- Counter pre-wired to load center                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |      | <ul style="list-style-type: none"> <li>- Customer side of counter front to include stainless steel sub fascia with laminated raised panels installed on stand-offs and LED back lighting behind panels.</li> <li>- Includes, from right to left (from customer side), (1) 60" griddle section on right end, provision for and Installation of 6-pan hot food drop-in food well (hot wells NOT included, supplied by dealer). Includes (1) 5 pan, self contained refrigerated cold well located on left end.</li> <li>- Sneeze guard(s), convertible style. All welded stainless steel tubular construction with 3/8" tempered glass panels. LED lighting. Sneeze guard in front of grill section shall be straight, fixed vertical style. Any required heat lamps are NOT included, to be supplied by dealer.</li> <li>- Stainless steel legs with adjustable feet</li> <li>- Stainless steel, removable, toe kick on all customer exposed sides.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                           |
| 23   | 1 ea | <b>HOT/COLD COUNTER - DINING ROOM</b> <p>168" L. X 52" W, Island style (Overall width at top, cabinet base 36" W.)</p> <ul style="list-style-type: none"> <li>- 3 CM Stone top, Premium series</li> <li>- Provisions for (4) Plate lowerators, plate lowerators NOT included, supplied by others</li> <li>- Provisions for (2) soup wells, soup wells NOT included, supplied by others.</li> <li>- 16/304 Stainless steel cabinet body with stainless steel under shelf. Counter laminated on all sides.</li> <li>- (1) Integral enclosure to accommodate and include silverware cylinders on end of counter.</li> <li>- Full compliment of laminated stainless steel doors with soft-close hinges on (1) side of counter. Doors include venting for refrigeration as required.</li> <li>- Electrical load center</li> <li>- Counter pre-wired to load center</li> <li>- (1) 4 Pan, self contained refrigerated cold wells at salad section.</li> <li>- (1) Provision for (1) 3 Pan, Hot food well, hot well NOT included, supplied by others.</li> <li>-(1) Sneeze guard, approx. 108" L., Self serve, island style. All welded stainless steel tubular construction with 3/8" tempered glass panels and LED lighting.</li> <li>- Stainless steel legs with adjustable feet</li> <li>- Stainless steel, removable, toe kick on all customer exposed sides.</li> </ul> |
| 24   | 1 ea | <b>BEVERAGE COUNTER</b> <p>Approx. 212" X 114" X 212" "U" shape (overall dimensions)</p> <ul style="list-style-type: none"> <li>- Overall dimensions include tray slides</li> <li>- 29" Counter top/body width</li> <li>- Design intent based on existing counter</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |      | <ul style="list-style-type: none"> <li>- 14/304 Stainless steel top with marine edge as required</li> <li>- Provision for cup rack lowerators on front of counter, lowerators NOT included, supplied by others.</li> <li>- Provisions for existing equipment on top of counter</li> <li>- 16/304 Stainless steel cabinet base. Customer side of counter includes laminated exterior. Operator side of counter includes a bottom shelf to accommodate the soda bag-in-the box containers as required. Counter is "U" shape with access for employee inside of counter assembly. Hinged doors as required.</li> <li>- 14/304 Stainless steel "V" groove tray slides on front and both long sides of counter.</li> <li>- Electrical load center</li> <li>- Pre-wiring of counter</li> <li>- Electrical outlets as required</li> <li>- Internal utility chase, compartmentalized for electrical, water and syrup lines.</li> <li>- Stainless steel legs with adjustable bullet feet</li> </ul> |
| 25   | 1 ea | <b>CONDIMENT COUNTER - DINING ROOM</b><br><br>Approx. 106" L. (at rear) X 66" L. (at front) X 21" W.<br><ul style="list-style-type: none"> <li>- 3 CM Stone top with 4" rear splash</li> <li>- 16/304 Stainless steel cabinet body with laminated exterior and stainless steel bottom shelf.</li> <li>- (3) Stainless steel doors, laminated</li> <li>- Stainless steel legs with adjustable bullet feet.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 26   | 1 ea | <b>MIXED USE COUNTER - DINING ROOM</b><br><br>Approx. 126" L. X 36" W.<br><ul style="list-style-type: none"> <li>- 3 CM Stone top with 4" rear splash</li> <li>- 16/304 Stainless steel cabinet body with laminated exterior and stainless steel bottom shelf.</li> <li>- (6) Stainless steel doors, laminated</li> <li>- Stainless steel legs with adjustable bullet feet.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 27   | 1 ea | <b>DISH TABLE - POT WASH - SOILED</b><br><br>Approx. 218" L. X 44" "L" shape<br><ul style="list-style-type: none"> <li>- Specify pot washer manufacturer make and model</li> <li>- 14/304 Stainless steel top with 10-1/2" back splash</li> <li>- (3) 26" X 30" X 14" D. sink bowls</li> <li>- (1) Install and weld-in collar for disposer and provide disposer control bracket (verify if desired/required)</li> <li>- (3) Lever wastes with over flows</li> <li>- (3) Lever waste handle brackets</li> <li>- Stainless steel legs with adjustable bullet feet</li> <li>- All welded construction</li> </ul>                                                                                                                                                                                                                                                                                                                                                                              |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      | 1 ea | T&S Brass B-0113-CR-V-B EasyInstall Pre-Rinse Unit, single-deck mount, 1.15 GPM spray valve (B-0107), 44" flexible stainless steel hose, 20" riser, 18" flexible supply lines, 6" wall bracket, vacuum breaker, quarter-turn Cerama cartridges, low lead, 2019 DOE PRSV - Class II                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|      | 2 ea | T&S Brass B-0290-01 Big-Flo Mixing Faucet, wall mount, 8" adjustable centers, 16" swing nozzle with plain end outlet, lever handles with color coded indexes, low-lead, 3/4" female NPT, ANSI, NSF, ADA Compliant                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|      | 2 ea | T&S Brass B-0427 Supply Nipple, 3/4" x 2-1/2"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|      | 1 ea | T&S Brass Order in quantities of (2) per faucet                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 28   | 1 ea | <b>DISH TABLE - POT WASH - CLEAN</b><br><br>Approx. 44" X 156" "L" shape<br>- Specify pot washer manufacturer make and model<br>- 14/304 Stainless steel top with 10-1/2" back splash<br>- Provision for utility line running vertically on long wall side<br>- Stainless steel legs with adjustable bullet feet<br>- All welded construction                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 29   | 1 ea | <b>GRIDDLE, ELECTRIC, COUNTERTOP</b><br><br> Vulcan HEG48E<br>Heavy Duty Griddle, electric, countertop, 48" W x 24" D cooking surface, 1/2" thick polished steel griddle plate, bottom mounted snap action thermostat every 12", low profile, stainless steel front, sides, front top ledge with "Cool Bullnose", front grease trough, 4" back & tapered side splashes, 4" adjustable legs, cCSAus, NSF<br><br>1 ea 1 year limited parts & labor warranty, standard<br>1 ea 480v/60/3-ph, 21.6 kW, 29.2 amps<br>1 ea STAND/C-48 Equipment Stand, universal, 49" W x 24" H, 1/2" marine edge, undershelf, stainless steel, 5" casters                                                                                                                                                                                                                                                                                                                                                                                       |
| 30   | 2 ea | <b>GRIDDLE, ELECTRIC, FLOOR MODEL</b><br><br> Evo America, LLC (Middleby) 10-0600-EVT<br>Evo® EVent® 48E PLUS Full Metal Surround Cooking Station, electric, 48"W x 24"D rectangular steel cooktop surrounded with black granite, self-contained ventilation, multi-stage filtration system, integrated fire suppression system, 100° F to 425° F (38° C to 218° C) temperature range, touch panel display, includes: cleaning kit, (2) stainless steel spatulas, (1) stainless steel scraper, UL, UL EPH Classified, Made in USA<br><br>2 ea OWNER RESPONSIBILITY: Before any Evo EVent Electric Cooktop with Ventless Recirculating Ventilation System can be powered up for the first time, the factory installed UL300 Buckeye fire suppression system must be armed, commissioned, and tagged by a certified and locally licensed BUCKEYE Fire Suppression contractor. This commissioning is also the commencement of an agreement between the Buckeye agent and the owner and cannot be altered by Evo, Inc., its agents, dealers, or service agencies. Cost will vary by individual Buckeye agent and are |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |      | paid by the customer, not by Evo.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|      | 2 ea | NOTE: Before purchasing and installing this equipment, Evo, Inc. recommends that operators apply for permits as required by local jurisdictional authorities. Required permits vary by jurisdiction and may include Electrical, Fire, Mechanical and Food Service. Permits are the responsibility of the operator and/ or its contractors.                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|      | 2 ea | 1 year parts & labor warranty (contact factory for details)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|      | 2 ea | 208v/60/3-ph, 32.0 amps, 6.7 kW, 8-foot cord, NEMA 15-50P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|      | 2 ea | 10-0150-EVT-FMS Customization for 10-0148-EVT: Metal surround, stainless steel enclosure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|      | 2 ea | 10-0150-EVT-34 Caster Kit, for 34" working height, ADA Compliant                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|      | 2 ea | 13-0220-EVT Mesh Pre-Filter, aluminum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|      | 2 pk | 13-0240-EVT Replaceable Charcoal Filter (12 pack)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|      | 2 ea | 20-EVT-1100 Recommended Spare Parts Kit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 31   | 1 ea | <b>COMBI OVEN, ELECTRIC</b><br> Alto-Shaam 7-20E PRO<br>Prodigy™ Pro Combi Oven/Steamer, electric, boiler-free, countertop, capacity (7) 18" x 26" full size sheet or (16) 12" x 20" full size hotel pan (GN 1/1), Wi-Fi enabled control with steam/convection/combi cooking modes, removable "T" style temperature probe, (2) power levels, programmable cool-down, SafeVent™ steam venting, (5) cleaning levels, triple-pane door, high efficiency LED lighting, (2) side racks with (8) non-tilt support rails, (4) shelves, door hinged right, stainless steel construction, adjustable stainless steel legs, EcoSmart®, cULus, UL EPH Classified, CE, IPX5, EAC, city-wide COA for New York City, ENERGY STAR® |
|      | 1 ea | NOTE: Subject to Manufacturer's Terms & Conditions. See Documents Section                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|      | 1 ea | One year parts and labor warranty, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|      | 1 ea | Alto-Shaam Certified Chef provides complimentary support and training on all Alto-Shaam combi ovens                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|      | 1 ea | It is the sole responsibility of the owner/operator/purchaser of this equipment to verify that the incoming water supply is comprehensively tested and, if required, provide a means of water treatment that would meet the compliance requirements with the manufacturers water quality standards published on the product spec sheet. Non-compliance with these minimum standards will potentially damage this equipment and/or components and VOID the original equipment manufacturers warranty                                                                                                                                                                                                                                                                                                  |
|      | 1 ea | ECO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|      | 1 ea | 480v/50/60/3-ph, 22.4-23.1 amps, 18.7-19.2kW, NO cord or plug                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|      | 1 kt | 5026932 Installation Kit, for electric combi ovens, Copper, rated up to 30.0 amps, includes quick disconnect kit, per oven ((NET) NO FURTHER DISCOUNTS APPLY) (Note: Required to meet NYC requirements)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|      | 1 ea | Wifi, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|      | 1 ea | Single                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|      | 1 ea | 5037355 QTI1+CR Water Filter System for single combi or Converge ovens, (1) CTO-Q10 activated carbon cartidge, reduces chlorine &                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |      | sediment, (1) CTOS-QCR catalytic carbon cartridge, reduces chloramine; outlet pressure gauge, water-shut off valve, bypass valve; 3/4" inlet, 3/4" outlet; NOTE: hardware for mounting to a wall and connection hoses are not included; ((NET) NO FURTHER DISCOUNTS APPLY)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|      | 1 ea | NOTE: Factory Authorized Installation Program (above) MUST be selected for water filtration field install option to become available                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|      | 1 ea | HO-36870 HO-36870 Hose, 3/4" NPT, 6' long; NOTE: installation kits only contain 2 hoses, a third inlet hose is required to connect the water filtration system                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|      | 1 ea | Removable "T" style temperature probe, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|      | 1 ea | Recessed Door, for 7-20s (security package not available with this option)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|      | 3 ea | CE-46991 Alto-Shaam, Concentrated Oven Cleaner, Quantity 50 tablets per container (75 gram tablet size). (Replaces CTP/CTC cleaner, CE-36354)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|      | 1 ea | CE-27889 Scale Free™ deliming product, 4 lb. bottle, citrus-based, non-corrosive                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|      | 1 ea | 5016083 Combi Oven Stand, stationary, 25-7/16" x 39-13/16" x 36-5/16" (645mm x 1010mm x 922mm), with shelf, stainless steel, for 7-20 or 10-20                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 32   | 1 ea | <b>ICE MAKER, CUBE-STYLE</b><br> Manitowoc IDT1900W<br>Indigo NXT™ Series Ice Maker, cube-style, water-cooled, self-contained condenser, 48"W x 24"D x 29-1/2"H, production capacity up to 1900 lb/24 hours at 70°/50° (1666 lb AHRI certified at 90°/70°), easyTouch display with 13 different language options, date/time stamp display, automatic reminder/alert icon, one touch asset information, automatic detection of accessories, continuous operating status, programmable production options (time, weight, day or night), one touch cleaning with displayed instructions, Alpha-San anti-microbial protection, acoustical ice sensing probe, self-diagnostic technology, DuraTech™ exterior, dice size cubes, R410 refrigerant, NSF, cULus, CE |
|      | 1 ea | WARRANTY-ICE-SC 3 year parts & labor (Machine), 5 year parts & labor (Evaporator), 5 year parts & 3 years labor (Compressor), standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|      | 1 ea | (-263E) 208-230v/60/3-ph, 13.0 amps, add suffix "3" to model number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|      | 1 ea | AR-40000-P Arctic Pure® Plus Primary Water Filter Assembly, includes head, shroud, hardware, mounting assembly, & (1) filter cartridge, 40,000 gallon capacity, 1,001-2,500 lbs./ice per day                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|      | 1 ea | WARRANTY-ARCPURE 3 year parts & labor warranty on cap, housing, hardware, & mounting assembly (does not refer to filter cartridge), standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|      | 1 ea | LB1448 Upright Ice Storage Bin, large, first ice in/first ice out, 48"W x 34"D x 67"H, stainless steel front & sides, polyethylene liner, 1337 lbs. capacity, 45 cu. ft of internal volume of capacity, AHRI, NSF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|      | 1 ea | 3 year parts & labor warranty, std                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|      | 1 ea | Limited lifetime warranty on polyethylene liner                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      | 1 ea | K0034900 Ice Deflector, for 48" Indigo ice machines on LB-Style bins, or on non Manitowoc bins (universal)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 33   | 1 ea | <b>DISHWASHER, POT/PAN/UTENSIL, DOOR TYPE</b><br> Champion PP-20-PT<br>Pot & Pan Washer, rack type, double rack, pass through design, built-in, 70 degree rise, booster heater, tank heat, 15 HP pump motor, jet spray arms, manual controls, external wash down hose with spray nozzle, (2) stainless steel utensil racks with (2) hold down lids, (2) stainless steel racks for bun/sheet pans, all stainless steel construction<br>1 ea **NOTE: Please be advised that all quotes provided are valid for a period of 30 days from the date issued. Champion Industries reserves the right to make price adjustments, price increases or add surcharges as appropriate due to tariffs or market fluctuation that are out of our control. Thank you for your understanding.<br>1 ea 1 year parts & labor warranty, standard<br>1 ea Complimentary factory authorized performance test included, upon equipment start-up. Consult local Champion sales representative for coordination of the start-up. If customer is beyond 60 miles from Champion authorized service agent, consult factory.<br>1 ea Single point electrical connection<br>1 ea Electric, standard<br>1 ea 480v/60/3-ph<br>1 ea 901246 Champion ION Scale Prevention System<br>1 ea Steam extraction fan<br>1 ea Vent fan control switch<br>1 ea Stainless steel steam table pan rack (3" deep maximum) (each)<br>1 ea Bowl & kettle grid, stainless steel (each)<br>1 ea Utensil basket with hinged lid, stainless steel mesh (each) |
| 34   | 1 ea | <b>BOOSTER HEATER, ELECTRIC</b><br> Hatco S-45<br>Imperial Booster Heater, electric, 16 gallon storage capacity, stainless steel front, custom fitting & Castone® lined tank, 45.0kW, NSF, cULus, Made in USA<br>1 ea NOTE: Sale of this product must comply with Hatco's Minimum Resale Price Policy; consult order acknowledgement for details<br>1 ea NOTE: Includes 24/7 parts & service assistance, call 414-671-6350<br>1 ea One year parts & labor warranty, ten year warranty on Castone tank, standard<br>1 ea 480v/50/3-ph (Export)<br>1 ea QSSHOCK (QUICK SHIP ACCESSORY) Shock Absorber (reduce water hammer)<br>1 ea SSBB Stainless steel body & base (available at time of purchase only)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 35   | 1 ea | <b>DISPOSER</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

| Item                                                                              | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------------------------------------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |      | InSinkErator SS-500-18A-AS101<br>SS-500™ Complete Disposer Package, with 18" diameter bowl, 6-5/8" diameter inlet, with removable splash baffle & reversible bowl cover, 5 HP motor, stainless steel construction, includes syphon breaker, (2) solenoid valves, (2) flow control valves, programmable AquaSaver® Control Center AS-101 with water-saving technology, automatic water saving function, auto reversing, timed run, post flush |
|                                                                                   | 1 ea | (3) years parts & labor warranty from date of installation (standard)                                                                                                                                                                                                                                                                                                                                                                        |
|                                                                                   | 1 ea | Standard height disposer body                                                                                                                                                                                                                                                                                                                                                                                                                |
|                                                                                   | 1 ea | Specify voltage                                                                                                                                                                                                                                                                                                                                                                                                                              |
|                                                                                   | 1 ea | SYPHON STD Syphon breaker standard, 1/2" (11477)                                                                                                                                                                                                                                                                                                                                                                                             |
|                                                                                   | 1 ea | DEJAMWRENCH Dejamming wrench, fits 6-5/8" opening only (Not for use with throat guard) (13993)                                                                                                                                                                                                                                                                                                                                               |
|                                                                                   |      |                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 36                                                                                | 1 ea | <b>SINK HEATER</b><br>Hatco 3CS-9B<br>Sink Heater, Electric, undersink design, electric operation, stainless steel front, for over 21" square sink area, 9.0 kW (balanced), NSF, CE, cULus, Made in USA                                                                                                                                                                                                                                      |
|                                                                                   | 1 ea | NOTE: Sale of this product must comply with Hatco's Minimum Resale Price Policy; consult order acknowledgement for details                                                                                                                                                                                                                                                                                                                   |
|                                                                                   | 1 ea | NOTE: Includes 24/7 parts & service assistance, call 414-671-6350                                                                                                                                                                                                                                                                                                                                                                            |
|                                                                                   | 1 ea | 3CS-480V 480v/50/60/3-ph (available at time of purchase only)                                                                                                                                                                                                                                                                                                                                                                                |
|                                                                                   | 1 ea | TEMP MON Temperature monitor (built-in), (available at time of purchase only)                                                                                                                                                                                                                                                                                                                                                                |
|                                                                                   | 1 ea | SSBB Stainless steel body & base (available at time of purchase only)                                                                                                                                                                                                                                                                                                                                                                        |
|                                                                                   | 1 ea | FR-FLUSH Flush hose kit                                                                                                                                                                                                                                                                                                                                                                                                                      |
| 37                                                                                | 2 ea | <b>CONVECTION OVEN, ELECTRIC</b><br>Imperial (Middleby) PCVDE-2<br>(QUICK SHIP) Convection Oven, electric, (2) deck, bakery depth, manual controls, (2) speed fan motor, dual open 50/50 doors, windows, (5) racks per deck, interior lights, stainless steel front, sides, doors, top & legs, cETLus, ETL-Sanitation, CE                                                                                                                    |
|                                                                                   | 2 ea | Quick Ship items have limited configurations & that standard configuration may not apply. Contact factory for details                                                                                                                                                                                                                                                                                                                        |
|                                                                                   | 2 ea | Limited one year parts and labor warranty, standard                                                                                                                                                                                                                                                                                                                                                                                          |
|                                                                                   | 2 ea | (2) 208v/50/60/3-ph, 31.0 amps, 11.0 kW                                                                                                                                                                                                                                                                                                                                                                                                      |
|                                                                                   | 2 ea | STAND-CASTERS Swivel casters (set of 4) two with brakes, per set                                                                                                                                                                                                                                                                                                                                                                             |
| 38                                                                                | 1 ea | <b>ELECTRIC FLOOR FRYER</b><br>Vulcan 1ER85DF<br>Fryer, electric, 21" W, free-standing, 85 lbs. capacity, solid state digital controls with melt cycles, KleenScreen PLUS® filtration system, twin baskets, stainless steel cabinet & fry tank, (4) adjustable legs, cCSAus, NSF, ENERGY STAR®                                                                                                                                               |
|                                                                                   |      |                                                                                                                                                                                                                                                                                                                                                                                                                                              |



| Item | Qty  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      | 1 ea | 1 year limited parts & labor warranty, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|      | 1 ea | 10 year limited tank warranty, standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|      | 1 ea | 480v/50/60/3-ph (add -2 suffix), 24kW, 29.0 amps (requires separate 120v/60/1-ph, 5.0 amps, NEMA 5-15P to operate the filter motor/pump & digital controls (not supplied with fryer)                                                                                                                                                                                                                                                                                                                                          |
| 0    | 1 ea | <b>DELIVERY AND INSTALLATION</b><br><br>Includes:<br><ul style="list-style-type: none"> <li>- Freight/Delivery</li> <li>- Removal of existing equipment from building, no relocation of equipment removed from site</li> <li>- Setting in place of new cafeteria fabrication/equipment</li> <li>- Assembly of new fabrication/equipment</li> <li>- Stone seaming</li> <li>- Installation of sneeze guards</li> <li>- Final connections</li> <li>- removal of half walls</li> <li>-upgrade the electrical as needed</li> </ul> |