

DESCRIPTION/SPECIFICATION

RQ009: INSPECTION AND ACCEPTANCE AT ORIGIN

RP001: DLA PACKAGING REQUIREMENTS FOR PROCUREMENT

RA001: THIS DOCUMENT INCORPORATES TECHNICAL AND/OR QUALITY REQUIREMENTS (IDENTIFIED BY AN 'R' OR AN 'I' NUMBER) SET FORTH IN FULL TEXT IN THE DLA MASTER LIST OF TECHNICAL AND QUALITY REQUIREMENTS FOUND ON THE WEB AT:

[HTTP://WWW.DLA.MIL/HQ/ACQUISITION/OFFERS/EPROUREMENT.ASPX](http://www.dla.mil/hq/acquisition/offers/eprocurement.aspx). FOR SIMPLIFIED ACQUISITIONS, THE REVISION OF THE MASTER IN EFFECT ON THE SOLICITATION ISSUE DATE OR THE AWARD DATE CONTROLS. FOR LARGE ACQUISITIONS, THE REVISION OF THE MASTER IN EFFECT ON THE RFP ISSUE DATE APPLIES UNLESS A SOLICITATION AMENDMENT INCORPORATES A FOLLOW-ON REVISION, IN WHICH CASE THE AMENDMENT DATE CONTROLS.

RQ011: REMOVAL OF GOVERNMENT IDENTIFICATION FROM NON-ACCEPTED SUPPLIES

RQ018: CONTRACTOR RETENTION OF SUPPLY CHAIN TRACEABILITY DOCUMENTATION THIS ITEM REQUIRES SUPPLY CHAIN TRACEABILITY DOCUMENTATION IN ACCORDANCE WITH DLA DIRECTIVE (DLAD) PROCUREMENT NOTES C03 CONTRACTOR RETENTION OF SUPPLY CHAIN TRACEABILITY DOCUMENTATION. THE FULL TEXT OF C03 CAN BE FOUND IN THE DLAD PROCUREMENT NOTES ON THE WEB AT:

[HTTP://WWW.DLA.MIL/HQ/ACQUISITION/OFFERS/EPROUREMENT.ASPX](http://www.dla.mil/hq/acquisition/offers/eprocurement.aspx).

ITEM DESCRIPTION (SECTION C):

THE SHOE, WOMEN'S, DRESS, BLACK, POROMERIC UPPER SHALL BE A PLAIN TOE OXFORD, OUTSOLE AND HEEL IS POLYURETHANE AND OIL RESISTANT, REMOVABLE CUSHION INSERT. THE INSOLE HAS A CUSHIONED HEEL AND ARCH SUPPORT, AND A BREATHABLE LINING. EACH SHOE SHALL HAVE AN INDELIBLE LABEL TO INCLUDE THE AMERICAN SIZING INFORMATION.

THEN REMOVABLE CUSHION INSERT FABRIC AND THE BREATHABLE LINING FABRIC FOR THE NON-WOVEN CLOTH SHALL BE DOMESTICALLY PRODUCED MATERIAL AND MUST CONFORM TO THE FOLLOWING REQUIREMENTS:

CHARACTERISTICS

REQUIREMENTS

TEST METHOD

MARTINDALE ABRASION

**FABRIC ONLY
DRY**

**PASS, NO HOLES
153,600 REV/ 9,600 CYCLES (MIN)**

ASTM 4966 1/

**BURSTING STRENGTH
FABRIC ONLY**

125 (MIN)

ASTM 3787

1/ AS DESCRIBED IN THE TEST METHOD; MARTINDALE TESTER; PRESSURE APPLIED: 12KPA; VISUALLY EXAMINE SPECIMENS AFTER 3200 CYCLES; ABRADANT CHANGED AFTER EACH 3200 CYCLES. USE OPTION 1 FOR EVALUATION; NO HOLE APPEARS.

BAR CODE LABEL/ HANG TAG; EACH PAIR OF BOOTS SHALL BE BAR-CODED WHICH IS CLEARLY LEGIBLE AND READABLE BY SCANNER. THE BAR CODING ELEMENT SHALL BE A 13 DIGIT NATIONAL STOCK NUMBER (NSN). THERE SHALL BE A 12 DIGIT (UPC) NUMBER ASSIGNED FOR ALL NSNS BY DSCP. THE INITIALS "UPC" MUST APPEAR BENEATH THE CODE. THE BAR CODE FOR NSN AND UPC TYPE SHALL BE A MEDIUM TO HIGH DENSITY AND SHALL BE LOCATED SO THAT IT IS COMPLETELY VISIBLE ON THE ITEM WHEN IT IS FOLDED AND OR PACKAGED AS SPECIFIED AND CAUSES NO DAMAGE TO THE ITEM.

QUALITY ASSURANCE PROVISIONS:

THE CONTRACTOR SHALL ASSURE THAT ALL ITEMS ARE FREE OF CONSUMER TYPE DEFECTS SUCH AS: NOT PROPERLY MATED, ANY SPOT, STAIN OR FOREIGN MATTER, NOT SPECIFIED COLOR, FINISH, CHIPPED, STREAKY, CRACKED OR SHOW RUNS ON UPPERS; LINING WRINKLED OR EXCESSIVE FULLNESS; ANY CUT, TEAR, HOLE, REPAIR, ABRASION; ANY COMPONENT OR ASSEMBLY MISPLACED, OPERATION OMITTED OR NOT PROPERLY PERFORMED; ANY OPEN SEAM, LOOSE OR TIGHT STITCH TENSION, ANY ROW OF STITCHING OMITTED, NEEDLE HOLES OR NEEDLE CHEWS, THREAD ENDS EXPOSED, ANY PROTRUDING POINT ON MIDSOLE; BAR CODE LABEL/TAG OMITTED OR NOT READABLE BY SCANNER, HUMAN READABLE INTERPRETATION (HRI) OMITTED OR ILLEGIBLE, NOT VISIBLE ON PACKAGED ITEM CAUSES DAMAGE TO THE ITEM.

COMPONENT TESTING .EACH SUCCESSFUL OFFEROR WILL HAVE THE FIRST THREE LOTS OF COMPONENT MATERIALS (AS SPECIFIED IN THE CONTRACT) TESTED AT A QLL LABORATORY CAPABLE OF PERFORMING THE TESTS AS STATED IN THE SALIENT CHARACTERISTICS OF THE RESULTANT CONTRACT. ASSUMING THESE LOTS PASS, THE CONTRACTOR(S) WILL SUBMIT A CERTIFICATE OF COMPLIANCE FOR ALL TESTS OF ALL SUBSEQUENT LOTS. THE GOVERNMENT RESERVES THE RIGHT TO DRAW SAMPLES FROM ANY LOT AND PERFORM WHATEVER TESTS DEEMED NECESSARY AT ANY TIME DURING THE LENGTH OF THE CONTRACT.

SAMPLING FOR VISUAL INSPECTION. EXAMINATION FOR ABOVE DEFECTS SHALL BE IN ACCORDANCE WITH INSPECTION LEVEL II, AQL 2.5 OF AMERICAN NATIONAL STANDARD ANSI/ASQC Z1.4. 1993.

PACKAGING, PACKING AND MARKING (SECTION D)

PREPARATION FOR DELIVERY:

THE SHOES SHALL BE UNIT PACKAGED IN A ONE-PIECE STYLE SET UP BOX (FANCY NOT PLAIN) IN ACCORDANCE WITH STANDARD COMMERCIAL PRACTICES. TISSUE OR KRAFT PAPER SHALL BE USED TO COMPLETELY SEPARATE THE PAIR. A COMPANY NAME OR LOGO MAY BE ADDED TO ENHANCE THE BOX APPEARANCE.

PACKING INSTRUCTIONS:

SIX (6) PAIR OF SHOES, COMPOSED OF ONE SIZE AND WIDTH SHALL BE PACKED IN A FIBERBOARD SHIPPING CONTAINER CONFORMING TO TYPE CF (VARIETY SW) OR CF, CLASS DOMESTIC, GRADE 275 OF ASTM D5118/D5118M. CLOSURE SHALL BE IN ACCORDANCE WITH ASTM D1974. THE SELECTION OF THE CLOSURE MATERIAL SHALL BE AT THE DISCRETION OF THE CONTRACTOR. THE SHOE UNIT PACKS WILL BE PLACED ON END, SUCH THAT THE UNIT PACK LABEL IS CLEARLY VISIBLE FROM THE TOP OF AN OPENED SHIPPING CONTAINER. EACH SHIPPING CONTAINER SHALL CONTAIN ONLY ONE NSN AND UPC.

ALL PALLETIZED LOADS SHALL CONTAIN ONLY ONE NSN AND UPC TO THE MAXIMUM EXTENT POSSIBLE. PALLETS MAY HAVE EXTERIOR CONTAINERS NOT OF THE SAME NSN AND UPC, BUT THE PALLET SHALL BE CLEARLY MARKED "MIXED" AND EACH APPLICABLE NSN/UPC SHALL BE LISTED WITH ITS TOTAL QUANTITY. THE OUTER DIMENSIONS AND STACKING PATTERN OF THE PALLET SHALL BE SUCH THAT IT FORMS A COMPACT, SQUARED LOAD CENTERED ON THE BASE AND SQUARED ON ALL CORNERS.

PRES/PACK C/C TO ASTM-D-3951

SIGNIFICANT NOTE - "PALLETIZATION IS REQUIRED FOR THESE SUPPLIES".

NOTE: THE FOLLOWING APPLIES TO ALL NON-MANUFACTURED WOOD PACKAGING MATERIALS:

"ALL WOOD PACKAGING MATERIAL (WPM) ACQUIRED BY DOD MUST MEET REQUIREMENTS OF INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM) 15, "GUIDELINES FOR REGULATING WOOD PACKAGING MATERIALS IN INTERNATIONAL TRADE." DOD SHIPMENTS INSIDE AND OUTSIDE OF THE UNITED STATES MUST MEET ISPM 15 WHENEVER WPM IS USED TO SHIP DOD CARGO, OR WHEN WOOD IS BEING ACQUIRED BY DLA FOR FUTURE USE AS PACKAGING MATERIAL. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAME AND CLEATS. PACKAGING MATERIALS EXEMPT FROM THE REQUIREMENTS ARE MATERIALS THAT HAVE UNDERGONE A MANUFACTURING PROCESS, SUCH AS CORRUGATED FIBERBOARD, PLYWOOD, PARTICLEBOARD, VENEER, AND ORIENTED STRAND BOARD

(OSD). ALL WPM SHALL COMPLY WITH ONE OF THE FOLLOWING OFFICIAL QUALITY CONTROL PROGRAMS:

HEAT TREATMENT (HT) OR KILN DRIED HEAT TREATMENT (KD HT) IN ACCORDANCE WITH AMERICAN LUMBER STANDARD COMMITTEE, INCORPORATED (ALSC) WOOD PACKAGING MATERIAL PROGRAM AND WPM ENFORCEMENT REGULATIONS (SEE [HTTP://WWW.ALSC.ORG](http://www.alsc.org)); OR ALL WPM SHALL INCLUDE CERTIFICATION/QUALITY MARKINGS IN ACCORDANCE WITH THE ALSC OR NWPCA STANDARDS, AS APPLICABLE. MARKINGS SHALL BE PLACED IN AN UNOBSTRUCTED AREA THAT WILL BE READILY VISIBLE TO INSPECTORS. PALLET MARKINGS SHALL BE APPLIED TO THE STRINGER OR BLOCK ON DIAGONALLY OPPOSITE SIDES OF THE PALLET AND BE CONTRASTING AND CLEARLY VISIBLE. ALL CONTAINERS SHALL BE MARKED ON A SIDE OTHER THAN THE TOP OR BOTTOM, CONTRASTING AND CLEARLY VISIBLE. ALL DUNNAGE USED IN CONFIGURING AND/OR SECURING THE LOAD SHALL ALSO COMPLY WITH ISPM 15 AND BE MARKED WITH AN ASLC APPROVED DUNNAGE STAMP. FAILURE TO COMPLY WITH THE REQUIREMENTS OF THIS RESTRICTION MAY RESULT IN REFUSAL, DESTRUCTION, OR TREATMENT OF MATERIALS AT THE POINT OF ENTRY. THE AGENCY RESERVES THE RIGHT TO RECOUP FROM THE CONTRACTOR ANY REMEDIATION COSTS INCURRED BY THE GOVERNMENT."

**PALLET SHALL BE 4 WAY ENTRY, WINGED TYPE. PALLETIZED LOAD DIMENSIONS SHALL NOT EXCEED 43 INCHES IN LENGTH, 52 INCHES IN WIDTH, AND 54 INCHES IN HEIGHT (INCLUDING THE PALLET).RE FERE
NCE PAGE 16 OF MIL-STD-147, ANY 4-WAY ENTRY PALLET ILLUSTRATED IS ACCEPTABLE.**

THE PALLETIZED LOAD SHALL BE BONDED USING APPROVED COMMERCIAL BONDING MATERIALS. THE USE OF METAL BANDING, IN SECURING BOXES TO PALLETS, IS DISCOURAGED. PALLET LOADS SHALL CONTAIN THE SAME NUMBER OF CARTONS, OF IDENTICAL QUANTITIES, OF ONE NSN, TO THE MAXIMUM EXTENT POSSIBLE.

PALLET LOADS CONTAINING MORE THAN ONE NSN SHALL BE CLEARLY MARKED TO LIST ALL THE NSN'S CONTAINED IN THE LOAD. NO CARTON SHALL HAVE MORE THAN ONE NSN. AT THE END OF A SIZE RUN, NO MORE THAN ONE CARTON PER NSN MAY BE SHORT OR OVER THE SPECIFIED QUANTITY. SAID CARTON SHALL BE CLEARLY MARKED "SHORT" OR "OVER".

MIL-STD-147 IS HEREBY REFERENCED FOR GUIDANCE FOR PALLETIZED LOADS.

MARKING:

EACH UNIT PACK AND EXTERIOR CONTAINER SHALL BE MARKED FOLLOWING STANDARD COMMERCIAL PRACTICES. UNIT PACK IDENTIFICATION SHALL INCLUDE THE ITEM NAME, NSN AND UPC WITH BAR CODE, CONTRACT NUMBER, SIZE AND WIDTH AND AS AN OPTION, THE CONTRACTOR'S NAME AND/OR LOGO. THE INITIALS "UPC" MUST APPEAR UNDER THE UPC BAR CODE. THE EXTERIOR CONTAINERS SHALL BE MARKED TO IDENTIFY THE NSN WITH BAR CODE, QUANTITY AND UNIT OF ISSUE, DATE OF PACK, CONTRACT NUMBER, SHIPMENT NUMBER, PALLET GROSS WEIGHT AND CUBE AND A VISIBLE MARKING WITH THE WORDS "MADE FOR DLA-TROOP SUPPORT".

DEPOT SHIPMENTS FOR BOOTS SHALL BE MARKED IN ACCORDANCE WITH THE MOST RECENT VERSION OF MIL-STD-129, AND INCLUDE RFID IDENTIFICATION.