

ATTACHMENT 1 (SPEC)

Model#: J40XNT/Electric Forklift

Included Items	Description	Quantity
Model	Hyster® J40XNT - Counterbalanced Sit-Down Electric Rider Lift Truck - 4,000 lb. Nominal Capacity @ 24" Load Center	1
Construction	Key Switch Start Standard Construction - Operating Temperatures +32° F to +120° F 36 Volt	
Powertrain Options	UL Classification Type "E"	
Battery Compartment	25.3" Battery Compartment Battery Compartment With Auxiliary Counterweight Spacer Platform Battery Removal without Rollers - Lift Out	
Mast	3 Stage Full Free Lift Mast - Class II - 187" (4750mm) Maximum Lift Height - 82" (2080mm) Overall Lowered Height - 59" (1505mm) Free Lift Height without Load Backrest - 236" (5980mm) Overall Extended Height with Load Backrest Mast Tilt - 5° Forward / 5° Back	
Carriages & Attachments	38.5" (977mm) Wide - Class II - Hook Type Integral Sideshift Carriage 48" (1220mm) High Load Backrest Extension	
Forks	42" Long x 1.6" Thick x 3.9" Wide (1067mm x 40mm x 100mm) - Class II Hook Type - Standard Taper Forks	
Hydraulics	3 Function (1 Auxiliary) Hydraulic Control Valve Mechanical Lever Hydraulic Controls - Seat Side	
Hoses	1 Auxiliary Function Hose Group - 2 Hoses Internally Mounted	
Wheels & Tires	Drive Tire - 200 / 50-10 - Pneumatic Shaped Solid (PSS) - Standard Compound - Lug Tread Steer Tires - 15 x 4.5 x 8 - Pneumatic Shaped Solid (PSS) - Standard Compound	

ATTACHMENT 1 (SPEC)

Operator Compartment	81.5" (2070mm) Overhead Guard - Grid Style Display - High Mount - Mounted in Upper Right Corner of Overhead Guard Rear Drive Handle with Horn Button
Directional Control	Seat Side Directional Control On Demand Hydrostatic Power Assist Steering Steering Wheel with Spinner Knob Steer Column with Infinitely Adjustable Tilt
Seat	Full-Suspension Vinyl Seat Seat Belt - Black - No-Cinch with ELR (Emergency Locking Retractor)
Telemetry	Hyster Tracker Wireless Monitoring with Cellular connectivity - GSM 7 Year, Level 1 Telematic Communication and Portal Fees - Monitoring
Lights & Alarms	Work Lights - LED Plastic Lens - 2 Front and 1 Rear Audible Alarm - Reverse Direction Activated - Self-Adjusting 82-102 dB(A) Amber Strobe Light - Ignition Activated DC to DC Converter - Primary - For Factory Installed Options - 25 amps/300 watts @ 12 volts
Warranty	12 Months / 2,000 Hours Manufacturer's Warranty, 36 Months/ 6,000 Hours Manufacturer's Powertrain Warranty
Literature & Nameplate	English Literature Pack and Labels
Battery & Charger Accessories	Battery Charging System - Conventional - Includes Single Battery Connector Under the Hood Power Collect (SPED) - allows the flexibility to install a qualified lithium-ion/TPPL CAN connected battery, or a lead acid/TPPL (non-CAN connected) battery into the truck Battery Connector - Grey SB® 350

Additional Items or Accessories Included

	Description	Quantity
P&D		1
Battery	18-85-21	1
Charger	36V/140A-3	1
Watering System		1