

TECHNICAL DATA PACKAGE

NIIN: PNTDP0159 VERSION:001

PAGE 1

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

1. SCOPE

1.1 The material covered in this contract/purchase order will be used in a crucial shipboard system. The use of incorrect or defective material would create a high probability of failure resulting in serious personnel injury, loss of life, loss of vital shipboard systems, or loss of the ship itself. Therefore, the material has been designated as SPECIAL EMPHASIS material (Level I, Scope of Certification, or Quality Assured) and special control procedures are invoked to ensure receipt of correct material.

1.1.1 DSSP Scope of Certification Material - Material Control Division (B) applies to this material.

1.1.2 This Hose, Assembly contains non-metallic materials which must satisfy the toxicity and flammability requirements of NAVSEA SS800-AG-MAN-010/P-9290. Use of any material other than that specified requires special engineering approval and may require testing.

2. APP DOCS

2.1 Order of Precedence - In the event of a conflict between the text of this contract/purchase order and the references and/or drawings cited herein, the text of this contract/purchase order must take precedence. Nothing in this contract/purchase order, however, must supersede applicable laws and regulations unless a specific exemption has been obtained.

2.2 Applicable Documents - The document(s) listed below form a part of this contract/purchase order including modifications or exclusions.

2.2.1 Specification Revisions - The specification revisions listed under "Documents References" below are the preferred revision. Older and/or newer revisions are acceptable when listed within Contract Support Library Reference Number CSD155 in ECDS (Electric Contractor Data Submission) at: <https://register.nslc.navy.mil/>. This is to allow Contractors to use certain acceptable older specification revisions to purge their existing stock of material certified to those older revisions or to use newer specification revisions when material is certified to newly released revisions, without requiring the submittal of waiver/deviation requests for each specification revision on every contract. Revisions of specifications reflecting editorial and/or re-approval (e.g. E2009, R2014, etc.) are considered inconsequential, but are acceptable when their revisions are listed within CSD155 or elsewhere within this contract.

2.2.2 Documents, drawings, and publications supplied are listed under "Drawing Number". These items should be retained until an award is made.

2.2.3 "Document References" listed below must be obtained by the Contractor. Ordering information is included as an attachment to this contract/purchase order.

2.3

DOCUMENT REFERENCES

SPEC NO.	SLASH NO.	PART NO.	REV	DATE	DISTR CD	AMEND	CHD NTC	SUPP
ANSI/ASQ Z1.4	0	0		01/01/2008	A			
ANSI/NCSL Z540.3	0	0		03/26/2013	A			
ISO/IEC 17025	0	0		05/15/2005	A			
ISO10012	0	0		04/15/2003	A			
ISO_9001	0	0		11/15/2008	A			
MIL-F-24787	0	0		09/03/1993	A			
MIL-H-24136	0	0	B	09/03/1993	A			
MIL-I-45208	0	0	A	07/24/1981	A	1		
MIL-PRE-27617	0	0	G	08/15/2011	A			
MIL-STD-1622	0	0	B	11/15/2006	A		1	
MIL-STD-45662	0	0	A	08/01/1988	A			
MIL-STD-792	0	0	F	05/19/2006	A			
MIL-STD-792	0	0	F	02/23/2023	A		1	
QPL 24136	0	0	QPD	12/18/2020	A			
QPL 24787	0	0	QPD	11/05/2020	A			

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 2

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

SS800-AG-MAN-010/P-9290 0 0 A 03/24/2020 A 42

3. REQUIREMENTS

3.1 The Hose Assembly, must be manufactured in accordance with NAVSEA Drawing number 6640965 assembly 321, NAVSEA Drawing number 6640819 and Electric Boat Specification 3461, except as amplified or modified herein.

3.2 A hydrostatic test in accordance with Note A of drawing 6640965 sheet 321 is required. Only a C of C is required for this test.

The hose assembly must be hydrostatically tested as follows:

- a. Draw a circumferential chalk line around the hose next to each fitting attachment. Measure distance from the lines to fitting edges at four places 90° apart.
- b. Attach test fitting or adapter. Flanged hose fittings should have strong backs installed to prevent distortion of the flange when the hose assembly is subjected to proof pressure if the hose design pressure exceeds the fitting rated pressure.
- c. Using fresh water, apply a hydrostatic proof pressure per Note A of drawing 6640965 sheet 319. Hold this pressure for 1 to 5 minutes. Hose must not burst, leak or show signs of fitting separation.
- d. Upon completion of test, measure the distance from chalk lines to fittings (refer to paragraph a above). Any change in measurement from those obtained in paragraph a is reason for rejection of the tested hose assembly.

3.3 Lubrication per NAVSEA drawing 6640965 sheet 321-1 Note D must be with MIL-PRF-27617 Type III lubricants Krytox 240AC, Christo-Lube 111, or Christo-Lube 116.

Item 3219-1 of drawing 6640965 must be a MIL-H-24136 qualified item. Item 321-2 of drawing 6640965 must be a MIL-F-24787 qualified item.

3.4 Testing Certification - Certifications are required for the following tests on the items listed below. Additional testing on other piece parts (if any) per applicable drawings and specifications is still required, but certifications are only required as listed below.

- Test - Hydrostatic test in accordance with Note B of drawing 6640965 sheet 321.
Item - Each hose assembly
Performance - Pressurize the hose assembly to the pressure specified in Note B of drawing 6640965 sheet 321 using fresh water as a test medium; maintain pressure for at least 1 minute to accomplish inspection.
Acceptance - No Leakage is allowed

3.5 General Application Cleaning - Cleaning must be in accordance with MIL-STD-1622 .

3.6 Off-Gassing Analysis is required in accordance with NAVSEA SS800-AG-MAN-010/P-9290A, Appendix F, paragraphs F4.2, F4.3, and F4.4. Off-Gassing Analysis is not required for every lot of stock material (plate, bar, castings, etc.) formed by the same vendor, if NAVSEA SS800-AG-MAN-010/P-9290A, Section F4.4 is satisfied.

3.6.1 Off-Gassing Analysis must be conducted by one of the following labs:

1 ALS Simi Valley
Mr. Michael Conejo
2655 Park Center Dr. Suite A
Simi Valley, CA 93065

Phone (805) 577-2083

2 Electric Boat Corp.
DSS-ACL
Craig Adamson
75 Eastern Point Road
Groton, CT 06340-4989

Phone (860) 433-5866

3 Naval Surface Warfare Center - Crane
(NSWC-Crane)
Mike Jones
300 Highway 361
Bldg 3395
Crane, In 47522-5001

Phone (812) 854-6313

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 3

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

Note: This lab contains the only chamber authorized for ordnance sampling.

4 Naval Experimental Diving Unit
(NEDU)
Chuck Mayberry
321 Bullfinch Road
Panama City, FL
32407

Phone (850) 230-3163

5 Naval Undersea Warfare Center
(NUWC-Keyport)
Dan Seacrist
NUWC DIV KEYPORT
Code 513 HOSUB SOF Branch
610 Dowell Street, Building 880
Keyport, WA 98345

Phone (360) 315-4881

6 VSOL Group
Kelly Horiuchi
VSOL Group, LLC
4014 Camino Ranchero, Suite B
Camarillo, CA 93012

Phone (805) 419-0851

7 A&B Environmental Services
Ashley Hall
A&B Environmental Services
10100 East Freeway, Suite 100
Houston, TX 77029

Phone (713) 453-6060

3.6.2 Each item being supplied for the off-gas test must be odor tested prior to shipment to the off-gas test lab. Perform the odor test per the requirements specified in paragraph F.4.4.1.b of NAVSEA SS800-AG-MAN-010/P-9290A.

Note: The vendor must contact lab to determine test chamber size and depth limitations.

Note: Each shipment of material to be off-gas tested must be accompanied by paperwork identifying the following:

- The NSN
- The Procuring Activity
- The Contract Number
- The Serial Numbers of units in shipment

3.6.3 The listed labs have been assessed and accepted; however, due to the requirements of biennial reassessments there could be occasions when a given lab may have restrictions levied on them. It is incumbent upon the customer to contact the lab or NAVSEA 07Q4 to ascertain the current lab status. NAVSEA point of contact is Mr. Greg Sorrells (SEA 07Q43) at (202)781-0910.

3.7 The pressure tolerance must be as specified in the assembly drawing, detail drawing, design specification or elsewhere in this contract. Where pressure tolerances are not provided by drawings, specifications or specified elsewhere in this contract, the following must be used:

For pressure tests below 100 PSIG, the pressure tolerance must be +1 PSIG / -0 PSIG.

For pressure tests at or above 100 PSIG up to and including 2500 PSIG, the pressure tolerance must be +2% / -0 PSIG rounded off to the nearest multiple of the smallest graduation on an analog test pressure gauge, not to exceed 50 PSIG.

For pressure tests above 2500 PSIG, the pressure tolerance must be +2% / -0 PSIG, rounded off to the nearest multiple of the smallest graduation on an analog test pressure gauge, not to exceed 200 PSIG.

The pressure test time tolerance must be as specified in the assembly drawing, detail drawing, design specification or elsewhere in this contract. Where pressure test time tolerances are not provided by

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 4

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

drawings, specifications or specified elsewhere in this contract, the following must be used:

For a test duration up to and including 1 hour, the tolerance must be +5 minutes / - 0 minutes.

For a test duration of more than 1 hour up to and including 24 hours, the tolerance must be +30 minutes / - 0 minutes.

For a test duration of more than 24 hours, the tolerance must be + 60 minutes / - 0 minutes.

3.8 Mercury Free - Mercury and mercury containing compounds must not be intentionally added or come in direct contact with hardware or supplies furnished under this contract. Mercury contamination of the material will be cause for rejection.

3.9 See CDRL DI-MISC-80678 (Test Certification) - A statement of tests performed, listing the pieces tested, must be furnished along with a copy of the test results. Certification must include the contractor's name, address, and date, quantity inspected, identified to the contract/purchase order and item number, and the Contractor's or authorized personnel's signature. Test certifications must reference the standard/specification, including the revision, to which the testing was performed and the acceptance criteria used. Test procedure numbers may also be referenced on test reports. Test reports on weldments must be identified to weld joint and layer.

3.10 Configuration Control - The Contractor must maintain the total equipment baseline configuration. For items of proprietary design, Contractor drawings showing the latest assembly configuration must be provided to the Government in electronic (C4) format. Definitions are provided elsewhere in the Contract/Purchase Order.

3.10.1 Waivers/Deviations - All waivers and deviations, regardless of significance or classification require review and approval by the Contracting Officer. Waivers and Deviations must be designated as Critical, Major, or minor. The Contractor must provide a copy of this request to the QAR. Requests must include the information listed below.

- a. A complete description of the contract requirement affected and the nature of the waiver/deviation (non-conformance), including a classification of Critical, Major, or Minor.
- b. Number of units (and serial/lot numbers) to be delivered in this configuration.
- c. Any impacts to logistics support elements (such as software, manuals, spares, tools, and similar) being utilized by Government personnel or impacts to the operational use of the product.
- d. Information about remedial action being taken to prevent reoccurrence of the non-conformance.

3.10.2 All requests for Waivers/Deviations on NAVSUP-WSS Contracts must be submitted to the NAVSUP WSS Contracting Specialist via eMail.

3.10.3 ECPs - The Government will maintain configuration control and change authority for all modifications or changes affecting form, fit, function, or interface parameters of the Equipment and its sub-assemblies. The Contractor must submit an Engineering Change Proposal (ECP) for any Class I or II changes that impact the Equipment covered by this contract. ECPs must be prepared in Contractor format, and must include the following information:

- a. The change priority, change classification (Class I or Class II), and change justification.
- b. A complete description of the change to be made and the need for that change.
- c. A complete listing of other Configuration Items impacted by the proposed change and a description of the impact on those CIs.
- d. Proposed changes to documents controlled by the Government.
- e. Proposed serial/lot number effectivities of units to be produced in, or retrofitted to, the proposed configuration.
- f. Recommendations about the way a retrofit should be accomplished.
- g. Impacts to any logistics support elements (such as software, manuals, spares, tools, and similar) being utilized by Government personnel in support of the product.
- h. Impacts to the operational use of the product.
- i. Complete estimated life-cycle cost impact of the proposed change.
- j. Milestones relating to the processing and implementation of the engineering change.

3.10.4 A copy of the final waiver/deviation (both approved and disapproved) must be forwarded with the applicable asset(s).

3.11 Certificate of Compliance - (SPECIAL EMPHASIS MATERIAL) The Contractor must prepare and submit a certificate of compliance certifying that the items/components furnished under this contract comply with the requirements of the procurement document, including any/all invoked specifications and drawings.

*
* QUALITY ASSURANCE REQUIREMENTS *
*

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 5

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

3.12 Quality System Requirements - The Contractor furnishing items under this contract/purchase order must provide and maintain a quality system in accordance with ISO-9001 as amplified or modified herein, with the calibration system requirements of ISO-10012 or ANSI-Z540.3 with ISO-17025. A Quality System in accordance with MIL-I-45208, with the calibration system requirements of MIL-STD-45662, is acceptable as an alternate.

3.12.1 The Contractor's quality system and products supplied under the system are subject to evaluation, verification inspection, and acceptance/nonacceptance by the Government representative to determine the system's effectiveness in meeting the quality requirements established in the Contract/Purchase Order.

3.12.2 The Contractor's quality system must be documented and must be available for review by the Contracting Officer or his representative prior to initiation of production and throughout the life of the contract. The Prime Contractor must, upon notification, make his facilities available for audit by the contracting Officer or his authorized representative.

3.12.3 See CDRL DI-QCIC-81110 (Inspection System Procedures) - All suppliers of Deep Submergence Systems Program (DSSP) material are required to submit a copy of their current documented quality system procedures to the Procurement Contracting Officer (PCO) prior to award of any contract/purchase order. Suppliers that have a copy of their current quality system procedures on file at the Procuring Activity may request the PCO waive this requirement.

3.12.4 This contract provides for the performance of Government Quality Assurance at source. The place or places of performance may not be changed without the authorization of the Procurement Contracting Officer. Upon receipt of this order, promptly notify the Government representative who normally services your plant so that appropriate planning for Government inspection can be accomplished. If you do not have an assigned Government representative, notify the nearest Defense Contract Management Agency (DCMA) Office. In the event that a local Government representative or DCMA Office cannot be located, our purchasing agent should be notified immediately.

3.12.5 Any changes made by the Contractor to a qualified quality system will require re-submittal to the PCO and concurrence by the Government Quality Assurance Representative prior to adoption.

3.13 Contractor Inspection Requirements - The Contractor must maintain adequate records of all inspections and tests. The records must indicate the nature and number of observations made, the number and type of deficiencies found, the quantities approved and rejected and the nature of corrective action taken as appropriate. Inspection records must be traceable to the material inspected.

3.13.1 The supplier's gauges, measuring and test equipment must be made available for use by the Government representative when required to determine conformance with Contract requirements. When conditions warrant, the supplier's personnel must be made available for operations of such devices and for verification of their accuracy and condition.

3.13.2 All documents and reference data applicable to this contract must be available for review by the Government representative. Copies of documents required for Government inspection purposes must be furnished in accordance with the instructions provided by the Government Representative.

3.14 Subcontractor Inspection Requirements - The Government has the right to inspect at source, any supplies or services that were not manufactured or performed within the contractor's facility. Such inspection can only be requested by or under authorization of the Government representative. Any purchasing documents to a subcontractor must cite the applicable portions of the contractually invoked quality system (e.g. calibration requirements), plus any product requirements that apply to the supplies being purchased. When the Government elects to perform source inspection at the subcontractor's facility, applicable purchase documents must be annotated with the following statement: "A Government inspection is required prior to shipment from your plant. Upon receipt of this order, promptly notify the Government representative who normally services your plant so that appropriate planning for Government inspection can be accomplished. If you do not have an assigned Government representative, notify the nearest Defense Contract Management Agency (DCMA) Office. In the event that a local Government representative DCMA Office cannot be located, our purchasing agent should be notified immediately."

3.14.1 The prime contractor's program must include procedures to assess the capability of the prospective suppliers to produce the products or supply the services in accordance with the contract, prior to the issuance of any purchase document.

3.14.2 Each sub-tier supplier of material or services for items in Section 3 of this contract must be subjected to a periodic review or audit by the Prime to determine the continued capability of the supplier to control the quality of the products or services specified in the purchase order or contract.

3.14.3 The prime contractor must ensure that the purchased product conforms to specified purchase

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 6

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

requirements and this contract. The type and extent of control applied to the supplier and the purchased product must be dependent upon the effect of the purchased product on the end item represented by this contract.

3.14.4 The prime contractor must evaluate the requirements of the contract and select suppliers based on their ability to supply the product in accordance with the prime contractor's requirements and the contract. Criteria for selection and evaluation must be established. Records of this effort must be available for review by the government.

3.14.5 The prime contractor's supplier quality assurance program must provide for a review of purchase documents to assure applicable quality requirements are included or referenced in the documentation for compliance by the supplier.

3.15 Government Furnished Material and/or Equipment (GFM/GFE) - When material or equipment is furnished by the Government, the Contractor must develop documented control procedures that require at least the following:

3.15.1 Visual examination upon receipt to detect damage during transit.

3.15.2 Inspection for completeness and proper type.

3.15.3 Verification of material quality received.

3.15.4 Periodic inspection and precautions to assure adequate storage conditions and to guard against damage from handling and deterioration during storage.

3.15.5 Functional testing, either prior to or after installation, or both, as required by the Contract to determine satisfactory operation.

3.15.6 Identification and protection from improper use or disposition.

3.15.7 Reporting to the Government, any GFM or GFE property found damaged, malfunctioning, or otherwise unsuitable for use. In the event of damage or malfunction during or after installation, the supplier must determine and record probable cause and necessity for withholding the material from use.

3.15.8 For GFE material, and as required by the terms of the bailment agreement, the supplier must establish procedures for adequate storage, maintenance, and inspection of bailed Government material. Records of all inspection and maintenance performed on bailed property must be maintained.

3.15.9 Material returned to the contractor must be handled as GFM.

3.16 Traceability and Certification Requirements - To assure that correct materials are installed in DSSP systems, it is imperative that traceability be maintained from the material to all required Objective Quality Evidence (OQE).

3.16.1 The following provides the minimum requirements for maintaining material traceability and supplements the requirements specified elsewhere in the contract/purchase order.

3.17 Material Traceability - Traceability markings must be permanently applied to the material in accordance with MIL-STD-792 or to a tag affixed to the material, and annotated on the required OQE. The traceability marking may be any vendor traceability number/code which provides complete traceability to the required OQE. Traceability Marking/Identification may include such items as Nomenclature, Part Number, Technical Description, National Stock Number (NSN), etc. Traceability must be maintained through all process operations including any subcontracted operations, to the finished component.

3.17.1 When traceability markings on the material would be removed by a manufacturing or fabrication process, the marking must be recorded prior to removal and be immediately restored upon completion of the process. If this cannot be done or is impractical, an appropriate material control procedure (such as a bag and tag, tagging, and/or tote box control) must be employed. The material control procedure must provide a method of positive control to preclude commingling of material or loss of traceability. The traceability marking must be reapplied upon completion of the final manufacturing process.

3.17.2 The material control process must include requirements for the maintenance of traceability for items sent out for subcontracted operations. If such operations would remove traceability markings on the material, purchase or work orders must specify a method and marking location for remarking. The contractor must also ensure that subcontractor production controls are adequate to preclude commingling of materials during processing.

3.18 Final Inspection - The following inspections must be performed prior to Government inspection and acceptance.

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 7

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

3.18.1 Material Sampling - Material must be inspected for form, fit, and function. Lot acceptance must be based on zero defects and lot rejection based on one defect. The sample size must be in accordance with the sampling plan(s) in the applicable military specification or standard, federal specification or standard, or drawing to which the material was manufactured. In the absence of such sampling plans, sampling inspection must be per ANSI/ASQ-Z1.4, general inspection level II (for sample size selection code), table IIA (for sample size).

SMALL LOT SIZES - For lot sizes of fifty or less, the minimum sample size must be eight units. For lot sizes of eight or less, the sample size must be one hundred percent of the lot.

3.18.2 The Manufacturer may elect to use Statistical Process Control (SPC) to assure product quality in lieu of the above attribute sampling plan, provided that the SPC methodology/system used provides acceptable products to the Government. However, the Government Inspection Activity may perform their acceptance inspection of the material using the attribute sampling plan outlined above.

3.18.3 All OQE required by the Contract and all data concerning material traceability (OQE to traceability marking) must be 100% inspected. The certification test reports must also be 100% inspected for completeness and legibility.

3.19 Test Certification - When test certifications are required elsewhere in the contract, certification documents must be positive and unqualified. Disclaimers such as "to the best of our knowledge" or "we believe the information contained herein is true" are not acceptable.

3.19.1 If material is received without the required test certification papers or with incorrect/missing data on the certification papers, the material will be rejected.

3.20 See DI-MISC-80678 (SOC OFF-GASSING ANALYSIS) - Non-Metallic Material off-gassing test reports must, as a minimum, record the following data per NAVSEA SS800-AG-MAN-10/P9290, Appendix F:

- a. Testing facility name, address, and phone number.
- b. Date material tested.
- c. A positive statement that material composition was reviewed by NAVSEA to identify any additional target or non-target compounds prior to testing (See note below).
- d. Lot or batch number of material.
- e. Material chemical name or product name, model number, and serial number for end items/complete assemblies.
- f. Manufacturer of material.
- g. Sample weight.
- h. Sample surface area.
- i. Curing procedure - a description of pretest curing (include cure time and conditions) or burn-in operation (when applicable).
- j. Pressure and volume of test chamber.
- k. Temperature of test chamber. Indicate whether or not the electrical equipment/assembly was energized based on burn-in bench testing results.
- l. Total time specimen was in chamber before chemical analysis.
- m. Signature and date of test director.
- n. Test results:
 - (1) List of constituents analyzed or identified.
 - (2) Method of analysis used to analyze constituent (see Table F-5).
 - (3) Allowable limit of each constituent (see Section F.6).
 - (4) Reporting limit for each constituent (see paragraph F.5.4.c).
 - (5) Absolute measured level of each constituent.
 - (6) Normalized measured level of each constituent (ppm/L or ppm/g/L - see paragraph F.4.2.c)
 - (7) Evidence of odor before and after the test (see paragraph F.4.4.1.b).
 - (8) Curing/burn-in testing results, including cure time and cure conditions (e.g., temperature, pressure, cleaning, etc.). If burn-in bench testing of powered equipment was done prior to off-gas testing, annotate that along with test conditions.

Note: The product name, including model and serial number, for end items may be used for complete equipment assemblies (also known as Commercial Off the Shelf (COTS) material) when the material chemical name is unknown. The testing activity must attempt to identify the non-metallic material of complete equipment assemblies and provide them when available. This option is not allowed for non-metallic material that is fabricated from raw non-metallic material.

The activity requesting laboratory off-gas testing must provide the Safety Data Sheet (SDS) to the appropriate Program Manager to ascertain whether additional target compounds or non-target compounds need to be looked for during the off-gas testing (See Section F.5.3.d).

The non-metallic material off-gas test reports must be evaluated in accordance with Section F.6. All off-gas test reports will be retained and maintained in a manner suitable for audit. Non-metallic off-gas test reports that are used to qualify a specific material or are being used in lieu of the testing specified in Section F.5.5 must be submitted to the Program Manager for approval and will be

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 8

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

maintained to support DSS certification.

3.21 See CDRL DI-MISC-80678 (Special Emphasis C of C) - The certificate of compliance must show traceability to the marking applied on each individual item, and must contain the following information:

1. Contractor's name, address, phone number and date.
2. The contract/purchase order number (i.e. N00104-11-P-FA12).
3. The national stock number (NSN). The 18 character National Stock Number for Special Emphasis Material includes the two digit COG, the four digit FSC, the 9 digit NIIN, and the two digit SMIC (i.e. 1H 4820 012345678 D4) ("N/A" when Not Applicable).
4. Lubricants, sealants, anti-seize, and/or thread locking compounds. ("N/A" when Not Applicable).
5. Cure date ("N/A" when Not Applicable).
6. Manufacturer's compound number ("N/A" when Not Applicable).
7. When weld procedure submittal is required by the contract, a statement that the approval date of the qualification data precedes any production or repair welding performed on this Contract. ("N/A" when Not Applicable).
8. A statement for any Hull, Mechanical and Electrical (HM&E) testing required that include the name of the test and that it was performed satisfactorily. If no HM&E testing is required, the statement should read "Hull, Mechanical and Electrical (HM&E) testing - N/A."
9. A statement to the effect that all items furnished on this contract are in full compliance with the specifications and requirements.
10. Contractor's or authorized personnel's signature.

3.21.1 For Connectors, Cables, and Junction Boxes procured to EB Specs S-5343934-1, S-5343934-2, S-5343934-3, or Dry Deck Shelter Specification S-5486639-1, the Certificate Of Compliance must also include the information below:

11. A notation that 32 root mean square (RMS) finishes are in accordance with the specifications and are free of imperfections.
12. Direct reading of O-ring surface diameters with specified standard.

3.21.2 For Self-Locking Hex Nuts procured to NASM 25027, the Certificate Of Compliance must also include the information below:

13. A statement to the effect that qualification testing in accordance with NASM 25027 Paragraph 3.2 is satisfactorily performed.

4. QA PROV

P| Notes to DCMA QAR and the Contractor -

4.0.1 DCMA QAR and the Contractor for proprietary designs - Departures from Contractor imposed requirements, not specifically covered by the contract, must be judged individually on the basis of the effect, if any, on contractual requirements. When there is a disagreement between the Contractor and the Government representative as to the effect on contractual requirements, the departure must be considered a nonconformance and be submitted to the PCO for disposition.

4.0.2 DCMA QAR and the Contractor for proprietary designs - All records of departures from Contractor imposed requirements must be maintained and available for review at the Contractor's facility. A copy must be given to the local Government representative. A record of these departures, traceable to the applicable part number and contract number must be submitted to the PCO.

4.0.3 DCMA QAR and the Contractor for proprietary designs - For proprietary designs, the contractor's part numbers are acceptable for reference only. The delivered material must conform to all drawings, specifications, and other contractual requirements.

4.0.4 DCMA QAR - It is the responsibility of DCMA QAR to review Non-Destructive Testing (NDT) procedures for NAVSUP Contracts/Purchase Orders.

4.0.5 DCMA QAR and the Contractor - The ECDS (Electronic Contractor Data Submission) system is available for certain data submissions and to submit questions and clarifications, and waiver requests on Contracts and Solicitations. ECDS can be found at: <https://register.nslc.navy.mil/>

5. PACKAGING

5.1 Preservation, Packaging, Packing and Marking - Preservation, Packaging, Packing and Marking must be in accordance with the Contract/Purchase Order Schedule and as specified below.

6. NOTES

6.1 Several definitions of terms that apply to LI/SOC items are listed below. All terms may not apply to every item.

6.1.1 The ECDS (Electronic Contractor Data Submission) system is at: <https://register.nslc.navy.mil/>

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 9

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

This application will require advance registration using a PKI Digital Certificate. Information on initiating a PKI can be found at: <http://iase.disa.mil/pki/eca/Pages/index.aspx> A Vendor User Guide is available as CSD001 in the CSD (Contract Support Document) Library within ECDS.

6.1.2 Critical Safety Item (CSI). Any ship part, assembly, or support equipment containing a critical characteristic whose failure, malfunction, or absence of which could cause a catastrophic or critical failure resulting in loss of, or serious damage to the ship, or unacceptable risk of personal injury or loss of life.

6.1.3 Critical Process. As determined by the TWH, any process, operation or action performed on a Ship CSI that serves to establish a critical characteristic (such as welding, soldering, machining, polishing, cleaning, or assembling) or confirm that a critical characteristic is within drawing or specification compliance (such as, testing, measurement, or non-destructive evaluation).

6.1.4 First Article. Pre-production models, initial product samples, test samples produced to ensure a manufacturer's capability to meet full specification requirements.

6.1.5 First Article Test (FAT). Contractually required testing and inspection of a supplier's pre-production, production, or "production representative" specimens to evaluate a manufacturer's ability to produce conforming product prior to the Government's commitment to receive subsequent production items. First Article Testing is product specific and does not assess manufacturing process controls nor does it assure the effectiveness of the manufacturer's quality program.

6.1.6 Government Source Inspection (GSI). GSI is independent oversight performed by a government representative usually a DCMA Quality Assurance Representative (QAR)) to assure that those unique product quality and system elements, identified by the Contracting Agency as important, are observed and evaluated.

6.1.7 Quality Assurance Letter of Instruction (QALI). A QALI is a formal document initiated by a contracting activity that provides essential requirements and instructions for contracted materials to be independently verified and accepted by a government representative prior to shipment.

6.1.8 Objective Quality Evidence (OQE) - The quantitative and qualitative data of all mechanical, chemical, and performance tests performed (as required by the applicable specification, drawing, or purchase document) to prove that the material supplied conforms to the specified requirements.

6.1.9 Surface Discontinuity: Any surface irregularity, marking, or localized change in physical character of the surface, other than dimensional, that exists infrequently at one or several places. (Examples: burrs, dents, nicks, scratches, gouges, pits, center-punches, scribes, and tool marks) Surface discontinuities less than 0.005-inch in depth are acceptable provided they do not violate any other design requirements specified in this Contract/Purchase Order.

6.1.10 Traceability Code - A code or number providing traceability to the actual chemical and mechanical properties of the specified heat, batch, or form from which the material originated.

6.1.11 Verification - An examination performed to determine compliance with a specific requirement.

6.1.12 A nonconformance is defined as affecting or violating the following:

- The requirements of this contract/purchase order.
- Contractually invoked drawings (i.e. envelope dimensions, interface dimensions with mating parts/equipment, center of gravity, weights, piece part identification, material, etc.).
- Contractually invoked federal, military, or commercial specifications and/or standards.
- Form, fit, function, performance to contract requirements, reliability, maintainability, interchangeability, safety of personnel or equipment, or additional cost to the Government.

6.1.13 Waiver - A written authorization to accept an item, which during manufacture, or after having been submitted for Government inspection or acceptance, is found to depart from specified requirements, but nevertheless is considered suitable for use as is or after repair by an approved method.

6.1.14 Deviation - A specific written authorization (granted prior to the manufacture of an item) to depart from a particular requirement(s) of an item's current approved configuration documentation for a specific number of units or a specified period of time, and to accept an item which is found to depart from specified requirements, but nevertheless is considered suitable for use "as is" or after repair by an approved method.

6.1.15 Critical Waiver/Deviation - This waiver/deviation consists of a departure involving safety.

6.1.16 Major Waiver/Deviation - This waiver/deviation consists of a departure involving:

- Performance
- Interchangeability, Reliability, Survivability, Maintainability,

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 10

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

or Durability of the item or its repair parts

- Health or Safety
- Effective Use or Operation
- Weight, Stability, or Structural Integrity
- System design parameters as schematics, flows, pressures or temperatures
- Compartment arrangements or assigned function

6.1.17 Minor Waiver/Deviation - This waiver/deviation consists of a departure which does not involve any of the factors listed as critical or major

6.1.18 Engineering Change (EC): A change to the current approved configuration documentation of a configuration item at any point in the life cycle of the item.

6.1.19 Engineering Change Proposal (ECP): A proposed Engineering Change and the documentation by which the change is described, justified, and submitted to the Government for approval or disapproval.

6.1.20 Class I ECP - A class I ECP is approved by the Government's Configuration Control Board and authorized with a contract modification.

6.1.21 Class II ECP - A class II change is typically reviewed for concurrence in classification by the local government representative, unless otherwise specified elsewhere in the contract/purchase order.

6.2 In accordance with OPNAVINST 5510.1 all documents and drawings provided by the U.S. Navy to perspective Contractors must include a "Distribution Statement" to inform the contractor of the limits of distribution, and the safeguarding of the information contained on those documents and drawings.

6.2.1 There are 7 (seven) separate distribution statement codes used for non-classified documents and drawings. The definition for each is as follows:

- A... approved for public release; distribution is unlimited.
- B... distribution authorized to US Governments agencies only.
- C... distribution authorized to US Government agencies and their contractors.
- D... distribution authorized to DoD and DoD contractors only.
- E... distribution authorized to DoD Components only.
- F... further distribution only as directed by Commander, Naval Sea Systems Command, code 09T.
- X... distribution is authorized to US Government agencies and private individuals or enterprises eligible to obtain export controlled technical data in accordance with OPNAVINST 5510.161.

6.3 Ordering Information for Document References - The Department of Defense Single Stock Point (DODSSP), Website <http://www.dsp.dla.mil/>, provides product information for the Department Of Defense Index Of Specifications and Standards (DODISS) (i.e. Military/Federal Specifications and Standards), Data Item Descriptions (DIDs), and other DODSSP Products. Most Specifications can obtained directly from <http://quicksearch.dla.mil/>

A. Availability of Cancelled Documents - The DODSSP offers cancelled documents that are required by private industry in fulfillment of contractual obligations in paper format. Documents can be requested by phoning the Subscription Services Desk.

B. Commercial Specifications, Standards, and Descriptions - These specifications, standards and descriptions are not available from Government sources. They may be obtained from the publishers of the applicable societies.

C. Ordnance Standards (OS), Weapons Specifications (WS), and NAVORD OSTD 600 Pages - These type publications may be obtained by submitting a request to:

Commander, Indian Head Division, Naval Surface Warfare Center
Code 8410P, 101 Strauss Avenue
Indian Head, MD 20640-5035

D. On post-award actions, requests for "Official Use Only" and "NOFORN" (Not Releasable To Foreign Nationals) documents must identify the Government Contract Number, and must be submitted via the cognizant Defense Contract Management Command (DCMC) for certification of need for the document. On pre-award actions such requests must be submitted to the PCO for certification of need for the document.

E. NOFORN Military Specifications and Standards (including Amendments, Change Notices and Supplements, but NOT interim Changes) to be ordered from:

Contracting Officer
NAVSUP-WSS
Code 87321
5450 Carlisle Pike

TECHNICAL DATA PACKAGE (DRAFT PRINT)

NIIN: PNTDP0159 VERSION: 001

PAGE 11

ITEM NAME: HOSE ASSEMBLY

Oct 28, 2025

P.O. Box 2020
Mechanicsburg, Pa. 17055-0788

F. Nuclear Reactor Publications Assigned NAVSEA Documents and Identification Numbers (i.e. NAVSEA Welding Standard, NAVSEA 250-1500-1) are to be ordered from:

Commanding Officer
NAVSUP-WSS
Code 009
5450 Carlisle Pike
P.O. Box 2020
Mechanicsburg, Pa. 17055-0788

G. Technical Manuals Assigned NAVSEA Identification Numbers (i.e. NAVSEA Welding And Brazing Procedure, NAVSEA S9074-AQ-GIB-010/248) are to be ordered from:

Commanding Officer
NAVSUP-WSS
Code 1 Support Branch
700 Robbins Avenue
Philadelphia, Pa. 19111-5094

H. Interim Changes and Classified Specifications must be obtained by submitting a request on DD Form 1425 to NAVSUP-WSS.

7. DD FORM 1423 COMMENTS