Single Page Application (SPA)

- A single HTML page w/JS to change contents
  - Can appear to be many "pages" to user
  - All one "page" to browser!
- React is not only way to make SPA
- React does not have to be a SPA
- SPA sometimes desirable
  - When complex JS state
  - No reload JS when no real page navigation
- SPA NOT always desirable!
  - Why not a plain website?
  - Why not a React generated website?

Navigation in a SPA

- Core SPA issue
  - Browser navigation reloads HTML + JS
- Links and Forms?
  - Change state and contents
    - Looks like page change
  - Do NOT actually navigate
    - Keeps base HTML + JS
    - Apply changes in content

Prevent forms and links from navigating

Links and Forms

- `.preventDefault()` on event
    - `onSubmit` (forms) or `onClick` (buttons)
- Update state so render changes HTML
    - Looks like a new page

Simple vs Complex

- Faking page navigation has lots of details
- Libraries are made to handle this **routing**
    - Ex: `react-router`, `@tanstack/router`
- We aren't using any such libraries
    - Not because the libraries aren't good
    - Learning the concepts, not one library
    - You can then learn any library
        - AFTER this course

Simple Example

- We want to show the user the current "page"
- So some variable is used to decide what to render
    - We will have a "page" state

```
const [page, setPage] = useState('Home');

return (
  <>
    { (page === 'Home) && <Home/> }
    { (page === 'About') && <About/> }
  </>
);
```

Simple Navigation

- Changing page needs to change page state
    - Pass the setter

```
const [page, setPage] = useState('Home');

return (
  <>
    <NavBar setPage={setPage} />
    { (page === 'Home) && <Home/> }
    { (page === 'About') && <About/> }
  </>
);
```

- Simplified example!
    - Learn the concept, not the specific syntax

Using the Setter

```
function NavBar({ setPage }) {

  function go(event, page) {
    event.preventDefault();
    setPage(page);
  }

  return (
    <nav>
      <ul>
        <li><a href="" onClick={ (e) => go(e, "Home") }>
          Home
        </a></li>
        <li><a href="" onClick={ (e) => go(e, "About") }>
          About
        </a></li>
      </ul>
    </nav>
  );
}
```

Details to Consider

- What to use as href?
    - `#` vs `#something` vs a path
    - How does this impact UX?
- "Deeplinking" (later)
    - What about Back button?
    - What about Reloading the page?
    - Or saving/sending the url?
- Can have different ways to call state change
    - Should `preventDefault()`
    - Way to change state needs to be passable

One Approach

```
const [page, setPage] = useState('#home');

function navToHash(eventOrHash) {
  eventOrHash.preventDefault?.(); // optional chaining
  const hash = eventOrHash.target?.hash || eventOrHash;
  setPage(hash);
}

return (
  <>
    <NavBar navToHash={navToHash} />
    { (page === '#home') && <Home/> }
    { (page === '#about') && <About/> }
  </>
);
```

```
// Elsewhere
    <li><a href="#home" onClick={ navToHash }>
      Home
    </a></li>
```

Core SPA Concepts

- Everything is one HTML file
    - Even when generated from many `.jsx`
    - Remember that's what the browser sees!
- **state** is a vital concept
    - Changed behavior is either CSS or state!
        - Or both
    - Functionality is a lot of state
- No clear line between UI and Functionality