Geely Automotive Research Institute
(Ningbo)Co.Ltd

Document Release Status
RELEASED

Release Date	Version
2023-7-17	(3)
Document No	Issue
0000000000	**003**
Volume No	Page No
01	**1 (3)**

Geely Automotive Research Institute

Document Type	Reference No
ECU VMM DPR	

Document Name
ECU VMM DPR

GEEA 3.0

Vehicle Mode Management DPR for ECU

1.1 Current consumption

Current consumption for the ECU shall not exceed specification in table below. The requirement values are max allowed current consumption per specified mode. If there is no requirement specified, the cell is marked with "n/a". Requirements according to the matrix are valid for supply voltage range 12.5 to 14.5V, and the full specified temperature range for the component. The verification conditions are specified in VMM verification method, DVM 310VMM.

The stated current consumption levels are for the node itself, i.e. not for controlled loads outside of its housing. Measured data (and estimations) shall be presented for the ECU in the Load database, in a format that enables evaluation of requirement values.

Off /Sleep: The node has no activity and has reached its absolute lowest power consumption, but still need to be powered e.g. to maintain memory.

Standby: The node has no functionality noticeable for the customer but is still active i.e. waiting to be activated by the customer or function.

Active: The node has normal functionality i.e. activated and noticeable for the customer. Waiting for a button push before activating noticeable function is not considered to be an Active state, see Standby.

ECU	Off /Sleep(mA) (Normal)	Off /Sleep(mA) (Factory/Transport)	Standby(mA)	Active(A)
IGM	0.1;	0.1;	50;	0.075:Driving; 1:Activation;

1.2 Power Supply

ECUs shall be designed / configured according to the power supply in the table below. If the ECU have any change of power supply designed， VMM must to be contacted and approve the power supply.

ECU	ECU Name	Power Supply
IGM2	Inverter Generator Module	KL30；CPSR

1.3 Operational Conditions

ECUs shall comply to an operational time as specified according to table below.

Operation state	Operation Condition	Operational time
Life time		≥ 15 years FIC C functions ≥ 10 years FIC A/B functions
ECU is continuous power feed or activity	OC1	≥ 131 500h FIC C functions ≥ 88 000h FIC A/B functions

(Power supply is KL30)		
Driving (Power supply is not KL30)	OC2	≥ 13 500 h FIC C functions, ≥ 9 000 h FIC A/B functions available. Loads may be restricted.
PHEV "Plugged in" Preconditioning only	OC3	≥ 6 000 h
PHEV "Plugged in" charging/preconditioning	OC4	≥ 30 000 h
Other functionalities active in non-driving states		Not specified

Note: OC2+OC3 is valid for components active in both Driving and Preconditioning
OC2+OC4 is Valid for components active in both Driving and “Plugged in ” charging/Preconditioning.