


TriProof Flex I / LL217-Modular LED Linear&Tri-proof light











Light

Trunking



LL217-Modular LED Linear & Tri-proof light is the optimal solution for almost all linear lighting applications thanks to its flexibility, good quality of lighting, precise beam shaping and easy installation.


LED Linear Trunking System adopts patented modular pre-assembled connector design (electrical and mechnical connections) and the system can hold up to 10*2.5mm wires for multi-functions.

Unique sealing material and technique ensures IP65 and makes the light workable even in harsh industrial surroundings.

FEATURES

- IP65
- Modular design, parts interchangeable
- End-to-end connectable, quick installation

- Patented sliding clip design
- · Various installations: suspending, flush mounting
- Can be integrated with Dimming (0-10V), emergency function, motion sensing
- 5 years warranty









LED CHARACTERISTICS

Input Voltage 100-277VAC Warranty 5 years

cover striped-frosed&striped-clear

THD <10%

PF >0.9 CCT(K) 4000/5000/6500 1P level

ameter							
Type No.	Length (mm)	Wattage (W)	Beam Angle	Lumen (lm)	LED	Lifespan	Input Voltage
217-0001	1500	30	130°	3900	2835	70000Hrs	100-277VAC
217-0002	1500	45	130°	5850	2835	70000Hrs	100-277VAC
217-0003	1500	65	130°	8450	2835	70000Hrs	100-277VAC
217-0004	1500	30	130°	4800	2835	50000Hrs	100-277VAC
217-0005	1500	45	130°	7200	2835	50000Hrs	100-277VAC
217-0006	1500	65	130°	10400	2835	50000Hrs	100-277VAC
217-0007	1500	65	2×30°	8450	3030	90000Hrs	100-277VAC
217-0008	1500	65	2×60°	8450	3030	90000Hrs	100-277VAC
217-0009	1500	65	20°/30°/45°/60°/90°	7800	3030	90000Hrs	100-277VAC
217-0010	2400	36	130°	4680	2835	50000Hrs	100-277VAC
217-0011	2400	72	130°	9360	2835	50000Hrs	100-277VAC
217-0012	2400	116	130°	15080	2835	50000Hrs	100-277VAC
217-0023	1500	45	30°/60°/90°	5850	2835	50000Hrs	100-277VAC
217-0024	1500	65	30°/60°/90°	8450	2835	50000Hrs	100-277VAC
217-0025	1500	45	30°/60°/90°	6750	2835	50000Hrs	100-277VAC
217-0026	1500	65	30°/60°/90°	9750	2835	50000Hrs	100-277VAC



Light Distribution



















Connector (patented)



• Single plug connector 3*2.5mm²



• Double plug connector 6*2.5mm²



• **PG**For up to 5*1.5mm²




• PG(plus)
For up to 10*2.5mm²





Surface mounted accessories







Sliding clip



Interconnection clip

Suspending accessories



Suspending clip



Interconnection clip

Wiring accessories



Power cable



Interconnection cable




Dimming power cable




Dimming interconnection cable


















Application









Parking garage

• Supermarket

Workshop

Warehouse

Emergency Battery Backup

Lithium battery/Nickel-cadmium battery: 12V, 2800mA

Emergency Output	Discharge	Charging	Emergency Current
20W	90min	100-200mA	700mA
10W	180min	100-200mA	350mA




Motion Sensing

Reliable Detection Sensitivity





Sensing Angle	180°
Sensing Distance	3-10m
Delay Time Settings	0s, 5s, 10s, 15s, 20s, 30s, 60s, 120s
Dimming Settings	5%, 10%, 15%, 20%, 25%, 30%, 60%



About us

11 YEARS LED Experience

Zhengzhou Inledco Lighting Co., LTD , located in Zhengzhou city, Henan Province, China, is a leading LED lights manufacturer with professional R&D teams. We started researching and designing LED lights from 2006 and have been exporting 100% of our products to North America and Europe ever since. We are committed to innovation and development of LED lights. Several series of innovative products have been developed and patented, some of which are even leading the trend in the market .

Zhengzhou inledco Lighting Co., LTD Add: High Technology Development Zone, Zhengzhou Henan China

Tel:+86-371-86549719 Postcode: 450000

E- mail: info@ledinpro.com Website: www.ledinpro.com